



**BUILDING CODE COMPLIANCE OFFICE**  
METRO-DADE FLAGLER BUILDING  
140 WEST FLAGLER STREET, SUITE 1603  
MIAMI, FLORIDA 33130-1563  
(305) 375-2901 FAX (305) 375-2908

**CONTRACTOR LICENSING SECTION**  
(305) 375-2527 FAX (305) 375-2558

**CONTRACTOR ENFORCEMENT DIVISION**  
(305) 375-2966 FAX (305) 375-2908

**PRODUCT CONTROL DIVISION**  
(305) 375-2902 FAX (305) 372-6339

**PRODUCT CONTROL NOTICE OF ACCEPTANCE**

**Von Duprin Division**  
**2720 Tobey Drive**  
**Indianapolis ,IN 46219**

Your application for Notice of Acceptance (NOA) of:

**Component Approval-VonDuprin Model 99 Rim Exit Device w/ HH54 Mullion**

under Chapter 8 of the Code of Miami-Dade County governing the use of Alternate Materials and Types of Construction, and completely described herein, has been recommended for acceptance by the Miami-Dade County Building Code Compliance Office (BCCO) under the conditions specified herein.

This NOA shall not be valid after the expiration date stated below. BCCO reserves the right to secure this product or material at any time from a jobsite or manufacturer's plant for quality control testing. If this product or material fails to perform in the approved manner, BCCO may revoke, modify, or suspend the use of such product or material immediately. BCCO reserves the right to revoke this approval, if it is determined by BCCO that this product or material fails to meet the requirements of the South Florida Building Code.

The expense of such testing will be incurred by the manufacturer.

**ACCEPTANCE NO.: 00-0421.03**  
**EXPIRES: 10/12/2003**

Raul Rodriguez  
Chief Product Control Division

**THIS IS THE COVERSHEET, SEE ADDITIONAL PAGES FOR SPECIFIC AND GENERAL  
CONDITIONS  
BUILDING CODE & PRODUCT REVIEW COMMITTEE**

This application for Product Approval has been reviewed by the BCCO and approved by the Building Code and Product Review Committee to be used in Miami-Dade County, Florida under the conditions set forth above.

Francisco J. Quintana, R.A.  
Director  
Miami-Dade County  
Building Code Compliance Office

**APPROVED: 10/12/2000**

**Von Duprin Inc.**

**ACCEPTANCE No.:** 00-0421.03  
**APPROVED** : OCT 12 2000  
**EXPIRES** : OCT 12 2003

**NOTICE OF ACCEPTANCE: SPECIFIC CONDITIONS**

**1. SCOPE**

1.1 This approves a **component** consisting of a surface mounted Rim panic device w\ Mullion for use with 16 ga flush outswing commercial steel door, as described in Section 2 of this Notice of Acceptance, designed to comply with the South Florida Building Code (SFBC), 1994 Edition for Miami-Dade County, for the locations where the pressure requirements, as determined by SFBC Chapter 23, do not exceed the Design Pressure Rating values indicated in the approved drawings.

**2. PRODUCT DESCRIPTION**

2.1 **Component Approval- Von Duprin 99 Rim Device w\ HH54 Mullion & 499F strike - Impact Resistant** and its components shall be constructed in strict compliance with the following documents: Drawing No 270 W revision B, sheets 1 through 1 of 1, prepared by the manufacturer, bearing the Miami-Dade County Product Control approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Division. These documents shall hereinafter be referred to as the approved drawings.

**3. LIMITATIONS**

- 3.1 Each of this device is approved to be used as equal alternate to corresponding lock approved to be used in Single or Double Outswing Commercial Steel Doors holding a current Miami-Dade County Product Control Notice of Acceptance. The lowest Design Pressure Rating shall apply.
- 3.2 This device shall be installed in a commercial steel door panel no wider than 48" & higher than 84".
- 3.3 Installation of this device requires steel reinforcement (14ga x4"x20") at the mid-span of hinge stile.
- 3.4 Optional "switch signal" devices listed may be used with this Rim model, as long as it do not effect the mechanical properties of this exit device and/ or inhibit egress.

**4. INSTALLATION**

- 4.1 The surface mounted Rim panic device and its components shall be installed in strict compliance with the approved drawings.
- 4.2 This panic can be installed as part of an impact resistant unit.

**5. LABELING**

5.1 This device shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved".

**6. BUILDING PERMIT REQUIREMENTS**

- 6.1 Application for building permit shall be accompanied by copies of the following:
  - 6.1.1 This Notice of Acceptance.
  - 6.1.2 The door system's Notice of Acceptance.
  - 6.1.3 Manufacturer's installation instruction.
  - 6.1.4 Duplicate copies of the approved drawings, as identified in Section 2 of this Notice of Acceptance, clearly marked to show the components selected for the proposed installation.
  - 6.1.5 Any other documents required by the Building Official or the South Florida Building Code (SFBC) in order to properly evaluate the installation of this system.

Ishaq I. Chanda  
Ishaq I. Chanda, P.E. Product Control Examiner  
Product Control Division

**Von Duprin Inc.**

**ACCEPTANCE No.:** 00-0421.03

**APPROVED** : OCT 12 2000

**EXPIRES** : OCT 12 2003


**NOTICE OF ACCEPTANCE: STANDARD CONDITIONS**

1. Renewal of this Acceptance (approval) shall be considered after a renewal application has been filed and the original submitted documentation, including test supporting data, engineering documents, are no older than eight (8) years.
2. Any and all approved products shall be permanently labeled with the manufacturer's name, city, state, and the following statement: "Miami-Dade County Product Control Approved", or as specifically stated in the specific conditions of this Acceptance.
3. Renewals of Acceptance will not be considered if:
  - a) There has been a change in the South Florida Building Code affecting the evaluation of this product and the product is not in compliance with the code changes;
  - b) The product is no longer the same product (identical) as the one originally approved;
  - c) If the Acceptance holder has not complied with all the requirements of this acceptance, including the correct installation of the product;
  - d) The engineer who originally prepared, signed and sealed the required documentation initially submitted is no longer practicing the engineering profession.
4. Any revision or change in the materials, use, and/or manufacture of the product or process shall automatically be cause for termination of this Acceptance, unless prior written approval has been requested (through the filing of a revision application with appropriate fee) and granted by this office.
5. Any of the following shall also be grounds for removal of this Acceptance:
  - a) Unsatisfactory performance of this product or process.
  - b) Misuse of this Acceptance as an endorsement of any product, for sales, advertising or any other purpose.
6. The Notice of Acceptance number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the Notice of Acceptance is displayed, then it shall be done in its entirety.
7. A copy of this Acceptance as well as approved drawings and other documents, where it applies, shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at all time. The engineer need not reseal the copies.
8. Failure to comply with any section of this Acceptance shall be cause for termination and removal of Acceptance.
9. This Notice of Acceptance consists of pages 1, 2 and this last page 3.

Ishaq I. Chanda

Ishaq I. Chanda, P.E. Product Control Examiner  
Product Control Division

**END OF THIS ACCEPTANCE**




#425 SEX BOLTS (DEVICE THRU-BOLTED WITH #10-24 MACHINE SCREWS)

(4) 5/16"-18 MACHINE SCREWS  
(2) 1/4"-20 MACHINE SCREWS TO MOUNT COVER  
COVER

499-F STRIKE MOUNTED WITH (7) 1/4"-20 STAINLESS MACHINE SCREWS

AUX. LATCH

LATCH BOLT CENTERCASE





APPROVED AS COMPLYING WITH THE SOUTH FLORIDA BUILDING CODE  
DATE October 12, 2000  
BY Ishaq I. Chauda  
PRODUCT CONTROL DIVISION  
BUILDING CODE COMPLIANCE OFFICE  
ACCEPTANCE NO. 00-0421.03

PROJECTION 13/16" (21MM)

ALL ELECTRICAL COMPONENTS MUST BE UL APPROVED


- NOTES:
1. ALL FINISHES, 3' & 4' DOOR MODELS OFFERED
  2. PN MODEL OFFERED
  3. ALL MODELS OFFERED IN BOTH 98 & 99 SERIES
  4. E, RX, EL, SS OPTIONS AVAILABLE SEE VON DUPRIN FOR OPTIONS
  5. ELECTRICAL INSTALLATION UNDER SEPARATE APPROVAL.

OUTSIDE TRIM FUNCTIONS  
SEX BOLTS OR 990EO PLATE MAY BE USED FOR "EXIT ONLY" APPLICATIONS



ALL TRIM HAS #10-24 STUDS FOR THRU-BOLTING

DESIGN PRESSURE RATING	
EXTERIOR	+65
INTERIOR	-65



- FEATURES
- NONHANDED
  - FIELD SIZEABLE
  - 3/4" (19MM) THROW, LATCH BOLT
  - LATCH BOLT DEADLOCKING
  - EIGHT POPULAR FINISHES


DIMENSIONS  
TOUCHBAR HEIGHT OF FINISHED FLOOR 39 13/16" (935MM) AT CENTER

TOUCHBAR PROJECTION  
NEUTRAL 3 13/16" (97MM)  
DEPRESSED 3 1/16" (78MM)

CENTER CASE 8" X 2 1/4" X 2 3/4" (203MM X 57MM X 70MM)


DEVICE LENGTH - SHORT 33" 2'6" TO 3' (762MM TO 914MM) DOOR SIZE  
LONG 45" 3'1" TO 4' (940MM TO 1219MM) DOOR SIZE

14GAX 4 "X20" HINGE SIDE REINFORCEMENT REQUIRED IN DOOR.




MULLION FITTING  
8620 STEEL

HARDWARE OPTIONS



MULLION BODY  
.25" THK. WALL A 500 GRADE STEEL



VON DUPRIN, INC.  
2720 TOBEY DRIVE  
INDIANAPOLIS, INDIANA 46219

TITLE  
99 RIM DEVICE W/HH54 MULLION  
SFBC CERTIFICATION

DO NOT SCALE	DWG NO. 270W	REV B
	SHEET 1 OF 1	