



**BUILDING CODE COMPLIANCE OFFICE (BCCO)  
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA  
METRO-DADE FLAGLER BUILDING  
140 WEST FLAGLER STREET, SUITE 1603  
MIAMI, FLORIDA 33130-1563  
(305) 375-2901 FAX (305) 375-2908**

**NOTICE OF ACCEPTANCE (NOA)**

---

**Spectrum Building Materials, Inc.  
2742 NW 112<sup>th</sup> Avenue  
Miami, FL 33172**

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by the BCCO and accepted by the Building Code and Product Review Committee to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The BCCO (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BCCO reserves the right to revoke this acceptance, if it is determined by BCCO that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the South Florida Building Code, 1994 Edition for Miami-Dade County or Florida Building Code.

**DESCRIPTION: Mixta Spanish "S" Clay Roof Tile**

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 4.  
The submitted documentation was reviewed by Frank Zuloaga, RRC



**NOA No.: 01-0504.13  
Expiration Date: 02/14/07  
Approval Date: 02/14/02  
Page 1 of 4**

**ROOFING SYSTEM APPROVAL:**

**Category:** Roofing  
**Sub-Category:** Roofing Tiles  
**Material:** Clay

**1. SCOPE**

This new a roofing system using Spanish Mixta "S" Clay Roof Tile, as manufactured HDR S.A. described in Section 2 of this Notice of Acceptance, designed to comply with the South Florida Building Code, 1994 Edition for Miami-Dade County. For the locations where the pressure requirements, as determined by applicable Building Code, does not exceed the design pressure values obtain by calculations in compliance with RAS 127 using the values listed in section 4 herein. The attachment calculations shall be done as a uplift based system.

**2. PRODUCT DESCRIPTION**

<u>Manufactured by Applicant</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
Mixta "S"	L = 18.5" W = 11" Min. 3/8" thick	PA 112	High profile, one-piece, "S" shaped, clay roof tile equipped with one-nail holes. For direct deck adhesive attached applications. □
Trim Pieces	L = varies W = varies Varying thickness	PA 112	Accessory trim, clay roof pieces for use at hips, rakes, ridges and valley terminations. Manufactured for each tile profile. □

**2.1 COMPONENTS OR PRODUCTS MANUFACTURED BY OTHERS**

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>	<u>Manufacturer</u>
Roof Tile Adhesive ("Polypro® AH160")	N/A	See PCA	Two-component polyurethane adhesive designed for adhesive set roof tile applications.	Polyfoam Products, Inc. (With current NOA)
Hurricane Clip & Fasteners	Clips Min. 1/2" width Min. 0.060" thick Clip Fasteners Min. 8d x 1 1/4"	PA 114 Appendix E	Corrosion resistant clips with corrosion resistant nails.	Generic (With current NOA)



**3. LIMITATIONS**

- 3.1 Fire classification is not part of this acceptance.
- 3.2 For mortar or adhesive set tile applications, a static field uplift test shall be performed in accordance with RAS 106.
- 3.3 Applicant shall retain the services of a Miami-Dade County Certified Laboratory to perform quarterly test in accordance with PA 112, appendix 'A'. Such testing shall be submitted to the Building Code Compliance Office for review.
- 3.4 Minimum underlayments shall be in compliance with the applicable Roofing Applications Standards listed section 4.1 herein.
- 3.5 30/90 hot mopped underlayment applications may be installed perpendicular to the roof slope unless stated otherwise by the underlayment material manufacturers published literature.
- 3.6 This acceptance is for wood deck applications. Minimum deck requirements shall be in compliance with applicable Building Code.

**4. INSTALLATION**

- 4.1.1 Mixta Spanish "S" Clay Roof Tile and its components shall be installed in strict compliance with Roofing Application Standard RAS 120.
- 4.2 Data For Attachment Calculations

Table 1: Average Weight (W) and Dimensions (l x w)			
Tile Profile	Weight-W (lbf)	Length - l (feet)	Width - w (feet)
Spanish Mixta "S" Tile	7.5	1.53	0.85

Table 3: Attachment Resistance Expressed as a Uplift - F' (lbf) for Single Patty Adhesive Set Systems		
Tile Profile	Tile Application	Minimum Attachment Resistance
Spanish Mixta "S" Tile	PolyPro	82.8 <sup>1</sup>
1 Paddy placement of 27.9 grams of Polypro™.		

**5. LABELING**


All tiles shall bear the imprint or identifiable marking of the manufacturer's name or logo, or following statement: "Miami-Dade County Product Control Approved".

**6. BUILDING PERMIT REQUIREMENTS**

- 6.1 Application for building permit shall be accompanied by copies of the following:
  - 6.1.1 This Notice of Acceptance.
  - 6.1.2 Any other documents required by the Building Official or applicable Building Code in order to properly evaluate the installation of this system.



**PROFILE DRAWING**



**MIXTA SPANISH "S" CLAY ROOF TILE**

**END OF THIS ACCEPTANCE**



**NOA No.: 01-0504.13**  
**Expiration Date: 02/14/07**  
**Approval Date: 02/14/02**  
**Page 4 of 4**

**A. TESTS:**

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Asphalt Technologies, Inc.	SBM-01-02-01	PA 100	11/21/2000
PRI Asphalt Technologies, Inc.	SBM-001-02-01	PA 101	11/07/2000
PRI Asphalt Technologies, Inc.		PA 102□	
PRI Asphalt Technologies, Inc.		Physical Properties PA 112	01/29/01
PRI Asphalt Technologies, Inc.	SBM-003-02-01	PA 101	10/17/01

**B. OTHER**

1. Notice of Acceptance number 01-0504.13