



MIAMI-DADE
BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION

MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908

NOTICE OF ACCEPTANCE (NOA)

Innovative Window Concepts
505 Industrial Way
Boynton Beach, FL 33426

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series 1072 Aluminum Single Hung Window

APPROVAL DOCUMENT: Drawing No. **W03-95**, dated 10-20-03, with revision "A", dated 01-12-04, titled "Series 1072 Alum. Single Hung Window (S.M.I.)", sheets 1 through 5 of 5, prepared by Al-Farooq Corporation, signed and sealed by Humayoun Farooq, P.E., bearing the Miami-Dade County Product Control Renewal stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: Small Missile Impact Resistant

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of this page 1 and evidence pages E-1, as well as approval document mentioned above. The submitted documentation was reviewed by **Theodore Berman, P.E.**

Handwritten signature
 1/29/2004

NOA No 03-1201.04
Expiration Date: February 19, 2009
Approval Date: February 19, 2004
Page 1

Innovative Window Concepts

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

1. Manufacturer's die drawings and sections.
2. Drawing No. **W03-95**, dated 10-20-03, with revision "A", dated 01-12-04, titled "Series 1072 Alum. Single Hung Window (S.M.I.)", sheets 1 through 5 of 5, prepared by Al-Farooq Corporation, signed and sealed by Humayoun Farooq, P.E.

B. TESTS

1. Test reports on
 - 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Small Missile Impact Test, per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading, per FBC, TAS 203-94
 - 6) Force Entry Test, per FBC 2411 3.2.1 and TAS 202-94along with marked-up drawings and installation diagram of an aluminum single hung window, prepared by American Test Lab of South Florida, Test Report No. **ATL-0422.02-03**, dated 07/24/03, signed and sealed by Henry Hattem, P.E.

C. CALCULATIONS

1. Anchor calculations, ASTM-E1300- 98, and comparative analysis, prepared by Al-Farooq Corp. on 10/25/03, signed and sealed by Humayoun Farooq, P.E.

D. QUALITY ASSURANCE


1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS

1. Notice of Acceptance No. **01-0205.02** issued to Solutia Inc. for "Saflex/Keepsafe Maximum", dated 05/17/01, expiring on 05/21/06.

F. STATEMENTS

1. Statement letter of compliance, dated October 25, 2003, signed and sealed by Humayoun Farooq, P.E.
2. Statement letter of no financial interest October 25, 2003, signed and sealed by Humayoun Farooq, P.E.



Theodore Berman, P.E.
Deputy Director, Product Control Division
NOA No 03-1201.04
Expiration Date: February 19, 2009
Approval Date: February 19, 2004

UNEQUAL LITES WINDOWS					
DESIGN LOAD CAPACITY - PSF					
FLANGE DIMS.		ANCHORS TYPE 'A'		ANCHORS TYPE 'B'	
WIDTH	HEIGHT	EXT.(+)	INT.(-)	EXT.(+)	INT.(-)
19-1/8"	50-5/8" (4)	90.0	114.2	90.0	160.0
24"		90.0	91.0	90.0	160.0
26-1/2"		82.4	82.4	90.0	160.0
32"		68.3	68.3	90.0	159.3
37"		59.0	59.0	90.0	137.8
40"		54.6	54.6	90.0	127.4
48"	45.5	45.5	90.0	106.2	
53-1/8"	41.1	41.1	90.0	95.9	
19-1/8"	63" (5)	90.0	114.7	90.0	160.0
24"		90.0	91.4	90.0	160.0
26-1/2"		82.8	82.8	90.0	160.0
32"		68.6	68.6	90.0	160.0
37"		59.3	59.3	90.0	138.4
40"		54.9	54.9	90.0	128.0
48"	45.7	45.7	90.0	106.7	
53-1/8"	41.3	41.3	90.0	96.4	
19-1/8"	76" (6)	90.0	114.1	90.0	160.0
24"		90.0	90.9	90.0	160.0
26-1/2"		82.4	82.4	90.0	160.0
32"		68.2	68.2	90.0	159.2
37"		59.0	59.0	90.0	137.7
40"		54.6	54.6	90.0	127.3
48"	45.5	45.5	90.0	106.1	
53-1/8"	41.1	41.1	90.0	95.9	

* NO. IN PARENTHESIS INDICATE NO. OF ANCHORS PER JAMB.


UNEQUAL LITES WINDOWS					
DESIGN LOAD CAPACITY - PSF					
FLANGE DIMS.		ANCHORS TYPE 'A'		ANCHORS TYPE 'B'	
WIDTH	HEIGHT	EXT.(+)	INT.(-)	EXT.(+)	INT.(-)
19-1/8"	50-5/8" (6)	90.0	160.0	90.0	160.0
24"		90.0	136.5	90.0	160.0
26-1/2"		90.0	123.7	90.0	160.0
32"		90.0	102.4	90.0	160.0
37"		88.6	88.6	90.0	160.0
40"		81.9	81.9	90.0	160.0
48"	68.3	68.3	90.0	159.3	
53-1/8"	61.7	61.7	90.0	143.9	
19-1/8"	63" (7)	90.0	160.0	90.0	160.0
24"		90.0	128.0	90.0	160.0
26-1/2"		90.0	115.9	90.0	160.0
32"		90.0	96.0	90.0	160.0
37"		83.0	83.0	90.0	160.0
40"		76.8	76.8	90.0	160.0
48"	64.0	64.0	90.0	140.0	
53-1/8"	57.8	57.8	90.0	134.9	
19-1/8"	76" (8)	90.0	152.2	90.0	160.0
24"		90.0	121.3	90.0	160.0
26-1/2"		90.0	109.8	90.0	160.0
32"		90.0	90.9	90.0	160.0
37"		78.7	78.7	90.0	140.0
40"		72.8	72.8	90.0	140.0
48"	60.6	60.6	90.0	140.0	
53-1/8"	54.8	54.8	90.0	127.3	

* NO. IN PARENTHESIS INDICATE NO. OF ANCHORS PER JAMB.


WINDOWS RATED FOR SMALL MISSILE IMPACT.
SHUTTERS REQUIRED FOR INSTALLATIONS UP TO 30 FT. OF GRADE
SHUTTERS NOT REQUIRED FOR INSTALLATIONS ABOVE 30 FT.

SERIES 1072 ALUM SINGLE HUNG WINDOW (S.M.I.)
DESIGN LOAD RATINGS FOR THESE WINDOWS TO BE AS PER CHARTS SHOWN ON SHEETS 1 AND 2.

THIS PRODUCT IS DESIGNED TO COMPLY WITH THE HIGH VELOCITY HURRICANE ZONE OF THE 2001 FLORIDA BUILDING CODE.
WOOD BUCKS BY OTHERS, MUST BE ANCHORED PROPERLY TO TRANSFER LOADS TO THE STRUCTURE.
ANCHORS SHALL BE AS LISTED, SPACED AS SHOWN ON DETAILS. ANCHOR EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.
ANCHORING OR LOADING CONDITIONS NOT SHOWN IN THESE DETAILS ARE NOT PART OF THIS APPROVAL.



GLAZING DETAIL



UNEQUAL LITES (ORIEL TYPE)

TYPICAL ELEVATION
TESTED UNIT

Approved as complying with the Florida Building Code
Date 02/19/04
NOA# 03-1201.04
Miami Dept. Product Control
Division
By *[Signature]*

Engr. DR. HUMAYOUN FAROOQ
STRUCTURES
FLA. PE # 16557
C.A.N. 3538
JAN 19 2004

afc
AL-FAROOQ CORPORATION
ENGINEERS, PLANNERS & PRODUCT DESIGN
1235 SW 87 AVE
MIAMI, FLORIDA 33174
TEL. (305) 264-8100 FAX. (305) 262-6978
COMP-ANL\W03-95IWS

SERIES 1072 ALUM SINGLE HUNG WINDOW (S.M.I.)
INNOVATIVE WINDOW CONCEPTS
505 INDUSTRIAL WAY
BOYNTON BEACH, FL. 33426
TEL. (561) 493-2303 FAX. (561) 493-2302

no	date	description	NO CHANGE THIS SHEET
A	01.13.04		

date: 10-20-03
scale: 1/2"=1'-0"
dr. by: HAMID
chk. by:


drawing no. **W03-95**
sheet 1 of 5

EQUAL LITES WINDOWS						
DESIGN LOAD CAPACITY - PSF						
FLANGE DIMS.		ANCHORS TYPE 'A'		ANCHORS TYPE 'B'		
WIDTH	HEIGHT	EXT.(+)	INT.(-)	EXT.(+)	INT.(-)	
19-1/8"	26"	90.0	111.2	90.0	160.0	
24"		88.6	88.6	90.0	160.0	
26-1/2"		80.3	80.3	90.0	160.0	
32"		66.5	66.5	90.0	155.1	
37"		(2)	57.5	57.5	90.0	134.1
40"		53.2	53.2	90.0	124.1	
48"		44.3	44.3	90.0	103.4	
53-1/8"		40.0	40.0	90.0	93.4	
19-1/8"	38-3/8"	90.0	113.0	90.0	160.0	
24"		90.0	90.1	90.0	160.0	
26-1/2"		81.6	81.6	90.0	160.0	
32"		67.5	67.5	90.0	157.6	
37"		(3)	58.4	58.4	90.0	136.3
40"		54.0	54.0	90.0	126.1	
48"		45.0	45.0	90.0	105.1	
53-1/8"		40.7	40.7	90.0	94.9	
19-1/8"	50-5/8"	90.0	114.2	90.0	160.0	
24"		90.0	91.0	90.0	160.0	
26-1/2"		82.4	82.4	90.0	160.0	
32"		68.3	68.3	90.0	159.3	
37"		(4)	59.0	59.0	90.0	137.8
40"		54.6	54.6	90.0	127.4	
48"		45.5	45.5	90.0	106.2	
53-1/8"		41.1	41.1	90.0	95.9	
19-1/8"	63"	90.0	114.7	90.0	160.0	
24"		90.0	91.4	90.0	160.0	
26-1/2"		82.8	82.8	90.0	160.0	
32"		68.6	68.6	90.0	160.0	
37"		(5)	59.3	59.3	90.0	138.4
40"		54.9	54.9	90.0	128.0	
48"		45.7	45.7	90.0	106.7	
53-1/8"		41.3	41.3	90.0	96.4	
19-1/8"	76"	90.0	114.1	90.0	160.0	
24"		90.0	90.9	90.0	160.0	
26-1/2"		82.4	82.4	90.0	160.0	
32"		68.2	68.2	90.0	159.2	
37"		(6)	59.0	59.0	90.0	137.7
40"		54.6	54.6	90.0	127.3	
48"		45.5	45.5	90.0	106.1	
53-1/8"		41.1	41.1	90.0	95.9	

* NO. IN PARENTHESIS INDICATE NO. OF ANCHORS PER JAMB.

EQUAL LITES WINDOWS						
DESIGN LOAD CAPACITY - PSF						
FLANGE DIMS.		ANCHORS TYPE 'A'		ANCHORS TYPE 'B'		
WIDTH	HEIGHT	EXT.(+)	INT.(-)	EXT.(+)	INT.(-)	
19-1/8"	26"	90.0	160.0	90.0	160.0	
24"		90.0	132.9	90.0	160.0	
26-1/2"		90.0	120.4	90.0	160.0	
32"		90.0	99.7	90.0	160.0	
37"		(3)	86.2	86.2	90.0	160.0
40"		79.8	79.8	90.0	160.0	
48"		66.5	66.5	90.0	155.1	
53-1/8"		60.0	60.0	90.0	140.1	
19-1/8"	38-3/8"	90.0	160.0	90.0	160.0	
24"		90.0	150.1	90.0	160.0	
26-1/2"		90.0	135.9	90.0	160.0	
32"		90.0	112.6	90.0	160.0	
37"		(5)	90.0	97.4	90.0	160.0
40"		90.0	90.1	90.0	160.0	
48"		75.0	75.0	90.0	160.0	
53-1/8"		67.8	67.8	90.0	158.2	
19-1/8"	50-5/8"	90.0	160.0	90.0	160.0	
24"		90.0	136.5	90.0	160.0	
26-1/2"		90.0	123.7	90.0	160.0	
32"		90.0	102.4	90.0	160.0	
37"		(6)	88.6	88.6	90.0	160.0
40"		81.9	81.9	90.0	160.0	
48"		68.3	68.3	90.0	159.3	
53-1/8"		61.7	61.7	90.0	143.9	
19-1/8"	63"	90.0	160.0	90.0	160.0	
24"		90.0	128.0	90.0	160.0	
26-1/2"		90.0	115.9	90.0	160.0	
32"		90.0	96.0	90.0	160.0	
37"		(7)	83.0	83.0	90.0	160.0
40"		76.8	76.8	90.0	160.0	
48"		64.0	64.0	90.0	149.3	
53-1/8"		57.8	57.8	90.0	134.9	
19-1/8"	76"	90.0	152.2	90.0	160.0	
24"		90.0	121.3	90.0	160.0	
26-1/2"		90.0	109.8	90.0	160.0	
32"		90.0	90.9	90.0	160.0	
37"		(8)	78.7	78.7	90.0	160.0
40"		72.8	72.8	90.0	160.0	
48"		60.6	60.6	90.0	141.5	
53-1/8"		54.8	54.8	90.0	127.8	

* NO. IN PARENTHESIS INDICATE NO. OF ANCHORS PER JAMB.



TYPICAL ELEVATION
TESTED UNIT

Approved as complying with the
Florida Building Code
Date 02/19/04
NOA# 03-1201.04
Miami Dade Product Control
Division
By [Signature]

Engr: DR. HUMAYOUN FAROOQ
STRUCTURES
FLA. PE # 16557
C.A.N. 3538

JAN 19 2004

afsc

AL-FAROOQ CORPORATION
ENGINEERS, PLANNERS & PRODUCT DESIGN
1235 SW 87 AVE
MIAMI, FLORIDA 33174
TEL. (305) 264-8100 FAX. (305) 262-6978
COMP-ANL\W03-95IWS


SERIES 1072 ALUM SINGLE HUNG WINDOW (S.M.I.)
INNOVATIVE WINDOW CONCEPTS
505 INDUSTRIAL WAY
BOYNTON BEACH, FL. 33426
TEL. (561) 493-2303 FAX. (561) 493-2302

no.	date	description
A	01.13.04	NO CHANGE THIS SHEET

date: 10-20-03
scale: 1/2" = 1'-0"
dr. by: H-AMID
chk. by:

drawing no.
W03-95

sheet 2 of 5



WOOD BUCKS NOT BY I.W.C., MUST SUSTAIN LOADS IMPOSED BY GLAZING SYSTEM AND TRANSFER THEM TO THE BUILDING STRUCTURE.

TYPICAL ANCHORS: SEE ELEV. FOR SPACING

ANCHORS TYPE 'A'

3/16" TAPCONS

INTO 2BY WOOD BUCKS OR WOOD STRUCTURE
1-3/8" MIN. PENETRATION INTO WOOD

THRU 1BY BUCKS INTO MASONRY OR DIRECTLY INTO MASONRY
1-1/4" MIN. EMBED INTO CONC. OR MASONRY

ANCHORS TYPE 'B'

1/4" TAPCONS

INTO 2BY WOOD BUCKS OR WOOD STRUCTURE
1-1/2" MIN. PENETRATION INTO WOOD

THRU 1BY BUCKS INTO MASONRY OR DIRECTLY INTO MASONRY
1-1/4" MIN. EMBED INTO CONC. OR MASONRY

3/16" TEKS OR SELF DRILLING SCREWS

INTO METAL STRUCTURES (1/8" MIN. THICKNESS)
(1/4" MAX. SHIM SPACE)

#10 SMS OR SELF DRILLING SCREWS

INTO DADE COUNTY APPROVED MULLIONS
(NO SHIM SPACE)

SEALANT:

ALL JOINTS AND FRAME CONNECTIONS SEALED WITH SCHNEE MOREHEAD SEAM SEALER SM5504.

Approved as complying with the
Florida Building Code
Date 02/19/04
NOA# 03-1201.04
Miami Dade Product Control
Division
By: *Guadalupe Berman*

Engr. DR. HUMAYOUN FAROOQ
STRUCTURES
FLA. PE # 16557
C.A.N. 3538

[Signature]

JAN 19 2004

afc

AL-FAROOQ CORPORATION
ENGINEERS, PLANNERS & PRODUCT DESIGN
1235 SW 87 AVE
MIAMI, FLORIDA 33174
TEL. (305) 264-8100 FAX. (305) 262-6978

SERIES 1072 ALUM SINGLE HUNG WINDOW (S.M.I.)
INNOVATIVE WINDOW CONCEPTS
505 INDUSTRIAL WAY
BOYNTON BEACH, FL. 33426
TEL. (561) 493-2303 FAX. (561) 493-2302


no.	date	by	description
A	01.13.04		NO CHANGE THIS SHEET

date: 10-20-03
scale: 1/2" = 1"
dr. by: HAMID
chk. by:


drawing no.
W03-95

sheet 3 of 5


COMP-ANL\W03-95\WS



ITEM NO.	PART NO.	QUANTITY	DESCRIPTION	MATERIAL	MANF./SUPPLIER/REMARKS
1	021-029	1	FRAME HEAD	6063-T5	ARCH ALUM.
2	021-002	1	FRAME SILL	6063-T5	ARCH ALUM.
3	021-005	2	FRAME JAMB	6063-T5	ARCH ALUM.
4	022-007	1	MTG. RAIL	6063-T5	ARCH ALUM.
6	022-004	1	VENT TOP RAIL	6063-T5	ARCH ALUM.
7	022-001	1	VENT BOTTTOM RAIL	6063-T5	ARCH ALUM.
8	021-003	2	VENT SIDE RAIL	6063-T5	ARCH ALUM.
18	021-011	4/ LITE	GLAZING BEAD	6063-T5	ARCH ALUM.
23	021-008	2/ VENT	SNAP LATCH (2 @ 3" LG)	6063-T5	ARCH ALUM.
24	025-000	2	ULTRA LIFT BALANCE		CALDWELL MFG
24A	024-000	2	BLOCK & TACKLE BALANCE		BSI
25	006-001	2	SPRING	ST/ST	IND. SPRING
26	004-005	-	UEK BRACKET	STEEL	CALDWELL MFG
27	010-001	-	SASH STOP	RIGID VINYL	MASTER TOOL
28	004-002	-	SWEEP LOCK @ 7" FROM ENDS	METAL	SULLIVAN & ASSOC.
29	016-001	AS REQD.	FIN SEAL	WOOL PILE	ULTRA FAB
30	023-001	-	FILLED BULB VINYL		AMESBURY
31	015-009	-	CHIMNEY PLUG	CLOSED CELL	FRANK LOWE RUBBR
33	008-014	AS REQD.	#8X1 PPH SMS	ST/ST	
34	008-031	2/ END	#10X1 PPH SMS	ST/ST	
37	012-001	-	SEAM SEALER SM5504	ACRYLIC	SCHNEE MOREHEAD
39	008-010	-	#8X1/2 UCFHPH SMS	ST/ST	
40	008-017	-	#8X1 1/4 FHPH SMS	ST/ST	
42	015-001	AS REQD.	BULB VYNIL	VINYL	MASTER TOOL
45	015-006	-	0.150 SPACER	VINYL	FRANK LOWE RUBBR
46	012-004	-	DOW 995	SILICONE	DOW CORNING
49	010-010	-	SASH GUIDE TOP	RIGID PVB	M & M PLASTICS
50	010-011	-	SASH GUIDE BOT	RIGID PVB	M & M PLASTICS
51	008-002	-	#6X1/2 FHPH SMS	ST/ST	
55	003-001	AS REQD.	ROLL FORM SCREEN FRAME	ALUMINUM	FLORIDA SCREEN



TYPICAL ANCHORS
SEE ELEV. FOR SPACING



METAL STRUCTURES
(STEEL OR ALUM. 1/8" MIN. THICK)
STEEL : Fy = 36 KSI MIN.
ALUMINUM : 6063-T5 MIN.

Approved as complying with the
Florida Building Code
Date 02/19/04
NOA# 03-1201-04
Miami Dade Product Control
Division
By *Glenn Berner*

Engr: DR. HUMAYOUN FAROOQ
STRUCTURES
FLA. PE # 18557
C.A.N. 3538
[Signature]
JAN 19 2004

afsc

AL-FAROOQ CORPORATION
ENGINEERS, PLANNERS & PRODUCT DESIGN
1235 SW 87 AVE
MIAMI, FLORIDA 33174
TEL. (305) 264-8100 FAX. (305) 262-6978


SERIES 1072 ALUM SINGLE HUNG WINDOW (S.M.I.)
INNOVATIVE WINDOW CONCEPTS
505 INDUSTRIAL WAY
BOYNTON BEACH, FL. 33426
TEL (561) 493-2303 FAX. (561) 493-2302

COMP-ANL\W03-95IWS


revisions:	no	date	by	description
	A	01.13.04		NO CHANGE THIS SHEET

date: 10-20-03
scale: 1/2" = 1"
dr. by: H-AMID
chk. by:


drawing no.
W03-95
sheet 4 of 5




1 FRAME HEAD




4 FIXED MEETING RAIL




3 FRAME JAMB




6 VENT TOP RAIL




2 FRAME SILL




7 VENT BOTTOM RAIL





23 LATCH




8 VENT SIDE RAIL




18 GLAZING BEAD



FRAME CORNERS



VENT TOP CORNER



VENT BOTTOM CORNER

Approved as complying with the Florida Building Code
 Date: 02/19/04
 NOAH 03-1201.04
 Miami Dade Product Control
 Division
 By: *Alison Bern*

Engr: DR. HUMAYOUN FAROOQ
 STRUCTURES
 FLA. PE # 16557
 C.A.N. 3538
 JAN 19 2004

afc
AL-FAROOQ CORPORATION
 ENGINEERS, PLANNERS & PRODUCT DESIGN
 1235 SW 87 AVE
 MIAMI, FLORIDA 33174
 TEL. (305) 264-8100 FAX. (305) 262-6978
 COMP-ANL\W03-95IWS

SERIES 1072 ALUM SINGLE HUNG WINDOW (S.M.I.)
INNOVATIVE WINDOW CONCEPTS
 505 INDUSTRIAL WAY
 BOYNTON BEACH, FL. 33426
 TEL. (561) 493-2303 FAX. (561) 493-2302

no	date	description	by	REV. PER BCCO COMMENTS
A	01.13.04			

date: 10-20-03
 scale: 1/2" = 1"
 dr. by: HAMID
 chk. by:

drawing no.
W03-95
 sheet 5 of 5