



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**CertainTeed Corporation (PA)
1400 Union Meeting Road
Blue Bell, PA 19422**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: CertainTeed Coatings and Cements

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This revises NOA #03-0407.09, and consists of pages 1 through 5.
The submitted documentation was reviewed by Frank Zuloaga, RRC



**NOA No.: 04-0630.02
Expiration Date: 08/27/08
Approval Date: 10/21/04
Page 1 of 5**

ROOFING SYSTEM APPROVAL

Category: Roofing
Sub-Category: Cements and Coatings
Fire Classification: See General Limitation #1

1. SCOPE:

CertainTeed's Roof Cements and Coatings, coatings used on existing roof assemblies as described in Section 4 of this Notice of Acceptance.

2. APPROVED DISTRIBUTOR:

CertainTeed Corporation products are also distributed by Bradco Supply Inc., East Coast Supply, and Allied Building Supply, Inc. Signed Manufacturer Distributor Agreements are on file at the Office of Building Code Compliance.

3. LIMITATIONS:

- 3.1 Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this products.
- 3.2 CertainTeed Roof Cements and Coatings shall not be applied in inclement weather conditions.
- 3.3 All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test result shall be made available to BCCO upon request.
- 3.4 All approved products listed herein shall be labeled in compliance with TAS 121.
- 3.5 Change in materials, use or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
- 3.6 These roof coatings shall not be applied over, prepared roofing; i.e., fibercement shingles, quarry slate, cement or clay roof tile, metal shingles, wood shingles or shakes.
- 3.7 CertainTeed Roof Cements and Coatings shall be used as a roof system in accordance with applicable building code. CertainTeed Roof Cements and Coatings is not approved to be used as a repair or recover system.
- 3.8 All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9B-72 of the Florida Administrative Code.

4. INSTALLATION:

- 4.1 CertainTeed Roof Cements and Coating shall be installed in accordance with manufacturer's Product Data Sheet.



NOA No.: 04-0630.02
Expiration Date: 08/27/08
Approval Date: 10/21/04
Page 2 of 5

PHYSICAL PROPERTIES OF COMPONENTS

- Tradename:** FlintPatch
- Application Rate:** This material is applied by trowel spread to an average thickness of 1/8". For systems approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
- Specifications:** ASTM D 4586 type I
- Description:** An asbestos-free, general purpose flashing cement for repairing leaks in shingles, concrete, metal or asphalt roofs.
- Container Size:** 1, 3 and 5 gallons. Note all precautions on container.
- Tradename:** FlintPatch, Caulk Grade
- Application Rate:** This material is applied by caulk gun in an appropriate bead width. For systems approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
- Specifications:** ASTM D 4586 type I
- Description:** Rubber reinforced asbestos-free wet/dry flashing cement for repairing of leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices.
- Container Sizes:** Tubes. Note all precautions on container.
- Tradename:** FlintBond, Brush Grade
- Application Rate:** This material is applied by brush, squeegee, roller or spray at an approximate rate of 1 gal./100 ft². On porous or irregular surfaces, consult manufacturer for application rates. For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
- Specifications:** ASTM D3019 type III
- Description:** A cold applied, SBS polymer modified asphalt adhesive. Used to adhere SBS modified bitumen membranes, base and ply sheets, BUR ply sheets or fully granulated cap sheets.
- Container Size:** 1, 3, 5 gallons. Note all precautions on container
- Tradename:** FlintBond, Trowel Grade
- Application Rate:** This material is applied by trowel in a uniform 1/8"-1/4" thickness. On porous or irregular surfaces, consult manufacturer for application rates. For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
- Specifications:** ASTM D3019 type III
- Description:** A cold applied, SBS polymer modified asphalt adhesive. Used to make repairs on existing modified applications and flashings on vertical surfaces.
- Container Size:** 1, 3 and 5 gallons. Note all precautions on container
- Tradename:** FlintBond, Caulk Grade
- Application Rate:** This material is applied by caulk in an appropriate bead width. For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
- Specifications:** ASTM D3019 type III
- Description:** A cold applied, SBS polymer modified asphalt adhesive. Used to make repairs on existing modified applications and flashings on vertical surfaces.
- Container Size:** Tube. Note all precautions on container



Tradename: FlintCoat-A150
Application Rate: Applied by brush, roller or spray at an approximate rate of 1 to 1.5 gal/100 ft². For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 2824 Type III
Description: An asbestos-free fibrated aluminum roof coating consisting of asphalts, pigment flakes of aluminum, solvents and reinforcing fibers. For use on modified bitumen membranes, metal corrugated decks and steep asphalt which has aged for 90 days.
Container Size: 5, 55 gallons. Note all precautions on container.

Tradename: FlintPrime
Application Rate: Applied by brush or spray at an approximate rate of ¾" to 1 gal/100 ft². For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance
Specifications: ASTM D-41
Description: A general purpose asphalt primer. For use in the preparation of all types of surfaces previous to the application of hot or cold asphalt coatings.
Container Size: Spray cans, 1, 3 and 5 gallons. Note all precautions on container.

Tradename: FlintCoat-A NF
Application Rate: Applied by brush, roller or spray at an approximate rate of ½" to 1 gal/100 ft². For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 2824 type I
Description: A non-fibrated aluminum roof coating consisting of asphalt, solvents and fine aluminum flakes.
Container Size: 5, 55 gallons. Note all precautions on container.

Tradename: FlintCoat-E
Application Rate: Apply by brush or spray at an approximate rate of 4 gal/100 ft². For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 1227 type II Class I
Description: An asbestos-free emulsion roof coating manufactured with refined asphalt, bentonite clay, emulsifiers and fibers.
Container Size: 5, 55 gallons. Note all precautions on container.

Tradename: FlintSeal FA Fibrated Aluminum Roof Coating
Application Rate: Applied by brush, squeegee, roller or spray at an approximate rate of 1 to 1 ½ gal/100sq. ft.. For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 2824 Type III
Description: An asbestos free fibrated aluminum roof coating consisting of asphalts, pigment flakes of aluminum, solvents and reinforcing fibers. For use on modified bitumen membranes, metal corrugated decks and steep asphalt which has aged for 90 days.
Container Size: 1, 5, 55 gallons. Note all precautions on container.



Tradename: FlintSeal NFA Non-Fibrated Aluminum Coating
Application Rate: Applied by brush, roller or spray at an approximate rate of 1 gal/200sq. ft. For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 2824 type I
Description: A non-fibrated aluminum roof coating consisting of asphalt, solvents and fine aluminum flakes.
Container Size: 5, 55 gallons. Note all precautions on container.

Tradename: FlintSeal Mastic
Application Rate: This materials is applied by towel and spread to an advantage thickness of 1/8", approximately 8 gal./sq. For systems approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 4586 type I
Description: A general purpose plastic cements for repairing leaks in shingles, concrete, metal or asphalt roofs.
Container Size: 5 gallons. Notice all precautions on container.

Tradename: FlintSeal Adhesive (Brush and Trowel)
Application Rate: This material is applied by squeegee, roller, brush or towel at a rate of 1 gal./100 sq.ft. On porous or irregular surfaces consult manufacturer for application rates. For system approvals, refer to specific Roof Assembly, Product Control Notice of Acceptance.
Specifications: ASTM D 3019 type III and ASTM D 3409
Description: A cold applied, SBS polymer modified asphalt adhesive. Used to make repairs on existing modified application and flashing on vertical surfaces and to adhere SBS modified bitumen membranes.
Container Size: 5, 55 gallons. Note all precautions on container.

END OF THIS ACCEPTANCE



NOA No.: 04-0630.02
Expiration Date: 08/27/08
Approval Date: 10/21/04
Page 5 of 5