



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**Firstline Corporation
511 Highland Drive
Valdosta GA 31601**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by the BCCO and accepted by the Building Code and Product Review Committee to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: ROOFTEX 30^B™ & PLY-DRY™

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This new NOA consists of pages 1 through 3.
The submitted documentation was reviewed by Frank Zuloaga, RRC



**NOA No.: 04-0819.04
Expiration Date: 06/09/10
Approval Date: 06/09/05
Page 1 of 3**

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: 07520 Underlayment
Material: Synthetic polymers

1. SCOPE:

This acceptance is for ROOFTEX 30^B™ and PLY-DRY™ Underlayment as manufactured by Firstline Corporation, as described in Section 2 of this Notice of Acceptance, for use with approved prepared roof assemblies.

2. PRODUCT DESCRIPTION:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specification</u>	<u>Product Description</u>
ROOFTEX 30 ^B ™ & PLY-DRY™	40" x 300' 48" x 250' 24" x 250'	N/A	Woven synthetic polymer underlayment with UV protected surface.

3. EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
RADCO Test Report	C9053	RAD-3426	06/17/04
RADCO Test Report	C9053	RAD-3361	01/21/04

4. LIMITATIONS

- 4.1 Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this product
- 4.2 This acceptance is for prepared roofing applications. Minimum deck requirements shall be in compliance with applicable building code.
- 4.3 ROOFTEX 30^B™ and/or PLY-DRY™ shall not be hot mopped, refer to manufacturer's published literature for product compatibility.
- 4.4 Any modifications to this Notice of Acceptance shall void such approval.

5. INSTALLATION

- 5.1 ROOFTEX 30^B™ and/or PLY-DRY™ shall be installed in strict compliance with applicable Building Code.
- 5.2 ROOFTEX 30^B™ and/or PLY-DRY™ shall be installed with a minimum 4-inch head lap in a single layer fashion.
- 5.3 ROOFTEX 30^B™ and/or PLY-DRY™ shall be fastened with corrosion resistant tin-caps and 12 gauge 1 ¼" annular ring-shank nails, spaced 6" o.c. at all laps staggered rows fastened 12" o.c. in the field of the roll at a row spacing of 12 inches on center. For the 24 inch roll a total of two rows of fasteners, and for the 40 & 48 inch rolls a minimum of four rows of fasteners spaced as referenced above.
- 5.4 ROOFTEX 30^B™ and/or PLY-DRY™ is a component used in roof assemblies. Roof assemblies are approved under specific assembly Notice of Acceptance.



NOA No.: 04-0819.04
Expiration Date: 06/09/10
Approval Date: 06/09/05
Page 2 of 3

- 5.5 ROOFTEX 30^B™ and/or PLY-DRY™ may be used with Asphaltic shingles, Wood shakes and shingles, Non-structural metal roofing, and quarry slate. ROOFTEX 30^B™ shall not be used as roof tile underlayment.
- 5.6 ROOFTEX 30^B™ and/or PLY-DRY™ may be used with any approved roof covering Notice of Acceptance listing ROOFTEX 30^B™ and/or PLY-DRY™ as a component part of an assembly in the Notice of Acceptance. If ROOFTEX 30^B™ or PLY-DRY™ is not listed, a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
- 5.7 For fire classification of specific roof assemblies using ROOFTEX 30^B™ and/or PLY-DRY™ refer to a current Approved Roofing Materials Directory for fire ratings of this product.

6. LABELING

- 6.1 All packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo and yellow line to identify the ASTM Standard designation.

7. BUILDING PERMIT REQUIREMENTS

- 7.1 Application for building permit shall be accompanied by copies of the following:
 - 7.1.1 This Notice of Acceptance.
 - 7.1.2 Any other documents required by the Building Official or applicable building code in order to properly evaluate the installation of this material.

END OF THIS ACCEPTANCE



NOA No.: 04-0819.04
Expiration Date: 06/09/10
Approval Date: 06/09/05
Page 3 of 3