



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**Tamko Roofing Products, Inc.
P.O. Box 1404
Joplin, MO 64802**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: TAMKO Coatings and Cements

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No. 03-0507.09 and consists of pages 1 through 8.
The submitted documentation was reviewed by Jorge L. Acebo



**NOA No.: 05-0301.10
Expiration Date: 07/24/08
Approval Date: 10/04/05
Page 1 of 8**

ROOFING SYSTEM APPROVAL

Category: Roofing
Sub-Category: Cements and Coatings
Fire Classification: See General Limitation #1

APPROVED DISTRIBUTERS:

Tamko Roofing Products, Inc products are also distributed by the following suppliers: Allied Building Products Corp., Bitec, The Celotex Corporation, Nord Bitumi U. S. Inc., Rooftop Partners I L.P., Gulfside Supply, Inc., L & W Supply Corporation, East Coast Supply Corporation, Therma-Seal Roofs, Inc., HTH Distributors, Inc., and The Sunniland Corporation. Signed Manufacturer/Distributor Agreements are on file at the Office of Building Code Compliance.

EVIDENCE SUBMITTED

| <u>Test Agency</u> | <u>Test Identifier</u> | <u>Test Name/Report</u> | <u>Date</u> |
|-------------------------------|--|-------------------------|-------------|
| PRI Asphalt Technologies Inc. | LB14194-611C | ASTM D-4479-93 | 03/14/94 |
| PRI Asphalt Technologies Inc. | 28094 #631C 28094 #631G 28094 #504Q | ASTM D-4586-93 | 03/28/94 |
| PRI Asphalt Technologies Inc. | 1615 | ASTM D-449-86 | 03/29/94 |
| PRI Asphalt Technologies Inc. | 97994 #704C 97994 #704G 97994 #704P | ASTM D-2824-85 | 04/08/94 |
| PRI Asphalt Technologies Inc. | 44194 #714C 44194 #714G 44194 #714GM 44194 #714P 44194 #714T | ASTM D-2824-85 | 04/14/94 |
| PRI Asphalt Technologies Inc. | 103401 #690C 103401 #690G 103401 #690P | ASTM D-1227 | 04/21/94 |
| PRI Asphalt Technologies Inc. | LB14194-611G LB14194-611P LB14194-611T | ASTM D-4479-93 | 03/14/94 |



NOA No.: 05-0301.10
Expiration Date: 07/24/08
Approval Date: 10/04/05
Page 2 of 8

| <u>Test Agency</u> | <u>Test Identifier</u> | <u>Test Name/Report</u> | <u>Date</u> |
|---------------------------------|--|---------------------------|-------------|
| PRI Asphalt Technologies Inc. | 21694 #630C 21694 #630 G 21694 #630P 21694 #630 PT 21894 #505C 21894 #505G 21894 #505P | ASTM D3019-85 | 03/14/94 |
| PRI Asphalt Technologies Inc. | 23494 #504C 23494 #504G 23494 #504P | ASTM D-4586-93 | 03/17/94 |
| PRI Asphalt Technologies Inc. | 25794 #501C 25794 #502C 25794 #502G 25794 #502GT 25794 #502P | ASTM D-4586-93 | 03/23/94 |
| PRI Asphalt Technologies Inc. | 26894 #601C 26894 #601G 26894 #601P | ASTM D41 | 03/25/94 |
| PRI Asphalt Technologies Inc. | 28094 #631P | ASTM D-4586-93 | 03/28/94 |
| PRI Asphalt Technologies Inc. | 60LS #553A | ASTM D962 | 05/11/94 |
| PRI Asphalt Technologies Inc. | 63594 #600P | ASTM D41 | 07/13/94 |
| PRI Asphalt Technologies Inc. | 69494 #715.1 | ASTM D2824-85 Type III | 07/21/94 |
| PRI Asphalt Technologies Inc. | TAP-057-02-01 | ASTM D 3019 | 03/22/02 |
| Underwriters Laboratories, Inc. | 99NK39450 | ASTM D4586 | 02/07/00 |



PHYSICAL PROPERTIES OF COMPONENTS

- Trade names: **Tam-Pro Q-10 Elastomeric Flashing Cement**
Tam-Pro Q-15 Elastomeric Flashing Cement
- Thickness: See Systems Approvals Below.
- Specifications: ASTM D-4586, Type I; ASTM D 3409
- Description: A smooth trowel grade modified asphalt based mastic used in the construction of fiberglass or organic built-up; roofing. Generally applied in thickness of 1/8", it may also be used for repairs or in conjunction with cotton or fiberglass reinforcing mesh.
- Container Size: 3, 5 gallons. Note all cautions on container label.
- Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.
- Trade name: **Tam-Pro Q-5 Heavy Bodied Flashing Cement**
- Thickness: See Systems Approvals Below.
- Specifications: ASTM D-4586, Type I
- Description: A thick smooth trowel grade asphalt based cement used in the construction of fiberglass or organic built-up roofing. Generally applied in 1/8" thickness, it may also be used for repairs or in conjunction with cotton or fiberglass reinforcing mesh.
- Container Size: 3, 5 gallons. Note all cautions on container label.
- Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.
- Trade Name: **Tam-Pro 808 Cold Application Cement**
- Thickness: See Systems Approvals Below.
- Specifications: ASTM D-3019 Type III
- Description: A brushable grade asphalt cement for use as blind nail or lap cement when used with 90# MSR or selvage roofing.
- Container Size: 5 gallons. Note cautions on container label.
- Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.



Trade Name: **Tam-Pro 843 Fire Rated (FR) Fibered Aluminum Roof Coating**

Thickness: See Systems Approvals Below.

Specifications: ASTM D-2824 Type III

Description: A brush or spray grade fire retardant, asphalt surfacing material containing aluminum pigment to provide weathering and fire protection surfacing for Built-Up and modified bitumen roof systems. Built-Up roofs should weather 90 days prior to applying aluminum roof coating or 5 days if applied over Vector 90F Roof Emulsion. Over modified bitumen membrane in accordance with membrane manufacturer's instructions. Apply at the rate of 1 to 2 gal/100 sq. ft.

Container Size: 5 or 55 gallons. Note cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

Trade Name: **Tam-Pro 856 CPA Premium SBS Adhesive or Premium SBS Adhesive**

Thickness: See Systems Approvals Below.

Specifications: ASTM D 3019 Type III

Description: A brush, squeegee or spray grade SBS modified asphalt adhesive for use in adhering SBS modified bitumen roofing membranes. Apply evenly at a rate of 1 to 1 1/2 gal/100 sq. ft. Application rates in excess of these parameters may cause membrane softening, blistering or granule loss. Note: Not for use with APP modified bitumen membranes or membranes having a plastic or polyethylene backing.

Container Size: 3, 5 or 55 gallons. Note cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

Trade Name: **Tam-Pro Q-20 CPA Premium SBS Flashing Cement or Premium SBS Flashing Cement Tube**

Thickness: See Systems Approvals Below.

Specifications: ASTM-D4586, Type I

Description: A smooth trowel grade SBS modified asphalt mastic for use in vertical flashing details of SBS modified bitumen membranes roof systems. Apply at a nominal thickness of 1/8" per SBS membrane manufacturers' recommendations and published flashing details. Note: Not for use with APP modified bitumen membranes or membranes having a plastic or polyethylene backing.

Container Size: 10.5 oz. Cartridges, 3 or 5 gallons. Note cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.



Trade Name: **Tam-Pro 829 Fibered Roof Coating**

Thickness: See Systems Approvals Below.

Specifications: ASTM D-4479

Description: A brush grade asphalt based coating used to protect or prolong the life of asphalt or metal roofing. Application rate depends on porosity of surface. Consult manufacturer.

Container Size: 5 or 55 gallons. Note cautions on container labels.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

Trade Name: **Tam-Pro 801 Plastic Roof Cement or Contractor's Choice Plastic Roof Cement**

Thickness: See Systems Approvals Below.

Specifications: ASTM D-4586, Type I
Asbestos Free

Description: Multipurpose trowelable asphalt based cement used in new flat roof or reroof construction to "tie off", edge strips, gravel guards, etc. Used in shingle application to seal edges or seal down shingles.

Container Size: 3 or 5 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

Trade Name: **Tam-Pro 846 Fibered Emulsion Coating**

Thickness: See Systems Approvals Below.

Specifications: ASTM D-1227 Type II

Description: A brush or spray grade water/asphalt emulsion combined with bentonite clays and fibers. Provides a protective coating over asphalt roofs at the application rate of 3 to 4 gal/100 sq. ft. May also be used as a surface coat prior to applying aluminum roof coating. For surfacing apply at a rate of 1 1/2 to 2 gal/ 100 sq. ft.

Container Size: 5 gallons. Note cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.



Trade Name: **Tam-Pro 854 Fibered Aluminum Roof Coating 1.5#**
Tam-Pro 840 Fibered Aluminum Roof Coating 2#
Tam-Pro 841 Fibered Aluminum Roof Coating 3#

Thickness: See Systems Approvals Below.

Specifications: ASTM D-2824 Type III
Asbestos Free

Description: A brush or spray grade asphalt surfacing material containing aluminum pigment to provide weathering protection over Built-Up, metal or mobile home roof systems. Apply at the rate of 1 to 2 gall/100 sq. ft.

Container Size: 5 or 55 gallons. Note cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

Trade Name: **Tam-Pro 803 Wet or Dry Surface Plastic Roof Cement**

Thickness: See Systems Approvals Below.

Specifications: ASTM D 4586, Type I
Asbestos Free

Description: A thick trowel grade asphalt based cement containing additives to enhance bonding to wet surfaces. Used primarily as a repair medium on wet or damp roofs or as a plastic cement in new or reroof construction.

Container Size: 3 or 5 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

Trade Name: **Tam-Pro 830 Non-Fibered Aluminum Roof Coating 1.5#**
Tam-Pro 834 Non-Fibered Aluminum Roof Coating 2#
Tam-Pro 855 Non-Fibered Aluminum Roof Coating 3#

Thickness: See Systems Approvals Below.

Specifications: ASTM D-2824 Type I

Description: A non-fibered brush or spray grade asphalt surfacing material containing aluminum pigment to provide weathering protection over asphalt, metal or mobile home roofs. Apply at the rate of 1 gal/100 sq. ft. on asphalt roofs or 1 gal/200 sq. ft. on metal surfaces.

Container Size: 5 or 55 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.



Trade Name: **Tam-Pro 813 Quick Dry Primer**

Thickness: See Systems Approvals Below.

Specifications: ASTM D-41

Description: A brush grade, asbestos free, asphalt based material used to prepare concrete, masonry, metal and other surfaces to receive hot or cold asphalt materials used to adhere roof membranes. Apply with brush or spray. Application rate varies depending upon surface. Consult manufacturer.

Note: Not for use with coal tar materials.

Container Size: 1, 5 or 55 gallons. Note all cautions on container label.

Systems Approvals: Methods of application and quantities shall comply specific Roof Assembly, Product Control Notice of Acceptance.

LIMITATIONS

1. Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire rating of this product.
2. Tamko Roofing Products shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to BCCO upon request.
5. All approved products listed herein shall be labeled in compliance with TAS 121.
6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
7. Tamko Roofing Products shall be applied in accordance with manufacturer's published application instructions.

END OF THIS ACCEPTANCE



NOA No.: 05-0301.10
Expiration Date: 07/24/08
Approval Date: 10/04/05
Page 8 of 8