



BUILDING CODE COMPLIANCE OFFICE (BCCO)
 PRODUCT CONTROL DIVISION

MIAMI-DADE COUNTY, FLORIDA
 METRO-DADE FLAGLER BUILDING
 140 WEST FLAGLER STREET, SUITE 1603
 MIAMI, FLORIDA 33130-1563
 (305) 375-2901 FAX (305) 375-2908

NOTICE OF ACCEPTANCE (NOA)

Karnak Corporation
 330 Central Avenue
 Clark, NJ 07066

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: P-21 Cold Process Coating System

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This renews NOA No. 00-1227.03 and consists of pages 1 through 3.
 The submitted documentation was reviewed by Jorge L. Acebo



NOA No.:05-1207.02
Expiration Date: 05/24/11
Approval Date: 03/23/06
 Page 1 of 3

ROOFING ASSEMBLY APPROVAL

Category: Roofing
Sub-Category: Maintenance Coating
Materials: Asphalt
Maximum Design Pressure: N/A

TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:

<u>Products</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
(#19 AF) Flashing Cement	1,5 gallon pails	ASTM D 4586 type I	Trowel grade, asphalt, flashing cement.
(#78 AF) Cold Process Cement	5,55 gallons	ASTM D 3019 type III, ASTM D 4479 type I	Multipurpose asphalt cement for lap sealing, blind nail coverings and other sealing purposes.
(#108) Primer	5,55 gallons	ASTM D 41	Primer for use on wood, concrete, metal, masonry and tile.
(#55) UG Cotton Fabric	Various Width Rolls	Proprietary	Cotton Reinforcement fabric.
(#3036) Poly Mat	Various Width Rolls	Proprietary	Reinforcement fabric manufactured of continuous polyester filaments bonded at the filament junctions.
(#5548) Resat- Mat	Various Width Rolls	Proprietary	Reinforcement fabric manufactured of continuous polyester filaments bonded at the filament junctions.

Evidence Submitted:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Underwriter Laboratories, Inc.	R12199	ASTM Compliance	07/28/94
The Center for Applied Engineering, Inc.	07-07-00-70	ASTM Compliance	06/09/94
Worth Engineering, Inc.	Job No. 9204	ASTM Compliance	03/03/92



NOA No.:05-1207.02
Expiration Date: 05/24/11
Approval Date: 03/23/06
Page 2 of 3

Maintenance Coating Application:

Preparation: Remove all loose gravel, dirt, dust and any foreign matter that may inhibit adhesion of coating by vacuuming, sweeping, power brooming or power washing. Repair all blisters and delaminations with Karnak #19AF Flashing Cement and #3036 Poly-Mat or #55G Cotton Membrane.

All existing roof surface shall be primed with Karnak #108 Asphalt Primer at a rate of 1 gal/sq. The primer shall be fully cured (dry to the touch) before coating the roof.

Coating Application: Coat clean, primed and dry existing roof with Karnak #78AF Cold Process Fibered Roof Cement at a minimum rate of 3 gal/sq.

Embed the polyester reinforcing scrim cloth (Karnak #5548 Resat-Mat) into the Karnak #78AF. Karnak #5548 mat shall be broomed into the wet coating.

Followed by a second application of Karnak #78AF Cold Process Fibered Asphalt Roof Cement applied at rate of not less than 4 gal/sq., completely covering the polyester scrim.

Surfacing: Embed dry, clean dry gravel into the "wet" coating at a minimum rate of not less than 400lb/sq.

System Limitations:

1. This Notice of Acceptance is for a Roof Maintenance Coating System as described by applicable building code.
2. All product and/or product containers shall bear the manufacturer's name and logo and the Metro-Dade Logo for identification in the field.
3. Karnak P-21 system shall not be utilized in areas of ponding water.

END OF THIS ACCEPTANCE



NOA No.:05-1207.02
Expiration Date: 05/24/11
Approval Date: 03/23/06
Page 3 of 3