



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**Tremco Incorporated
3735 Green Road
Beachwood, OH 44122**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Cements, Adhesives & Coatings

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This renews NOA No, 02-0507.01 and consists of pages 1 through 5.
The submitted documentation was reviewed by Jorge L. Acebo.



**NOA No.: 07-0321.10
Expiration Date: 06/27/12
Approval Date: 05/10/07
Page 1 of 5**

ROOFING SYSTEM APPROVAL

Category: Roofing
Sub-Category: Cements and Coatings

EVIDENCE SUBMITTED

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Underwriter Laboratories, Inc.	R6692	Wing Uplift and Fire Classification	
PRI Asphalt Technologies, Inc.		ASTM D 4479	7/3/96
PRI Asphalt Technologies, Inc.		ASTM D 1227	7/3/96
PRI Asphalt Technologies, Inc.		ASTM D 4586	7/3/96
PRI Asphalt Technologies, Inc.		ASTM D 2824	5/25/99



NOA No.: 07-0321.10
Expiration Date: 06/27/12
Approval Date: 05/10/07
Page 2 of 5

PHYSICAL PROPERTIES OF COMPONENTS

- Tradename:** BURMastic® Adhesive
- Thickness:** See Systems Approvals Below
- Specifications:** ASTM D 4479
- Description:** BURMastic® is a proprietary asbesto-free cold applied asphalt surfacing material for built-up-roofs. Coverage Rate 4-5 gal/sq.
- Container Size:** 5 and 55 gallons. Note all precautions on container.
- Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.
-
- Tradename:** Tremlastic™, Emulsified Bitumen Roof Coating
- Thickness:** See Systems Approvals Below
- Specifications:** ASTM D 1227, Type III
- Description:** A cold-applied modified asphalt emulsion used as a protective coating on smooth asphalt roofs and flashings. Coverage Rate: 4-5 gal/sq.
- Container Size:** 5 and 55 gallons. Note all precautions on container.
- Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.
-
- Tradename:** Tremco One-Coat Aluminum
- Thickness:** See Systems Approvals Below
- Specifications:** ASTM D 2824, Type III
- Description:** An asphalt-base, heavily fibrated aluminum roof coating formulated with a blend of rust inhibiting oils. Used as an exterior grade maintenance coating used to provide a protective and reflective weathering surface for all types of vertical and horizontal surfaces, such as asphalt emulsion coated roof surfaces, granule surfaced modified bitumen, and metal.
- Container Size:** 5 and 55 gallons. Note all precautions on container.
- Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.



Tradename: ELSTM, Asphalt Roof Cement (Asbestos-Free)

Thickness: See Systems Approvals Below

Specifications: ASTM D 4586

Description: An asphalt-base, heavily fibrated mastic blended with penetrating oils and plasticizing agents. Used to repair and restore flashings and asphalt built-up-roofing defects including blisters, cracks, and punctures. Trowel applied at an approximate rate of 12 ft²/gal.

Container Size: 5 and 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.



NOA No.: 07-0321.10
Expiration Date: 06/27/12
Approval Date: 05/10/07
Page 4 of 5

LIMITATIONS

1. Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Tremco, Inc. products shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to BCCO upon request.
5. All approved products listed herein shall be labeled in compliance with TAS 121.
6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance
7. Tremco, Inc shall be applied in accordance with manufacturer's published application instructions.

END OF THIS ACCEPTANCE



NOA No.: 07-0321.10
Expiration Date: 06/27/12
Approval Date: 05/10/07
Page 5 of 5