



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**Elastomeric Roofing Systems, Inc.
6900 Bleck Drive
Rockford, MN 55373**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: OlyBond, OlyBond 500 & OlyBond 500 Green

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No. 07-0404.01 and consists of pages 1 through 3.
The submitted documentation was reviewed by Jorge L. Acebo.



**NOA No 07-1012.08
Expiration Date: 07/29/12
Approval Date: 11/29/07
Page 1 of 3**

ROOFING ASSEMBLY APPROVAL

Category: Roofing
Sub-Category: Cements, Adhesives and Coatings
Type: Adhesives
Sub-Type: Polyurethane

SCOPE:

This approves OlyBond, OlyBond 500 & OlyBond 500 Green Adhesive by the Elastomeric Roofing Systems, Inc., as described in this Notice of Acceptance. The use of this acceptance is limited to those roof assemblies where OlyBond & OlyBond 500 Adhesive is specifically listed as an accepted component.

PRODUCT DESCRIPTION:

Spray Polyurethane Foam with the properties described below:

Description	Test	Properties
OlyBond Adhesive		
Flame Spread Index	ASTM E84	15
Smoke Develop Index	ASTM E84	10
Self Ignition Temperature	ASTM D1929-91	698° F
Density @ 73° F	ASTM D 1622	3.45 lb/ft ³
Compressive Strength @ 10% deformation	ASTM D 1621	11.4 psi.
Tensile	ASTM D 1623	34.9 psi.
Water Absorption	ASTM D 2842	4.30%
OlyBond 500 & OlyBond 500 Green Adhesive		
Flame Spread Index	ASTM E84	15
Smoke Develop Index	ASTM E84	10
Self Ignition Temperature	ASTM D1929-91	698° F
Density @ 73° F	ASTM D 1622	4.41 lb/ft ³
Compressive Strength @ 10% deformation	ASTM D 1621	5.6 psi.
Tensile	ASTM D 1623	9 psi.
Water Absorption	ASTM D 2842	16.1%

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Specification</u>	<u>Date</u>
PRI Asphalt Technologies, Inc.	ERS-004-02-01	ASTM D 1621	05/09/02
		ASTM D 1622	
		ASTM D 1623	
		ASTM D 2842	
Underwriters Laboratories, Inc.	UL 723	02NK7835	03/18/02
Factory Mutual System	3001472	4450/4470	04/14/99
	3008869	4470	03/19/01
	3014692	4470	08/05/03
	3031350	4470	09/27/07



NOA No 07-1012.08
 Expiration Date: 07/29/12
 Approval Date: 11/29/07
 Page 2 of 3

LIMITATIONS:

1. OlyBond, OlyBond 500 & OlyBond 500 Green Adhesives shall have a quality control testing program by an approved independent listing agency having unannounced follow-up visits. Follow up test results shall be made available to Miami-Dade County Product Control Department upon request.
2. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9B-72 of the Florida Administrative Code.

INSTALLATION:

OlyBond, OlyBond 500 & OlyBond 500 Green Adhesives shall be installed in strict compliance with the roof assembly's assemblies Notice of Acceptance, and manufacturers published literature.

LABELING:

OlyBond, OlyBond 500 & OlyBond 500 Green Adhesives containers shall comply with the Standard Conditions listed herein.

BUILDING PERMIT REQUIREMENTS

As required by the Building Official or applicable Building Code in order to properly evaluate the installation of this system. This Notice of Acceptance on its own cannot be used to obtain a building permit.

END OF THIS ACCEPTANCE

