MIAMI-DADE

BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION

MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908

NOTICE OF ACCEPTANCE (NOA)

The Garland Company, Inc.
3800 East 91 Street
Cleveland, OH 44105

SCOPE:
This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by the BCCO and accepted by the Building Code and Product Review Committee to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The BCCO (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BCCO reserves the right to revoke this acceptance, if it is determined by BCCO that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Garland's White-Knight Coating Series

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 3.
The submitted documentation was reviewed by Jorge Acebo

MIAMI-DADE COUNTY APPROVED

NOA No.: 08-1024.02
Expiration Date: 04/13/11
Approval Date: 12/24/08

ROOFING SYSTEM APPROVAL

Category: Roofing
Sub-Category: Cement-Adhesive-Coatings
Material: Polyurethane Elastomeric

SCOPE:

This approves "**Garland's White-Knight Coating Series**" as a maintenance roof coating system, as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code..

EVIDENCE SUBMITTED:

Test Agency	Test Identifier	Test Name/Report	Date
PRI Asphalt Technologies	NDJB-007-02-01	ASTM D 6083-TAS 114(H)	08/22/05

PHYSICAL PROPERTIES OF COMPONENTS:

Trade names: **White-Knight FR Base Coat**

Thickness: See Description Below.

Specifications: ASTM D 6083, FBC (HVHZ) TAS 114(H) Delamination

Description: A black single component aromatic solvent based polyurethane elastomeric coating membrane that is applied as a base coat at an application rate of: 0.5 gal./100 ft^2 minimum.
- SBS Roofs: Apply to a minimum thickness of 8 dry mils
- EPDM Roofs: Apply to a minimum thickness of 8 dry mils
- TPO Roofs:Apply to a minimum thickness of 8 dry mils
- PVC Roofs:Apply to a minimum thickness of 8 dry mils

Container Size: 5 and 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA..

Trade names: **White-Knight**

Thickness: See Description Below.

Specifications: ASTM D 6083, FBC (HVHZ) TAS 114(H) Delamination

Description: A white single component aromatic solvent based polyurethane elastomeric coating membrane that is applied as a top coat at an application rate of: 1.5 gal./100 ft^2 minimum.
- SBS Roofs: Apply to a minimum thickness of 16 dry mils
- EPDM Roofs: Apply to a minimum thickness of 16 dry mils
- TPO Roofs:Apply to a minimum thickness of 16 dry mils
- PVC Roofs:Apply to a minimum thickness of 16 dry mils

Container Size: 5 and 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA..

MAINTENANCE COATING APPLICATION:

Preparation: Remove all lose gravel, dirt, dust and any foreign matter that may inhibit adhesion of coating by vacuuming, sweeping, power brooming or power washing. Repair all blisters and delaminations.

Coating Application: Coat the clean and dry existing roof with White-Knight FR Base Coat at a minimum rate of: 0.5 gal/sq.(Apply to a minimum thickness of 8 dry mils)

Apply the White-Knight top coat onto White-Knight FR Base Coat at a minimum rate of: 1.5 gal/sq.(Apply to a minimum thickness of 16 dry mils)

LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
2. **Garland's White-Knight Coating Series** shall not be applied in inclement weather conditions.
3. **Garland's White-Knight Coating Series** shall only be applied to EPDM, PVC, TPO and SBS roofing only.
4. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list the products listed herein as part of their roof assemblies Notice of Acceptance.
5. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to BCCO upon request.
6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
7. **Garland's White-Knight Coating Series** shall be applied in accordance with manufacturer's published application instructions and limitations.
8. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9B-72 of the Florida Administrative Code.
9. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.

MIAMI-DADE COUNTY APPROVED

END OF THIS ACCEPTANCE