



**BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION**

**MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908**

NOTICE OF ACCEPTANCE (NOA)

**Soprema, Inc.
310 Quadral Drive
Wadsworth, OH 44281**

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: 'R' NOVA Roof Coating

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This renews NOA#08-0708.01 and consists of pages 1 through 6.
The submitted documentation was reviewed by Alex Tigera.



**NOA No.: 10-0128.02
Expiration Date: 06/02/15
Approval Date: 06/23/10
Page 1 of 6**

ROOFING COMPONENT APPROVAL

Category: Roofing
Subcategory: Cements, Coatings and Adhesives
Deck Type: Roof Maintenance Coating
Materials: Acrylic Elastomeric

SCOPE:

This approves a roofing maintenance coating system using ‘R’ NOVA Roof Coating as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:

PHYSICAL PROPERTIES OF COMPONENTS:

Trade name: ‘R’ NOVA
Thickness: See Systems Approvals Below.
Specification: ASTM D 6083
Description: A premium white elastomeric roof coating water-based acrylic latex coating. All installation details in accordance with manufacturer’s recommended application procedures.
Container Size: 1 and 5 and 275 (Totes) gallons. Note all cautions on container label.

MANUFACTURING LOCATIONS:

- ‘R’ NOVA Roof Coating**
1. Garland, TX
 2. Bartow, FL
 3. Kingman, AZ

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Description</u>	<u>Date</u>
PRI Asphalt Technologies	HGC-023-02-01	ASTM D 6083	07/17/03
	HGC-023-02-01	ASTM D 6083	06/26/06



EXISTING SUBSTRATES:

Substrate: New or Existing Spray Applied Polyurethane Foam
All General Limitations apply.

System 1

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: (Required) Apply two coats of 'R'NOVA in two equal coats at right angles with a combined rate of 2 gal/sq. (70ft²/gal/coat) by brush or spray.

Maximum Design Pressure: N/A

System 2

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A

Substrate: Existing SBS Smooth Surface Modified Bituminous Roof System
All General Limitations apply.

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A



Substrate: Existing SBS Granulated Cap Sheet Modified Bituminous Roof System
All General Limitations apply.

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A

Substrate: Existing APP Modified
All General Limitations apply.

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A

Substrate: Existing Built-Up Roofing System
All General Limitations apply.

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A



Substrate: Existing PVC Membrane Roof Systems
All General Limitations apply.

Preparation: The existing surface should be smooth, clean (using a 10% TSP/water solution), sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A

Substrate: Existing HYPALON Membrane Roof System
All General Limitations apply.

Preparation: The existing surface should be smooth, clean, sound and dry prior to the application of the 'R'NOVA coating. All surface preparation shall be in compliance with the coating manufacture's current published application instructions.

Foundation Coat: Apply one coat of 'R'NOVA at a rate of 1 gal/sq (70ft²/gal) by brush or spray. Allow to thoroughly dry before application of the finish coats.

Finish Coat: Apply 'R'NOVA finish coat at right angles to the foundation coat at a rate of 1 gal/sq. (70ft²/gal) by brush or spray.

Maximum Design Pressure: N/A



LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Soprema products shall not be applied in inclement weather conditions.
3. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to BCCO upon request. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9B-72 of the Florida Administrative Code.
4. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
5. This NOA is for the sole use as a roof maintenance coating system in accordance with applicable Building Code.
6. 'R'NOVA coating shall not be covered with stone chips, screeds, tiles or soil.
7. Approved primer is required on all unprotected iron and steel.
8. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
9. Contractor shall be a Soprema, Inc., trained and approved applicator familiar with the details and specifications published by the manufacturer.
10. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



BUILDING PERMIT REQUIREMENTS:

1. This Notice of Acceptance.
2. Any other documents required by the Building Official or applicable Building Code in order to properly evaluate the installation of this system.

END OF THIS ACCEPTANCE

