



BUILDING AND NEIGHBORHOOD COMPLIANCE DEPARTMENT (BNC)  
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/building/](http://www.miamidade.gov/building/)

**NOTICE OF ACCEPTANCE (NOA)**

**Marco Industries, Inc.**  
9410 E 54<sup>th</sup> Street  
Tulsa, OK. 74145

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Section and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

**DESCRIPTION: Python™ Ridge Vent**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 3.  
The submitted documentation was reviewed by Alex Tigera.



NOA No. 10-1109.03  
Expiration Date: 02/17/16  
Approval Date: 02/17/11

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Static Roof Vent  
**Materials:** Plastic

### TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT

<u>Product</u>	<u>Dimensions</u>	<u>Test Specification</u>	<u>Product Description</u>
Python™ Ridge Vent	Length: 20" Width: 11-3/4" Height: 1"	TAS 100(A)	Fibrous mesh ridge vent used in Asphalt shingle roof systems.

### MANUFACTURING LOCATION

1. Tulsa, OK

### EVIDENCE SUBMITTED

<u>Test Agency/Identifier</u>	<u>Name</u>	<u>Report</u>	<u>Date</u>
PRI Construction Materials Technologies	TAS 100(A)	MII-007-02-01	09/07/10
PRI Construction Materials Technologies	ASTM D 635 ASTM D 1929 ASTM D 2843	MII-007-02-02	01/12/10



NOA No. 10-1109.03  
Expiration Date: 02/17/16  
Approval Date: 02/17/11

## APPROVED APPLICATIONS

- Tradename:** Python™ Ridge Vent
- System Type C:** Mechanical attachment of ridge vent under composition ridge shingle.
- Slot:** Cut a 1" slot along the apex of the roof by cutting 1/2" on each side of the ridge. The 1" slot shall terminate approximately 12" from the rake edge.
- Installation:** Roll out ridge vent centered over the void. Apply a 1/2" wide bead of sealant on the bottom of the vent, approximately 1/2" from the vent edge. Sealant shall also be used at the ends of the vent (after the slot opening) where the vent meets the roof deck.
- Ridge Shingle:** Install pre-manufactured or field cut ridge shingles over the ridge vent in compliance with the shingle manufacturers Notice of Acceptance (NOA) and the installation instructions using two (2) 12 gauge 2-1/4" ring shank galvanized nails per shingle. Drive the fastener ar enough to leave a 1/2" gap between the asphalt shingle on the deck and the ridge shingle applied over the vent.
- Net Free Area:** Refer to manufacturers published literature
- Minimum Slope:** 3:12

## LIMITATIONS:

1. Refer to applicable Building Code for required ventilation.
2. Ridge vent ventilators shall not be installed on roof mean heights greater than 33 ft.
3. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9B-72 of the Florida Administrative Code.

**END OF THIS ACCEPTANCE**



NOA No. 10-1109.03  
Expiration Date: 02/17/16  
Approval Date: 02/17/11