



DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY  
 AFFAIRS (PERA)  
 BOARD AND CODE ADMINISTRATION DIVISION  
**NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY  
 PRODUCT CONTROL SECTION  
 11805 SW 26 Street, Room 208  
 Miami, Florida 33175-2474  
 T (786)315-2590 F (786) 31525-99  
[www.miamidade.gov/pera](http://www.miamidade.gov/pera)

**System Components Corporation**  
 P.O. Box 2432  
 Issaquah, WA 98027

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

**DESCRIPTION: FelTex® High Performance Roof Wrap**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews NOA No. 06-0919.01 and consists of pages 1 through 3.

The submitted documentation was reviewed by Jorge L. Acebo.



NOA No.: 12-0207.01  
 Expiration Date: 03/01/17  
 Approval Date: 03/22/12  
 Page 1 of 3

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Underlayment  
**Material:** Polypropylene

### SCOPE:

This acceptance is for **FelTex® High Performance Roof Wrap**, as described in this Notice of Acceptance, for use with approved prepared roof assemblies where ASTM D226 Type II underlayment is specified and installed with prescribed approved fasteners and fastener densities. Designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

### PRODUCT DESCRIPTION:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specification</u>	<u>Product Description</u>
FelTex® High Performance Roof Wrap	48" x 250' rolls 48" x 100' rolls	ASTM D 226 Type II ASTM D 2626	Synthetic Polymer base sheet with UV stable low-slip backing.

### MANUFACTURING LOCATION:

1. Xiamen, China

### EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Intertek Testing Services	3093039COQ-007A 3093039COQ-007B	ASTM D 226-Type II ASTM D 2626-04	01/18/07

### INSTALLATION:

1. FelTex® High Performance Roof Wrap shall be installed in strict compliance with applicable Building Code.
2. FelTex® High Performance Roof Wrap shall be applied to a smooth, clean and dry roof deck. The roof shall be free of irregularities.
3. FelTex® High Performance Roof Wrap shall be installed with a minimum 4-inch head lap in a shingle fashion.
4. FelTex® High Performance Roof Wrap shall be fastened with corrosion resistant tin-caps and approved roofing nails spaced 6 inches o.c. minimum at all laps and three staggered rows fastened at 12 inches o.c. minimum in the field of the roll. Nails shall be driven flush and 90 degrees to the roof deck.
5. FelTex® High Performance Roof Wrap shall be fastened with some looseness, notably in valley applications.



NOA No.: 12-0207.01  
Expiration Date: 03/01/17  
Approval Date: 03/22/12  
Page 2 of 3

## **BUILDING PERMIT REQUIREMENTS**

Application for building permit shall be accompanied by copies of the following:

1. This Notice of Acceptance.
2. Any other documents required by the Building Official or applicable building code in order to properly evaluate the installation of this material.

## **LIMITATIONS:**

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. This acceptance is for prepared roofing applications. Minimum deck requirements shall be in compliance with applicable building code.
3. FelTex® High Performance Roof Wrap shall not be hot mopped; refer to manufacturer's published literature for product compatibility.
4. FelTex® High Performance Roof Wrap is a component used in roof assemblies. Roof assemblies are approved under specific assembly Notice of Acceptance.
5. FelTex® High Performance Roof Wrap shall not be left exposed as a temporary roof for longer than 30 days of application.
6. FelTex® High Performance Roof Wrap may be used with Asphalt shingles, Wood shakes and shingles, Non-structural metal roofing, and quarry slate. FelTex® High Performance Roof Wrap shall not be used as an underlayment within a roof tile assembly.
7. FelTex® High Performance Roof Wrap may be used with any approved roof covering Notice of Acceptance listing FelTex® High Performance Roof Wrap as a component part of an assembly in the Notice of Acceptance. If FelTex® High Performance Roof Wrap is not listed; a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
8. For fire classification of specific roof assemblies using FelTex® High Performance Roof Wrap refer to a current Approved Roofing Materials Directory for fire ratings of this product.
9. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9N-3 of the Florida Administrative Code.
10. All membranes or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



**END OF THIS ACCEPTANCE**



NOA No.: 12-0207.01  
Expiration Date: 03/01/17  
Approval Date: 03/22/12  
Page 3 of 3