



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

NOTICE OF ACCEPTANCE (NOA)

Tremco Incorporated
3735 Green Road
Beachwood, OH 44122

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Cements, Adhesives & Coatings

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This renews and revises NOA# 11-0301.08 and consists of pages 1 through 8.
The submitted documentation was reviewed by Alex Tigera.



NOA No.: 12-0621.01
Expiration Date: 06/27/18
Approval Date: 04/11/13
Page 1 of 8

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cement-Adhesive-Coatings
Material: N/A

SCOPE:

This approves Tremco’s Cements, Adhesives and Coatings as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

MANUFACTURING LOCATION

1. Cleveland, OH.
2. Medina, OH.

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Underwriter Laboratories, Inc.	R6692	Wing Uplift and Fire Classification	
PRI Asphalt Technologies, Inc.		ASTM D 4479	7/3/96
		ASTM D 1227	7/3/96
		ASTM D 4586	7/3/96
		ASTM D 2824	5/25/99
PRI Construction Materials Technologies, LLC	TRE-068-02-01	ASTM D 3019	12/05/12
	TRE-068-02-01	ASTM D 3019	12/05/12
	TRE-069-02-01	ASTM D 3019	12/05/12
	TRE-070-02-01	ASTM D 4479	12/05/12
	TRE-071-02-01	ASTM D 3019	12/05/12
	TRE-072-02-01	ASTM D 5100	12/05/12
	TRE-075-02-01	ASTM D 6152	12/05/12
	TRE-076-02-01	ASTM D 6152	12/05/12
	TRE-077-02-01	ASTM D 1227	12/05/12
	TRE-078-02-01	ASTM D 1227	12/05/12
	TRE-079-02-01	ASTM D 41-11	12/05/12
	TRE-080-02-01	ASTM D 6083-05	12/05/12
	TRE-081-02-01	ASTM D 2824	12/05/12
	TRE-082-02-01	ASTM D 4586	12/05/12
	TRE-083-02-01	ASTM D 2824	12/05/12
	TRE-088-02-01	ASTM D 3019	4/02/12
	TRE-104-02-01	ASTM D 6947	1/31/13
TRE-105-02-01	ASTM D 3019	1/31/13	
TRE-108-02-01	ASTM D 5100	1/31/13	
FM Approvals	3042560	ASTM D 4470	4/23/12
	3044153	ASTM D 4470	5/8/12
Momentum Technologies, Inc	NX07G1A	ASTM D 7311	3/21/12



PHYSICAL PROPERTIES OF COMPONENTS

Tradename: BURMastic® Adhesive
Thickness: See Systems Approvals Below
Specifications: ASTM D 4479
Description: BURMastic® is a proprietary asbesto-free cold applied asphalt surfacing material for built-up-roofs. Coverage Rate 4-5 gal/sq.
Container Size: 5 and 50 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: BURMastic® Adhesive SF
Thickness: See Systems Approvals Below
Specifications: ASTM D 3019
Description: BURMastic® is a proprietary asbesto-free cold applied solvent free asphalt surfacing material for built-up-roofs. Coverage Rate 4-5 gal/sq.
Container Size: 55 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: BURMastic® FR
Thickness: See Systems Approvals Below
Specifications: ASTM D 4479
Description: BURMastic® is a proprietary asbesto-free cold applied asphalt surfacing material for built-up-roofs with a fire rated flood coat. Coverage Rate 4-5 gal/sq.
Container Size: 5 and 52 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: One-Coat Aluminum
Thickness: See Systems Approvals Below
Specifications: ASTM D 2824, Type III
Description: An asphalt-base, heavily fibrated aluminum roof coating fomulated with a blend of rust inhibiting oils. Used as an exterior grade maintenance coating used to provide a protective and reflective weathering surface for all types of vertical and horizontal surfaces, such as asphalt emulsion coated roof surfaces, granule surfaced modified bitumen, and metal.
Container Size: 5 and 55 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.



Tradename: ELS™, Asphalt Roof Cement (Asbestos-Free)
Thickness: See Systems Approvals Below
Specifications: ASTM D 4586
Description: An asphalt-base, heavily fibrated mastic blended with penetrating oils and plasticizing agents. Used to repair and restore flashings and asphalt built-up-roofing defects including blisters, cracks, and punctures. Trowel applied at an approximate rate of 12 ft²/gal.
Container Size: 2 and 5 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: Tremlastic SP
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: Non-fibered, polymer modified asphalt emulsion.
Container Size: 5 and 53 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: ICE Coating
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: High solids, water-based, elastomeric coating.
Container Size: 5 and 53 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: Rock-It Adhesive
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: A cold applied white, highly reflective, low volatile surfacing adhesive.
Container Size: 5 and 52 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.



Tradename: **Rock-It Adhesive WB**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: A cold applied white, waterbased, highly reflective, asbestos-free, polymeric low volatile surfacing adhesive containing a biobased resin..
Container Size: 5 and 52 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **POWERply White on White Adhesive**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: White cold process adhesive for modified bitumen roof systems applies with a coverage rate of 1 ½ - 2 gallons per square ply.
Container Size: 5 and 52 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **Double Duty Aluminum**
Thickness: See Systems Approvals Below
Specifications: ASTM D 2824
Description: Aluminum pigmented roof coating
Container Size: 1 and 5 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **FAS-n-FREE Adhesive**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: One part, solvent free insulation adhesive
Container Size: 5 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.



Tradename: **POWERply Standard Cold Adhesive**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: Cold applied ply sheet and membrane adhesive
Container Size: 5 and 50 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **POWERply Rubberized Cold Adhesive**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: Cold applied proprietary SEBS modified asbestos free asphalt adhesive for modified bitumen membrane systems.
Container Size: 5 and 52 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **POWERply Modified Hot Melt Adhesive**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: Polymer modified hot melt adhesive
Container Size: 55 lb. Keg. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **THERMmastic Adhesive**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: Polymer modified hot melt adhesive
Container Size: 55 lb. Keg. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.



Tradename: **TREMprime WB**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: Polymer modified asphalt emulsion primer
Container Size: 1, 5 and 53 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **TREMprime QD Low Odor**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: A refined asphalt primer base
Container Size: 1, 5 and 55 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Tradename: **AlphaGuard MT Fluid Applied Maintenance System**
Thickness: See Systems Approvals Below
Specifications: Proprietary
Description: a base coat, a glass mat for system strength, and a top coat restoration maintenance system.
Container Size: 2 and 5 gallons. Note all precautions on container.
Systems Approvals: Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

Installation Procedure: AlphaGuard MT Fluid Applied Roof System for use as a maintenance coating is a fiberglass reinforced polyurethane roof coating, roller applied in three coats. AlphaGuard Re-Prime is applied at 450-600 ft²/gal (11.0 – 14.7 m²/L) over BUR, SBS and APP Modified Bitumen with granule surfacing, APP Modified Bitumen with smooth surfacing, Spray Polyurethane Foam, and Polyisobutylene membranes.

AlphaGuard MT Base Coat is applied over the AlphaGuard Re-Prime at a rate of 3 gal/sq. (1.2 L/m²).

AlphaGuard Glass Mat reinforcement is wet laid into AlphaGuard MT Base Coat.

AlphaGuard MT Top Coat is applied over the AlphaGuard Glass Mat at a rate of 2 gal/sq. (0.8 L/m²). See manufacturers specification for drying time between coats.



LIMITATIONS

1. Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Tremco, Inc. products shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9N-3 of the Florida Administrative Code.
5. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance
7. Tremco, Inc shall be applied in accordance with manufacturer's published application instructions.

END OF THIS ACCEPTANCE



NOA No.: 12-0621.01
Expiration Date: 06/27/18
Approval Date: 04/11/13
Page 8 of 8