

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786)315-2590 F (786) 31525-99

www.miamidade.gov/economy

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

KST Coatings, A Business Unit of the Sherwin Williams Company 101 W. Prospect Ave. Cleveland, OH 44115

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Uni-Flex 41-300 & Kool Seal 66-300 Elastomeric Roof Coatings

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews and revises NOA No. 09-0413.05 and consists of pages 1 through 3. The submitted documentation was reviewed by Jorge L. Acebo.

MIAMI-DADE COUNTY
APPROVED

NOA No.: 14-0408.08 Expiration Date: 07/01/19 Approval Date: 06/19/14 Page 1 of 3

ROOFING COMPONENT APPROVAL

<u>Category</u>: Roofing

Sub-Category: Cement-Adhesive-Coatings

Materials: Elastomeric

SCOPE:

This approves "Uni-Flex 41-300 & Kool Seal 66-300 Elastomeric Roof Coatings" as maintenance roof coatings as manufactured by KST Coatings, as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

MANUFACTURING LOCATIONS:

1. Orlando, FL

EVIDENCE SUBMITTED:

<u>Test Agency</u> <u>Test Identifier</u> <u>Test Name/Report</u> <u>Date</u>
PRI Construction Materials Technologies, LLC KSTC-007-02-01 ASTM D 6083 02/09/09

PHYSICAL PROPERTIES OF COMPONENTS:

Trade names: Uniflex 41-300 Elastomeric Roof Coating

Kool Seal 66-600 Elastomeric Roof Coating

Application Rate: Apply a Base Coat at a minimum rate of 1 gallon per 100 square feet.

Apply a Top Coat at a minimum rate of 1.5 gallons per 100 square feet.

Specifications: ASTM D 6083

Description: Acrylic elastomeric coatings applied as listed above to the following roof surfaces:

- Galvanized Metal Roofs; over one coat of 41-320 Premium Gray Elastomeric at an application of 1 gal/100 ft².
- SBS Granule Surfaced Modified Bitumenous Membrane; over one coat of 41-510 MB Base Coat at an application of 1.5 gal/100 ft².
- EPDM Single Ply Membranes; over one coat of 41-321 SPE Gray Base Coat at an application of 1.5 gal/100 ft².
- Hypalon Single Ply Membranes; over one coat of 41-321 SPE Gray Base Coat at an application of 1.5 gal/100 ft².
- TPO Single Ply Membrane; over one coat of 41-321 SPE Gray Base Coat at an application of 1.5 gal/100 ft².
- PVC Single Ply Membrane; over one coat of 41-321 SPE Gray Base Coat at an application of 1.5 gal/100 ft².
- Concrete (as specified above in application rate)
- Concrete; over one coat of Loxon Primer (A24W300) at an application of .5 gal/100 ft².
- BUR Smooth Surface Membrane; over one coat of 41-510 MB Base Coat at an application of 1.5 gal/100 ft².
- Spray Polyurethane Foam; over one coat of 41-320 Premium Gray Elastomeric at an application of 1.5 gal/100 ft².

Container Size: 5, 55, 275 gallons. Note all cautions on container label.

Systems Methods of application and quantities shall comply with the specific Roof Approvals: Assembly System's Product Control Notice of Acceptance where it exceeds

standards of this NOA.



NOA No.: 14-0408.08 Expiration Date: 07/01/19 Approval Date: 06/19/14 Page 2 of 3

BUILDING PERMIT REQUIREMENTS:

Application for building permit shall be accompanied by copies of the following:

- 1. This Notice of Acceptance
- 2. Any other documents required by the building official or the Applicable Building Code in order to properly evaluate the installation of this system.

LIMITATIONS:

- 1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
- 2. Uni-Flex 41-300 & Kool Seal 66-300 Elastomeric Roof Coatings shall not be applied in inclement weather conditions.
- 3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list the products listed herein as part of their roof assemblies Notice of Acceptance.
- 4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade Product Control upon request.
- 5. Change in materials, use, or manufacture of any products listed herein shall be cause for termination of this Notice of Acceptance.
- 6. Uni-Flex 41-300 & Kool Seal 66-300 Elastomeric Roof Coatings shall be applied in accordance with manufacturer's published application instructions.
- 7. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
- 8. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE



NOA No.: 14-0408.08 **Expiration Date: 07/01/19** Approval Date: 06/19/14

Page 3 of 3