



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474

T (786) 315-2590 F (786) 315-2599

[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

## NOTICE OF ACCEPTANCE (NOA)

**Entegra Roof Tile, Inc.**  
1289 NE 9<sup>th</sup> Ave  
Okeechobee, FL 34972

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: Regal S-Tile

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No.15-1102.05 and consists of pages 1 through 6.  
The submitted documentation was reviewed by Gaspar J Rodriguez.



NOA No.: 16-0421.06  
Expiration Date: 12/16/17  
Approval Date: 10/06/16  
Page 1 of 6

## ROOFING SYSTEM APPROVAL

**Category:** Roofing  
**Sub Category:** Roofing Tiles  
**Material:** Concrete

### 1. SCOPE

This approves a roofing system using **Regal S-Tile**, as manufactured by Entegra Roof Tile as described in Section 2 of this Notice of Acceptance. For the locations where the pressure requirements, as determined by applicable building code, do not exceed the values listed in section 4 herein. The attachment calculations shall be done as a moment based system.

### 2. PRODUCT DESCRIPTION

<u>Manufactured by</u> <u>Applicant</u>	<u>Dimensions</u>	<u>Test</u> <u>Specifications</u>	<u>Product</u> <u>Description</u>
Regal S-Tile	Length: 17 ¼" Width: 13 ¼" ½" thick	TAS 112	High profile concrete roof tile for direct deck, batten, nail-on, mortar or adhesive set applications.
Trim Pieces	Length: varies Width: varies	TAS 112	Accessory trim, concrete roof pieces for use at hips, rakes, ridges and valley terminations.

#### 2.1 MANUFACTURING LOCATION

2.1.1. Deerfield Beach, FL



NOA No.: 16-0421.06  
Expiration Date: 12/16/17  
Approval Date: 10/06/16  
Page 2 of 6

**2.2 EVIDENCE SUBMITTED:**

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Redland Technologies	7161-03 Appendix III	PA 102	Dec. 1991
	7161-03 Appendix III	PA 102(A)	Dec. 1991
	7161-03 Appendix II	PA 108 (Nail-On)	Dec. 1991
	Letter of Aug. 1, 1994	PA 108 (Nail-On)	Aug. 1994
	P09647-01	PA 108(Mortar Set)	Aug. 1994
	P0402	Withdrawal Resistance Testing of screw vs. smooth shank nails	Sept. 1993
The Center for Applied Engineering, Inc.	94-083	PA 101 (Adhesive Set)	April 1994
	94-084	PA 101 (Mortar Set)	May 1994
	25-7094-9	PA 102 (4" Headlap, Nails, Direct Deck, New Construction)	Oct. 1994
	25-7094-6	PA 102 (4" Headlap, Nails, Battens)	Oct. 1994
	25-7183-4	PA 102 (2 Quik-Drive Screws, Direct Deck)	Feb. 1995
	25-7183-3	PA 102 (2 Quik-Drive Screws, Battens)	Feb. 1995
	25-7214-3	PA 102 (1 Quik-Drive Screw, Direct Deck)	March, 1995
	25-7214-7	PA 102 (1 Quik-Drive Screw, Battens)	March, 1995
All State Engineering & Testing Consultants, Inc.	Project No. 307025Test #MDC-76	PA 100	Oct. 1994
	YQ-135	PA 112	Dec. 1998
Walker Engineering	Calculations	Aerodynamic Multiplier	March 1999
IBA Consultants, Inc.	2381-252	TAS 112	09/20/07

**3. LIMITATIONS**

- 3.1 Fire classification is not part of this acceptance.
- 3.2 For mortar or adhesive set tile applications, a static field uplift test shall be performed in accordance with TAS 106.
- 3.3 Applicant shall retain the services of a Miami-Dade County Certified Laboratory to perform quarterly test in accordance with TAS 112, appendix ‘A’. Such testing shall be submitted to the Building Code Compliance Office for review.
- 3.4 Minimum underlayment shall be in compliance with the applicable Roofing Applications Standards listed section 4.1 herein.
- 3.5 30/90 hot mopped underlayment applications may be installed perpendicular to the roof slope unless stated otherwise by the underlayment material manufacturers published literature.
- 3.6 This acceptance is for wood deck applications. Minimum deck requirements shall be in compliance with applicable building code.



#### 4. INSTALLATION

4.1 Regal S-Tile and its components shall be installed in strict compliance with Roofing Application Standard RAS 118, RAS 119, and RAS 120.

4.2 Data For Attachment Calculations

Tile Profile	Weight-W (lbf)	Length-l (ft)	Width-w (ft)
Regal S-Tile	10.4	1.4375	1.1

Tile Profile	$\lambda$ (ft <sup>3</sup> ) Batten Application	$\lambda$ (ft <sup>3</sup> ) Direct Deck Application
Regal S-Tile	0.287	0.311

Tile Profile	3": 12"		4": 12"		5": 12"		6": 12"		7": 12" or greater	
	Battens	Direct Deck	Battens	Direct Deck						
Regal S-Tile	7.77	8.34	7.65	8.20	7.49	8.03	7.30	7.83	7.10	7.61

Tile Profile	Fastener Type	Direct Deck (Min 15/32" plywood)	Direct Deck (Min. 19/32" plywood)	Battens
Regal S-Tile	2-10d Ring Shank Nails	28.6	41.2	19.4
	1-10d Smooth or Screw Shank Nail	5.1	6.8	2.8
	2-10d Smooth or Screw Shank Nails	6.9	9.2	7.3
	1 #8 Screw	20.7	20.7	18.1
	2 #8 Screw	43.2	43.2	29.8
	1-10d Smooth or Screw Shank Nail (Field Clip)	23.1	23.1	19.0
	1-10d Smooth or Screw Shank Nail (Eave Clip)	29.3	29.3	24.0
	2-10d Smooth or Screw Shank Nails (Field Clip)	27.6	27.6	38.6
	2-10d Smooth or Screw Shank Nails (Eave Clip)	38.1	38.1	41.8
	2-10d Ring Shank Nails <sup>1</sup>	33.1	48.1	45.2

1 Installation with a 4" tile headlap and fasteners are located a min. of 2½" from head of tile.



**Table 6: Attachment Resistance Expressed as a Moment  $M_f$  (ft-lbf)  
for Two Paddy Adhesive Set Systems**

Tile Profile	Tile Application	Minimum Attachment Resistance
Regal S-Tile	Adhesive <sup>2</sup>	29.3 <sup>3</sup>
2 See manufactures component approval for installation requirements.		
3 The Dow Chemical Company TileBond one-component foam, minimum weight per paddy 10.7 grams. ICP Adhesives Polyset® AH-160 two-component foam. Average weight per paddy 8 grams.		

**Table 7: Attachment Resistance Expressed as a Moment -  $M_f$  (ft-lbf)  
for Single Paddy Adhesive Set Systems**

Tile Profile	Tile Application	Minimum Attachment Resistance
Regal S-Tile	ICP Adhesives Polyset® AH-160 two-component foam	66.5 <sup>4</sup>
	ICP Adhesives Polyset® AH-160 two-component foam	38.7 <sup>5</sup>
4 Large paddy placement of 63 grams		
5 Medium paddy placement of 24 grams		

**Table 8: Attachment Resistance Expressed as a Moment -  $M_f$  (ft-lbf)  
for Mortar or Adhesive Set Systems**

Tile Profile	Tile Application	Attachment Resistance
Regal S-Tile	Mortar Set	24.5

**5. LABELING**

All tiles shall bear the imprint or identifiable marking of the manufacturer's name or logo, or following statement: "Miami-Dade County Product Control Approved".

**H or HANSON**

**TILE IDENTIFICATION MARKS (LOCATED ON UNDERSIDE OF TILE)  
REGAL S-TILE**

**6. BUILDING PERMIT REQUIREMENTS**


6.1 Application for building permit shall be accompanied by copies of the following:

6.1.1 This Notice of Acceptance.

6.1.2 Any other documents required by the Building Official or applicable building code in order to properly evaluate the installation of this system.



## PROFILE DRAWINGS



**Regal S-Tile**

**END OF THIS ACCEPTANCE**

