



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

## NOTICE OF ACCEPTANCE (NOA)

**MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

**Tremco Incorporated**  
**3735 Green Road**  
**Beachwood, OH 44122**

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: Cements, Adhesives & Coatings

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews and revises NOA# 16-1212.09 and consists of pages 1 through 6.  
The submitted documentation was reviewed by Hamley Pacheco, P.E.



**NOA No.: 18-0416.05**  
**Expiration Date: 06/27/24**  
**Approval Date: 07/03/19**  
**Page 1 of 6**

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Cement-Adhesive-Coatings  
**Material:** N/A

### SCOPE:

This approves Tremco's Cements, Adhesives and Coatings as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

### MANUFACTURING LOCATION

1. ML #1
2. ML #2
3. ML #3
4. ML #4

### EVIDENCE SUMMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Underwriter Laboratories, Inc.	R6692	Wing Uplift and Fire Classification	
TRINITY   ERD	TRM-SC7905.12.14	ASTM D1227	12/29/14
	TRM-SC12495.08.17-2	Various Standards	08/29/17
	TRM-SC14485.10.17	ASTM D6152	10/12/17
NEMO   ETC.	TRM-SC14360.03.18-R1	ASTM D2824	05/25/18
PRI Construction Materials Technologies, LLC	TRE-068-02-01	ASTM D 3019	12/05/12
	TRE-078-02-01	ASTM D 1227	12/05/12
	TRE-082-02-01	ASTM D 4586	12/05/12
	TRE-083-02-01	ASTM D 2824	12/05/12
	TRE-105-02-01	ASTM D 3019	01/31/13
	TRE-068-02-01	ASTM D 3019	02/12/13
FM Approvals	3042560	ASTM D 4470	4/23/12
	3044153	ASTM D 4470	5/08/12



NOA No.: 18-0416.05  
Expiration Date: 06/27/24  
Approval Date: 07/03/19  
Page 2 of 6

## PHYSICAL PROPERTIES OF COMPONENTS

**Tradename:** Alumanation 101  
**Thickness:** See Systems Approvals Below  
**Specifications:** ASTM D 2824, Type III  
**Description:** Metallic pigmented, industrial maintenance coating formulated from specially processed asphaltic liquids, non-drying oils, a proprietary blend of natural and synthetic fibers and aluminum pigment.  
**Container Size:** 5 and 55 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #2*

**Tradename:** Alumanation 201  
**Thickness:** See Systems Approvals Below  
**Specifications:** ASTM D 2824, Type III  
**Description:** Superior grade metallic pigmented, industrial maintenance coating formulated from specially processed asphaltic liquids, non-drying oils, a proprietary blend of natural and synthetic fibers and aluminum pigment.  
**Container Size:** 5 and 55 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #2*

**Tradename:** Alumanation 301  
**Thickness:** See Systems Approvals Below  
**Specifications:** ASTM D 2824, Type III  
**Description:** An asphalt-base, heavily fibrated aluminum roof coating fomulated with a blend of rust inhibiting oils. Used as an exterior grade maintenance coating used to provide a protective and reflective weathering surface for all types of vertical and horizontal surfaces, such as asphalt emulsion coated roof surfaces, granule surfaced modified bitumen, and metal.  
**Container Size:** 5 and 55 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance

*Manufacturing Location ML #2*



**Tradename:** BURMastic® Adhesive  
**Thickness:** See Systems Approvals Below  
**Specifications:** Proprietary  
**Description:** BURMastic® is a proprietary asbesto-free cold applied asphalt surfacing material for built-up-roofs. Coverage Rate 4-5 gal/sq.  
**Container Size:** 5 and 50 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #1*

**Tradename:** BURMastic® Adhesive SF  
**Thickness:** See Systems Approvals Below  
**Specifications:** Proprietary  
**Description:** BURMastic® is a proprietary asbesto-free cold applied solvent free asphalt surfacing material for built-up-roofs. Coverage Rate 4-5 gal/sq.  
**Container Size:** 55 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #3*

**Tradename:** ELS™  
**Thickness:** See Systems Approvals Below  
**Specifications:** ASTM D 4586  
**Description:** An asphalt-base, asbesto-free heavily fibrated mastic blended with penetrating oils and plasticizing agents. Used to repair and restore flashings and asphalt built-up-roofing defects including blisters, cracks, and punctures. Trowel applied at an approximate rate of 12 ft<sup>2</sup>/gal.  
**Container Size:** 2 and 5 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #1*

**Tradename:** FAS-N-FREE  
**Thickness:** See Systems Approvals Below  
**Specifications:** Proprietary  
**Description:** One part, solvent free insulation adhesive  
**Container Size:** 5 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #1 and ML #3*



**NOA No.: 18-0416.05**  
**Expiration Date: 06/27/24**  
**Approval Date: 07/03/19**  
**Page 4 of 6**

**Tradename:** **POWERply Standard Cold Adhesive**  
**Thickness:** See Systems Approvals Below  
**Specifications:** Proprietary  
**Description:** Cold applied ply sheet and membrane adhesive  
**Container Size:** 5 and 50 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #1*

**Tradename:** **THERMastic 80**  
**Thickness:** See Systems Approvals Below  
**Specifications:** Proprietary  
**Description:** Polymer modified hot melt adhesive  
**Container Size:** 55 lb. Keg. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #4*

**Tradename:** **TremLastic S**  
**Thickness:** See Systems Approvals Below  
**Specifications:** ASTM D 1227  
**Description:** Non-fibered, rubberized asphalt emulsion.  
**Container Size:** 5 and 53 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #2*

**Tradename:** **TREMprime WB Primer**  
**Thickness:** See Systems Approvals Below  
**Specifications:** Proprietary  
**Description:** Polymer modified asphalt emulsion primer  
**Container Size:** 1, 5 and 53 gallons. Note all precautions on container.  
**Systems Approvals:** Methods of application and quantities shall comply specific Roof assembly, Product Control Notice of Acceptance.

*Manufacturing Location ML #2*



## **LIMITATIONS:**

1. Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Tremco, Inc. products shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
5. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance
7. Tremco, Inc shall be applied in accordance with manufacturer's published application instructions.

**END OF THIS ACCEPTANCE**



**NOA No.: 18-0416.05**  
**Expiration Date: 06/27/24**  
**Approval Date: 07/03/19**  
**Page 6 of 6**