

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

Tejar USA LLC 8525 NW 29 Street Doral, Florida 33122

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Caribe "S" Clay Roof Tile

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA 18-1024.07 and consists of pages 1 through 5.

The submitted documentation was reviewed by *Freddy Semino*





NOA No.: 19-0620.04 Expiration Date: 04/04/24 Approval Date: 08/01/19 Page 1 of 5

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599 www.miamidade.gov/economy

ROOFING ASSEMBLY APPROVAL

Category:	Roofing
Sub Category:	Roofing Tiles
Material:	Clay

1. Scope

This approves a roofing system using **Caribe "S" Clay Roof Tile** manufactured by **Alfareria Hispano Venezolana, C.A.,** and is distributed by **Tejar USA LLC.** as described in Section 2 of this Notice of Acceptance. For locations where the pressure requirements, as determined by applicable Building Code does not exceed the design pressure values obtained by calculations in compliance with RAS 127 using the values listed in section 4 herein. The attachment calculations shall be done as a moment based system.

2. **PRODUCT DESCRIPTION**

<u>Manufactured by</u> <u>Applicant</u>	Dimensions	Test <u>Specifications</u>	Product <u>Description</u>
Caribe "S" Clay Roof Tile	L = 18.2" W = 10.8" .50" thick nominal 3.25" high	ASTM C1167 Type I Grade 1	High profile clay roof tile. For mortar or adhesive set applications with the nominal interlocking side lap.
Trim Pieces	Length: varies Width: varies varying thickness	TAS 112	Accessory trim, clay roof pieces for use at hips, rakes, ridges and valley terminations manufactured for tile profile.

2.1 MANUFACTURING LOCATION

2.1.1. Guacara, Carabobo, Venezuela

2.2 EVIDENCE SUBMITTED

Test Agency	<u>Test Identifier</u>	Test Name/Report	Date
Fenestration Testing Laboratory	10336	ASTM C1167	12/10/18
	10368	TAS 101	03/07/19
	10652	TAS 101	03/20/19
American Test Lab of south	RT0603.01-19	TAS 101	06/06/19
Florida			



NOA No.: 19-0620.04 Expiration Date: 04/04/24 Approval Date: 08/01/19 Page 2 of 5

3. LIMITATIONS:

- **3.1** Fire classification is not part of this acceptance.
- **3.2** For mortar applications, a static field uplift test in accordance with TAS 106 may required, refer to applicable building code.
- **3.3** Applicant shall retain the services of a Miami-Dade County Certified Laboratory to perform quarterly test in accordance with TAS 112, appendix 'A'. Such testing shall be submitted to the Regulatory and Economic Development Department Product Control Section for review.
- **3.4** Minimum underlayment shall be in compliance with the applicable Roofing Applications Standards listed section 4.1 herein.
- **3.5** 30/90 hot mopped underlayment applications may be installed perpendicular to the roof slope unless stated otherwise by the underlayment material manufacturers published literature.
- **3.6** This acceptance is for wood deck applications. Minimum deck requirements shall be in compliance with applicable building code.
- **3.7** All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3

4. INSTALLATION

- **4.1** Clay Type Tile and its components shall be installed in strict compliance with Roofing Application Standard RAS-120 (Mortar Set and Adhesive Set Tile Applications).
- **4.2** Data For Attachment Calculations.

Table 1: Average Weight (W) and Dimensions (I x w)			
Tile ProfileWeight-W (lbf)Length-I (ft)Width-w (ft)			
Caribe "S" Clay Roof Tile	6.2	1.56	0.90

Table 2: Aerodynamic Multipliers - λ (ft³)			
Tile λ (ft³) λ (ft³)			
Profile	Batten Application	Direct Deck Application	
Caribe "S" Clay Roof Tile	N/A	0.29	

Table 3: Restoring Moments due to Gravity - Mg (ftlbf)						
Tile Profile	2":12"	3":12"	4":12"	5":12"	6":12"	7":12" or Greater
Caribe "S" Clay Roof Tile	Direct Deck	Direct Deck	Direct Deck	Direct Deck	Direct Deck	Direct Deck
	4.27	4.22	4.15	4.05	3.95	3.83



Tile Application	Minimum Attachment
	Resistance
ICP Adhesives and Sealants Polyset® RTA-1	56.24 ¹
ingle component polyurethane foam tile adhesive.	
	Polyset [®] RTA-1 ingle component polyurethane

Tile Profile	Tile Application	Minimum Attachment Resistance
Caribe "S" Clay Roof Tile	ICP Adhesives and Sealants ICP Adhesives Polyset® AH-160	51.9 ²
	Two component polyurethane foam tile adhesive.	
2 31.6 grams of ICP Adhesives Polyset® AH-160		

Table 5: Attachment Resistance Expressed as a Moment - M _f (ftlbf) for Mortar Set Systems		
Tile Profile	Tile Application	Minimum Attachment Resistance
Caribe "S" Clay Roof Tile	QUIKRETE [®] Roof Tile Mortar FL-15	110.41

5. LABELING

5.1 All tiles shall bear the imprint or identifiable marking of the manufacturer's name or logo as detailed below, or following statement: "Miami-Dade County Product Control Approved".


MADE IN VENEZUELA BY ALFARERIA HISPANO VENEZOLANA, C.A. PHONE (0245) 5715838 FAX (0245) 5718752

(LOCATED ON THE TOP PAN OF TILE)

NOA No.: 19-0620.04 Expiration Date: 04/04/24 Approval Date: 08/01/19 Page 4 of 5



PROFILE DRAWING



Caribe "S" Type Clay Roof Tile

6. **BUILDING PERMIT REQUIREMENTS:**

- 6.1 Application for building permit shall be accompanied by copies of the following:
 - **6.1.1** This Notice of Acceptance.
 - **6.1.2** Any other documents required by Building Official or Applicable building code in order to properly evaluate the installation of this system.

END OF THIS ACCEPTANCE



NOA No.: 19-0620.04 Expiration Date: 04/04/24 Approval Date: 08/01/19 Page 5 of 5