

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208

Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

Tischler Und Sohn (USA) Ltd. Six Suburban Avenue Stamford, Ct. 06901

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Tischler series Inswing Wood Doors-L.M. Impact

APPROVAL DOCUMENT: Drawing No.1617 REV C, titled "In-Swing Impact Wood Panel Doors", sheets 1 through 19 of 19, dated 10/08/08 and last revised on May 15, 2018, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren Schaefer, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large Missile Impact Resistant Limitations:

- 1. MDF material: Medite Exterior MDF panel EN 622 Type MDF-H2
- 2. See sheets 10 thru 13 for reinforcements, see panel glazing options on sheet 17.
- 3. Lower design pressure shall control when doors mulled w/ Tishler's transom (under separate approval) see sheet 8.
- 4. CMU to conform to ASTM-C 90 and min 2000 psi net compressive masonry strength.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, Wedel (Schleswig-Holstein), Germany and series and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA # 18-0531.11 and consists of this page 1 and evidence pages E-1, E-2, E-3 & E-4, as well as approval document mentioned above.

The submitted documentation was reviewed by Ishaq I. Chanda, P.E.

MIAMI-DADE COUNTY
APPROVED

Ishaq I. Chands

NOA No. 20-0629.09 Expiration Date: May 27, 2024 Approval Date: August 13, 2020

Page 1

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

1. Evidence submitted under previous approvals

A. DRAWINGS

- 1. Manufacturer's parts drawings and sections (submitted under files below)
- 2. Drawing No.**1617 REV B**, titled "In-Swing Impact Wood Panel Doors", sheets 1 through 19 of 19, dated 10/08/08 and last revised on FEB 20, 2014, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren Schaefer, P.E.

(Note: The revision consists of updating angle clip masonry screws)

- B. TESTS (submitted under files #14-0303.07/#11-1101.14/ #09-0212.06)
 - 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

Along with installation diagram of Single & Double Outswing /Inswing, Tilt/Turn Mahogany Wood French doors w/wo Sidelite & Transom, w/ MDF & wood Veneered Panels and different shapes top, prepared by Architectural Testing, Test Report(s) No. **ATI 77326.01-109-18**, dated 02/03/09 and **ATI 77327.01-109-18**, dated 02/202/09, both signed and sealed by Michael D. Stremmel, P.E.

2. Additional test report: ATI 77324.01-109.18 (specimen A3-1 & A3-7) issued by Architectural Testing per TAS 201, 202 and 203-94.

C. CALCULATIONS

1. Anchor calculations and structural analysis complying w/ FBC 2014 dated 02/20/2014, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed & sealed by Warren Schaefer, P.E.

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. Test report No. ATI-86006.01-106-18 (Rev 2) dated 12/12/08 and ATI-86006.02-106-18 02/05/09 for "Durability of Wood-Based Composite Lumber and panels" per ASTM ASTM D-1761 and ASTM D-4761, issued by Architectural Testing Lab (submitted under 11-1101.14 / #09-0212.06).

F. STATEMENTS

- 1. Statement letters of conformance to FBC **5th** Edition (2014), dated MAR 27, 2014 and e-mail dated APR 17, 2014, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E.
- 2. Statement letters of conformance to FBC 2010, dated OCT 28, 2011 and "No financial interest dated OCT 24, 2011, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E. (submitted under #11-1101.14)
- 3. E-mail statement dated 03/31/09, issued by Michael D. Stremmel, P.E. of Architectural testing in reference to low sill, water infiltration test (submitted under 11-1101.14/#09-0212.06)

Ishaq 1. Chands

Ishaq I. Chanda, P.E. Product Control Unit Supervisor NOA No. 20-0623.09 Expiration Date: May 27, 2024

Approval Date: August 13, 2020

Tischler Und Sohn (USA) Ltd.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

G. OTHER

- 1. This NOA revises & renews NOA # 11-1101.14, expiring 05/27/14.
- 2. Test proposal # **07-3533** dated Oct 22, 2007, approved by BCCO.
 - 3. Distribution agreement between Tishler Und Sohn (USA) and Tishler/Cornelius Korn GmbH, Germany, signed by Tim Carpenter & Wilhem Korn, respectively.
- 4. Tishler's current Fixed Casement windows NOA(s) w/ Drawing references No. 1514 or 1533.

2. Evidence submitted under previous approval

A. DRAWINGS

1. None.

B. TESTS

1. None

C. CALCULATIONS

1. None

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS

1. Statement letters of conformance to FBC 2017(6th Edition) and still complies with FBC 2014 (5th Edition), dated JUL 20,2017, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E.

G. OTHER

- 1. This NOA revises NOA # 14-0303.07, expiring 05/27/2019.
- 2. E-mail request dated 10/12/17 for correction of Tischler Und Sohn manufacturing location in Germany, signed by Stefan Precht, VP project management.

3. Evidence submitted under previous approval

A. DRAWINGS

1 Drawing No.**1617 REV** C, titled "In-Swing Impact Wood Panel Doors", sheets 1 through 19 of 19, dated 10/08/08 and last revised on May 15, 2018, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren Schaefer, P.E.

B. TESTS

1. None

C. CALCULATIONS

1. Anchor calculations and structural analysis complying w/ FBC 2017(6th Edition) dated May 15, 2018, prepared by W.W. Schaefer Engineering & Consulting, P.A. signed & sealed by Warren Schaefer, P.E.

Ishaq I. Chands

Ishaq I. Chanda, P.E. Product Control Unit Supervisor NOA No. 20-0623.09

Expiration Date: May 27, 2024 Approval Date: August 13, 2020

Tischler Und Sohn (USA) Ltd.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

3. Evidence submitted under previous approval (continue):

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. None

F. STATEMENTS

- 1. Statement letters of conformance to FBC 2017(6th Edition) and still complies with FBC 2017 (6th Edition), dated May 15, 2018, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E.
- 2. Statement letter dated May 11, 2018, issued by Tishler Und Sohn, Ltd, requesting Renewal, signed by Timothy K. Carpenter, company's president.

G. OTHER

- 1. This NOA revises & renews NOA # 17-0803.32, expiring 05/27/2024.
- 2. Distribution agreement between Tishler Und Sohn (USA) and Tishler/Cornelius Korn GmbH, Germany, signed by Tim Carpenter & Wilhem Korn, respectively.
- 3. E-mail request dated 10/12/17 for correction of Tischler Und Sohn manufacturing location in Germany, signed by Stefan Precht, VP project management.

4. New Evidence submitted

A. DRAWINGS

1. None.

B. TESTS

1. None

C. CALCULATIONS

1. None

D. OUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS

1. Statement letters of conformance to FBC 2020(7th Edition) dated 06/05/20, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E.

G. OTHER

1. This NOA revises NOA # 18-0531.11, for FBC 2020 code update.

Ishaq 1. Chands

Ishaq I. Chanda, P.E.
Product Control Unit Supervisor
NOA No. 20-0623.09
Expiration Date: May 27, 2024

Approval Date: August 13, 2020

LOCK STRIKE REQUIREMENTS (TOP OF PANEL)

PANEL QUANTITY WIDTH PER PANEL RECTANGULAR PANEL ALL WIDTHS ARCH & ROUND TOP PANEL OVER 32" 3 28" TO 32"

OPENING TYPE

(SUBSTRATE)

MIN. 2X4 WOOD FRAME OR BUCK

(MIN. GR. 3 & G=0.55)

MIN. 1/8" THK A36 STEEL

MIN. 1/8" THK 6063-T5 ALUM

C-90 CMU/2500 PSI CONCRETE

MIN. 2X6 WOOD FRAME OR BUCK

(MIN. GR. 3 & G=0.55)

MIN. 1/8" THK A36 STEEL

MIN. 1/8" THK 6063-T5 ALUM

C-90 CMU/2500 PSI CONCRETE

MIN. 2X6 WOOD FRAME OR BUCK

(MIN. GR. 3 & G=0.55)

MIN. 1/8" THK A36 STEEL

MIN. 1/8" THK 6063-T5 ALUM.

MIN. 2X6 WOOD FRAME OR BUCK

(MIN. GR. 3 & G=0.55)

MIN. 1/8" THK A36 STEEL

MIN. 1/8" THK 6063-T5 ALUM.

C-90 CMII/2500 PSI CONCRETE L

(1) LOCK STRIKE REQUIREMENTS (BOTTOM OF PANEL)

PANEL			QU/	YTITNA
	WID	PER	antity Pane	
	ALL	PANEL	SHAP	ES
	ALL W	IDTHS		2

(1) WHEN ADA SILL IS USED WITH DOUBLE DOORS, ONLY THE KFV LOCK SYSTEM MAY BE USED. WHEN ADA SILL IS USED WITH A SINGLE DOOR, BOTH THE KFV & SIEGENIA LOCK SYSTEMS APPLY BUT DO NOT REQUIRE SILL STRIKES.

FRAME ANCHOR REQUIREMENTS TABLE

FRAME/SILL SCREWS

MIN. 18 GA. 33 KSI METAL STUD (2)1/4-14 SELF TAP/DRILLING SCREW

MIN. 18 GA. 33 KSI METAL STUD (2)12-14 SELF TAP/DRILLING SCREW

MIN. 18 GA. 33 KSI METAL STUD (2)8-18 SELF TAP/DRILLING SCREW

MIN. 18 GA. 33 KSI METAL STUD (2)8—18 SELF TAP/DRILLING SCREW

FRAME/SILL/CLIP/BRACKET TO

OPENING FASTENER TYPE

NO. 14 SMS/WOOD SCREW OR

1/4" BTI SCREW

(2)1/4-14 SELF TAP/DRILLING SCREW

(2)1/4-14 SELF TAP/DRILLING SCREW

NO. 12 X 1 1/2" SMS

(2)12-14 SELF TAP/DRILLING SCREW

(2)12-14 SELF TAP/DRILLING SCREW

NO. 8 X 1 1/2" SMS

(2) 8-18 SELF TAP/DRILLING SCREW

(2) 8-18 SELF TAP/DRILLING SCREW

NO. 8 X 1 1/2" SMS

(2) 8-18 SELF TAP/DRILLING SCREW

(2) 8-18 SELF TAP/DRILLING SCREW

(1) 1/4" CONCRETE SCREW

(1) 1/4" CONCRETE SCREW

BTI BRACKET SCREWS

ANGLE CLIP SCREWS

(1) 1/4" CONCRETE SCREW

INSTALLATION CLIP SCREWS

LOCK STRIKE REQUIREMENTS (LOCK SIDE OF PANEL)

	<u> </u>
(1) PANEL	QUANTITY
HEIGHT	PER PANEL
ALL PANEL	SHAPES
OVER 96"	4
76" TO 96"	3
1) THE "PANEL	HEIGHT" IS

(1) THE "PANEL HEIGHT IS CONSIDERED TO BE FULL PANEL HEIGHT FOR RECTANGULAR UNITS OR DISTANCE FROM THE BASE OF PANEL TO PANEL SRINGLINE FOR SHAPED **UNITS**

MINIMUM MINIMUM

1/4"

FULL

FULL

FULL

1 1/4"

3/8"

FULL

FULL

FULL

1 1/4"

1 3/8'

FULL

FULL

FULL

1 3/8'

FULL

FULL

FULL

1 1/4'

EMBED EDGE DIST

3/4"

1/2"

1/2"

1/2"

2"

3/4"

1/2"

1/2

1/2"

2"

3/4"

1/2"

1/2"

1/2"

3/4"

1/2"

1/2"

1/2"

2"

_				•	
QUANTITY			(2) PANEL	QUANTITY	
	PER PANEL		HEIGHT	PER PANEL	
SHAPES			ALL PANEL	SHAPES	
	4		ALL HEIGHTS	3	
Ę		1 1		·	

(1) WHEN DOOR IS TILT-ŤÚRN, ONLY 2 HINGES ARE USED COMBINED WITH LOCK POINTS. WHEN DOOR IS SWING ONLY, ONLY HINGES EXIST.

(2) THE "PANEL HEIGHT" IS CONSIDERED TO BE FULL PANEL HEIGHT FOR RECTANGULAR UNITS OR DISTANCE FROM THE BASE OF PANEL TO PANEL SRINGLINE FOR SHAPED UNITS

(1) LOCK STRIKE	HINGE REQUIR	EMENTS
REQUIREMENTS	(1) PANEL	QUANTITY
(HINGE SIDE OF	HEIGHT	PER PANE
TILT-TURN DOORS)	POT HINGE	S
TILI-TONN DOORS)	OVER 99"	5

76 10 99	4
SCREWED-IN HI	NGES
OVER 99"	5
76" TO 99"	4
(1) THE "PANEL HEIGH	HT" IS
CONSIDERED TO BE F	ULL PANEL
HEIGHT FOR RECTANGE	JLAR UNITS
OR DISTANCE FROM	THE BASE

76" TO 99"

FOR SHAPED UNITS

PER PANEL

HINGE REQUIREMENTS (TILT-TURN DOORS)

OF PANEL TO PANEL SRINGLINE

2 PER DOOR (ALL SIZES OF ALL DOORS)

HESE DRAWINGS ARE APPLICABLE ONLY TO THE PRODUC SPECIFIED. THEY MAY NOT BE USED FOR THE ASSEMBLY AND/OR INSTALLATION OF ANY OTHER PRODUCT NOR MAY THEY BE USED FOR RATIONAL AND/OR LOCAL APPROVAL OF ANY PRODUCT NOT PRODUCED BY THE MANUFACTURER STATED ON THESE DRAWINGS.

GENERAL NOTES:

1. THIS PRODUCT HAS BEEN TESTED, ANALYZED & APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN THE "ALLOWABLE DESIGN PRESSURE TABLE(S)".

2. OPENINGS, BUCKING & BUCKING FASTENERS MUST BE PROPERLY DESIGNED & INSTALLED TO TRANSFER WIND LOADS TO THE STRUCTURE. 3. ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS &

SHALL NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS. SPECIFIED ANCHOR EMBED TO BASE MATERIAL SHALL BE BEYOND WALL FINISH OR STUCCO. 4. THE DETAILS & SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS TESTED & PROPOSED FOR CONFORMANCE WITH THE FLORIDA BUILDING CODE PROTOCOLS

TAS-201, 202 & 203 FOR LARGE MISSILE IMPACT PRODUCTS. 5. THIS PRODUCT HAS BEEN DESIGNED IN ACCORDANCE WITH AND MEETS THE REQUIREMENTS OF THE FLORIDA BUILDING CODE (FBC) INCLUDING HIGH VELOCITY

HURRICANE ZONES (HVHZ).

6. IMPACT SHUTTERS ARE NOT REQUIRED WITH THIS PRODUCT.
7. ALL ANCHORS SECURING PRODUCT FRAMES TO PRESSURE TREATED BUCKS OR WOOD FRAMING SHALL BE CAPABLE OF RESISTING CORROSION CAUSED BY THE PRESSURE TREATING CHEMICALS IN THE WOOD.

8. DETERMINE THE POSITIVE & NEGATIVE DESIGN LOADS TO USE WHEN REFERENCING THESE DOCUMENTS IN ACCORDANCE WITH THE GOVERNING CODE AND GOVERNING WIND VELOCITY. FOR WIND LOAD CALCULATIONS IN ACCORDANCE WITH THE FLORIDA BUILDING

CODE, A DIRECTIONALITY FACTOR OF Kd = 0.85 MAY BE APPLIED PER THE ASCE-7 STANDARD. 9. NO INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE CERTIFICATION OF

THIS PRODUCT. WIND LOAD DURATION FACTOR Cd = 1.6 WAS USED FOR WOOD SCREW ANALYSIS ONLY.

10. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF FLORIDA BUILDING CODE.

11. All WOOD MEMBERS OF THIS PRODUCT THAT MAY POSSIBLY COME INTO CONTACT WITH MASONRY OR CONCRETE SUBSTRATES, ARE SUBJECT TO MOISTURE &/OR ARE SUBJECT TO THE OUTSIDE ENVIRONMENT SHALL BE OF AN APPROVED DURABLE SPECIES OR BE TREATED IN AN APPROVED METHOD WITH AN APPROVED PRESERVATIVE PER FBC

PANEL WIDTH DIMENSIONS ARE APPROXIMATELY 3" LESS THAN THE FRAME WIDTH & PANEL HEIGHT DIMENSIONS ARE APPROXIMATELY 1 3/4 LESS THAN THE FRAME HEIGHT

ALLOWABLE DESIGN PRESSURE (SINGLE & DOUBLE OPERABLE DOORS)

MAX. FRAME	MAX. FRAME	ALLOWABLE	PRESSURE
WIDTH (IN.)	HEIGHT (IN.)	POSITIVE (PSF)	NEGATIVE (PSF)
	SINGLE	DOOR	
51 1/8	120	70	70
41 1/4 99		70	(1) 85
	DOUBLE	DOOR	
79 1/16	120	70	70
79 1/16	99	70	(1)(2)85
ł			

- (1) HIGHER PRESSURE OF -85 PSF IS ONLY APPLICABLE WITH STANDARD SILL (USE OF ADA SILL IS NOT APPLICABLE TO UNITS WITH PRESSURE EXCEEDING +/-70 PSF).
- (2) HIGHER PRESSURE OF -85 PSF IS ONLY APPLICABLE WITH DOUBLE DOORS WHEN THE DOUBLE DOOR MEETING STILES ARE BAR REINFORCED (REF. SECTIONS).

PRODUCT REVISED as complying with the Florida Building Code 20-0623.09 NOA-No.

Expiration Date 05/27/2024

Ishag 1. Chank

Miami-Dade Product Control

eroduct revisio as complying with the Florida Acceptance No 18-053/.11 Expiration Detectedy 27, 2014

Bude Praduct Control

CORNER CONSTRUCTION:

RECTANGULAR FRAME CORNERS: MORTISE & TENON CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT. ARCHED FRAME CORNERS: ARCHED FRAME BUTTED TO STRAIGHT

FRAME, JOINED WITH ONE(1) NO.14 X 3" WOOD SCREW. & GLUED WITH PONAL SUPER 3 WOOD GLUE OR FOLIVALENT HALF ROUND FRAME CORNERS: FINGER JOINT CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT.

RECTANGULAR PANEL CORNERS: OPTION 1 (USED WITH STILE & RAIL CONDITIONS WHERE

MEMBERS ARE 4.250" OR LESS IN OVERALL HEIGHT): MORTISE & TENON CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT. OPTION 2 (USED WITH STILE & RAIL CONDITIONS WHERE

MEMBERS ARE GREATER THAN 4.250" IN OVERALL HEIGHT): MEMBERS ARE SQUARE CUT, BUTTED, JOINED WITH FIVE(5) \$5/16 X 2" WOOD DOWELS, & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT.

ARCHED PANEL CORNERS: ARCHED RAIL BUTTED TO STRAIGHT STILE, JOINED WITH ONE(1) NO.14 X 3" WOOD SCREW, & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT. HALF ROUND PANEL CORNERS: FINGER JOINT CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR

SILL CORNERS: ALL SILL CONDITIONS: SILL IS BUTTED TO THE JAMBS & JOINED WITH THREE(3) NO.6 X 2" WOOD SCREWS & SEALED WITH

W. SCHAEFER ENGINEERING
CONSULTING, P.A. (CA 6809)
7480 150TH COURT NORTH
PALM BEACH GARDENS, FL 33418
PHONE: 561-744-3424 Ż ું **∻ જ** \$ 2018 SCHAEFER, NO. 44135 NAZ NAZ NAZ CERT

CHECKED BY

W.W.S.

10/08/08

1=24

S 4 20 20

DOORS

PANEL

WOOD

IMPACT

I-SWING


CTURER


TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600

1617 SHEET NO.

1 of 19

o so emoy 2000 i si concrete i i i i i i concrete sonem	1 1/7
(1) CONCRETE SCREWS SHALL BE ELCO ULTRACONS, ELCO CRETE-FLEX O	R HILTI
KWIK-CON II (HARDENED STEEL OR S.S.).	
(2) ALL SELF TAP/DRILLING SCREWS SHALL BE MIN. GR. 5	





ALLOWABLE DESIGN PRESSURE

SEE PRESSURE TABLE ON SHEET 1

DUE TO HINGE CONDITION VARIATIONS, HINGES ARE NOT SHOWN IN ELEVATIONS, SEE SECTIONS & HINGE TABLES FOR HINGE REQUIREMENTS

20-0623.09 NOA-No.

Expiration Date 05/27/2024

By Ishag 1. Chands Miami-Dade Product Control

PRODUCT REVISED as complying with the Florids **Building Code** Acceptance No 18-0531-1


Mr. au' Rodel Product Control

CTURER
TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600 DOORS PANEL W. SCHAEFER ENGINEERING
CONSULTING, P.A. (CA 6809)
7480 150TH COURT NORTH
PALM BEACH GARDENS, FL. 33418
PHONE: 551-744-3474 WOOD IMPACT ું કે શ્ર 2018 LO 1617 SHEET NO. 3 of 19

DRAWN BY: W.R.M.

1=24

ATE: 10/08/08



FRAME SCREWS. INSTALLATION CLIPS, BTI BRACKETS OR ANGLE CLIPS WHERE SHOWN. SEE "FRAME ANCHOR REQUIREMENTS TABLE" ON SHEET 1 FOR SPRINGLINE REQUIREMENTS (BTI OPPOSITE BRACKETS NOT ACTIVE APPLICABLE AT SILL). 17" MAX. O.C. (TYP. AT SIDES & HEAD) -MIDDLE ANCHOR NOT REQUIRED WHEN FRAME WIDTH IS 41 1/4" OR SMALLER 8" MAX. 7" MAX. → — 7" мах. 51 1/8" MAX. FRAME WIDTH **PRODUCT REVISED** as complying with the Florida Building Code **INTERIOR ELEVATION:** SINGLE HALF ROUND DOOR 20-0623.09 NOA-No. (TURN ONLY CONDITION) Expiration Date 05/27/2024 SCALE: 1/2" = 1'-0"Ishaq 1. Chands

APPROVED SHAPED (OPERABLE DOORS)



NOTES:

1. OTHER SHAPES MAY APPLY PROVIDING THEY ARE SIMILAR TO THOSE SHOWN & HAVE CORNER CONSTRUCTION AS DESCRIBED IN THIS DRAWING.

2. ALL SHAPED UNITS MUST FIT INSCRIBED INTO THE ALLOWABLE RECTANGULAR UNITS & BE GOVERNED BY THE ALLOWABLE PRESSURE OF THE RESPECTIVE RECTANGULAR UNIT.

ALLOWABLE DESIGN PRESSURE

SCALE: 1/2" = 1'-0"

SEE PRESSURE TABLE ON SHEET


DUE TO HINGE CONDITION VARIATIONS, HINGES ARE NOT SHOWN IN ELEVATIONS, SEE SECTIONS & HINGE TABLES FOR HINGE REQUIREMENTS


ANCHOR NOTE: ANCHOR SPACING AT THE HEAD OF ALL TYPES OF SHAPED DOORS MUST EQUAL THAT SPECIFIED AT THE SIDES (17" MAX. O.C.)

Miami-Dade Product Control

Ë. TISCHLER UND SOHN (USA) L.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 069
203-674-0600 DOORS PANEL WOOD SULTANTS
W. SCHAEFER ENGINEERING
CONSULTING, P.A. (CA 6809)
7480 150TH COURT NORTH IMPACT IN-SWING ું કે જ 2018 La 1617 SHEET NO. 4 of 19

W.W.S. ATE: 10/08/08






(TURN & TILT CONDITION)

SCALE: 1/2" = 1'-0"

APPROVED SHAPED (OPERABLE DOORS)



1. OTHER SHAPES MAY APPLY PROVIDING THEY ARE SIMILAR TO THOSE SHOWN & HAVE CORNER CONSTRUCTION AS DESCRIBED IN THIS DRAWING.

2. ALL SHAPED UNITS MUST FIT INSCRIBED INTO THE ALLOWABLE RECTANGULAR UNITS & BE GOVERNED BY THE ALLOWABLE PRESSURE OF THE RESPECTIVE RECTANGULAR UNIT.

ALLOWABLE DESIGN PRESSURE

SEE PRESSURE TABLE ON SHEET

SCALE: 1/2" = 1'-0"

DUE TO HINGE CONDITION VARIATIONS. HINGES ARE NOT SHOWN IN ELEVATIONS, SEE SECTIONS & HINGE TABLES FOR HINGE REQUIREMENTS

ANCHOR NOTE: ANCHOR SPACING AT THE HEAD OF ALL TYPES OF SHAPED DOORS MUST EQUAL THAT SPECIFIED AT THE SIDES (17" MAX. O.C.)

PRODUCT REVISED as complying with the Florida Building Code NOA-No. 20-0623.09


Expiration Date 05/27/2024


By Ishag 1. Chands Miami-Dade Product Control

PRODUCT REVISED as complying with the Florida kedding Code Acceptance No 18-053/-11

CHECKED BY: W.W.S. ATE: 10/08/08 1=24 TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600 DOORS PANEL WOOD ENGINEERING P.A. (CA 6809) IMPACT VSULTANTS
W. SCHAEFER
CONSULTING, P ું ×ું શ્ર 2018 La 1617 SHEET NO.

5 of 19





FRAME SCREWS ARE NOT **APPLICABLE** FOR USE WITH FIXED PANEL DOOR SILLS

INTERIOR ELEVATION; DOUBLE DOORS WITH FIXED PANELS

SCALE: 1/2" = 1'-0"

(RECTANGULAR DOORS SHOWN, SHAPED DOORS ALSO APPLY. SEE "APPROVED SHAPED" TABLE ON SHEETS 4 & 5)

MULTIPLE UNIT NOTES:

WHERE SHOWN AT MULLION ENDS. SEE

"FRAME ANCHOR REQUIREMENTS TABLE"

ON SHEET 1 FOR REQUIREMENTS (BT)

BRACKETS NOT APPLICABLE AT SILL).

- 1. FOR ALL DETAIL NOT SHOWN, SEE INDIVIDUAL UNIT ELEVATIONS.
- 2. THERE IS NO LIMIT ON THE NUMBER OF DOORS THAT MAY BE COMBINED IN ONE DIRECTION INTO ONE OPENING PROVIDING THE OPENING IS DESIGNED TO SUPPORT ALL LOADS TRANSFERED FROM THE DOORS & THEIR MULLIONS.
- 3. OXXO UNIT IS SHOWN. ALL OTHER FIXED/OPERABLE COMBINATIONS ALSO APPLY WITH THE MULLION CONDITIONS SHOWN.
- 4. INDIVIDUAL DOOR/FIXED PANEL SIZES SHALL BE RESTRICTED AS SPECIFIED IN THE SINGLE UNIT
- 5. BOTH TURN ONLY & TILT & TURN CONDITIONS APPLY.

	N	MULLION			DRA	WN I	
		DESIGN	PRESSU	<u> </u>		1=2	4
	MAXIMUM MULLION SPAN	MAXIMUM LOAD WIDTH	,	WABLE RE (PSF)	DATE		
	(IN.)	(IN.)	POS.	NEG.	ΒΥ		
		52	53.8	53.8	\mathbb{H}	H	_
		48	58.3	58.3	No		
	120	44	63.6	63.6	RIPT		
	120	40	70.0	70.0	DESCRIPTION		
		36	70.0	70.0			
		32	70.0	70.0	REVISION		
		52	59.8	59.8	쮼		
		48	64.8	64.8	NO.		_
	108	44	70.0	70.0		Щ	Г
		40	70.0	70.0			
		36	70.0	70.0	1		
		52	70.0	75.2	1		ŀ
	99	48	70.0	81.5	1		
		46	70.0	85.0	1		ľ
		52	70.0	77.5	1		
-	96	48	70.0	84.0	1		
		44	70.0	85.0			
	84	52	70.0	85.0	1		ı

NOTES:

- 1. LOAD WIDTH IS THE DISTANCE BETWEEN PANEL CENTERLINES.
- 2. ALLOWABLE UNIT PRESSURE SHALL BE THE LESSER OF THE PRESSURES SHOWN IN THIS TABLE & THOSE SPECIFIED FOR THE INDIVIDUAL DOOR/FIXED PANEL.
- 3. SIZE VALUES IN TABLE ARE $\pm 1/4$ "

PRODUCT REVISED as complying with the Florida Building Code NOA-No. 20-0623.09

Expiration Date 05/27/2024

By Ishaq 1. Chands Miami-Dade Product Control

PRODUCT REVISED as complying with the Florids building Code Acceptance No 18-053 Mit and Bade Product Contro

	<u> </u>	
IN-SWING IMPACT WOOD	CONSULTANTS W. W. SCHAEFER ENGINEERING & CONSULTING, P.A. (CA 6809)	7480 150TH COURT NORTH PALM BEACH GARDENS, FL 33418
11	344. F. 1	£.
11.		0.

TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600


DOORS


PANEL


10/08/08


\$ 2018


1617 SHEET NO. 7 of 19














SCREWED IN HINGE CONDITION SHOWN, POT HINGE CONDITION ALSO APPLIES (FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)



SCREWED IN HINGE CONDITION SHOWN, POT HINGE CONDITION ALSO APPLIES (FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)



(FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)



SECTION G5
SCALE: 1/2 FULL 12

SCREWED IN HINGE CONDITION SHOWN, POT HINGE CONDITION ALSO APPLIES (FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)

PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 20-0623.09

Expiration Date <u>05/27/2024</u>


By | Shang | . Change


Miami-Dade Product Control


	NO. REVISION DESCRIPTION BY							
		PANEL DOORS	MANUFACTURER	TISCHLER UND SOHN (USA) LTD.		STAMFOR	203-674-0600	
. 1972 E S	DRAWING TITLE	IN-SWING IMPACT WOOD PANEL DOORS	STATI HANDS	W W SCHAFFFR ENGINEERING	& CONSULTING, P.A. (CA 6809)	7480 150TH COURT NORTH	PALM BEACH GARDENS, FL 33418 PHONE: 561-744-3424	
	CERTIFICATION			MAK 1,5 2018			WARREN W SCHAEFER, P.E.	r.k. NO. 44100
5.07		DR/ 1	6 SHE 2	NG 17 ET OI	NO 7 NO	19	REV. C	


CHECKED BY: W.W.S.


ATE: 10/08/08














ITEM #	ITEM DESCRIPTION	MANUFACTURER/NOTES
	PARTS	
1	HEAD/JAMB	MAHOGANY
2	TOP RAIL	MAHOGANY
3	STANDARD BOTTOM RAIL	MAHOGANY
4	BOTTOM RAIL (USED WITH ADA THRESHOLD)	MAHOGANY
5	STILE	MAHOGANY
6A	ACTIVE MEETING STILE (USED WITH REINFORCEMENT)	MAHOGANY
6B	ACTIVE MEETING STILE (USED WITHOUT REINFORCEMENT)	MAHOGANY
7A	INACTIVE MEETING STILE (USED WITH SIEGENIA LOCK SYSTEM & REINFORCEMENT)	MAHOGANY
7B	INACTIVE MEETING STILE (USED WITH SIEGENIA LOCK SYSTEM & WITHOUT REINFORCEMENT)	MAHOGANY
8A	INACTIVE MEETING STILE (USED WITH KFV LOCK SYSTEM & REINFORCEMENT)	MAHOGANY
8B	INACTIVE MEETING STILE (USED WITH KFV LOCK SYSTEM & WITHOUT REINFORCEMENT)	MAHOGANY
9	FIXED ASTRAGAL	MAHOGANY
10	MID-RAIL	MAHOGANY
11	ONE-PIECE MULLION	MAHOGANY
12	BOTTOM RAIL DRIP EDGE	MAHOGANY
13	MULLION BAR COVER	MAHOGANY
	ASTRAGAL	MAHOGANY
14 15	MULLION BAR COVER	MAHOGANY
16	GLAZING BEAD	MAHOGANY
19	SPACER BLOCK	MAHOGANY
20	SPACER BLOCK	MAHOGANY
21	SPACER BLOCK (USED WITH KFV	MAHOGANY
21	MULTI-POINT LOCK SYSTEM)	
22	SUB-SILL	MAHOGANY
23	SUB-SILL	MAHOGANY
24	ADA SUB-SILL	MAHOGANY
	STANDARD SILL	BRONZE
25 26	OPTIONAL ADA SILL	BRONZE
27	CONTINUOUS SILL STRIKE/COVER	BRONZE
	MEETING STILE REINFORCEMENT	34 KSI STAINLESS STEEL OR A36 STEEL
28	VERTICAL FIXED ASTRAGAL REINFORCEMENT	34 KSI STAINLESS STEEL OR A36 STEEL
29 30	VERTICAL MULLION REINFORCEMENT	34 KSI STAINLESS STEEL OR A36 STEEL
	TRANSOM MULLION REINFORCEMENT	34 KSI STAINLESS STEEL OR A36 STEEL
31	INSTALLATION CLIP	GALVANIZED 54 KSI STEEL
32	ANGLE CLIP	6061-T6 ALUMINUM
33	BTI BRACKET	GALVANIZED 54 KSI STEEL
34	HARDWARE	GALANTELD OF NOT OTHER
37	SCREWED IN HINGE	74mm X 16mm GENIATEC GMBH; FE 74WF 120mm X 16mm GENIATEC GMBH; TUE120WF
		85mm X 20mm SIMONS BAKA; C1–20 130mm X 15mm ANUBA; 515 SM 130mm X 18mm ANUBA; 518 SM
70	DOT HINGE	BY: SIEGENIA AUBI KG TYPE: SI
38	POT HINGE	BY: STEGENIA AUDI NG TIPE: SI BY: KFV: STRAIGHT SHOOT
39	MULTI-POINT LOCK SYSTEM	BY: KEV: STRAIGHT SHOUT BY: SIEGENIA AUBI KG TYPE: MUSHROOM
40	MULTI-POINT LOCK SYSTEM	AS REQUIRED TO OPERATE LOCK SYSTEM
41	HANDLE	IND WENGINED TO OF ENAIT FORK STOTEM

ITEM #	ITEM DESCRIPTION	MANUFACTURER/NOTES
	SEALS & SEALANT	S
45	WEATHERSTRIP	THERMOPLASTIC ELASTOMER; BY: DEVENTER
46	WEATHERSTRIP	THERMOPLASTIC ELASTOMER; BY: DEVENTER
47	WEATHERSTRIP!	THERMOPLASTIC ELASTOMER; BY: DEVENTER
48	WEATHERSTRIP	THERMOPLASTIC ELASTOMER; BY: DEVENTER
49	WEATHERSTRIP	THERMOPLASTIC ELASTOMER; BY: WEGNER
	FASTENERS	
52	0.06" X 1.26" S.S. CURVED NAIL	4" FROM CORNERS & 12" MAX. O.C.
53	0.18" X 1.57" WOOD SCREW	3 PER HINGE INTO STILE
54	0.18" X 1.57" WOOD SCREW	4 PER HINGE INTO JAMB
55	0.30" X 3.94" BAUTEC WOOD SCREW	WITHIN 8" OF ENDS & 18" MAX. O.C.
57	0.24" X 3.74" WOOD SCREW	WITHIN 8" OF ENDS & 18" MAX. O.C.
58	0.18" X 2" WOOD SCREW	WITHIN 6" OF ENDS & 17" MAX. O.C.
59	0.136" X 1.26" SELF TAPPING SCREW	WITHIN 4" OF ENDS & 13 3/4" MAX. O.C.
60	0.136" X 1.50" SELF TAPPING SCREW	WITHIN 4" OF ENDS & 13 3/4" MAX. O.C.
61	0.11" X 0.87" SELF TAPPING SCREW	WITHIN 4" OF ENDS & 13 3/4" MAX. O.C.

CHECKED BY: W.W.S. DATE: 10/08/08

CTURER
TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600

PANEL DOORS

WOOD

IMPACT

W. SCHAEFER ENGINEERING CONSULTING, P.A. (CA 6809)

MAY 15 2018

DRAWING NO. 1617

SHEET NO. 19 of 19

Mitael Bade Product Control

NOTE: WOOD USED IN TESTING WAS SIPO MAHOGANY WITH A SPECIFIC GRAVITY OF G = 0.62 AND A MODULUS OF ELASTICITY OF E = 1,6000,000 PSI. OTHER WOOD SPECIES APPLICABLE FOR USE WITH THIS PRODUCT ARE THOSE WITH A SPECIFIC GRAVITY OF 0.62 AND MODULUS OF ELASTICITY OF 1,600,000 PSI OR GREATER. ALL WOOD IS MINIMUM GRADE 2 MILLED BY TISCHLER UND SOHN TO SELECT.

