



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION
NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

Stockmeier Urethanes USA, Inc.
200 Columbia Blvd.
Clarksburg, West Virginia 26301

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Stobicoat® N889 Elastomeric Roof Coating

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 3.

The submitted documentation was reviewed by Alex Tigera.



NOA No.: 22-0316.02
Expiration Date: 01/19/28
Approval Date: 01/19/23
Page 1 of 3

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cement-Adhesive-Coatings
Material: Elastomeric

SCOPE:

This approves “**Stobicoat® N889 Elastomeric Roof Coating**” as a roof coating, as manufactured by Stockmeier Urethanes USA, Inc. and described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

MANUFACTURING LOCATION:

1. Federalsburg, MD.

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name / Report</u>	<u>Date</u>
PRI Construction Materials	2403T00001	ASTM D6083	02/03/22
Technologies LLC	2403T00002		

PHYSICAL PROPERTIES OF COMPONENTS:

Trade name: Stobicoat® N889 Elastomeric Roof Coating

Application Rate: Surface receiving Stobicoat® N889 must be clean, stable, dry and free of contaminants that would affect the proper bonding of Stobicoat® N889 at an application rate of:

- **Modified Bitumen SBS Smooth or Granule Surface:** Using roller, brush or spray machine, evenly apply Stobicoat® N889 at an approximate consumption of 1.3 lb/yd². Final thickness shall be 36 mils.
- **Modified Bitumen APP Smooth or Granule Surface:** Using roller, brush or spray machine, evenly apply Stobicoat® N889 at an approximate consumption of 1.3 lb/yd². Final thickness shall be 36 mils.
- **Concrete:** Using roller, brush or spray machine, evenly apply Stobicoat® N889 at an approximate consumption of 1.3 lb/yd². Final thickness shall be 36 mils
- **Single Ply PVC:** Using roller, brush or spray machine, evenly apply Stobicoat® N889 at an approximate consumption of 1.3 lb/yd². Final thickness shall be 36 mils
- **Single Ply EPDM:** Using roller, brush or spray machine, evenly apply Stobicoat® N889 at an approximate consumption of 1.3 lb/yd². Final thickness shall be 36 mils
- **Galvanized Metal:** Using roller, brush or spray machine, evenly apply Stobicoat® N889 at an approximate consumption of 1.3 lb/yd². Final thickness shall be 36 mils

Specifications: ASTM D6083

Description: A 1-component polyurethane coating. Cures using moisture in the atmosphere.

Container Size: 5 gallon pails, 55-gallon drums or 275-gallon totes. Note all cautions on container label.



NOA No.: 22-0316.02
Expiration Date: 01/19/28
Approval Date: 01/19/23
Page 2 of 3

LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Stockmeier Urethanes USA, Inc. products shall not be applied in inclement weather conditions.
3. The product listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their Roof Assembly Notice of Acceptance. If a product is not listed as part of roof assemblies Notice of Acceptance, a request may be made to the local building official or the Miami Dade Product Control Section for approval provided that appropriate documentation is provided.
4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency, and shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code. Follow up test results shall be made available to Miami-Dade Product Control office upon request.
5. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
6. Stockmeier Urethanes USA, Inc. products shall be applied in accordance with manufacturer's published application instructions.
7. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below



END OF THIS ACCEPTANCE

