



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

**MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

SOPREMA, Inc.
310 Quadral Drive
Wadsworth, OH 44281

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: SOPREMA Cements, Adhesives and Coatings

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of the NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 5.

The submitted documentation was reviewed by Jorge L. Acebo.



NOA No.: 22-0706.01
Expiration Date: 02/09/28
Approval Date: 02/09/23
Page 1 of 5

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cements and Coatings
Materials: Asphalt

SCOPE:

This approves SOPREMA Cements, Adhesives and Coatings, for use on existing roof assemblies, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code. The uses of the "Proprietary" components specified in this approval are limited to being used only in those roof system assemblies wherein they are specifically listed as an accepted component.

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
NEMO ETC, LLC	ASTM D4586	4p-SOP-19-SSLAP-01.A	07/29/19
	ASTM D4586	4p-SOP-19-SSLAP-05.A	03/25/20
	Physical Properties	4p-SOP-21-SSLAP-04.A	06/22/22
	Physical Properties	4p-SOP-21-SSLAP-04.B	06/22/22
	ASTM D4586	4p-SOP-20-SSLAP-03.A	03/09/21
PRI Construction Materials Technologies	ASTM D4586	ENTL-002-02-01	11/16/16
	ASTM D3019	817T0017	01/21/21
	ASTM C920	1538T0005	08/04/21

MANUFACTURING LOCATIONS:

1. Drummondville, Quebec
2. Schoolcraft, MI
3. Kansas City, MO
4. Hallandale, FL

PHYSICAL PROPERTIES OF COMPONENTS

Trade Name: COLPLY Adhesive

Application Rate: 1.5 to 2 gallons per 100 square feet for sand-surfaced interply applications. The application rate over approved absorptive or rough substrate surfaces vary, requiring 2.5 gallons or more per 100 square feet. Granulated surfaces require 3 to 4 gallons per 100 square feet

Specifications: ASTM D3019

Description: Single component, asphalt cutback adhesive formulated for adhering SBS-modified bitumen membrane systems

Container Size: 5 gallon pail, 50 gallon drum, 350 gallon tote

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #3



NOA No.: 22-0706.01
Expiration Date: 02/09/28
Approval Date: 02/09/23
Page 2 of 5

PHYSICAL PROPERTIES OF COMPONENTS (CONTINUED)

Trade Name: COLPLY EF Adhesive
Application Rate: Apply at 1.5 to 2 gallons per 100 square feet for flashing applications
Specifications: Proprietary
Description: Solvent-free, Low VOC adhesive, designed for use with SBS-modified bitumen membrane systems
Container Size: 0.4 gallon cartridge, 5 gallon pail, 50 gallon drum
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #2

Trade Name: COLPLY Flashing Cement
Application Rate: Apply at 2-2.5 gallons per 100 square feet for sand-surfaced interply applications. The application rate over approved absorptive or rough substrate surfaces vary, requiring 2.5 gallons or more per 100 square feet. Granulated surfaces require 4 to 5 gallons per 100 square feet
Specifications: ASTM D4586
Description: Elastomeric bitumen based mastic compound
Container Size: 5 gallon pail
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #4

Trade Name: COLPLY EF Flashing Cement
Application Rate: Apply COLPLY EF Adhesive at 1.5 to 2 gallons per 100 square feet for sand-surfaced interply applications
Specifications: ASTM D4586
Description: Single-component viscous cement for use with SBS-modified bitumen membrane flashing assemblies
Container Size: 3.5 gallon pail
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #2

Trade Name: ELASTOCOL 500
Application Rate: Applied at a rate of 0.35 to 0.6 gallon per 100 square feet over non porous substrate
Specifications: Proprietary
Description: Asphalt based primer for use in approved multi-ply membrane and flashing assemblies.
Container Size: 5 gallon pail
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #1



PHYSICAL PROPERTIES OF COMPONENTS (CONTINUED)

Trade Name: ELASTOCOL Stick
Application Rate: Applied at a rate of 0.7 to 1 gallon per 100 square feet
Specifications: Proprietary
Description: SBS polymer based primer for use in approved multi-ply membrane and flashing assemblies
Container Size: 5 gallon pail
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #1

Trade Name: ELASTOCOL Stick Zero
Application Rate: Applied at a rate of 0.7 to 1 gallon per 100 square feet
Specifications: Proprietary
Description: Polymer based primer for use in approved multi-ply membrane and flashing assemblies
Container Size: 5 gallon pail
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #1

Trade Name: SOPRAMASTIC SP1
Application Rate: Applied to the approved area via cartridge tube applicator. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.
Specifications: ASTM C920
Description: Moisture cured polyether sealant for use in approved multi-ply membrane and flashing assemblies
Container Size: 10 oz. Tube
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #2

Trade Name: SOPRAMASTIC SBS ELASTIC CEMENT
Application Rate: Applied at a rate of 70 to 140 square foot per gallon
Specifications: ASTM D4586
Description: Modified bitumen mastic for use in approved flashing assemblies
Container Size: 5 gallon pail
Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.

Manufacturing Location #3



LIMITATIONS:

1. Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this products.
2. SOPREMA Cements, Adhesives and Coatings shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test result shall be made available to Miami-Dade Product Control upon request.
5. Change in materials, use or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
6. These roof coatings shall not be applied over, prepared roofing; i.e., fibercement shingles, quarry slate, cement or clay roof tile, metal shingles, wood shingles or shakes.
7. SOPREMA Cements, Adhesives and Coatings shall be used as components within approved roofing systems in accordance with applicable building code. SOPREMA Cements, Adhesives and Coatings are not approved to be used as repair or recover roof systems.
8. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below



9. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

END OF THIS ACCEPTANCE

