



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

**MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

Chem Link, Inc.
353 E. Lyon Street
Schoolcraft, MI 49087

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: **DuraGlaze Plus Sealant**

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 3.

The submitted documentation was reviewed by Jorge L. Acebo.



NOA No.: 22-0815.04
Expiration Date: 09/29/27
Approval Date: 09/29/22
Page 1 of 3

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cement-Adhesive-Coatings
Material: Elastomeric Joint Sealants

SCOPE:

This approves **DuraGlaze Plus** manufactured by Chem Link Inc., for use as a sealant as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

PRODUCT DESCRIPTION:

Tradename: DuraGlaze Plus
Specifications: TAS 132
Description: Solvent free, non-slump, moisture-cure, polyether sealant
Container Size: 10.1 oz. cartridges, 20 oz. sausages, and 1.5 gallon bucket (packaged in a 2 gallon pail).
Note all precautions on container.

PHYSICAL PROPERTIES OF COMPONENT:

Property	Standard	Results
Adhesion		
Aluminum (73° F) – direct to substrate	ASTM C794	48 pli. Dry/ 27 pli. Wet
Concrete (72° F) – direct to substrate	ASTM C794	37 pli. Dry/ 22 pli. Wet
Steel (73° F) – direct to substrate	ASTM C794	25 pli. Dry/ 26 pli. Wet
Vinyl (73° F) – direct to substrate	ASTM C794	27 pli. Dry/ 27 pli. Wet
Wood (73° F) – direct to substrate	ASTM C794	29 pli. Dry/ 20 pli. Wet
Tensile Strength @ 73°	ASTM D412	247 psi
Elongation @ 73°	ASTM D412	716 %
Modulus of Elongation	ASTM D412	302 psi.
Hardness (Shore A)	ASTM C661	46

Note: The physical properties listed above are presented at typical average values as determined by accepted ASTM test methods and are subject to normal manufacturing variation.

MANUFACTURING LOCATION

1. Schoolcraft, MI

EVIDENCE SUMMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Construction Materials Technologies, LLC	1538T0011/1538T0015	TAS 132	06/30/22



NOA No.: 22-0815.04
Expiration Date: 09/29/27
Approval Date: 09/29/22
Page 2 of 3

LIMITATIONS:

1. Fire classification is not part of this acceptance, refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Chem Link, Inc. products shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
5. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance
6. DuraGlaze Plus shall be applied in accordance with manufacturer's published application instructions.
7. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE



NOA No.: 22-0815.04
Expiration Date: 09/29/27
Approval Date: 09/29/22
Page 3 of 3