

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION NOTICE OF ACCEPTANCE (NOA)

Rust-Oleum Corporation 11 E. Hawthorn Pkwy Vernon Hills, IL 600661

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Rust-Oleum Silicone Roof Coating Systems

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews and revises NOA No. 21-0603.04 and consists of pages 1 through 3. The submitted documentation was reviewed by Jorge L. Acebo.



mail

NOA No.: 22-0829.05 Expiration Date: 05/03/28 Approval Date: 12/15/22 Page 1 of 3

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599 www.miamidade.gov/economy

ROOFING COMPONENT APPROVAL

Category:RoofingSub-Category:Cements - Coatings - AdhesivesMaterials:Elastomeric

SCOPE:

This approves **Rust-Oleum Silicone Roof Coating Systems** as described in this Notice of Acceptance. These products have been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

MANUFACTURING LOCATION:

1. Toronto, ON

EVIDENCE SUMITTED:

Test Agency	Test Identifier	<u>Test Name/Report</u>	Date
UL LLC	R20858	UL790	05/11/21
NEMO ETC LLC	4p-RUST-20-SSLAP-02.A	ASTM D6694	01/18/21

PHYSICAL PROPERTIES OF COMPONENTS:

Trade name:	995 Silicone Roof Coating, TremPro Silicone Roof Coating
Thickness:	See System Approvals Below
Specifications:	ASTM D 6694
Description:	A high solids silicone coating membrane applied to Spray Applied Polyurethane Foam (SPUF) Concrete, and existing (aged) acrylic surfaces applied at an application rate of: Spray Applied Polyurethane Foam: Apply a coat at a minimum rate of 1.5 gallons per 100 square feet. Concrete Surface: Apply a coat at a minimum rate of 1.5 gallons per 100 square feet. Aged Acrylic Surface: Apply a coat at a minimum rate of 1.5 gallons per 100 square feet.
Container Sizes:	5, 50, 275 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.
	11.7

Manufacturing Location #1



NOA No.: 22-0829.05 Expiration Date: 05/03/28 Approval Date: 12/15/22 Page 2 of 3

BUILDING PERMIT REQUIREMENTS:

As required by the Building Official or the applicable Building Code in order to properly evaluate the installation of this system. This Notice of Acceptance on its own cannot be used to obtain a building permit.

LIMITATIONS:

- 1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
- 2. Rust-Oleum Silicone Roof Coating Systems shall not be applied in inclement weather conditions.
- 3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list the products listed herein as part of their Roof Assembly Notice of Acceptance. See Roof System Notice of Acceptance (NOA) for application rates and uses.
- 4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade County Product Control upon request.
- 5. Change in materials, use, or manufacture of any products listed herein shall be cause for termination of this Notice of Acceptance.
- 6. Rust-Oleum Silicone Roof Coating Systems shall be applied in accordance with manufacturer's published application instructions unless specified otherwise within the NOA approvals.
- 7. The roof coatings listed herein shall not be applied over, prepared roofing; i.e., fibercement shingles, quarry slate, cement or clay roof tile, metal shingles, wood shingles or shakes.
- 8. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
- 9. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE

