



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786)315-2590 F (786) 31525-99

www.miamidade.gov/economy

Mid-States Asphalt and Cant Strip, Inc.
1637 51st Avenue
Tuscaloosa, AL. 35401

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: QUIK-STICK HT PRO+ Underlayment

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 3.

The submitted documentation was reviewed by Jorge L. Acebo.



NOA No.: 22-1020.13
Expiration Date: 06/29/28
Approval Date: 06/29/23
Page 1 of 3

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Underlayment
Material: SBS

SCOPE:

This approves “**QUIK-STICK HT PRO+ Underlayment**” manufactured by Mid-States Asphalt and Cant Strip, Inc., as described in this Notice of Acceptance. The use of this acceptance is limited to approved roofing system Notice of Acceptances listing the products below as a component part of an approved system within the approved roof system Notice of Acceptance.

PRODUCT DESCRIPTION:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
QUIK-STICK HT PRO+	39” x 66.8’	TAS 103 ASTM D1970	SBS modified self-adhesive membrane reinforced with non-woven fiberglass mat. Its textured film surface provides improved traction while working on the roof and is designed for use in Tile and non-structural Metal roof systems applications.

MANUFACTURING LOCATION:

1. Tuscaloosa, AL.

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Construction Materials	1085T0021.1	TAS 103/D1970	07/25/22
Technologies, LLC.	1085T0022.1	TAS 103/ASTM D4798	07/25/22
	1085T0024B	TAS 103/ASTM D1623	07/25/22


APPROVED ASSEMBLIES

Deck Type 1:	Wood, Non-Insulated
Deck Description:	Minimum 19/32” plywood, wood plank
System E(6):	Anchor sheet mechanically fastened to deck; membrane adhered.
Anchor/Base Sheet:	One or more plies of ASTM D226 Type II, ASTM D2626, with a minimum 4” wide side lap and a minimum 8” wide end lap, mechanically fastened to deck.
Fastening:	Approved nails and tin caps 6” o.c. within lap and two equally spaced staggered rows 12” o.c. in the field (for Anchor/Base sheet only).
Membrane:	QUIK-STICK HT PRO+ underlayment applied to an approved Anchor/Base Sheet. Membrane is to be back nailed along the head lap. The nails shall be, 11 gauge 1 ¹ / ₄ ” approved ring shank type applied with a minimum of a 1 ⁵ / ₈ ” approved tin cap as required per the High Velocity Hurricane Zone (HVHZ) section of the FBC.
Surfacing:	Approved Roof Assemblies as specified in Limitation #4.



NOA No.: 22-1020.13
Expiration Date: 06/29/28
Approval Date: 06/29/23
Page 2 of 3

LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
 2. QUIK-STICK HT PRO+ underlayment is designed for use as specified within approved roofing system NOA assemblies.
 3. This acceptance establishes the required physical properties testing and traceability of roofing membrane and accessory components listed in approved roofing applications. Minimum deck requirements shall be in compliance with applicable building code. QUIK-STICK HT PRO+ underlayment shall be installed in strict compliance with applicable Building Codes, Product Approvals and Manufacturers' specifications and guidelines.
 4. QUIK-STICK HT PRO+ underlayment may be used with mechanically fastened clay and concrete roof tiles or clay and concrete roof tiles set in, The Dow Chemical Company's TILE BOND™ Roof Tile Adhesive, or DAP Product's Inc. Touch'n Seal Storm Bond Roof Tile Adhesive.
 5. QUIK-STICK HT PRO+ underlayment shall not be left exposed as a temporary roof for longer than 180 days of application.
 6. When loading roof tiles on roof tile underlayment for (direct-to-deck) tile assemblies, the maximum roof slope shall be 6 in.:12 in. This slope limitations can be exceeded only by using battens in accordance with the Approved Tile System Notice of Acceptance and applicable Florida Building Code requirements. When battens are required, they shall be utilized during loading and installation of tiles
 7. Change in materials or manufacturing process or location of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
 8. QUIK-STICK HT PRO+ underlayment may be used with any approved Roof Assembly Notice of Acceptance listing QUIK-STICK HT PRO+ underlayment as a component part of an assembly in the Notice of Acceptance. If QUIK-STICK HT PRO+ underlayments is not listed; a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
 9. All membranes and accessories or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.
- 
10. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

END OF THIS ACCEPTANCE

