



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

Horton Automatics Division of Overhead Door
4242 Baldwin Boulevard
Corpus Christi, TX 78405

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series 110 Aluminum Automatic Sliding Door (Sx-O) w/ Breakout-NI

APPROVAL DOCUMENT: Drawing No. **040709-N REV 5**, titled "Series 2001/110 Non-Impact Single Slide", sheets 1 through 5 of 5 prepared by manufacturer, dated 11/25/09 and last revised on 10/08/18, signed and sealed by John E. Scates, P.E., bearing the Miami-Dade County Product Control Renewal stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: None

Limitations:

1. Approved Hurricane protection Devices complying w/ FBC, are required, as applicable.
2. Not approved where water infiltration is required.
3. See sheet **3** for anchor and substrates options. Applicable edge distance to be measured from screw center line to the outer face of the substrate.
4. See glazing details in sheet **2**. See Max DLO in sheet **1** and max DLO for optional Muntins in sheet **3**.
5. Electrical/ Electronic functions are not part of this approval and to be reviewed by appropriate Bldg. official.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and series and following statement: "Miami-Dade County Product Control Approved", noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA **revises & renews NOA # 20-0915.05** and consists of this page 1 and evidence pages E-1, E-2 & E-3 as well as approval document mentioned above.

The submitted documentation was reviewed by **Ishaq I. Chanda, P.E.**



Ishaq I. Chanda

Horton Automatics Division of Overhead Door

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

1. Evidence submitted under previous approvals

A. DRAWINGS

1. Manufacturer's die drawings and sections (see files below)
2. Drawing No. **040709-N REV 4**, titled "Series 2001/110 Non-Impact Single Slide", sheets 1 through 5 of 5 prepared by manufacturer, dated 11/25/09 and last revised on 07-31-16, signed and sealed by John E. Scates, P.E.

B. TESTS (submitted under files # 15-0922.10/#13-0530.14/#12-0801.09/ #10-0322.16)

1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
3) Water Resistance Test, per FBC, TAS 202-94 (Not conducted)
4) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with installation diagram of aluminum automatic sliding glass doors, prepared by Hurricane Testing Laboratories, Test Report No(s). **HTL-0322-0611-03** and **HTL-0322-0908-03** both dated 02/16/04, signed and sealed by Vinu J. Abraham, P.E.

C. CALCULATIONS

1. Anchor verification calculations and structural analysis complying w/ FBC 2014 (5th Edition), dated 09/11/15, prepared, signed and sealed by John E. Scates, P.E.
2. Glazing complies w/ ASTM E-1300-02, -04 & -09.

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. Technical data sheet of ExxonMobil Chemical's SantopreneTM 121-67W175 thermoplastic, extruded by Central Chemical Inc.

F. STATEMENTS

1. Statement letter of conformance to FBC 2014(5th Edition) & "No financial interest", dated 09/11/15, signed & sealed by John E. Scates, P.E.
2. Addendum letter dated 06-12-08, issued by Hurricane Testing lab, signed and sealed by Vinu Abraham, P. E. (submitted under files **#12-0801.05/ #08-0528.05**)
3. Lab compliance as part of the above referenced test report.

G. OTHER

1. This NOA **revises & renews** NOA # **13-0530.14**, expiring on October 09, 2023.

Ishaq I. Chanda

Ishaq I. Chanda, P.E.
Product Control Unit Supervisor
NOA No. 23-0622.12
Expiration Date: October 09, 2028
Approval Date: August 10, 2023

Horton Automatics Division of Overhead Door

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

2. Evidence submitted under previous approvals (#17-0828.03)

A. DRAWINGS

1. None.

B. TESTS

1. None

C. CALCULATIONS

1. None

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS

1. Statement letters of conformance to FBC 2017(6th Edition) & FBC 2014 (5th Edition) dated 11/02/17, prepared, signed and sealed by John E. Scates, P.E.

G. OTHER

1. This NOA revises NOA # 15-0922.10, expiring 10/09/2023.

3. Evidence submitted under previous approval

A. DRAWINGS

1. Drawing No. **040709-N REV 5**, titled "Series 2001/110 Non-Impact Single Slide", sheets 1 through 5 of 5 prepared by manufacturer, dated 11/25/09 and last revised on 10/08/18, signed and sealed by John E. Scates, P.E.

B. TESTS

1. None

C. CALCULATIONS

1. None

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS

1. Statement letters of conformance to FBC 2020(7th Edition) dated 08/28/20, prepared, signed and sealed by John E. Scates, P.E.

G. OTHER

1. This NOA revises NOA # 18-1025.09, expiring 10/09/2023. *Ishaq I. Chanda*

Ishaq I. Chanda, P.E.
Product Control Unit Supervisor
NOA No. 23-0622.12
Expiration Date: October 09, 2028
Approval Date: August 10, 2023

Horton Automatics Division of Overhead Door


NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

- 4. New Evidence submitted**
- A. DRAWINGS**
1. Drawing No. **040709-N REV 5**, titled “Series 2001/110 Non-Impact Single Slide”, sheets 1 through 5 of 5 prepared by manufacturer, dated 11/25/09 and last revised on 10/08/18, signed and sealed by John E. Scates, P.E.
- B. TESTS**
1. None.
- C. CALCULATIONS**
1. None.
- D. QUALITY ASSURANCE**
1. Miami Dade Department of Regulatory and Economic Resources (RER).
- E. MATERIAL CERTIFICATIONS**
1. None.
- F. STATEMENTS**
1. Statement letters of conformance to FBC 2023 (**8th** Edition) & “No financial interest” dated 06/23/23, prepared, signed and sealed by John E. Scates, P.E.
 2. Statement letters of conformance to FBC 2020(**7th** Edition) dated 08/28/20, prepared, signed and sealed by John E. Scates, P.E.
- G. OTHER**
1. This NOA **revises & renews NOA # 20-0915.05** and updates to FBC 2023, expiring 10/09/2028.


Ishaq I. Chanda

Ishaq I. Chanda, P.E.
Product Control Unit Supervisor
NOA No. 23-0622.12
Expiration Date: October 09, 2028
Approval Date: August 10, 2023

Series 110 Non-Impact Slide




"SX" PANEL
TOP PIVOT



"SX" PANEL
BTM. PIVOT

A.R. FLUSH BOLT (24)
ENGAGED IN TOP
BREAKAWAY BARS AT
HEADER



A.R. FLUSH BOLT
ENGAGED
IN THRESHOLD (24)


LOCK BOLT DETAIL

3-POINT LOCK

PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 20-0528.03


Expiration Date 10/31/2023

By Ishag I. Chande
Miami-Dade Product Control



CONNECTION BLOCK
WITH REINFORCEMENT

STRIKE RAIL (SX)



CONNECTION BLOCK

INTERLOCK RAIL (SX)
INTERLOCK RAIL (SO)
FIXED RAIL (SO)

WEATHERSEALS:
C350 NOSING SEAL
C524-FL SIDE PANEL BOTTOM SEAL
C293 WEATHER SEAL

HARDWARE:
C883 THRESHOLD/HEADER BOLT

SCHLEGEL CORP. SKIRTING SEAL #1104-5101
FELTON NYLON BRISTLE #490621
SCHLEGEL CORP. #8430-5016-7

ADAMS-RITE #4015

PRODUCT RENEWED
as complying with the Florida
Building Code
NOA-No. 23-0622.12


Expiration Date 10/09/2028

By Ishag I. Chande
Miami-Dade Product Control


PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 20-0915.05

Expiration Date 10/09/2023

By Ishag I. Chande
Miami-Dade Product Control




MUNTIN OPTION



GLAZING DETAIL

Series 110 Non-Impact Slide

JOHN E. SCATES
2560 King Arthur Blvd., Ste 124-54
Lewisville, TX 75058
FL PE 51737





John E. Scates 10/8/18

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 18-1025.09
Expiration Date 10/9/23
By Ishag I. Chande
Miami-Dade Product Control

NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARK-UPS	12/29/09	SERIES: 110 TYPE: "O-SX" & "SX-O"
3	REVISED FOR NOA RENEWAL	08/13/13	STYLE: NARROW FINISH:
4	REVISED FOR NOA	09/09/15	ACTUATION:
5	UPDATED GLAZING DETAIL	09/08/18	
6			
7			
8			

Misc. Details
Dwg. No. 040709-N

A DIVISION OF OVERHEAD DOOR CORP.
4242 BALDWIN BOULEVARD
CORPUS CHRISTI, TEXAS 78405-3399
361-888-5591 1-800-531-3111
FAX: 361-888-6510, 1-800-531-3108
JOB: **METRO-DADE**
LOCATION:
DISTRIBUTOR:
OWN: M. JONES P.O. # SHEET 2 of 5
CHIKA NADGOUDA DATE 04/10/09 REVISION 5



PRODUCT RENEWED
 as complying with the Florida
 Building Code
 NOA-No. 23-0622.12
 Expiration Date 10/09/2028
 By Ishag I. Chande
 Miami-Dade Product Control

PRODUCT REVISED
 as complying with the Florida
 Building Code
 NOA-No. 20-0915.05
 Expiration Date 10/09/2023
 By Ishag I. Chande
 Miami-Dade Product Control


HEADER
 Steel (0.125" Thick, Fy=36 KSI) - INTERCORP #14
 Steel HWH Self-Drilling Screw (Grade 5), 0.625"
 Min. Edge Distance
 Aluminum(0.125" Thick Min./6063-T5) - 1/4"-14
 HWH Sheetmetal Screw (Grade 5), 1" Min. Edge
 Distance.

JAMBS
 Steel (0.125" Thick, Fy=36 KSI) - ITW TEKS SCREW
 (Grade 5) #14-20, HWH Self-Drilling Screw
 0.625" Minimum Edge Distance
 Concrete(3350 PSI) - Crete-Flex SS4 1/4"
 HWH Concrete Screw/Anchor, 1.75" Embed,
 2.5" Min. Edge Distance
 Masonry(Solid CMU ASTM C-90 Block) -
 Crete-Flex SS4 1/4" HWH Concrete
 Screw/Anchor, 1.25" Embed, 2.5" Min. Edge
 Distance
 Aluminum(0.125" Thick Minimum/6063-T5) -
 1/4"-14 HWH Sheetmetal Screw (Grade 5), 1"
 Min. Edge Distance.
 Wood(#2 SYP)-1/4" x 4" Long Lag Bolt -
 Grade 5, 2.75" Minimum Penetration, 1" Minimum
 Edge Distance. Minimum Buck (2) 2X8 W/Min
 G = .55.

THRESHOLD
 Steel (0.125" Thick, Fy=36 KSI)- ITW TEKS SCREW
 #14-20 PFH w/Wings Self-Drilling Screw (Grade
 5), 0.625" Minimum Edge Distance
 Concrete(3350 PSI)- Crete-Flex SS4 FH 1/4"
 Concrete Screw 1.75" Embed, 2.5" Minimum
 Edge Distance
 Aluminum(0.125" Thick Minimum/6063-T5) -
 1/4"-14 FH Sheetmetal Screw (Grade 5), 1"
 Minimum Edge Distance

JOHN E. SCATES
 2560 King Arthur Blvd., 124-54
 Lewisville, TX 75056
 FL PE 51737

PRODUCT REVISED
 as complying with the Florida
 Building Code
 Acceptance No. 18-1025.09
 Expiration Date 10/9/23
 By Ishag I. Chande
 Miami-Dade Product Control



Series 110 Non-Impact
 Slide Anchor Locations


NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARK-UPS	12/29/09	SERIES: 110
3	REVISED FOR NOA RENEWAL	06/13/13	TYPE: "O-SX" & "SX-O"
4	REVISED FOR NOA	09/09/13	STYLE: NARROW
5	UPDATED GLAZING DETAIL	06/06/18	FINISH:
6			ACTUATION:
7			
8			

Anchor Locations
 Dwg. No. 040709-N

A DIVISION OF OVERHEAD DOOR CORP. 4242 BALDWIN BOULEVARD CORPUS CHRISTI, TEXAS 78405-3399 361-888-5591 1-800-531-3111 FAX: 361-888-6510, 1-800-531-3108			
Horton			
JOB: METRO-DADE			
LOCATION:			
DISTRIBUTOR:	P.O. #	SHEET 3 of 5	
CHK: ANAD800DA	DATE: 04/10/09	REVISION 6	


ITEM #	HORTON PART NUMBER	DESCRIPTION
1	C03600.005AB	ALUMINUM EXTRUSION: HEADER
2	C03601.002AB	ALUMINUM EXTRUSION: HEADER FACEPLATE
3	C00358.000R	ALUMINUM EXTRUSION: ASTRAGAL
4	C00314.0000	ALUMINUM EXTRUSION: INTERLOCK TOP
5	C00327.0000AB	ALUMINUM EXTRUSION: INTERLOCK LOWER
6	C00337.000R	ALUMINUM EXTRUSION: TOP RAIL (SX) & MUNTIN (SX/SO)
7	C00338.000R	ALUMINUM EXTRUSION: GLASS STOP
8	C00336.0001	ALUMINUM EXTRUSION: BOTTOM RAIL (SX)
9	C00325.0002	ALUMINUM EXTRUSION: BOTTOM RAIL (SO)
10	C00315.0000	ALUMINUM EXTRUSION: TRACK FILLER
11	C00330.0001	ALUMINUM EXTRUSION: BOTTOM GUIDE
12	C00386.0001	ALUMINUM EXTRUSION: ADAPTOR
13	C02801.0000	ALUMINUM EXTRUSION: TOP RAIL (SO)
14	C02899.0002	ALUMINUM EXTRUSION: CORNER BLOCK (USED AS REINFORCEMENT)
15	C00390.0000	ALUMINUM EXTRUSION: THRESHOLD 7"
16	C00351.0000	ALUMINUM EXTRUSION: JAMB TUBE 4" X 1-3/4 W/ POCKET
17	C00335.000R	ALUMINUM EXTRUSION: VERTICAL RAIL (SX/SO INTERLOCK) (SO FIXED)
18	C00363.0000	ALUMINUM EXTRUSION: VERTICAL RAIL (SX STRIKE)
19	C00818.000R	BAR TORSION
20	C00524.00FL	WEATHERSEAL BRUSH (FELTON #490621)
21	C00350.0000	NOSING SEAL SCHLEGEL #1104-5101
22	C00397.0000	ADAPTER FOR C00389.01FL
23	C00293.0000	WEATHER SEAL BRUSH SCHLEGEL #8430-5016-7
24	C00454.0000	LOCK, ADAMS RITE MS1850S W/ ADAMS RITE 4015 HEADER/THRESHOLD BOLT
25	C00463.0000	THUMBTURN ADAMS RITE 4066
26	C02098.0000	SECURITY POST; 1/2" O.D. X 3/4" LG X .083" WALL ALUM. TUBE
27	C00883.0000	3/8 HEXT BOLT ADAMS RITE 4015 EXTENDING INTO HEAD AND SILL 1/2"
28	C00843.01FL	BOTTOM GUIDE DOOR MOUNTED
29	C00844.01FL	BOTTOM GUIDE DOOR MOUNTED
30	C03638.0000	HEADER & FACEPLATE SUPPORT
31	C00371.000R	WEATHERSTRIP; PANEL TO JAMB
32	C00664.0001	#8 X 3/4 FHSMS
33	C09652.0000	#10 X 3/4 FHSMS
34	C00404.0000	1/4-20 LOCK NUT
35	C00417.0000	#14 X 1-1/2 HWSMS
36	C00449.0000	#10-24 X 1 FHMS
37	C03682.0006	DRIVE WHEEL ASSEMBLY
38	C03681.0001	IDLER WHEEL ASSEMBLY
39	C08151.0000	1/4-20 X 1 FHMS
40	C08150.0000	1/4-20 X 3/4 HHMB

ITEM #	HORTON PART NUMBER	DESCRIPTION
41	C00537.000R	CORNER BLOCK (SX TOP) (SX/SO MUNTIN)
42	C09490.0001	CORNER BLOCK (SO TOP)
43	C00536.0001	CORNER BLOCK (SX BOTTOM)
44	C09582.0002	CORNER BLOCK (SO BOTTOM)
45	C00341.0001	VINYL GLAZING BULB
46	C00289.0000	TRACK CAP
47	C00389.001FL	INTERLOCK SEAL SCHLEGEL #7595-6011-0
48	C01905.0000	STEEL TUBE (1-1/4" X 1-1/4" X 3/16" X 80.50") A-36
49	C00437.000AB	#10-24 X 1/2 FHSMS
50	C00353.0000	COVER; RECESS - JAMB
51	C00538.000R	BACKUP PLATE; CRS
52	C00552.0003	GLAZING BLOCK, SNAP-IN NYLON 6-6 MIN HARDNESS ROCKWELL M85



PRODUCT RENEWED
as complying with the Florida
Building Code
NOA-No. 23-0622.12
Expiration Date 10/09/2028
By Ishag I. Chande
Miami-Dade Product Control


PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 20-0915.05
Expiration Date 10/09/2023
By Ishag I. Chande
Miami-Dade Product Control




















PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 12-1025.09
Expiration Date 10/9/2023
By Ishag I. Chande
Miami-Dade Product Control

NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARKUPS	12/09/09	SERIES: 2001/110 TYPE: "O-SX" & "SX-O"
3	REVISED FOR NOA RENEWAL	09/13/13	STYLE: NARROW FINISH:
4	REVISED FOR NOA	09/09/15	ACTUATION:
5	UPDATED GLAZING DETAIL	09/09/18	Bill of materials
6			Dwg. No. 040709-N
7			
8			

A DIVISION OF OVERHEAD DOOR CORP. 4242 BALDWIN BOULEVARD CORPUS CHRISTI, TEXAS 78405-3399 361-888-5591 1-800-531-3111 FAX: 361-888-6510, 1-800-531-3108	
Horton	
JOB METRO-DADE	
LOCATION:	
DISTRIBUTOR:	
DWN: M.JONES	P.O. #
CHK: A. NADGOUDAI	DATE: 04/10/09
REVISION	5



6" X 8"
(152.4) (203.2)
ASSEMBLED



C1905
ASTM A-36 STEEL

PRODUCT RENEWED
as complying with the Florida
Building Code
NOA-No. 23-0622.12
Expiration Date 10/09/2028
By *Ishag I. Chande*
Miami-Dade Product Control

PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 20-0915.05
Expiration Date 10/09/2023
By *Ishag I. Chande*
Miami-Dade Product Control

ALL EXTRUSIONS ARE 6063-T5 UNLESS
OTHERWISE NOTED & t min=1/8"

Series 110 Non-Impact Slide

NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARK-UPS	11/28/09	SERIES: 110
3	REVISED FOR NOA RENEWAL	08/13/13	TYPE: "O-SX" & "SX-O"
4	REVISED FOR NOA	09/06/15	STYLE: NARROW
5	UPDATED GLAZING DETAIL	09/06/18	FINISH:
6			ACTUATION:
7			
8			

Extrusion chart
Dwg. No. 040709-N

JOHN E. SCATES
2560 King Arthur Blvd., Ste 124-54
Lewisville, TX 75056
FL PE 51737

JOHN E. SCATES
LICENSE
No. 51737
STATE OF
FLORIDA
PROFESSIONAL ENGINEER

John E. Scates
10/8/18

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 18-1025.09
Expiration Date 10/09/2023
By *Ishag I. Chande*
Miami-Dade Product Control

A DIVISION OF OVERHEAD DOOR CORP. 4242 BALDWIN BOULEVARD CORPUS CHRISTI, TEXAS 78405-3399 361-888-5591 1-800-531-3111 FAX: 361-888-6510, 1-800-531-3108
Horton
JOB: METRO-DADE
LOCATION:
DISTRIBUTOR:
OWN: M. JONES
CHK: A. NADGOUDA
P.O. #
DATE: 04/10/09
REVISION
SHEET 5 of 5