



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
 BOARD AND CODE ADMINISTRATION DIVISION

**NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY  
 PRODUCT CONTROL SECTION  
 11805 SW 26 Street, Room 208  
 Miami, Florida 33175-2474  
 T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

**VEKA, Inc.**  
**100 Veka Drive**  
**Fombell, PA 16123**

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER-Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

**DESCRIPTION:** The approved **White Rigid PVC Exterior Extrusions** for Windows and Doors are to be produced by Extruders Licensees in “Fenestration and Glazing Industry Alliance (FGIA) (formerly AAMA) Certification Programs for rigid PVC Extrusions”. The extrusions shall meet ASTM D 4726, classification (ASTM D 4216) 1-10154-33-0000, 1-20131-13-0000 or 1-40131-13 and the following properties:

| <u>Description</u>                                  | <u>Test</u> | <u>Performance</u> |
|---|-------------|--------------------|
| Rate of Burning                                     | ASTM D635   | Class CC1          |
| Self-Ignition Temperature                           | ASTM D1929  | 925°F > 650°F      |
| Average Smoke Density Rating                        | ASTM D2843  | 43 < 75            |
| Flame Spread Index                                  | ASTM E84    | 26.2 < 75          |
| Xenon Arch Light Exposure (Weathering)              | ASTM G155   | 4,500 Hours        |
| Tensile Strength (Difference: *Exposed & Unexposed) | ASTM D638   | 4.98% < 10%        |
| *Exposed per FBC Section 2615                       |             |                    |

**MISSILE IMPACT RATING: None**

This NOA **revises NOA # 22-1104.01** and consists of pages 1 and 2, as well as evidence page E-1.

The submitted documentation was reviewed by **Carlos M. Utrera, P.E.**



10/02/24

NOA No: 24-0904.04  
 Expiration Date: December 1, 2027  
 Approval Date: October 10, 2024  
 Page 1



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

**NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

**VEKA, Inc.**  
100 Veka Drive  
Fombell, PA 16123

**LIMITATION:** This approval does not include an evaluation of structural performance of this component. Test reports and other required documents shall be submitted to Miami-Dade County Product Control; showing that the systems using this PVC Extrusion will resist the loads according to Chapter 16 of the Florida Building Code, in order to issue a specific product approval for the system.

**LABELING:** Each carton containing certified extrusions shall be labeled with the AAMA PVC Extrusion Certification Label, the extruder name, city, state and "MDCA". In addition, (a) each Certified Extrusion shall be labeled every 4 ft or less on the underside with the Extruder Code and "MDCA" or (b) each finished product assembly shall be labeled with a permanent label and/or stamp with the Extruder Code and "MDCA".

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.



10/02/24

NOA No: 24-0904.04  
Expiration Date: December 1, 2027  
Approval Date: October 10, 2024  
Page 2

**NOTICE OF ACCEPTANCE: EVIDENCE PAGE**

**A. DRAWINGS**

1. None.

**B. TESTS “Submitted under AAMA Master File # 98-0036”**

1. Test report on Rate of Burning, Ignition Temperature, Density of Smoke, Surface Burning Characteristics, Accelerated Weathering and Tensile Properties Test of “PVC Extrusions from 5 different manufacturer” selected by AAMA”, prepared by ETC Laboratories, Test Report # ETC 97-264-40910, dated 04/21/1998, signed and sealed by J. L. Doldan, P.E.

**C. CALCULATION**

1. None.

**D. QUALITY ASSURANCE**

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

**E. MATERIAL CERTIFICATION “Submitted under FGIA Master File # 23-1652”**

1. Procedural Guide for the AAMA Fenestration Exterior Thermoplastic Profile Certification Program (AAMA 109-15).
2. Voluntary Specification for Rigid Polyvinyl Chloride (PVC) Exterior Profiles (AAMA 303-18).

**F. STATEMENTS**

1. Statement letter of code conformance to the 8<sup>th</sup> Edition (2023) of the FBC and standards’ equivalency issued by Turner Engineering & Consulting, Inc., dated 10/06/2023, signed and signed by Lucas A. Turner, P.E. “Submitted under FGIA Master File # 23-1652”
2. Statement letter of code conformance to the 7<sup>th</sup> Edition (2020) FBC and standards’ equivalency issued by Turner Engineering & Consulting, Inc., dated 07/07/2020, signed and signed by Lucas A. Turner, P.E. “Submitted under FGIA Master File # 20-0942”
3. Statement letter of code conformance to the 5<sup>th</sup> Edition (2014) FBC issued by Turner Engineering & Consulting, Inc., dated 02/19/2015, signed and signed by Lucas A. Turner, P.E. “Submitted under AAMA Master File # 15-0333”
4. Standards’ equivalency report issued by Turner Engineering & Consulting, Inc., dated 02/19/2015, signed and signed by Lucas A. Turner, P.E.

**G. OTHERS**

1. Release letter issued by Fenestration & Glazing industry Alliance (FGIA, formerly AAMA), dated 02/16/2024, signed by Jason Seals.
2. Acknowledgement letter issued by Veka, Inc., dated 08/28/2024, signed by Nils Hinrichsen.



---

**Carlos M. Utrera, P.E.**  
**Product Control Examiner**  
**NOA No 24-0904.04**  
**Expiration Date: December 1, 2027**  
**Approval Date: October 10, 2024**