



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

VEKA Inc.
100 Veka Drive
Fombell, PA 16123

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER-Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Capstock and Laminate White Rigid PVC Exterior Extrusions for Windows and Doors are to be produced by Extruders Licensees in "Fenestration and Glazing Industry Alliance (FGIA) (formerly AAMA) Certification Programs for rigid PVC Extrusions". The extrusions shall meet ASTM D 4726, classification (ASTM D 4216) 1-10154-33-0000, 1-20131-13-0000 or 1-40131-13 and the following properties.

<u>Description</u>	<u>Test</u>	<u>Performance</u>
Rate of Burning	ASTM D635	Class CC1
Self-Ignition Temperature	ASTM D1929	925°F > 650°F
Average Smoke Density Rating	ASTM D2843	43 < 75
Flame Spread Index	ASTM E84	26.2 < 75
Xenon Arch Light Exposure (Weathering)	ASTM G155	4,500 Hours
Tensile Strength (Difference: *Exposed & Unexposed)	ASTM D638	4.98% < 10%
*Exposed per FBC Section 2615		

The Capstock and Laminate White Rigid PVC Exterior Extrusions have been tested per AAMA 303 Section 4.6.1, Section 5.4, and Section 5.5.

MISSILE IMPACT RATING: None

This NOA revises NOA # 23-0620.03 and consists of pages 1 and 2, as well as evidence pages E-1 and E-2.

The submitted documentation was reviewed by **Carlos M. Utrera, P.E.**



10/02/24

NOA No: 24-0904.05
Expiration Date: July 27, 2028
Approval Date: October 10, 2024
Page 1



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

VEKA Inc.
100 Veka Drive
Fombell, PA 16123

LIMITATION: This approval does not include an evaluation of structural performance of this component. Test reports and other required documents shall be submitted to Dade County Product Control; showing that the systems using this PVC Extrusion will resist the loads according to Chapter 16 of the F.B.C., in order to issue a specific product approval for the system.

LABELING: Each carton containing certified laminated extrusions shall be labeled with the AAMA PVC extrusion certification label, the extruder's name, city, state, laminator's name: Grafcó International Laminating Corp., Woodbridge, ONT, Canada and "MDCA". In addition, (a) each certified extrusion shall be labeled every 4 ft. or less on the underside with the extruder code and "MDCA" or (b) each finished product assembly shall be labeled with a permanent label and/or stamp with the extruder code and "MDCA".

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.



10/02/24

NOA No: 24-0904.05
Expiration Date: July 27, 2028
Approval Date: October 10, 2024
Page 2

NOTICE OF ACCEPTANCE: EVIDENCE PAGE

A. DRAWINGS

1. None.

B. TESTS

	<u>Report No.</u>	<u>Test</u>	<u>Date</u>	<u>Seal & Signature</u>
1.	L3735.01-106.18 R0	ASTM D4803	11/10/20	Daniel C. Culbert, P.E.
2.	P5202.01-106.18 R0	AAMA 303	03/30/23	Tanya A. Dolby, P.E.

“Submitted under NOA # 15-0414.01”

3. E9407.01-106.18 ASTM D4803/AAMA 303 12/22/15 Joseph A. Reed, P.E.

“Submitted under AAMA Master File # 98-0036”

4. Test report on Rate of Burning, Ignition Temperature, Density of Smoke, Surface Burning Characteristics, Accelerated Weathering and Tensile Properties Test of “PVC Extrusions from 5 different manufacturer” selected by AAMA”, prepared by ETC Laboratories, report # **ETC 97-264-40910**, dated 04/21/1998, signed and sealed by J. L. Doldan, P.E.

C. CALCULATION

1. None.

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATION

“Submitted under FGIA Master File # 23-1652”

1. Procedural Guide for the AAMA Fenestration Exterior Thermoplastic Profile Certification Program (**AAMA 109-15**).
2. Voluntary Specification for Rigid PVC Exterior Profiles (**AAMA 303-18**).



Carlos M. Utrera, P.E.
Product Control Examiner
NOA No: 24-0904.05
Expiration Date: July 27, 2028
Approval Date: October 10, 2024

NOTICE OF ACCEPTANCE: EVIDENCE PAGE

F. STATEMENTS “Submitted under FGIA Master File # 23-1652”

1. Statement letter of code conformance to the 8th Edition (2023) of the FBC and standards’ equivalency issued by Turner Engineering & Consulting, Inc., dated 10/06/2023, signed and signed by Lucas A. Turner, P.E.

“Submitted under FGIA Master File # 20-0942”

2. Statement letter of code conformance to the 7th Edition (2020) FBC and standards’ equivalency issued by Turner Engineering & Consulting, Inc., dated 07/07/2020, signed and signed by Lucas A. Turner, P.E.

“Submitted under AAMA Master File # 15-0333”

3. Statement letter of code conformance to the 5th edition (2014) FBC issued by Turner Engineering & Consulting, Inc., dated 02/19/2015, signed and signed by Lucas A. Turner, P.E.
4. Standards’ equivalency report issued by Turner Engineering & Consulting, Inc., dated 02/19/2015, signed and signed by Lucas A. Turner, P.E.

G. OTHERS

1. Association release letter issued by the Fenestration and Glazing Industry Alliance (FGIA, formerly AAMA), dated 02/16/2024 and signed by Jason Seals.
2. Manufacturer’s acknowledgment letter issued by VEKA Inc., dated 08/28/2024, signed by Nils Hinrichsen.



Carlos M. Utrera, P.E.
Product Control Examiner
NOA No: 24-0904.05
Expiration Date: July 27, 2028
Approval Date: October 10, 2024