



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

**NOTICE OF ACCEPTANCE (NOA)**

**Polyglass USA, Inc.**  
1111 W. Newport Center Drive  
Deerfield Beach, FL 33442

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

**DESCRIPTION: Polyglass Silicone Roof Coatings**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews and revises NOA# 21-1229.03 and consists of pages 1 through 15.  
The submitted documentation was reviewed by Alex Tigera.

02/13/25



NOA No.: 24-1015.01  
Expiration Date: 01/09/30  
Approval Date: 02/13/25  
Page 1 of 15

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Cements and Coatings  
**Fire Classification:** See General Limitation #1

### SCOPE:

This approves **Polyglass Silicone Roof Coatings**, as manufactured by Polyglass USA, Inc. and as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

### MANUFACTURING LOCATION

1. New Albany, IN
2. Houston, TX
3. Guelph, ON, Canada
4. Winter Haven, FL
5. Phoenix, AZ
6. Pryor, OK.
7. Waukegan, IL

### EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Construction Materials Technologies Inc.	PRMA-010-02-01	ASTM D6694 / D903	08/20/18
	PRMA-011-02-01	ASTM D6694 / D903	08/20/18
	708T0098	Proprietary	06/17/21
	708T0099	Proprietary	06/17/21
	708T0097	ASTM D6694 / D903	12/15/21
	708T0119	Proprietary	07/26/22
	708T0130	ASTM D6694 / D903	02/15/23
	708T0013	Proprietary	08/02/2019
	708T0132	ASTM D6694 / D903	10/24/2023
	708T0129	ASTM D6694 / D903	10/24/2023
	708T0209	ASTM D6694 / D903	10/24/2023
	708T0208	ASTM D6694 / D903	10/24/2023
	708T0210	ASTM D6694 / D903	10/24/2023
	708T0211	ASTM D6694 / D903	10/24/2023
	708T0127	Proprietary	04/28/2023
	UL TGFU.R40482	UL 790	4/17/2023
	4P-CSL-22-SSLAP-01.A.R3	ASTM D6694	12/05/22
	4P-CSL-22-SSLAP-01.B	ASTM 6694	10/02/23
	4P-CSL-22-SSLAP-01.A	ASTM 6694	07/08/24
	1507T0009	ASTM D903	08/16/22
708T0131	ASTM D6694 / D903	08/07/2023	
708T0166	ASTM D6694	10/24/2023	
708T0236	ASTM D6694 / D903	05/03/2024	
708T0238	ASTM D6694 / D903	05/03/2024	



NOA No.: 24-1015.01  
Expiration Date: 01/09/30  
Approval Date: 02/13/25  
Page 2 of 15

**EVIDENCE SUBMITTED:**

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
	708T0206	ASTM D6694 / D903	05/07/2024
	708T0237	ASTM D6694 / D903	07/31/2024
	708T0256.1	ASTM D6694 / D903	07/31/2024
	708T0256.2	ASTM D6694 / D903	07/31/2024
	708T0213	ASTM D6694	07-31-2024

**PHYSICAL PROPERTIES OF COMPONENTS:**

**Trade name:** PolyBrite® 78  
**Application Rate:** Application rate varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** Proprietary  
**Description:** A low viscosity, sprayable, rinseable primer used to pretreat existing roof substrates.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #2*

**Trade name:** PolyBrite® 79  
**Application Rate:** Application rate varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** Proprietary  
**Description:** A low VOC compliant, solvent-based primer designed to improve adhesion to most TPO membranes.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #5*

**Trade name:** PolyBrite® 90  
**Application Rate:** Application rates varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** ASTM D6694  
**Description:** A premium grade, high solids, white or tinted, single component, silicone roof coating. May be applied by brush, roller or spray applications.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #6 and #7*



**Trade name:** PolyBrite® 90.1  
**Application Rate:** Application rates varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** ASTM D6694  
**Description:** A premium grade, high solids, white or tinted, single component, silicone roof coating. May be applied by brush, roller or spray applications.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #1*

**Trade name:** PolyBrite® 90.2  
**Application Rate:** Application rates varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** ASTM D6694  
**Description:** A premium grade, high solids, white or tinted, single component, silicone roof coating. May be applied by brush, roller or spray applications.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #3*

**Trade name:** PolyBrite® 95  
**Application Rate:** Application rate varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** ASTM D6694  
**Description:** A single component, white or tinted, solvent-borne, silicone roof coating. May be applied by brush, roller or spray applications.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #6*

**Trade name:** PolyBrite® 95.1  
**Application Rate:** Application rate varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** ASTM D6694  
**Description:** A single component, white or tinted, solvent-borne, silicone roof coating. May be applied by brush, roller or spray applications.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #1*



**Trade name:** PolyBrite® 95.2  
**Application Rate:** Application rate varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** ASTM D6694  
**Description:** A single component, white or tinted, solvent-borne, silicone roof coating. May be applied by brush, roller or spray applications.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #3*

**Trade name:** PolyBrite® 93  
**Application Rate:** Apply at 1/8" thick uniform application  
**Specifications:** Proprietary  
**Description:** A silicone flashing compound designed for use at various flashings and roof penetrations.  
**Container Size:** 2 gallon pail. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #1*

**Trade name:** PolyBrite® 98  
**Application Rate:** Application rate varies due to substrate. See Approved Substrates below for application rates.  
**Specifications:** Proprietary  
**Description:** A water-based, one-part primer/bleed blocker that enhances the adhesion of Polyglass silicone roof coatings to a variety of roof substrates.  
**Container Size:** 5 gallon pail, 55 gallon drum. See product data sheet for specific volume. Note all precautions on container.  
**Systems Approvals:** For systems approvals, refer to specific Roof Assembly Product Control Approval.  
*Manufacturing Location #4 and #5*



## ALL APPROVED SUBSTRATES:

### All Substrate Preparation:

All surfaces to receive coatings must be sound, clean, dry and free from any foreign matter such as dirt, oils, grease or other debris that could inhibit the adhesion. Visually inspect all metal and non-metal flashings, edges, drains, valleys and through-roof penetrations and repair as needed in compliance with Polyglass current published application instructions.

**NOTE:** Ponding water is unfavorable; all roof systems should ensure positive drainage.

*\*Application rates vary; refer to substrates systems below for approved application rates.*

All surface preparation and product application shall be in compliance with the current Polyglass instructions.

### GALVANIZED METAL ROOF SYSTEMS

For Galvanized Metal Roof Panel Systems, reference current Polyglass published specifications for treatment of gaps, seams (vertical and horizontal), joints, roof terminations, flashing, drains, scuppers skylights etc. Allow primers and base coats to dry prior to applying the next coat.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.5-3.0 gal/100ft <sup>2</sup> ) *

### AGED GALVANIZED METAL ROOF SYSTEMS

For Galvanized Metal Roof Panel Systems, reference current Polyglass published specifications for treatment of gaps, seams (vertical and horizontal), joints, roof terminations, flashing, drains, scuppers skylights etc. Allow primers and base coats to dry prior to applying the next coat.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 95.2	-	PolyBrite 95.2 (1.5-3.0 gal/100ft <sup>2</sup> ) *



## ALUMINUM ROOF SYSTEMS

For Aluminum Roof Panel Systems, reference current Polyglass published specifications for treatment of gaps, seams (vertical and horizontal), joints, roof terminations, flashing, drains, scuppers skylights etc. Allow primers and base coats to dry prior to applying the next coat.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90.2	-	PolyBrite 90.2 (1.5-3.0 gal/100ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.5-3.0 gal/100ft <sup>2</sup> ) *

## AGED TPO MEMBRANE ROOF SYSTEMS

For TPO Membrane Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90	PolyBrite 79 (0.3-0.4 gal/100ft <sup>2</sup> )	PolyBrite 90 (1.0-4.0 gal./100 ft <sup>2</sup> ) *
PolyBrite 90.1	PolyBrite 79 (0.3-0.4 gal/100ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal./100 ft <sup>2</sup> ) *
PolyBrite 90.2	PolyBrite 79 (0.3-0.4 gal/100ft <sup>2</sup> )	PolyBrite 90.2 (1.0-4.0 gal./100ft <sup>2</sup> ) *
PolyBrite 95	PolyBrite 79 (0.3-0.4 gal/100ft <sup>2</sup> )	PolyBrite 95 (1.0-4.0 gal./100 ft <sup>2</sup> ) *
PolyBrite 95.1	PolyBrite 79 (0.3-0.4 gal/100ft <sup>2</sup> )	PolyBrite 95.1 (1.0-4.0 gal./100ft <sup>2</sup> ) *
PolyBrite 95.2	PolyBrite 79 (0.3-0.4 gal/100ft <sup>2</sup> )	PolyBrite 95.2 (1.0-4.0 gal./100 ft <sup>2</sup> ) *



## EPDM MEMBRANE ROOF SYSTEMS

For EPDM Membrane Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

<b>Product</b>	<b>Primer (Application rate)</b>	<b>Top Coat (Application rate)</b>
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## AGED EPDM MEMBRANE ROOF SYSTEMS

For EPDM Membrane Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

<b>Product</b>	<b>Primer (Application rate)</b>	<b>Top Coat (Application rate)</b>
PolyBrite 90.2	-	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## AGED PVC MEMBRANE ROOF SYSTEMS

For PVC Membrane Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

<b>Product</b>	<b>Primer (Application rate)</b>	<b>Top Coat (Application rate)</b>
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>3</sup> ) *





## CONCRETE ROOF SYSTEMS

For Concrete Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	-	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.5-3.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95	-	PolyBrite 95 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## SPRAY APPLIED POLYURETHANE FOAM ROOF SYSTEMS

For Spray Applied Polyurethane Foam Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	-	PolyBrite 90.1 (1.0-4.0 gal/100ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.5-3.0 gal/100ft <sup>2</sup> ) *
PolyBrite 95	-	PolyBrite 95 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *



## APP GRANULATED CAP SHEET MOD BIT ROOF SYSTEMS

For APP Granulated Cap Sheet Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90 (1.0-4.0 gal / 100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## AGED APP GRANULATED CAP SHEET MOD BIT ROOF SYSTEMS

For APP Granulated Cap Sheet Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *



## AGED APP SMOOTH MOD BIT ROOF SYSTEMS

For APP Granulated Cap Sheet Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

<b>Product</b>	<b>Primer (Application rate)</b>	<b>Top Coat (Application rate)</b>
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	PolyBrite 98 (0.66 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	PolyBrite 98 (0.66 gal/100 ft <sup>2</sup> )	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *



## SBS GRANULATED CAP SHEET MOD BIT ROOF SYSTEMS

For SBS Granulated Cap Sheet Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates.

<b>Product</b>	<b>Primer (Application rate)</b>	<b>Top Coat (Application rate)</b>
PolyBrite 90	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	-	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## AGED SBS GRANULATED CAP SHEET MOD BIT ROOF SYSTEMS

For Aged SBS Granulated Cap Sheet Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90	-	PolyBrite 90 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.1	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	PolyBrite 98 (1.0 gal/100 ft <sup>2</sup> )	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## SBS SMOOTH SURFACE MOD BIT ROOF SYSTEMS

For Aged SBS Granulated Cap Sheet Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90.1	PolyBrite 98 (0.66 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *



## AGED SBS SMOOTH SURFACE MOD BIT ROOF SYSTEMS

For Smooth SBS Mod Bit Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90.1	PolyBrite 98 (0.66 gal/100 ft <sup>2</sup> )	PolyBrite 90.1 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95	PolyBrite 98 (.66 gal/100 ft <sup>2</sup> )	PolyBrite 95 (1.0-4.0 gal/100ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *

## ASPHALT BUILT-UP ROOF (BUR) GRANULE-SURFACED

For Asphalt Built-Up Granule-Surfaced Roof Systems, reference Polyglass USA published specifications for treatment of seams, terminations, counter flashings, fasteners and detail areas.

\*Apply one coat or two equal coats at a combined rate by brush or spray. Refer to Polyglass USA published specifications for details on application rates per coat.

Product	Primer (Application rate)	Top Coat (Application rate)
PolyBrite 90.2	-	PolyBrite 90.2 (1.0-4.0 gal/100 ft <sup>2</sup> ) *
PolyBrite 95.2	-	PolyBrite 95.2 (1.0-4.0 gal/100ft <sup>2</sup> ) *



## GENERAL LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Product shall be applied in strict compliance with Manufacturer's published application instructions when not in conflict with the information contained herein.
3. Coating products shall not be applied in inclement weather conditions.
4. The product listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their Roof Assembly Notice of Acceptance. If a product is not listed as part of roof assemblies Notice of Acceptance, a request may be made to the local building official or the Miami Dade County Product Control Section for approval provided that appropriate documentation is provided.
5. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to RER upon request.
6. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



7. The use of a reinforcing fabric in a maintenance coating is only to enhance the coatings ability to deliver efficient and long term performance through the protection of the underlying roof system and in this particular use does not become a roof system itself
8. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

**END OF THIS ACCEPTANCE**



NOA No.: 24-1015.01  
Expiration Date: 01/09/30  
Approval Date: 02/13/25  
Page 15 of 15