

Grille Tech, Inc. 5101 NW 36 Avenue Miami, FL 33142

SCOPE: This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER-Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Model WLF-DA15 Aluminum Louver

APPROVAL DOCUMENT: Drawing No. **0551-0402-10**, titled "WLF-DA15 Aluminum Wall Louver", sheets 1 through 6 of 6, dated 04/30/2009, with revision 4 dated 11/02/2023, prepared by Wolters Engineering, Inc, signed and sealed by Scott Wolters, P.E., bearing the Miami-Dade County Product Control renewal stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: A permanent label with the manufacturer's name or logo, manufacturing plant's city, state, model/series, and the following statement: "Miami-Dade County Product Control Approved", is to be located on each unit.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA **renews NOA # 23-1107.05** and consists of this page 1 and evidence pages E-1, E-2 and E-3, as well as approval document mentioned above.

The submitted documentation was reviewed by Carlos M. Utrera, P.E.



NOA No. 25-0404.02 Expiration Date: June 30, 2030 Approval Date: July 3, 2025 Page 1

06/25/25

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

1. Evidence submitted under previous NOA's

A. DRAWINGS "Submitted under NOA #15-0218.08"

1. Drawing No. 0551-0402-10, titled "WLF-DA15 Aluminum Wall Louver", sheets 1 through 6 of 6, dated 04/30/2009, with revision 1 dated 02/10/2015, prepared Wolters Engineering, Inc, signed and sealed by Scott Wolters, P.E.

B. TESTS "Submitted under NOA # 10-0518.05"

Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
2) Large Missile Impact Test per FBC, TAS 201-94

3) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of WLF-DA15 Aluminum Louver Systems", prepared by Hurricane Test Laboratory, Inc., Report No. **0551-0204-10**, dated 04/30/2010, signed and sealed by Vinu J. Abraham, P.E.

C. CALCULATIONS "Submitted under NOA #10-0518.05"

1. Anchor verification calculations and structural analysis prepared by Wolters Engineering, Inc, dated 05/12/2010, signed and sealed by Scott Wolters, P.E.

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER)

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS "Submitted under NOA #15-0218.08"

1. Statement letter of code conformance with 2010 and 5th edition (2014) FBC issued by Wolters Engineering, Inc, dated 05/20/2015, signed and sealed by Scott Wolters, P.E.

"Submitted under NOA # 10-0518.05"

- 2. No financial interest letter issued by Wolters Engineering, Inc, dated 10/13/2009, signed and sealed by Scott Wolters, P.E.
- **3.** Code compliance letter issued by Hurricane Test Laboratory, Inc., dated 04/29/2010, signed and sealed by Vinu J. Abraham, P.E.

Carlos M. Utrera, P.E. Product Control Examiner NOA No. 25-0404.02 Expiration Date: June 30, 2030 Approval Date: July 3, 2025

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

2. Evidence submitted under previous NOAs

A. DRAWINGS "Submitted under NOA #17-0919.08"

1. Drawing No. **0551-0402-10**, titled "WLF-DA15 Aluminum Wall Louver", sheets 1 through 6 of 6, dated 04/30/09, with revision 2 dated 09/08/2017, prepared Wolters Engineering, Inc, signed and sealed by Scott Wolters, P.E.

B. TESTS

1. None.

C. CALCULATIONS

1. None.

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER)

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS "Submitted under NOA # 20-0302.04"

1. Statement letter of code conformance with the 6th Edition (2017) FBC issued by Wolters Engineering, Inc, dated 02/19/2020, signed and sealed by Scott Wolters, P.E.

Carlos M. Utrera, P.E. Product Control Examiner NOA No. 25-0404.02 Expiration Date: June 30, 2030 Approval Date: July 3, 2025

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

3. Evidence submitted under NOA # 23-1107.05 and new

A. DRAWINGS

1. Drawing No. **0551-0402-10**, titled "WLF-DA15 Aluminum Wall Louver", sheets 1 through 6 of 6, dated 04/30/09, with revision 4 dated 11/02/2023, prepared Wolters Engineering, Inc, signed and sealed by Scott Wolters, P.E.

B. TESTS

1. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94

2) Large Missile Impact Test per FBC, TAS 201-94

3) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of WLF-DA15 Aluminum Louver Systems", prepared by Intertek, Report No. **S5976.01-450-18 R0**, dated 06/18/2025, signed and sealed by Tanya A. Dolby, P.E.

C. CALCULATIONS

1. None.

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS

- 1. Statement letter of code conformance with the 8th Edition (2023) of the FBC, issued by Wolters Engineering, Inc, dated 03/27/2025, signed and sealed by Scott Wolters, P.E.
- 2. Statement letter of code conformance with the 8th Edition (2023) of the FBC, issued by Wolters Engineering, Inc, dated 11/02/2023, signed and sealed by Scott Wolters, P.E.

Carlos M. Utrera, P.E. Product Control Examiner NOA No. 25-0404.02 Expiration Date: June 30, 2030 Approval Date: July 3, 2025 GENERAL NOTES

1, THIS ALUMINUM WALL LOUVER PRODUCT IS LARGE MISSILE IMPACT RESISTANT AND DOES NOT REQUIRE THE USE OF SHUTTERS.

▲2, THIS LOUVER SYSTEM HAS BEEN TESTED TO TAS 201-94, TAS 202-94 (LOADS ONLY), AND TAS 203-94 (REF. HTL TEST REPORT 0551-0204-10) AND MEETS THE REQUIREMENTS OF THE 8TH EDITION (2023) FLORIDA BUILDING CODE, INCLUDING THE HVHZ PROVISIONS.

THESE LOUVERS ARE 3. THIS LOUVER PRODUCT IS NOT TESTED FOR WATER INFILTRATION RESISTANCE. TO BE INSTALLED IN A LOCATION WHERE THE ROOM BEHIND THE LOUVER IS DESIGNED TO DRAIN WATER PENETRATING INTO THE ROOM, AND THE ROOM WILL HOUSE WATER RESISTANT / WATER PROOF EQUIPMENT, COMPONENTS, OR SUPPLIES. 4. THE STRUCTURAL ADEQUACY AND SUITABILITY OF THE WOOD BUCKS OR OTHER SUBSTRATES TO WHICH THE LOUVER SYSTEM IS TO BE INSTALLED SHALL BE VERIFIED BY A LICENSED ENGINEER OR REGISTERED ARCHITECT OR AS APPROVED BY THE AUTHORITY HAVING JURISDICTION,

5. AN ALLOWABLE STRESS INCREASE HAS NOT BEEN USED IN THE ANCHOR ANALYSIS FOR THIS SYSTEM. 6. WHERE DISSIMILAR MATERIALS OF ANY TYPE (LOUVER SYSTEM, ANCHORAGE, OR SUBSTRATE) COME IN CONTACT, THE MATERIALS MUST BE PROPERLY COATED OR OTHERWISE PROTECTED AS REQUIRED BY FBC TO PREVENT GALVANIC REACTIONS. SPECIAL CARE SHALL BE TAKEN TO PROTECT ALUMINUM LOUVERS FROM PRESSURE TREATED LUMBER, AND ALL FASTENERS SHALL BE SELECTED WITH PROPER COATING OR MATERIAL TYPES TO PREVENT REACTIONS WITH LOUVERS OR SUBSTRATES.

7. MINIMUM LOUVER SIZE IS 10" X 10"

8. LOUVERS MAY BE USED IN SINGLE UNIT CONFIGURATION, DOUBLE WIDE OR TRIPLE WIDE MULLED, OR DOUBLE HIGH MULLED CONFIG. 9. THE MAXIMUM DESIGN PRESSURE OF THIS LOUVER SYSTEM IS + / - 140.0 P.S.F.











									r	
	LE 1. QUALIFIED INSTALLATION						Β	LAT	S	S
ID	ANCHOR	SUBSTRATE	MIN.	MIN. EDGE						
			EMBED.	DISTANCE						
		CONCRETE (3.2 KSI MIN)	1"	2 1/2"					В	
B			1 1/4"	2 1/2" 1"					REVISION	
C			1 3/8"	1"						
	#12 WOOD SCREW GRADE 5 #12 TEK SMS GRADE 5	WOOD (G=0.42 MIN) 1/8" ALUM. 6063-T5 MIN.	1 3/8"	1/2"					BLADE	
F	#12 TEK SMS GRADE 5	1/8" STEEL 36 KSI MIN.		1/2"				ASE		
		THO STELE SO ROTWIN.	-	172			N	RELEASE	Щ	H H
TAB	LE 2. QUALIFIED MULLION CLIP	ANCHOR INFORMATION					DESCRIPTION		UPDATE	UPDATE
ID	ANCHOR	SUBSTRATE	MIN.	MIN. EDGE	QTY]	SCR	DRIGINAL		
			EMBED.	DISTANCE	PER CLIP		Ē			
	96" MAX. LENGTH VERTIC	AL MULLION, 61 5/8" MAX. I	LOUVER F	LANGE WDT	IS		ш	4/30/2009	2/10/2015	9/8/2017 2/22/22
G	5/16" ITW TAPCON	CONCRETE (2.9 KSI MIN)	2 1/4"	2 1/2"	4		DATE	30/)	9/8/2017 2/22/22
Н	#14 WOOD SCREW GRADE 5	WOOD (G=0.42 MIN)	2 1/2"	2 1/2"	6					
	#12 TEK SMS GRADE 5	1/8" STEEL 36 KSI MIN.	-	. 1"	4		REV.		-	വ ന
	60" MAX. LENGTH HORIZON		·····		HTS	1				
A	1/4" ITW TAPCON	CONCRETE (3.2 KSI MIN)	1"	2 1/2"	4					
D		WOOD (G=0.42 MIN)	1 3/8"	1"	4			P		
F	#12 TEK SMS GRADE 5	1/8" STEEL 36 KSI MIN.	-	1/2"	4			Š		Ĩ
LINE: HOR WOO	IDWN IN- S REQ'D TYPE H D DNLY. ABLE 2> INT.			12) SEE TBL 13) SEE DETAIL E-1 SEE TABLE		Building Čode NOA-No. 25-0404.02 Expiration Date <u>06/30/2030</u> By Miami-Dade Product Control PRODUCT REVISED as complying with the Florida Building Code NOA-No. <u>23-1107.05</u> Expiration Date <u>06/30/2025</u> By J	-	WLF-DA15 Aluminum Wall Louver	:	Large Missile Impact Resistant
ļ	EXT. SEE NOTE 2,SHEET 2(5) MULL (ANI	DETAIL E-2 CLIP TO SU	D BSTR MULL	ATE		Miami-Dade Product Control SCOT WOLTERS FLPE# 62354 WOLTERS ENGINEERING, INC. (COA# 27194) 15211 97TH ROAD N. WEST PALM BEACH, FL 33412	SCAI	E C K	040 N ⁻ IEE	IT.

							r	
		,			BY	LAT	S	S
SUBSTRATE		1						
							зI	
							ISI	
							ADE	
	-					ASE		
170 STELE SO KONVIN.		172			Z	SELE	Ľ	E E
ANCHOR INFORMATION					IPTI			UPDATE
SUBSTRATE	MIN.	MIN. EDGE	QTY]	SCR	LIGIN		
	EMBED.	DISTANCE	PER CLIP		Ä		비	88
AL MULLION, 61 5/8" MAX.	LOUVER F	LANGE WDT	HS]		5002	2015	22/22
CONCRETE (2.9 KSI MIN)	2 1/4"	2 1/2"	4	1	DATE	30/2) [)	9/8/2017 2/22/22
WOOD (G=0.42 MIN)	2 1/2"	2 1/2"	6]				
1/8" STEEL 36 KSI MIN.	-	. 1"	4]	REV		-	പന
TAL MULLION, 98 1/8" MAX	LOUVER	FLANGE HEIC	GHTS]				
CONCRETE (3.2 KSI MIN)	1"	2 1/2"	4	1				
WOOD (G=0.42 MIN)	1 3/8"		4			P		
1/8" STEEL 36 KSI MIN.	-	1/2"	4			Š		Ę
) 13 SEE DETAIL E-1	2.	Expiration Date <u>06/30/2030</u> By Miami-Dade Product Control PRODUCT REVISED as complying with the Florida Building Code NOA-No. <u>23-1107.05</u> Expiration Date <u>06/30/2025</u>		WLF-DA15 Aluminum	:	Large Missile Impact Resistant
CLIP TO SU	<u></u> BSTF	RATE		By Miami-Dade Product Control SCOJT WOLFERS FLPE# 62354 WOLTERS ENGINEERING, INC. (COA# 27194) 15211 97TH ROAD N WEST PALM BEACH, FL 33412	BRAV 05 SCAR	S 101 NW 36th AV	040 N ⁻ IEE	rs T
	AL MULLION, 61 5/8" MAX. CONCRETE (2.9 KSI MIN) WOOD (G=0.42 MIN) 1/8" STEEL 36 KSI MIN. CONCRETE (3.2 KSI MIN) WOOD (G=0.42 MIN) 1/8" STEEL 36 KSI MIN. DETAIL E-2 CLIP TO SU	SUBSTRATE MIN. EMBED. CONCRETE (3.2 KSI MIN) 1" GROUT FILLED CMU 1 1/4" WOOD (G=0.42 MIN) 1 3/8" 1/8" ALUM. 6063-T5 MIN. - 1/8" STEEL 36 KSI MIN. - ANCHOR INFORMATION SUBSTRATE MIN. SUBSTRATE MIN. CONCRETE (2.9 KSI MIN) 2 1/4" WOOD (G=0.42 MIN) 2 1/2" 1/8" STEEL 36 KSI MIN. - CONCRETE (2.9 KSI MIN) 2 1/2" 1/8" STEEL 36 KSI MIN. - TTAL MULLION, 61 5/8" MAX LOUVER CONCRETE (3.2 KSI MIN) CONCRETE (3.2 KSI MIN) 1" WOOD (G=0.42 MIN) 1 3/8" 1/8" STEEL 36 KSI MIN. - TAL MULLION, 98 1/8" MAX LOUVER CONCRETE (3.2 KSI MIN) 1" WOOD (G=0.42 MIN) 1 3/8" 1/8" STEEL 36 KSI MIN. - Image: Steel 36 KSI	SUBSTRATE MIN. MIN. EDGE CONCRETE (3.2 KSI MIN) 1" 2 1/2" GROUT FILLED CMU 1 1/4" 2 1/2" WOOD (G=0.42 MIN) 1 3/8" 1" 1/8" ALUM. 6063-T5 MIN. - 1/2" 1/8" STEEL 36 KSI MIN. - 1/2" ANCHOR INFORMATION SUBSTRATE MIN. EMBED. SUBSTRATE MIN. 2 1/2" 2 1/2" ANCHOR INFORMATION SUBSTRATE MIN. EMBED. SUBSTRATE MIN. 2 1/2" 2 1/2" VOOD (G=0.42 MIN) 2 1/2" 2 1/2" 1/2" VOOD (G=0.42 MIN) 2 1/2" 2 1/2" 1/2" VOOD (G=0.42 MIN) 2 1/2" 1/2" 1/2" VOOD (G=0.42 MIN) 1 3/8" 1" 1/2" TAL MULLION, 98 1/8" MAX LOUVER FLANGE HEIC CONCRETE (3.2 KSI MIN) - 1/2" WOOD (G=0.42 MIN) 1 3/8" 1" 1/2" 1/8" STEEL 36 KSI MIN. - 1/2" 1/2" UOOD (G=0.42 MIN) 1 3/8" 1" 1/2" 1/8" STEEL 36 KSI MIN. -	SUBSTRATE MIN. MIN. EMBED. DISTANCE CONCRETE (3.2 KSI MIN) 1'' 2 1/2" GROUT FILLED CMU 1 1/4" 2 1/2" WOOD (G=0.42 MIN) 1 3/8" 1" 1/8" ALUM 6063-T5 MIN. - 1/2" I/8" STEEL 36 KSI MIN. - 1/2" ANCHOR INFORMATION SUBSTRATE MIN. MIN. EDGE QTY SAL MULLION, 61 5/8" MAX. LOUVER FLANGE WIDTHS CONCRETE (2.9 KSI MIN) 2 1/2" 4 WOOD (G=0.42 MIN) 1 3/8" 1" 4 4 VOOD (G=0.42 MIN) 2 1/2" 2 1/2" 6 6 1/8" STEEL 36 KSI MIN. - 1" 4 4 VOOD (G=0.42 MIN) 1 1/8" 2 1/2" 4 4 WOOD (G=0.42 MIN) 1 3/8" 1" 4 4 WOOD (G=0.42 MIN) 1 3/8" 1" 4 4 WOOD (G=0.42 MIN) 1 3/8" 1" 4 4 1/8" STEEL 36 KSI MIN. - 1/2" 4 4 1/8" STEEL 36 KSI MIN. - 1/2" 4 4<	SUBSTRATE MIN. MIN. EDGE DISTANCE CONCRETE (3.2 KSI MIN) 1 14/2 WOOD (G=0.42 MIN) 1 14/4 1/8" STEL 36 KSI MIN. - 1/2" ANCHOR INFORMATION SUBSTRATE MIN. DISTANCE SUBSTRATE MIN. - 1/2" ANCHOR INFORMATION SUBSTRATE MIN. DISTANCE SUBSTRATE (2.9 KSI MIN) - 1/2" 4 VOOD (G=0.42 MIN) 1.1/2" 1/2" 4 ANCHOR INFORMATION SUBSTRATE MIN. DISTANCE PER CLIP ANCHOR INFORMATION SUBSTRATE MIN. 2.1/2" 4 WOOD (G=0.42 MIN) 1.1/2" 4 4 4 TAL MULLION, 98 1/9" MAX LOUVER FLANGE HEIGHTS 6 6 500/30/2030 CONCRETE (3.2 KSI MIN) - 1/2" 4 4 MCOD (G=0.42 MIN) 1.3/8" 1" 4 4 CONCRETE (3.2 KSI MIN) - 1/2" 4 7 BETAIL E -1 SEE TABLE 2. PRODUCT REVISED 8 complying with the Florida Buo 0/30/20	SUBSTRATE MIN MIN EDGE DISTANCE CONCRETE (3.2 KSI MIN) 1 12" GROUT FILLED CMU 1 1 14" 2 1/2" GROUT FILLED CMU 1 1 14" 2 1/2" MIN. 1 1/2" MIN. 1 1/2" ANCHOR INFORMATION SUBSTRATE MIN. 1 1/2" ANCHOR INFORMATION SUBSTRATE MIN. 1 1/2" ANCHOR INFORMATION SUBSTRATE PRODUCT RENEWED CONCRETE (2.3 KSI MIN) 1 1" 4 OUT OF CONCRETE (2.3 KSI MIN) 1 1/2" 4 OUT OF CONCRETE (2.3 KSI MIN) 1 1/2" 4 OUT OF CONCRETE (2.3 KSI MIN) 1 1/2" 4 OUT OF CONCRETE (2.3 KSI MIN) 1 1/2" 4 OUT OF CONCRETE (2.3 KSI MIN) 1 1/2" </td <td>SUBSTRATE MIN. MIN. EDGE EMBED. DISTANCE CONCRETE (3.2 KSI MIN) 1" 11/2" 21/2" WOOD (G=0.42 MIN) 1.38" 11/3" STEEL 36 KSI MIN. 1.12" ANCHOR INFORMATION 11/2" SUBSTRATE MIN. DOGE QUOD (G=0.42 MIN) 1.38" 11/3" STEEL 36 KSI MIN. 1.12" ANCHOR INFORMATION SUBSTRATE SUBSTRATE MIN. EDGE OTY AL MULLION, 61 5/8" MAX. LOUVER FLANGE PER CLIP ANCHOR INFORMATION SUBSTRATE CONCRETE (2.3 KSI MIN) 2.1/2" AL MULLION, 61 5/8" MAX. LOUVER FLANGE HEIGHTS CONCRETE (2.3 KSI MIN) 1.1/2" AL MULLION, 80 1/8" MAX. LOUVER FLANGE HEIGHTS CONCRETE (2.3 KSI MIN) 1.1/2" BUILDING CG= 0.42 MIN) 1.3/8" 11/8" STEEL 36 KSI MIN - CONCRETE (2.3 KSI MIN) - SEE TABLE 2. O SEE TAL MULLION, 80 1/8" MAX LOUVER FLANGE MEIGHTS CONCRETE C.3 KSI MIN - SEE TABLE 2. O -</td> <td>SUBSTRATE MIN. MIN.EDGE EMBED. DISTANCE CONCRETE (3.2 KSI MIN) 11/4" 13/8" 1" WOOD (G=0.42 MIN) 13/8" 11/8" STEEL 36 KSI MIN 11/2" ANCHOR INFORMATION SUBSTRATE SUBSTRATE MIN. EDGE GTY PALLION, 61 5/8" MAX.LOUVER FLANGE WDTHS GOVCRETE (2.9 KSI MIN) 2 1/2" ANCHOR INFORMATION SUBSTRATE MIN. EDGE GTY ANULLION, 61 5/8" MAX.LOUVER FLANGE WDTHS CONCRETE (2.9 KSI MIN) 2 1/2" 4 OCONCRETE (2.9 KSI MIN) 1 1/2" 4 4 MODD (G=0.42 MIN) 1 1/2" 4 4 OCONCRETE (2.9 KSI MIN) 1 1/2" 4 4 MODD (G=0.42 MIN) 2 1/2"</td>	SUBSTRATE MIN. MIN. EDGE EMBED. DISTANCE CONCRETE (3.2 KSI MIN) 1" 11/2" 21/2" WOOD (G=0.42 MIN) 1.38" 11/3" STEEL 36 KSI MIN. 1.12" ANCHOR INFORMATION 11/2" SUBSTRATE MIN. DOGE QUOD (G=0.42 MIN) 1.38" 11/3" STEEL 36 KSI MIN. 1.12" ANCHOR INFORMATION SUBSTRATE SUBSTRATE MIN. EDGE OTY AL MULLION, 61 5/8" MAX. LOUVER FLANGE PER CLIP ANCHOR INFORMATION SUBSTRATE CONCRETE (2.3 KSI MIN) 2.1/2" AL MULLION, 61 5/8" MAX. LOUVER FLANGE HEIGHTS CONCRETE (2.3 KSI MIN) 1.1/2" AL MULLION, 80 1/8" MAX. LOUVER FLANGE HEIGHTS CONCRETE (2.3 KSI MIN) 1.1/2" BUILDING CG= 0.42 MIN) 1.3/8" 11/8" STEEL 36 KSI MIN - CONCRETE (2.3 KSI MIN) - SEE TABLE 2. O SEE TAL MULLION, 80 1/8" MAX LOUVER FLANGE MEIGHTS CONCRETE C.3 KSI MIN - SEE TABLE 2. O -	SUBSTRATE MIN. MIN.EDGE EMBED. DISTANCE CONCRETE (3.2 KSI MIN) 11/4" 13/8" 1" WOOD (G=0.42 MIN) 13/8" 11/8" STEEL 36 KSI MIN 11/2" ANCHOR INFORMATION SUBSTRATE SUBSTRATE MIN. EDGE GTY PALLION, 61 5/8" MAX.LOUVER FLANGE WDTHS GOVCRETE (2.9 KSI MIN) 2 1/2" ANCHOR INFORMATION SUBSTRATE MIN. EDGE GTY ANULLION, 61 5/8" MAX.LOUVER FLANGE WDTHS CONCRETE (2.9 KSI MIN) 2 1/2" 4 OCONCRETE (2.9 KSI MIN) 1 1/2" 4 4 MODD (G=0.42 MIN) 1 1/2" 4 4 OCONCRETE (2.9 KSI MIN) 1 1/2" 4 4 MODD (G=0.42 MIN) 2 1/2"





