

#### DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION NOTICE OF ACCEPTANCE (NOA)

Airsouth Air Products, LLC 1055 E. 35th Street Hialeah, FL 33013

### Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER-Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

#### **DESCRIPTION:** Airsouth Commercial Units Steel Curbs

**APPROVAL DOCUMENT:** Drawing No. **24-82376**, titled "Airsouth Commercial Units Curbs", sheets 1 through 19 of 19, dated 02/15/2025, prepared by Engineering Express, signed and sealed by Richard Neet, P.E. on 06/02/2025, bearing the Miami-Dade County Product Control approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Section.

#### **MISSILE IMPACT RATING: None**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA consists of this page 1 and evidence page E-1, as well as the approval document mentioned above. The submitted documentation was reviewed by **Carlos M. Utrera, P.E.** 





06/30/25

NOA No. 25-0410.04 Expiration Date: July 10, 2030 Approval Date: July 10, 2025 Page 1

### **NOTICE OF ACCEPTANCE:** EVIDENCE SUBMITTED

#### A. DRAWINGS

1. Drawing No. **TIV/TEV-HV**, titled "TEV and TIV Hurricane Vents", sheets 1 through 4 of 4, dated 02/02/2021 and 02/18/2022, prepared by ACME Manufacturing Corporation, signed and sealed by Richard O. Boyette, P.E. on 02/20/2022 and 06/30/2022.

#### B. TESTS

1. None.

#### C. CALCULATIONS

1. Anchor verification calculations, prepared by Engineering Express, dated 03/11/2025, signed and sealed by Richard Neet, P.E.

#### D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

#### E. MATERIAL CERTIFICATIONS

1. None.

#### F. STATEMENTS

- 1. Statement letter of code conformance to the 8<sup>th</sup> edition (2023) of the FBC, issued by Engineering Express, dated 03/11/2025, signed and sealed by Richard Neet, P.E.
- 2. Statement letter of no financial interest, issued by Engineering Express, dated 03/11/2025, signed and sealed by Richard Neet, P.E.

Carlos M. Utrera, P.E. Product Control Examiner NOA No. 25-0410.04 Expiration Date: July 10, 2030 Approval Date: July 10, 2025

# **AIRSOUTH AIR PRODUCTS, LLC** AIRSOUTH COMMERCIAL UNITS CURBS PERFORMANCE EVALUATION

VALID FOR USE INSIDE AND OUTSIDE THE HVHZ (SEE LIMITATIONS HEREIN)

MAXIMUM-RATED ASD WIND PRESSURES: ± 122 PSF LATERAL & 96 PSF UPLIFT

APPROVED DESIGN CRITERIA

#### **DESIGN NOTES**

SITE-SPECIFIC ASD WIND PRESSURES SHALL BE DETERMINED IN ACCORDANCE WITH THE CURRENT EDITION OF ASCE 7 AND CHAPTER 1. 16 OF THE FLORIDA BUILDING CODE AND SHALL BE LESS THAN OR EQUAL TO THE MAXIMUM ASD DESIGN WIND PRESSURES LISTED HEREIN FOR THE UNIT MODEL IN QUESTION. DESIGN PRESSURES SHALL BE DETERMINED BY A REGISTERED DESIGN PROFESSIONAL ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH THE GOVERNING CODE AND ALLOWABLE STRESS DESIGN (ASD) METHODOLOGY.

#### **GENERAL NOTES**

THIS SYSTEM HAS BEEN DESIGNED AND SHALL BE FABRICATED IN ACCORDANCE WITH THE REOUIREMENTS OF THE FLORIDA BUILDING CODE EIGHTH EDITION (2023). THIS SYSTEM MAY BE USED WITHIN AND OUTSIDE OF THE HIGH-VELOCITY HURRICANE ZONE (HVHZ). THIS DESIGN IS NOT INTENDED TO CERTIFY IMPACT RESISTANCE OF THE MECHANICAL UNIT CABINETRY.

WIND LOAD DURATION FACTOR CD = 1.6 HAS BEEN USED FOR WOOD ANCHOR DESIGN.

REFER TO FASTENER MANUFACTURER'S PUBLISHED DATA SHEETS AND RECOMMENDATIONS FOR FASTENER INSTALLATION INSTRUCTION.

THIS PERFORMANCE EVALUATION CERTIFIES THE MECHANICAL UNIT-TO-CURB ATTACHMENT, CURB STRUCTURAL INTEGRITY, AND CURB-TO-HOST ATTACHMENT. INTEGRITY OF MECHANICAL UNIT AND EXISTING HOST STRUCTURE SHALL BE BY OTHERS

TIE-DOWN STRAP WHERE USED HEREIN: 5.

- FOR DIRECT MOUNT METHOD: SHALL BE 1" MIN. WIDE X 22GA MIN THICK, UTS=45 KSI MIN. (EQUIVALENT TO ASTM A653 GR 33 OR STRONGER) GALV. STEEL, TYP.
- FOR STRAP MOUNT METHOD: SHALL BE 2" MIN. WIDE X 22GA MIN THICK, UTS=45 KSI MIN. (EQUIVALENT TO ASTM A653 GR 33 OR STRONGER) GALV. STEEL, TYP

CURBS SHALL BE 16GA (0.055") THICK MINIMUM, ASTM A653 GR 33 G90 GALVANIZED STEEL (UTS = 45 KSI MIN.), OR STRONGER. SEE DETAILS HEREIN FOR MAXIMUM CURB HEIGHT.

ALL SPECIFICATIONS (INCLUDING BUT NOT LIMITED TO ROOFING MATERIALS, SEALING GASKETS, DUCTS, AND STRIP NAILS) NOT RELATED WITH THE STRUCTURAL PERFORMANCE OF THE CURB ARE NOT PART OF THIS CERTIFICATION.

DIMENSIONS SHOWN BETWEEN BRACKETS [] (WHERE APPLICABLE) ARE THE 8. EOUIVALENT IN MILIMETERS.

CURBS SHALL BEWELDED CONSTRUCTED: 1/8" CONTINUOUS FILLET WELD FOR ALL CONNECTING CURB ELEMENTS.

10. SUPPLEMENTAL "SHEET METAL SCREWS" OR "SMS" USED FOR TIE-DOWN STRAP ATTACHMENTS SHALL BE SAE GR 2 MIN. OR SELF-DRILLING SCREWS WITH WASHERS, TYP.

11. UNIT BASE RAIL SHALL BE 18GA THICK MINIMUM, ASTM A653 GR 33 G90 GALVANIZED STEEL (UTS = 45 KSI MIN.), OR STRONGER.

12. HOST STRUCTURE SHALL COMPLY WITH THE FOLLOWING SPECIFICATIONS:

- HOST CONCRETE SHALL BE 3000 PSI MIN. COMPRESSIVE STRENGTH AND SHALL BE NON-CRACKED REGULAR-WEIGHT CONCRETE. HOST CONCRETE SHALL BE BY OTHERS.
- HOST STEEL SHALL BE ASTM A36 (YS=36 KSI MIN.), 3/16" THICK MINIMUM. HOST STEEL SHALL BE BY OTHERS.
- HOST WOOD SHALL BE G=0.55 (G=SPECIFIC GRAVITY), 2"X8" MINIMUM. HOST WOOD SHALL BE BY OTHERS.

PRESSURE VALUES IN THIS APPROVAL ARE (ASD) ALLOWABLE DESIGN PRESSURES 10. UNLESS NOTED OTHERWISE.

11. ALL WELDING MUST BE DONE BY AN AWS CERTIFIED WELDER OR SHALL CONFORM TO TO THE CURRENT EDITION OF THE AISC STEEL CONSTRUCTION MANUAL, AS INSPECTED AND VERIFIED BY OTHERS, MIN. WELD IS 1/8" FULL PERIMETER FILLET WELD (U.N.O.). WELD ELECTRODES SHALL BE E70XX FOR CARBON STEEL. FOR STAINLÈSS STÉEL, WELD ELECTRODES SHALL FOLLOW ASTM E330-16 AND AMERICAN WELDING SOCIETY SPECIFICATION AWS A5.4 (E75XX MINIMUM). ALL WELDS NOT OTHERWISE IDENTIFIED SHALL BE CONTINUOUS. WELDS SHALL HAVE EVIDENCE OF UNIFORM SECTION, SMOOTHNESS OF WELD METAL, FREE FROM SLAG, AND ADEQUATE STRENGTH AND DURABILITY.

12. ALL DIMENSIONS AND THE ALLOWABLE NET WEIGHT OF MECHANICAL UNIT SHALL CONFORM TO LIMITATIONS STATED HEREIN, ALL MECHANICAL SPECIFICATIONS (CLEAR SPACE, TONNAGE, ETC.) SHALL BE AS PER MANUFACTURER RECOMMENDATIONS AND ARE THE EXPRESS RESPONSIBILITY OF THE CONTRACTOR.

13. PROVIDE (5) PITCHES MINIMUM PAST THE THREAD PLANE FOR SHEET METAL SCREWS, ALL FASTENER CONNECTIONS SHALL PROVIDE 1.5xDIAMETER EDGE FASTENERS SHALL BE CADMIUM-PLATED OR OTHERWISE DISTANCE. CORROSION-RESISTANT MATERIAL AND SHALL COMPLY WITH "SPECIFICATIONS FOR ALUMINUM STRUCTURES" SECTION J.3.7.2 BY THE ALUMINUM ASSOCIATION INC., AND ANY APPLICABLE FEDERAL, STATE AND OR LOCAL CODES.

14. REFER TO FASTENER MANUFACTURER'S PUBLISHED DATA SHEETS AND RECOMMENDATIONS FOR FASTENER INSTALLATION INSTRUCTIONS.

15. THE CONTRACTOR IS RESPONSIBLE FOR INSULATING ALL MEMBERS FROM DISSIMILAR MATERIALS TO PREVENT ELECTROLYSIS.

16. ELECTRICAL GROUND, WHEN REQUIRED, TO BE DESIGNED & INSTALLED BY OTHERS.

17. THE ARCHITECT/ENGINEER OF RECORD FOR THE PROJECT SUPERSTRUCTURE WITH WHICH THIS DESIGN IS USED SHALL BE RESPONSIBLE FOR THE INTEGRITY OF ALL SUPPORTING SURFACES TO THIS DESIGN WHICH SHALL BE COORDINATED BY THE PERMITTING CONTRACTOR.

18. EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED.

19. THE SYSTEM DETAILED HEREIN IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SPECIFIC SITE. FOR SITE CONDITIONS DIFFERENT FROM THE CONDITIONS DETAILED HEREIN, A LICENSED ENGINEER OR REGISTERED ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE IN CONJUNCTION WITH THIS DOCUMENT.

20. WATER-TIGHTNESS OF EXISTING HOST SUBSTRATE SHALL BE THE FULL RESPONSIBILITY OF THE INSTALLING CONTRACTOR, CONTRACTOR SHALL ENSURE THAT ANY REMOVED OR ALTERED WATERPROOFING MEMBRANE IS RESTORED AFTER FABRICATION AND INSTALLATION OF STRUCTURE PROPOSED HEREIN. THIS ENGINEER SHALL NOT BE RESPONSIBLE FOR ANY WATERPROOFING OR LEAKAGE ISSUES WHICH MAY OCCUR AS WATER-TIGHTNESS SHALL BE THE FULL RESPONSIBILITY OF THE INSTALLING CONTRACTOR.

21. INTERIOR MECHANISM AND/OR ELECTRICAL CIRCUITRY ARE OUTSIDE THE SCOPE OF THIS PROUCT EVALUATION.

22. SURVIVABILITY: THIS EVALUATION IS VALID FOR A NEWLY INSTALLED CURB AND DOES NOT INCLUDE CERTIFICATION OF THE PRODUCT BEYOND A DESIGN EVENT OR IF IMPACTED BY ANY DEBRIS, INSPECTIONS SHALL BE IMPLEMENTED ANNUALLY BY THE END USER AND AFTER EVERY NAMED STORM. ALL FASTENERS AND CABINET COMPONENTS ARE TO BE VERIFIED, AND ALL DAMAGED, LOOSE, CORRODED, AND/OR BROKEN FASTENERS AND CABINET COMPONENTS SHALL BE REPLACED TO ENSURE STRUCTURAL INTEGRITY AGAINST HURRICANE WIND FORCES. CONTACT THIS OFFICE FOR ANY REEVALUATION NEEDS OR AS DESIGNATED BY THE AUTHORITY HAVING JURISDICTION.

23. DURABILITY: COMPONENTS OR COMPONENT ASSEMBLIES SHALL NOT DETERIORATE, CRACK, FAIL, OR LOSE FUNCTIONALITY DUE TO GALVANIC CORROSION OR WEATHERING. ALL SUPPORTING COMPONENTS WHICH ARE PERMANENTLY INSTALLED SHALL BE PROTECTED AGAINST CORROSION, CONTAMINATION, AND OTHER SUCH DAMAGE AT ALL TIMES, EACH COMPONENT OR COMPONENT ASSEMBLY SHALL BE SUPPORTED AND ORIENTED IN ITS INTENDED INSTALLATION POSITION. ALL EXPOSED PLASTIC COMPONENTS SHALL BE CERTIFIED TO RESIST SUNLIGHT EXPOSURE AS SPECIFIED BY ASTM B117, OR ASTM G155 IN BROWARD OR MIAMI-DADE COUNTIES.

24. EXTENT OF CERTIFICATION: CERTIFICATION PERTAINS TO THE OVERALL STRUCTURAL INTEGRITY OF THE CURB COMPONENTS LISTED WITHIN THE EVALUATION AS REQUIRED BY CODE, SUBJECT TO THE LIMITATIONS AND CRITERIA STATED HEREIN. OPERABILITY DURING OR AFTER A DESIGN EVENT IS NOT INCLUDED IN THIS CERTIFICATION. WATER INFILTRATION IS OUTSIDE THE BOUNDS OF THIS CERTIFICATION. NO OTHER CERTIFICATIONS ARE INTENDED OTHER THAN AS DESCRIBED HEREIN, THIS EVALUATION ALONE DOES NOT OFFER ANY EVALUATION FOR LARGE MISSILE IMPACT DEBRIS OR CYCLIC WIND REQUIREMENTS UNLESS SPECIFICALLY STATED HEREIN.

25. ENGINEER SEAL AFFIXED HERETO VALIDATES STRUCTURAL DESIGN AS SHOWN

NOTE REGARDING USE OF THIS DOCUMENT & USE OUTSIDE FLORIDA: THIS IS A NON-SITE-SPECIFIC STRUCTURAL PERFORMANCE EVALUATION. THIS

PRODUCT EVALUATION IS VALID FOR USE IN **FLORIDA ONLY**. USE OF THIS EVALUATION REQUIRES A REVIEW & CERTIFICATION BY A LOCAL DESIGN PROFESSIONAL WHO SHALL BE RESPONSIBLE FOR THE PROPER ADAPTATION OF THIS GENERAL PERFORMANCE EVALUATION TO ANY SITE-SPECIFIC PROJECT. CONTACT THIS OFFICE AT **ENGINEERINGEXPRESS.COM/QUOTE** FOR ASSISTANCE WITH YOUR PROJECT-SPECIFIC NEEDS & FOR ADAPTATION & CERTIFICATION OF THIS DOCUMENT OUTSIDE OF FLORIDA.



Miami-Dade Product Control

FEDERAL CODES & FROM DEVIATIONS OF THIS PLAN. SPECIFIED HEREIN, WORK SHALL BE FIELD VERIFIED BY OTHERS. INSTALLATION OF MATERIALS.

INVALIDATE OUR CERTIFICATION.


<u> </u>	PA
COVE	R
CURB & UNIT N	1C
CARRIER CURB	S
LENNOX CURB	SF
TRANE CURB S	5P
UNIT-TO-CU	RE
CURB-TO-HC	)S

#### **TERMINOLOGY:**

THE FOLLOWING ABBREVIATIONS MAY APPEAR IN THIS APPROVAL:


"NUMBER", "&" FOR "AND", AND "Ø" FOR "DIAMETER".


CLARIFICATIONS.




# **CURB & UNIT MODEL SUMMARY**


Unit-Curb Group	Unit Manufacturer	Tonnage	Description	Unit Width (in)	Unit Depth (in)	Unit Height (in)	Min. Net Weight (lb)	Max. Net Weight (lb)
I	Carrier	3-6	WeatherMaker Single Packaged Rooftop	74.75	46.625	33.375 - 41.375	437	607
I	Carrier	7.5-12.5	WeatherMaker Single Packaged Rooftop	88.125	59.5	41.25 - 49.375	743	1041
I	Carrier	15	WeatherMaker Single Packaged Rooftop	115.875	63.375	57.375	1408	1408
Ι	Lennox	Box Size A	Model L Ultra-High Efficiency Pakcaged Electric 3-6 Ton	85.25	45	46.875	502	840
I	Lennox	Box Size B	Model L Ultra-High Efficiency Pakcaged Electric 7.5-12.5 Ton	129	60.125	46.875	870	1367
Ι	Trane	3-25	Precedent Packaged Rooftop Units: A.0 Cabinet	69.875	44.25	46.875	589	797
Ι	Trane	3-25	Precedent Packaged Rooftop Units: B.0 Cabinet	88.25	53.25	50.875	892	1017
Ι	Trane	3-25	Precedent Packaged Rooftop Units: C.0 Cabinet	99.625	63.125	50.875	950	2000
II	Carrier	17.5-27.5	WeatherMaker Single Packaged Rooftop: Footprint 1	127.875	86.375	49.375	1673	2351
II	Lennox	Box Size C	Model L Ultra-High Efficiency Pakcaged Electric 13-25 Ton	132.625	91.125	54.25	1724	2996
II	Trane	15-25	Foundation Packaged Rooftop Units	123.125	86.9375	58.625	2054	2103
II	Trane	3-25	Precedent Packaged Rooftop Units: D.0 & D.1 Cabinets	123	87	59 - 66	1218	2150
III	Carrier	17.5-27.5	WeatherMaker Single Packaged Rooftop: Footprint 2	141.5	86.375	49.375 - 57.375	1673	2351
III	Carrier	17.5-27.5	WeatherMaker Single Packaged Rooftop: Footprint 3	157.750	86.375	57.375	1673	2351
III	Lennox	Box Size D	Enlight Packaged Electric 25-30 Ton	145	90.75	65	2997	3585
IV	Lennox	Box Size E	Energence Rooftop Units	286	90	68	6100	6930








NOTE: UNIT-CURB GROUPS HAVE BEEN DESIGNATED BY ENGINEERING EXPRESS TO CHARACTERIZED THE TIEDOWN CALCULATIONS BASED ON THE UNITS OVERALL SIZES. SEE SHEETS 17 THRU 19 FOR THE TIEDOWN SPECIFICATIONS RELATED WITH EACH UNIT-GROUP CURB

























LENNOX 1 BOX SIZE 'A' / UNIT-CURB GROUP I 09 NOT TO SCALE MULTIPLE VIEWS





























## **TRANE CURBS SPECIFICATIONS**



## **TRANE CURBS SPECIFICATIONS**





1. BASE RAIL SHAPE MAY	VARY; SEE MANUFACTURER	DOCUMENTATION FOR	ACTUAL BASE RAIL SHAPE

4. USE THE FOLLOWING SCHEDULE TO OBTAIN THE TOTA	I NUMBER OF REQUIRED	) FASTENERS PER FACH UNT
I ODE THE TOELOWING SCHEDOLE TO ODIVIN THE TOTY		P ASI ENERS I ER EACH ONI

		UN	VIT-TO-CURB TIEDOWN SCHDEULE (DIRECT MOUNT MI	ETHOD)
UNIT-CURB GROUP	UNIT MANUFACTURER	TONNAGE	DESCRIPTION	# OF FASTE UNIT LOI
I	CARRIER	3-6	WEATHERMAKER SINGLE PACKAGED ROOFTOP	9
I	CARRIER	7.5-15	WEATHERMAKER SINGLE PACKAGED ROOFTOP	1
I	LENNOX	BOX SIZE A	MODEL L ULTRA-HIGH EFFICIENCY PACKAGED ELECTRIC 3-6 TON	1
I	LENNOX	BOX SIZE B	MODEL L ULTRA-HIGH EFFICIENCY PACKAGED ELECTRIC 7.5-12.5 TON	1.
I	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNIT: A.0 CABINET	9
I	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNIT: B.0 CABINET	1
I	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNIT: C.0 CABINET	12
II	CARRIER	17.5-27.5	WEATHERMAKER SINGLE PACKAGED ROOFTOP: FOOTPRINT 1	10
II	LENNOX	BOX SIZE C	MODEL L ULTRA-HIGH EFFICIENCY PACKAGED ELECTRIC 13-25 TON	13
II	TRANE	15-25	FOUNDATION PACKAGED ROOFTOP UNITS	19
II	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNITS: D.0 & D.1 CABINETS	19
III	CARRIER	17.5-27.5	WEATHERMAKER SINGLE PACKAGED ROOFTOP: FOOTPRINT 2	18
III	CARRIER	17.5-27.5	WEATHERMAKER SINGLE PACKAGED ROOFTOP: FOOTPRINT 3	20
III	LENNOX	BOX SIZE D	ENLIGHT PACKAGED ELECTRIC 25-30 TON	1!
IV	LENNOX	BOX SIZE E	EMERGENCE ROOFTOP UNITS	30


	Strap Schedule	5
Unit-Curb Group	Max. ASD Wind Pressure Lateral (Uplift)	# of Straps
T	±80psf (64psf)	0
1	±122psf (96psf)	3
П	±80psf (64psf)	0
11	±122psf (96psf)	3
TI	±80psf (64psf)	0
111	±122psf (96psf)	3
τv	±80psf (64psf)	0
10	±122psf (96psf)	10

# **UNIT-TO-CURB TIEDOWN SPECIFICATIONS: STRAP METHOD**

#### PRODUCT APPROVED

as complying with the Florida Building Code NOA-No. 25-0410.04 Approval Date 07/10/2025


By Hims Miami-Dade Product Control



NOTE: TIE-DOWN STRAPS QUANTITY SHOWN ARE AS APPLICABLE; SEE STRAP SCHEDULE

$\begin{pmatrix} 1 \end{pmatrix}$	UNIT ATTACHMENT	TO CURB, TYP.
18	NOT TO SCALE	ELEVATION VIEW

Strap Schedule				
Unit-Curb Group	Max. ASD Wind Pressure Lateral (Uplift)	# of Straps per Unit Long Side		
т	±80psf (64psf)	5		
	±122psf (96psf)	7		
TT	±80psf (64psf)	5		
	±122psf (96psf)	7		
TIT	±80psf (64psf)	7		
111	±122psf (96psf)	10		
IV	±80psf (64psf)	12		
10	±122psf (96psf)	20		



DETAIL 2/18 NOTES:

NOT TO SCALE

18


1. BASE RAIL SHAPE MAY VARY; SEE MANUFACTURER DOCUMENTATION FOR ACTUAL BASE RAIL SHAPE.

2. INSTALLER SHALL ENSURE THE DRILLED HOLE IS SLIGHTLY SMALLER IN DIAMETER THAN THE THREADED FASTENER'S MAJOR DIAMETER, SUCH THAT THREAD ENGAGEMENT WITH THE MATERIALS IN CONTACT IS GUARANTEED.

3. SEE GENERAL NOTE #5 FOR STRAP MINIMUM SPECIFICATIONS.

	RICHARD NEET, P.E. PE# 86488 CA# 9885	JUNE 2, 2025
	THE OTHER CARLES AND	
da	No. P.E. 81488	
	* *	
<u>4</u> 5	STATE OF	
г [	<u> Adama ( ) ( )</u>	<u></u>
	MONAL ENGLISH	<u>1</u> 2007 УОС
		SS.CC
		PRESS
SIDE PANEL		ADIC ADIC
NIT BASE L, SHAPE		<b>EXPRESS</b> <b>EXPRESS</b> <b>POSTAL ADDRESS</b> <b>34 NORTH FEDERAL HWY #7664 BOCA RATON, FL 33431 ENGINEERINGEXPRESS.COM</b>
1AY VARY		
#14 (1/4" Ø), E GR. 2 MIN. OR		POSTAL ADDRESS POSTAL ADDRESS: 2234 NORTH FEDERAL HWY #7664 BOCA RATON, FL 33431 ENGINEERINGEXPRESS.COM
SMS, TYP.		
EE		LC LC VOA)
ULE		IRSOUTH AIR PRODUCTS, LLC 1055 E 35TH STREET HIALEAH, FL 33013 (305) 8289-400 AIRSOUTH COMMERCIAL UNITS CURBS FLORIDA BULDING CODE EIGHTH EDITION (2023 IAMI-DADE COUNTY NOTICE OF ACCEPTANCE (NOA)
		CTS
		DU DU DU DU DU ACCE
		RO 1 STR 1 S
		AIR PROL 55 E 35TH STRE ALEAH, FL 3301 (305) 8289-400 COMMERCIAL UN G CODE EIGHTI ITY NOTICE OF,
TYP.		
SECTION VIE	W	
		SOL AIRS DADI
JRER		AIRSOUTH , 105 HI AIRSOUTH C FLORIDA BULDIN
IS		
I THAT		DATE 22/18/25 
		Z
		DRW MRT 
		INT ISSUE
		and a second particular and a subscription of the second
		copyright engineering express® 24-82376
		SCALE: NTS UNLESS NOTED
		f 8 <sup>19</sup>

## **CURB-TO-HOST TIEDOWN SPECIFICATIONS**



			CURB-TO-HOST TIE	DOWN SCHEDULE				
					MAX. AS	D WIND PRESSU	JRE   LATERAL (UPLIFT)	
UNIT-CURB GROUP	UNIT MANUFACTURER	TONNAGE	DESCRIPTION		± 80 PSF (64 PSF)		±	: 1
GROOT	MANOFACIORER			# OF FASTENERS PER UNIT LONG SIDE	# OF FASTENERS PER UNIT SHORT SIDE	TOTAL # OF FASTENERS	# OF FASTENERS PER UNIT LONG SIDE	7
I	CARRIER	3-6	WEATHERMAKER SINGLE PACKAGED ROOFTOP	7	4	22	9	Г
I	CARRIER	7,5-12.5	WEATHERMAKER SINGLE PACKAGED ROOFTOP	8	5	26	11	Г
I	CARRIER	15	WEATHERMAKER SINGLE PACKAGED ROOFTOP	8	5	26	11	Γ
I	LENNOX	BOX SIZE A	MODEL L ULTRA-HIGH EFFICIENCY PACKAGED ELECTRIC 3-6 TON	8	4	24	11	Γ
I	LENNOX	BOX SIZE B	MODEL L ULTRA-HIGH EFFICIENCY PACKAGED ELECTRIC 7.5-12.5 TON	9	6	30	13	Γ
I	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNIT: A.0 CABINET	6	4	20	9	Γ
I	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNIT: B.0 CABINET	8	5	26	11	Γ
I	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNIT: C.0 CABINET	9	6	30	12	Γ
II	CARRIER	17,5-27,5	WEATHERMAKER SINGLE PACKAGED ROOFTOP: FOOTPRINT 1	8	5	26	13	Γ
II	LENNOX	BOX SIZE C	MODEL L ULTRA-HIGH EFFICIENCY PACKAGED ELECTRIC 13-25 TON	7	6	26	11	
II	TRANE	15-25	FOUNDATION PACKAGED ROOFTOP UNITS	7	5	24	13	Γ
II	TRANE	3-25	PRECEDENT PACKAGED ROOFTOP UNITS: D.0 & D.1 CABINETS	7	5	24	13	Γ
III	CARRIER	17.5-27.5	WEATHERMAKER SINGLE PACKAGED ROOFTOP: FOOTPRINT 2	12	8	40	18	Γ
III	CARRIER	17.5-27.5	WEATHERMAKER SINGLE PACKAGED ROOFTOP: FOOTPRINT 3	14	8	44	20	Γ
III	LENNOX	BOX SIZE D	ENLIGHT PACKAGED ELECTRIC 25-30 TON	10	8	36	15	Γ
IV	LENNOX	BOX SIZE E	EMERGENCE ROOFTOP UNITS	32	10	84	47	Γ

CURB TO HOST TIEDOWN SCHEDULE NOTES:

- 1. ANCHORS SHALL BE AS FOLLOWS:
- CONCRETE ANCHORS: 1/4" Ø ITW TAPCONS W/ 1-3/4" EMBEDMENT & 3" MIN. E.D.
- WOOD ANCHORS: 3/8" Ø WOOD LAG SCREWS W/ 3" MIN. THREAD PENETRATION & 3/4" MIN. E.D.
- STEEL ANCHORS: 1/4" Ø SAE GR 5 SMS's W/ 3/4" MIN. E.D.
- 2. SEE GENERAL NOTE #12 FOR HOST STRUCTURE MINIMUM REQUIREMENTS.
- 3. CORNER ANCHORS SHALL BE POSITIONED AT 6" MIN. FROM ANY CURB EDGE.

RICHARD NEET, P.E. PE# 86488 CA# 9885	
PRODUCT APPROVED as complying with the Florida Building Code NOA-No. 25-0410.04 Approval Date 07/10/2025 By Him Miami-Dade Product Control	POSTAL ADDRESS. POSTAL ADDRESS: 2234 NORTH FEDERAL HWY #7664 BOCA RATON, FL 33431 ENGINEERINGEXPRESS.COM
122 PSF (96 PSF)   # OF FASTENERS PER UNIT SHORT SIDE TOTAL # OF FASTENERS   6 30   7 36   7 36   6 30   7 36   6 30   7 36   6 30   7 36   8 42   6 30   7 36   8 40   9 44   9 44   9 44   9 44   11 58   11 62   11 52   14 122	REMARKS   DRWN CHKD   DATE   AIRSOUTH AIR PRODUCTS, LLC     INTISSUE   MRT   ERVIN 02718/25   AIRSOUTH AIR PRODUCTS, LLC     INTISSUE   MRT   ERVIN 02718/25   AIRSOUTH AIR PRODUCTS, LLC     Intissue   1055 E 35TH STREET   HIALEAH, FL 33013     Intissue   .   .   .     ARSOUTH COMMERCIAL UNITS CURBS   .   .     International Subscription (2023)   .   .     International Subscription (2023)   .   .     International Collar BULDING CODE EIGHTH EDITION (2023)   .