


STANDARD DETAIL FOR SECURITY BARS, GRILLES & GRATES AT WINDOWS

DESIGNATED AS EMERGENCY ESCAPE & RESCUE OPENING. CODE: FBC 2023, 8th EDITION



FRONT VIEW

NOTES:

- MINIMUM NET CLEAR OPENING OF 5.7 SQ. FT EXCEPTION: FOR GROUND FLOOR OPENING NET CLEAR OPENING IS PERMITTED TO BE 5.0 SQ FT. 1.
- MINIMUM CLEAR OPENING FOR WIDTH AND HEIGHT IS IN ADDITION TO MINIMUM 2. CLEAR OPENING AREA REQUIRED IN NOTE 1.
- BAR, GRILL OR GRATE OPENING SHALL COINCIDE AND ALIGN WITH WINDOW OPENING, NO SHIFTING OF THE OPENING IS ALLOWED. 3.
- SECURITY DEVICE SHALL BE RELEASABLE AND OPENABLE FROM THE 4. INSIDE WITHOUT THE USE OF A KEY, TOOL, SPECIAL KNOWLEDGE OR FORCE GREATER THAN THAT REQUIRED FOR THE NORMAL OPERATION OF THE ESCAPE AND RESCUE OPENING.
- REFERENCES: 5. FBC 2023 (BUILDING) SECT. 1030.4 FBC 2024 (RESIDENTIAL) SECT. R310.4

THIS IS A GENERIC DETAIL, THE SECURITY GRILL SHALL FREELY SWING OUTWARD. THERE SHALL BE UNOBSTRUCTED ACCESS TO THE RELEASE MECHANISM INSIDE THE ROOM.



ABOVE

44"

Δ

OPENING

4

NOTE:

EXISTING

INTERIOR FINISH FLOOR

FROM INTERIOR FINISH FLOOR, SEE

GRADE

4

NOTE BELOW.

INSTALL RELEASE BAR THROUGH WALL AND SECURED INSIDE WITH REMOVABLE PIN. TO OPEN REMOVE PIN AND PUSH BARS OUTWARD.