



NOTES:

- 1.-PIPES MAY EXTEND INTO CATCH BASIN A MAXIMUM OF 4".
- 2.-USE 4,000 psi CONCRETE. (MINIMUM), MAXIMUM W/C=0.53, GRADE 60 STEEL FOR REBAR AND GRADE 65 FOR WWF.
- 3.-A SMOOTH LINE OF MORTAR 1/2" THICK INSIDE AND OUTSIDE.
- 4.-WEEP HOLES ARE TO BE USED WHEN THE YEARLY LOWEST WATER ELEVATION IS ABOVE THE TOP OF THE BOTTOM SLAB OF THE STRUCTURE.
- 5.-THIS STRUCTURE IS ONLY TO BE USED WHERE UTILITY CONFLICTS DO NOT ALLOW FOR INSTALLATION OF STANDARD STRUCTURES. THE INSTALLATION OF THIS STRUCTURE MUST BE APPROVED BY THE DEPARTMENT.

<p>MIAMI-DADE COUNTY</p> <p>DEPARTMENT OF TRANSPORTATION AND PUBLIC WORKS</p>	<p>APPROVED</p> <p>5/8/2018</p>	<p>REVISED</p> <p>5/8/2018</p> <p>_____</p> <p>_____</p> <p>_____</p>	<p>STANDARD STORM DRAINAGE DETAIL</p> <p>SWALE INLET (TYPE D-1)</p>	<p>SD 3.1</p> <p>SHEET 1 OF 2</p>
---	---------------------------------	---	---	-----------------------------------