QUALITY. VALUE. ECONOMIC GROWTH.					
WWW.MIAMIDADE.GOV/WATER	MIAMI-DADE COUNTY				



Product Specifications

Sheet Number: 2.2

Miami-Dade Water & Sewer Department Address: 3071 SW 38th Ave, Miami, FL 33146

Phone: (305) 665-7477

PVC Pipe Fittings

Minimum Standards



- For C900/C905: AWWA C105, C110/A21.10, C111/A21.11, C115/A21.15, C153/A21.53, C600
- For Sch. 80: ASTM D2467, D2464, 2564
- MDWASD specification: Sections 15060



Other Requirements

- NSF61/ANSI for potable water applications
- Cement Lining for water application
- Protecto 401 Lining for sewer application
- SDR C900 : 14, 18, 25
- SDR C905: 14, 18, 21, 25, 32.5, 41, 51
- SDR 35 is not allowed, except for hub cleanout with threaded plug at property line in cleanout box.

Applications

Water and Sewer

P	RE-	APPROVED MANUFACTURER	Issue Date:		
	1)	GF Central Plastics	4)	lpex	4-4-2016
	2)	Harrington Corp. (HARCO)	5)	Royal Plastic Trends	
l	3)	MultiFittings			Revised Date: 10-25-2017

SIZE	MANUFACTURER			MODEL	SUBMITTED
4" - 12"	GF Central Plastics			SDR 26 PVC, Molded PE2406/PE2708, PE3408/PE4710	
4" - 12"	HARCO			PVC C-900 GASKETED FITTINGS	
4" - 15"	HARCO			SDR-26 PVC Gasketed sewer fittings	
4" - 12"	IPEX			Blue Brute (Molded Gasketed PVC fittings)	
4" - 12"	IPEX			Blue Brute (Fabricated Gasketed PVC fittings)	
14" - 30"	IPEX			IPEX Centurion (Fabricated Gasketed PVC fittings)	
4" - 30"	IPEX			PVC Trench Tough for SDR26 Gasket Sewer Fittings	
4" - 12"	IPEX			PVC Trench Tough for C900/C905 PIPE, Gasket Sewer & Drain Fittings (non-pressure)	
4" - 24"	IPEX	IPEX		PVC Trench Tough for Heavy Wall Sewer Fittings	
4" - 30"	Royal Plastic Trends			G-Series, Injection Molded/Fabricated Gasketed PVC Sewer fittings	
4" – 15"	MultiFittings			SDR-26 PVC Gasketed sewer fittings	
SIZES FURI	NISHED:				
	□ 4"		12"	□ 20"	
	□ 6"		14"	□ 24"	
	□ 8"		16"	□ 30"	
	□ 10"		18"	□ Other	
COMMENTS	S:				

Approved by: David Vazquez, PE

Title: Specifications Manager