



BID NO.: 9719-0/18

**OPENING: 2:00 P.M.
Wednesday
January 9, 2013**

MIAMI-DADE COUNTY, FLORIDA

**I N V I T A T I O N
T O B I D**

**TITLE:
Tilt Frame Roll Off Trucks**

**FOR INFORMATION CONTACT:
LOURDES BETANCOURT, 305-375-4121, L1121@miamidade.gov**

IMPORTANT NOTICE TO BIDDERS:

- READ THIS ENTIRE DOCUMENT, THE GENERAL TERMS AND CONDITIONS, AND HANDLE ALL QUESTIONS IN ACCORDANCE WITH THE TERMS OUTLINED IN PARAGRAPH 1.2(D) OF THE GENERAL TERMS AND CONDITIONS.**
- FAILURE TO SIGN BID SUBMITTAL FORM IN SECTION 4 WILL RENDER YOUR BID NON-RESPONSIVE**

**MIAMI-DADE COUNTY
INTERNAL SERVICES DEPARTMENT
PROCUREMENT MANAGEMENT DIVISION**



MIAMI-DADE COUNTY, FLORIDA

INVITATION TO BID

Bid Number: 9719-0/18

Bid Title: TILT FRAME ROLL OFF TRUCKS

Procurement Officer: LOURDES BETANCOURT, CPPB

Bids will be accepted until 2:00 p.m. on JANUARY 9, 2013

Bids will be publicly opened. The County provides equal access and does not discriminate on the basis of disability in its programs or services. It is our policy to make all communication available to the public, including those who may be visually or hearing impaired. If you require information in a non-traditional format please call 305-375-5278.

Instructions: The Clerk of the Board business hours are 8:00am to 4:30pm, Monday through Friday. Additionally, the Clerk of the Board is closed on holidays observed by the County. Each Bid submitted to the Clerk of the Board shall have the following information clearly marked on the face of the envelope: the Bidders name, return address, Bid number, opening date of the Bid and the title of the Bid. Included in the envelope shall be an original and two copies of the Bid Submittal, plus attachments if applicable.

All Bids received time and date stamped by the Clerk of the Board prior to the bid submittal deadline shall be accepted as timely submitted. The circumstances surrounding all bids received and time stamped by the Clerk of the Board after the bid submittal deadline will be evaluated by the procuring department, in consultation with the County Attorney's Office, to determine whether the bid will be accepted as timely.

NOTICE TO ALL BIDDERS:

- **FAILURE TO SIGN THE BID SUBMITTAL FORM WILL RENDER YOUR BID NON-RESPONSIVE.**
- **THE BID SUBMITTAL FORM CONTAINS IMPORTANT CERTIFICATIONS THAT REQUIRE REVIEW AND COMPLETION BY ANY BIDDER RESPONDING TO THIS SOLICITATION.**

**MIAMI-DADE COUNTY
INTERNAL SERVICES DEPARTMENT
PROCUREMENT MANAGEMENT DIVISION**

SECTION 1
GENERAL TERMS AND CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

All general terms and conditions of Miami-Dade County Procurement Contracts for Invitations to Bid are posted online. Persons and Companies that receive an award from Miami-Dade County through Miami-Dade County's competitive procurement process must anticipate the inclusion of these requirements in the resultant Contract. These standard general terms and conditions are considered non-negotiable subject to the County's final approval.

All applicable terms and conditions pertaining to this solicitation and resultant contract may be viewed online at the Miami-Dade County Procurement Management website by clicking on the below link:

<http://www.miamidade.gov/procurement/library/general-terms-and-conditions-itb.pdf>

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

2.1 PURPOSE

The purpose of this solicitation is to establish a contract for the purchase of tilt frame roll off trucks for the Public Works and Waste Management Department. There are two types of Trucks the County intends to purchase.

Truck A - Cable Hoist

Truck B – Hook Arm Lift

2.2 TERMS OF CONTRACT: FIVE YEARS

This contract will commence on the first calendar day of the month succeeding approval of the contract by the Board of County Commissioners and contingent upon the completion and submittal of all required bid documents. This contract shall remain in effect for five (5) years and shall expire on the last day of the last month of the five-year period.

2.3 PRE BID CONFERENCE (HIGHLY RECOMMENDED) FOLLOWED BY INSPECTION OF EXISTING TRUCKS

A pre-bid conference will be held on Friday, December 21, 2012 at 10:00 a.m. at Internal Services Department Fleet Management Division Shop 3 at 8801 N.W. 58th Street, Miami, Florida 33178 to discuss the special conditions and specifications included within this solicitation. It is recommended that a representative of the firm attend this conference as the “cone of silence” will be lifted during the course of the conference and informal communication can take place.

Vendors are requested to bring this solicitation document to the conference, as additional copies may not be available. Multiple members of individual community councils may be present.

Existing truck types will be available for viewing after the pre-bid conference at the following location:

Fleet Management Division Shop 3
8801 N.W. 58th Street
Miami, Fl. 33178
(305) 418-2727

2.4 METHOD OF AWARD

The County may choose to award either Truck A or Truck B or both. Truck A award, if any, will be to the responsive and responsible Bidder offering the lowest price for Truck A and that meets the requirements below: Truck B award, if any, will be to the responsive and responsible Bidder offering the lowest price for Truck B and that meets the requirements below:

2.4.1 Bidder must be the vehicle's manufacturer or fabricator, or a licensed dealer thereof.

**SECTION 2
SPECIAL CONDITIONS**

TITLE: Tilt Frame Roll Off Trucks

2.4.2 There must be a service facility capable of supporting the proposed sale and of performing warranty repairs and supplying needed parts located in Miami-Dade or Broward County. The service facility may be subject to the County’s review and approval.

2.4.3 In accordance with Chapter 320 of the Florida Statutes, SS320.27, Bidder must be licensed by the state of Florida as motor vehicle dealers.

NOTE: The Bidder may be given the opportunity to submit the documentation to the County during the bid evaluation period. Failure to meet these requirements may result in the bid not being considered for award.

2.5 PRICES SHALL BE FIXED WITH ADJUSTMENTS ALLOWED:

The County’s anticipated purchasing schedule is:

Contract Year	Number of Truck A - Cable Hoist	Number of Truck B- Hook Arm Lift	Number of Truck B- Hook Arm Lift
	Model Year 2013	Model Year 2013	Model Year to be determined
1	3 Trucks	9 Trucks	
2 to 5			18*

*The County may purchase these 18 Trucks provided that the Trucks delivered by the awarded Bidder for Truck B during the first year are satisfactory and funding is available as appropriated by the County. The price adjustment to purchase the 18 additional trucks will be calculated using Producer Price Index Heavy Duty Truck manufacturing.

If a Bidder is awarded a contract under this solicitation, the price offered by the Bidder shall be firm and fixed for the first year of the Contract. For purchases during the remaining years of the contract (years 2, 3, 4 & 5), the County may consider an adjustment to price for the following based on the change in the pricing index listed below from contract inception:
Producer Price Index, Item - Series ID PCU336120336120 Industry: Heavy Duty Truck Manufacturing – Product: Heavy Duty Truck Manufacturing

It is the awarded Bidder’s responsibility to request any pricing adjustment under this provision. The awarded Bidder’s adjustment request cannot be in excess of the relevant pricing index change. If no adjustment request is received from the Awarded Bidder, the County will assume that the Awarded Bidder has agreed to waive any pricing adjustment the applicable purchase.

The County reserves the right to negotiate any price adjustment submitted by the awarded Bidder. The County may apply a reduction in pricing based on the downward movement of the applicable index.

2.6 COMPETENCY OF VENDORS AND ASSOCIATE SUBCONTRACTORS

The County may elect to conduct a pre-award inspection of the Bidder’s facility during the offer evaluation process. Offers will be considered only from firms which are regularly engaged in the business of providing or distributing the goods and/or performing the services as described in the solicitation, and who can produce evidence that they have a

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

satisfactory record of performance for a reasonable period of time. Bidder may be required to demonstrate that it have sufficient financial support and organization to ensure that they can satisfactorily execute the contract if awarded under the terms and conditions herein stated. In the event that a Bidder intends to sub-contract any part of its work to another vendor, or will obtain the goods specifically offered under this contract from another source of supply; the Bidder may be required to verify the competency of its sub-contractor or supplier. Miami-Dade County reserves the right, before awarding the contract, to require a Bidder to submit such evidence of its qualifications and the qualifications of its sub-contractor as it may deem necessary. The County may consider any evidence available to it of the financial, technical and other qualifications and abilities of any Bidder responding hereunder, including past performance with the County, in determining Bidder's responsibility for the purposes of selecting a Bidder for contract award.

2.7 CONTACT PERSON

2.7.1 For any additional information regarding the terms and conditions of this solicitation and resultant contract, Contact: Lourdes Betancourt, at (305) 375-4121 email – L1121@miamidade.gov.

2.7.2 To allow enough time for the County to respond, requests for clarification and additional information should be received at least 7 days before the Bid Opening Date.

2.8 SPECIAL CONDITIONS FOR BIDDING MOBILE EQUIPMENT

BIDDING EQUAL PRODUCTS, NO SUBSTITUTION COMPONENTS, MANUFACTURER'S CATALOGUES/BROCHURES AND PRODUCT DEMONSTRATIONS

2.8.1 Manufacturer's name, brand name and/or model number, when used in the specifications are for the sole purpose of establishing minimum requirements of levels of quality, standards of performance and design. They are in no way intended to prohibit the bidding of other manufacturer's brands of equal material, quality, design and standards of performance, unless the wording "NO SUBSTITUTION" is used.

2.8.2 When "NO SUBSTITUTION" is used in combination with a manufacturer's name, brand name and/or model number, the named item is the only item that will be accepted by the County.

2.8.3 When an equal product is bid, the Bidder shall furnish the factory information sheets (specifications, brochures, etc.) that show the product meets or exceeds the required specifications. Failure to meet this requirement may result in the bid being deemed non-responsive. The County will be sole judge of equality or similarity and the County's decision shall be final. Manufacturer's standard information sheets, catalogues, brochures and all supporting documentation submitted must show the product meets or exceeds the required specifications. Bids that are submitted with standard product literature which offer technical data or product descriptions indicating the item or product bid does not meet the required specifications must be accompanied by a letter, on the Bidder's company stationary, identifying those differences and describing how compliance with the required specifications is to be accomplished. Failure to comply with this requirement may result in the rejection of the bid for not meeting the specifications.

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

NOTE: Photographs, picture, and other graphic illustrations that are part of standard product literature will not be used in determining product compliance with these specifications.

2.8.4 After the Bid Submittals have been evaluated by the County, the Bidder offering the lowest price, as stipulated in Section 2, Paragraph 2.6 of this solicitation may be required to demonstrate the equipment, which has been proposed, for evaluation by and at no cost to the County. The purpose of the demonstration is to observe the equipment in an operating environment and verify its capability, suitability, and adaptability vis-à-vis the performance requirements stipulated in the bid. If a demonstration is required, the County will notify the Bidder of such in writing and will specify the date, time and location of the demonstration. If the Bidder fails to perform the demonstration on the date stipulated in the notice, the County may elect to reject the Bidder's proposal or to re-schedule the demonstration. The County will be the sole judge of the acceptability of the equipment in conformance with the Bid Specifications and its decision shall be final.

2.8.5 The equipment used for the demonstration shall be the same as the manufacturer's model identified in the Bidder's proposal. Accordingly, the equipment used in the demonstration shall create an expressed warranty that the actual equipment provided by the awarded Bidder during the contract period shall be similar to the equipment used in the demonstration.

EQUIPMENT FURNISHED

2.8.6 The equipment furnished by the awarded Bidder, during the term of the Contract, shall be new and the most recent model available. Demonstrator models are not acceptable. Vehicles that are equipped with the OEM manufacturer's standard accessories will have less than 50 miles recorded on the odometer at the time of delivery. Vehicles that are equipped with accessories, which are not the OEM manufacturer's standard order accessories, will have less than 100 miles recorded on the odometer at the time of delivery. Vehicles delivered outside this mileage requirement will not be accepted. Any optional components that are required in accordance with the Bid Specifications (refer to Section 3, of this Bid Solicitation) shall be considered standard equipment for the purposes of this solicitation. Any optional components that are recommended by the vehicle manufacturer for the application intended must be included and will be considered standard equipment for the purposes of this solicitation. The application and usage of all components, sub-components or parts must be in accordance with their manufacturers' recommendations, as well as the recommendations of all associated component manufacturers. Omission of any essential detail from these specifications does not relieve the awarded Bidder from furnishing a complete and ready to work unit. The silence of specifications on any point shall mean that only the finest commercial practices of the industry shall apply and all interpretations of the Bid Specifications shall be so governed.

2.8.7 The unit shall conform to all applicable Occupational Safety and Health Administration (OSHA), State and Federal, and American National Standards Institute (ANSI) requirements and standards, and Department of Transportation (D.O.T.) regulations. All components and included craftsmanship are to be in accordance with current Society of Automotive Engineers (S.A.E.) standards and recommended practices. The engineering, materials and workmanship shall exhibit a high level of quality and appearance, consistent with or exceeding the industry standards.

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

2.8.8 The equipment and features required are listed in the bid specifications (refer to Section 3, entitled "Technical Specifications"). The County may, after delivery and acceptance of the initial equipment ordered, make changes to the required equipment or equipment options supplied, provided; 1) such changes are mutually agreed between the awarded Bidder and the County, 2) all changes in per unit pricing are no more than the change in per unit documentable cost to the awarded Bidder, and 3) that the net amount of any such changes is no more than five percent of the per unit price originally bid.

BIDDER STATUS

2.8.9 See 2.4.2 above.

WARRANTY REQUIREMENTS

2.8.10 The awarded Bidder shall supply and be responsible for fulfilling the vehicle's warranty. Vehicles with a GVWR of 19,500 pounds or less will have a warranty free of deductibles with no less than the following coverage:

- Thirty-six months (36) or 36,000 miles full vehicle bumper to bumper.
- Sixty months (60) or 60,000 miles on the power train.
- Hybrid unique components (if hybrid) ninety-six months or 100,000 miles.

Vehicles with a GVWR of 19,501 pounds or more will have a warranty free of deductibles with no less than the following coverage:

- Twenty-four months (24) bumper to bumper.
- Sixty (60) months on the engine and transmission.
- Hybrid unique components (if hybrid) sixty (60) months.

ALL VEHICLES

- When vehicle or component manufacturers provide a warranty with coverage in excess of that stipulated herein, that additional coverage shall not be diminished by the requirements of this paragraph.
- When vehicle or component manufacturers provide a warranty with less coverage than that stipulated herein, the awarded Bidder shall provide a supplemental warranty that meets or exceeds the warranty requirements, as stipulated herein.
- The warranty terms shall be subject to Delay In Start Warranty Program (commence when the vehicle is put into service), if available from the vehicle's manufacturer.
- A written five (5) year 100% coverage warranty shall be supplied for the engine.
- A written five (5) year 100% coverage warranty for transmission shall be supplied for each vehicle purchased.
- The entire vehicle shall have a rust and corrosion protection warranty for a five (5) year period. The warranty shall require the complete repair of any rust or corrosion damage that occurs in the five (5) year warranty period.

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

2.8.11 The awarded Bidder shall promptly correct any warranted deficiency, at no cost to the County, at a warranty service center that meets the criteria stated in Paragraph 2.6.2 within five (5) calendar days after the County notified the awarded Bidder of such deficiency in writing. If the awarded Bidder fails to honor the warranty and/or fails to correct or replace the defect within the period specified, the County may, at its discretion, notify the awarded Bidder in writing that the awarded Bidder may be found in violation of the Contract or be subject to contractual default if the deficiencies are not corrected and/or replacement or repairs are not completed to the satisfaction of the County within the specified timeframe. If the awarded Bidder fails to satisfy the warranty within the period stipulated in the notice, the County may (a) place the awarded Bidder in default of its contract, and/or (b) procure the products or services from another vendor and charge the awarded Bidder for any additional costs that are incurred by the County, either through a credit memorandum or through invoicing.

2.8.12 The awarded Bidder and/or their local service representative may be required to enter into an Original Equipment Manufacturer (OEM) parts and service supply agreement with Miami-Dade County, during the useful life of the equipment furnished. This maintenance support agreement would be to supply parts, repairs and training or service at the County's discretion. By the submission of this bid, the Bidder agrees to enter into such agreement at the County's discretion, with parts and labor pricing at rates no higher than industry standard.

DELIVERY AND PAYMENT

2.8.13 All prices shall be quoted F.O.B. destination point. Deliveries are authorized at the County's Shop 3 Main Vehicle Facility, located at 8801 N.W. 58 Street, Doral, Florida 33172, between the hours of 8:00 A.M. and 2:00 P.M. weekdays, or at another location or at times that may be so designated on the purchase order. Contact the Facility Supervisor at (305) 591-9515, forty-eight (48) hours prior to delivery.

2.8.14 Delivery is required within the number of days stated by the awarded Bidder within the Bid Proposal. In no case may this date be later than 270 days from the date that the County department orders the equipment by sending Purchase Order to the awarded Bidder. All deliveries are to be made in accordance with good commercial practice. All equipment shall be delivered in full compliance with the bid specifications and requirements, and must be in excellent condition and ready to work. Upon verification of compliance with these requirements, the County will accept the delivered equipment. See Paragraph 2.9.16 for defective delivery correction requirement.

2.8.15 Upon failure to deliver the equipment in accordance with best commercial practices, excellent ready to work condition, and full compliance with the specifications and requirements to the County within the number of days stipulated in Paragraph 2.9.14., the awarded Bidder shall be subject to charges for liquidation damages in the amount of one tenth (1/10) of one percent (1%) of the per unit purchase price for each and every calendar day that each unit of the equipment order is not delivered in acceptable condition. This charge for liquidation damages is in addition to other remedies and timetable requirements listed in Paragraph 2.9.16 below.

2.8.16 The awarded Bidder shall be responsible for promptly correcting any equipment delivery deficiency, at no cost to the County, within ten (10) calendar days after the County

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

notifies the awarded Bidder of such deficiency in writing. If the awarded Bidder fails to correct or replace the defect within the period specified, the County may, at its discretion, notify the awarded Bidder in writing that the awarded Bidder may be found in violation of the Contract or be subject to contractual default if the deficiencies are not corrected and/or replacement or repairs are not completed to the satisfaction of the County within the specified timeframe. If the awarded Bidder fails to satisfy the delivery requirements within the period stipulated in the notice, the County may (a) place the awarded Bidder in default of its contract, and/or (b) procure the products or services from another vendor and charge the awarded Bidder for any additional costs that are incurred by the County either through a credit memorandum or through invoicing.

2.8.17 The County shall issue payment after completion of items (a) and (b) below, and as per the payment provisions established in Section 1, Paragraph 1.2, (H) (1):

- A. The delivered unit is successfully inspected for compliance with all specifications and requirements and is accepted (including delivery of the required manuals).
- B. All documentation described in the Purchase Order has been received as stipulated therein. The language that will appear in the Purchase Order is:

Application for Certificate of Title and/or Vehicle Registration (HSMV-8040), Certification of Motor Vehicle Sale Tax Exemption (MVC Form DR-41A), Motor Vehicle Dealer Title Reassignment Supplement (DHSMV 82994), Manufacturer's Statement of Origin To A Motor Vehicle and Service Policy shall be made out in the name of:

Miami Dade County, Florida
2225 N.W. 72nd Avenue,
Miami, Florida 33122.

- C. These documents must be dated to coincide with the delivery of the equipment, send all papers to:

Internal Services Department
Administrative and Business Services Division
2225 N.W. 72nd Avenue
Miami, Florida 33122

- D. All documents must be properly filled out and completed, signed and notarized by an authorized individual with no strike-over on any documents. Non-compliance will result in payment delays.

- E. The invoice is to be made out in triplicate to the name of the department as indicated on the Purchase Order and mailed to the same address as shown in the Purchase Order. The vehicle key numbers are to be noted on the invoice.

PARTS, REPAIRS AND TRAINING MANUALS

2.8.18 The awarded Bidder shall supply the County with a minimum of one (1) each; a comprehensive training manual which describes the appropriate use of the equipment purchased, and, a comprehensive repairs and parts manuals which identify the component

SECTION 2
SPECIAL CONDITIONS

TITLE: Tilt Frame Roll Off Trucks

parts and which describe the appropriate process for repairing the equipment purchased. This may be done by book, CD or via an online access to an appropriate website.

ALTERNATE BIDS

2.8.19 Alternate bids as noted in Section 1, Paragraph 1.3 (E) are not permitted as part of this solicitation.

MOTOR VEHICLE LICENSE REQUIREMENT

2.8.20 See 2.4.3 above.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

3.1 SCOPE OF WORK

These specifications are the minimum requirements for Model Year 2013 tilt frame roll-off trucks (both Truck A - Cable Hoist and Truck B - Hook Arm Lift, unless otherwise indicated) that will be used in combination with the County's existing roll-off containers. These units will be predominately operated on paved roads but are required to unload at landfill sites. All units shall be equipped with the manufacturer's standard equipment and be constructed using components recommended by their manufacturers for this application as well as meeting the following supplemental requirements.

- A. The trucks shall be designed to accommodate the County's existing 40 cubic yard containers. These containers are 22 feet in length.
- B. It is a requirement of this solicitation that the same systems as currently used with containers, mounts, covers, mechanisms, supports, etc., shall be furnished "ready to use". Bidders are encouraged to thoroughly inspect and become familiar with the systems being used.

3.2 OPERATION:

The County projects that each unit will accumulate about 35,000 miles per year.

3.3 CHASSIS:

GVWR minimum of 58,520 pounds.

- A. Minimum frame R.B.M. of 2,700,000 pounds.
- B. WB (wheelbase) - no greater than 216 inches.
- C. Curb to curb turning circle no greater than 83 feet.
- D. CT (cab to trunnion) - greater than 170 inches.
- E. AF (aft of frame) – stipulate your dimension in the chart.
- F. Must be extended at the front to accommodate a front mounted pump. The extended area at the top of the bumper shall be covered with 1/4" plate or expanded metal for safety.

3.4 CAB:

Peterbilt 320, Autocar Xpeditor, American LaFrance Condor or other LCF type design meeting chassis requirement in Section 3.3 above and subsequent specifications below. All trucks shall be equipped with manufacturer's OEM air-conditioning and heating systems and the following supplemental requirements:

- 1. A. Bostrom T905 mid-back air suspension driver's seat or Sears equal or other equal product and the manufacturer's standard passenger seat, with OEM installed seat belts.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

- B. Wide view type windshield with tinted safety glass all around.
- C. The cab shall be insulated against heat, cold and noise and have arm rests, a dome light, sun visors, a map compartment, AM-FM radio, two separately fused power points, a J-port not shared with any other electronic functions, rubber flooring, and non-skid rubber floor mats.
2. 6" X 16" stainless steel mirrors and 8" spot mirrors mounted on the left and right sides of the cab and exterior grab-handles. Bidders which offer mirror combinations with supports built into the cab body that perform the same functions are acceptable. Final locations of all mirrors shall be subject to County approval.
 3. Scale reading cab instrumentation, which includes an ammeter or voltmeter, speedometer with odometer, tachometer, Hobbs hour meter, oil-pressure, water temp, fuel, transmission temperature and air-pressure gauge, with a visual alert indicator and an audible alarm, are required. Where truck manufacturer or engine electronics include these functions in dashboard displays those displays shall be acceptable.
 4. Fiamm or Hadley 133 db single or dual trumpet single base or its equivalent shall be furnished. The final horn location is subject to approval by the County. Final horn location shall be approved by the County.
 5. Tilt and telescope steering column. Tinted glass on all windows, including windshield.
 6. Exterior grab handles, installed on both sides.
 7. A 5-pound (minimum), ANSI/U.L. approved, A B C rated dry chemical fire extinguisher shall be mounted on the floor next to the driver's seat. The fire extinguisher shall be easily accessible by opening the driver's side door. The fire extinguisher shall be tested to ANSI/UL 711 and ANSI/UL 299 marine type U.S.C.G. standards.

3.5 LIGHTS & REFLECTORS:

Lights and reflectors shall meet F.M.V.S.S. and Florida D.O.T regulations. LED lighting shall be used wherever possible.

3.6 COOLING SYSTEM:

Maximum capacity cooling system filled with extended life coolant and equipped with the recommended coolant filter or supplemental additive system.

3.7 ENGINE:

Engine shall be a Cummins ISX11.9 310/320V/320Rhp with 1150 foot pounds of torque, corresponding to Allison file 2-1509, or alternate listed below, "No Substitution". If not provided by engine electronics, an automatic safety device shall be installed and adjusted to prevent engine damage in case of oil pressure failure, cooling system overheating or low coolant level, by stopping (not de-rating) the engine. This system shall include a brief duration emergency override for safety purposes. Additional requirements are listed below:

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

1. Fuel filtration as recommended by the engine's manufacturer.
2. Webb 710 or 712 non-heated fuel/water separator, if available, or a Davco 382 Fuel-Pro or Fleetguard #FS1201."No Substitution"
3. Air filter with dash mounted air restriction indicator.
4. Electronic fly by wire accelerator control.
5. The awarded Bidder shall furnish a frame mounted skid plate to protect the engine and transmission fabricated from 3/16" steel plate. The skid plate design shall provide maximum ground clearance without restricting engine access or cooling and be a bolt on/off type. The skid plate shall provide access to any filtration or drains it restricts access to. All designs and mountings shall be subject to review, approval or change by the County's Fleet Management Division.
6. Puradyn PFT40 oil filter installed in a location mutually agreed.

NOTE 1: All generic filters used for liquids and fluids shall be the spin-on type and all lubricants shall be synthetic where recommended by the component's manufacturer in this application. NO SUBSTITUTION

NOTE 2: Cummins as used in this specification shall be understood to include Paccar branded Cummins manufactured engines.

3.8 TRANSMISSION:

Allison 4500 RDS with TC521 converter and Allison recommended S1 2100 RPM shift calibration, no torque limiting, in six (6) forward speed configuration with an external cooler and Allison push button selector or equal mounted either in the dashboard or another mutually agreed location which shall not interfere with the operator's hands or feet. All transmission mountings shall be in accordance with all transmission and truck manufacturer's recommendations and the lowest point of the transmission and attendant lines shall not be below the lowest point of the rear axle housing and shall be engineered for maximum ground clearance. The transmission oil cooler shall enable dissipation of the proper B.T.U.'s for extended function at maximum torque stop and go conditions.

3.9 FRONT AXLE AND SUSPENSION:

The front axle and suspension shall be rated with a minimum capacity of no less than 18,000/20,000 lbs. as recommended by the truck's manufacturer for this application and weight loading with 10 stud drums and non-aluminum hubs.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

3.10 REAR AXLE AND SUSPENSION:

The rear axle and suspension shall be a Hendrickson Haulmaxx rubber rear suspension with shock absorbers and a rated minimum capacity of 46,000 lbs. as recommended by the manufacturer for landfill applications with 10 stud drums and non-aluminum hubs.

1. Power divider – A driver controlled power divider affecting all axles shall be supplied with a dash mounted visual indicator and audible alarm to alert the operator when engaged.

3.11 WHEELS AND TIRES: NO SUBSTITUTION:

Accuride, Bud or Dayton steel 10 hole 9.0" wide wheels with Goodyear G289WHA or current equivalent model 315/80 R22.5 tires at all positions. Front wheel offsets shall be selected to provide maximum turning cramp angle on the axle used within the wheel width recommendations of the tire manufacturer.

3.12 FUEL TANK(S):

One step type all steel tank or all aluminum tank with a capacity no less than 100 gallons configured and selected to provide maximum ground clearance shall be mounted on the driver's side. The tank design must allow access to replacement of the fuel sender without removing the fuel tank.

3.13 EXHAUST:

Vertical to a height of 12' 10" with a tolerance of + 0"/-2" from ground level with an elbow at the top of the stack and a stainless steel or aluminum protective exhaust guard installed to prevent burns or injury to anyone entering the cab.

3.14 ELECTRICAL:

A twelve (12) volt system with no less than a 140-ampere alternator and 1800 CCA batteries. All copper wiring with each wiring circuit protected by a resettable circuit breaker having easy access. Two power points on a separately fused 30 amp circuit in addition to a J Port which may not be shared with any other electrical or electronic components, and must be located in the cab with convenient access. The J port must have its own circuit breaker.

1. A quick connect battery jumper connection shall be provided at a location near the battery box, which shall be finalized at the pre-construction conference.
2. An appropriately rated and sized battery disconnect switch is to be provided. The switch is to be wired into the outer cab marker lights which are to illuminate when the switch is in the "on" position.
3. The battery box top must be on a tether to prevent loss or theft.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

3.15 LINES, FITTINGS & WIRING:

All air, hydraulic, cooling and transmission lines shall be located and secured or clamped/anchored in the chassis. Should the chassis design offered prohibit this, they shall be securely mounted above the centerline of the axles. All pressure side hydraulic hoses that could "spray around" in case of a hose rupture shall be encased in a protective sheath, to prevent such occurrence.

As-built schematics for electrical, air and hydraulic systems shall be furnished with the equipment order of each equipment type. All subsequent deliveries of that equipment type under this contract shall be built to match any and all changes, requiring a new set of revised schematics.

3.16 FLAPS:

The flaps shall be appropriately mounted regulation size anti-sail flaps suitable for use in conjunction with mud flaps mounted front and rear of the rear tandems, plain black flap with no lettering or advertising.

3.17 TOW HOOK:

Both front and rear mounted manufacturer's recommended hook(s) or pin(s) appropriate for moving or towing the vehicle.

3.18 DRIVELINE:

Ratings and capacities as recommended by the manufacturer for the application and capacities intended with a 5.86 final drive ratio for the Cummins engine/transmission power package or a 5.57 ratio "No Substitution".

3.19 BRAKE SYSTEMS:

The brake systems shall be a "S" Cam drum Based system with all wheel ABS meeting Federal Motor Vehicle Safety Standards; Air Brake Systems; Final Rule, 74 Fed Reg. 37122 (July 27, 2009) (amending 49 C.F.R. 571.121 or the most current revision of the rule.

1. Front Axle - 16.5 X 7 brake linings as recommended for the axle selected with appropriately rated and sized brake chambers.
2. Rear Axle – 16.5 X 8.62 brake linings recommended for the axle selected with appropriately rated and sized spring set brake chambers on both rear axles.
3. Bendix "No Substitution" AD-IS or AD-IP air dryer and minimum 15 CFM compressor.
4. A Bendix® Puraguard QC Oil Coalescing filter down stream of the air dryer.
5. Maximum capacity air reservoir(s) equipped with automatic draining capability and pull cord drain valves conveniently located.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

3.20 TRUCK A. CABLE HOIST:

Must have a rated capacity no less than 60,000 pounds equipped as follows:

1. Hoist frame shall be designed and constructed to work with Miami-Dade County containers and withstand 60,000 pound loads. The hoist manufacturer must supply a 5 year warranty on the frame.
2. Hoist frame length shall be 23' 5" overall.
3. The front stop plates shall be fabricated from 1-1/2" steel.
4. There shall be four (4) outside rollers on each side that are 4" O.D. X 4"long.
5. Rear frame roller shall be standard for the model bid with seals and grease fittings.
6. Container securement must meet or exceed requirements of Federal Standards 49 CFR §393.102 for cargo securement devices and systems and ANSI Z245.1-2008 Section 7.3.4. Methodology may be subject to Miami-Dade County approval at the pre-construction conference.
7. Hydraulic cable drive cylinder or cylinders must be capable of maintaining no less than 60,000 pounds of cable pull force.
8. The hoist cylinders shall be of double configuration.
9. All cylinder shafts shall be chrome plated.
10. A 35 ton breaking strength cable with a 7/8" diameter and a 6 X 25 wire center is required.
11. All rollers and moving parts shall have grease fittings.
12. The vehicle's body shall be supplied with a an appropriately rated and sized Groeneveld auto lube system that services all recommended body grease points by dispensing the recommended rates and amounts of grease at all recommended locations.

3.21 TRUCK B. HOOK ARM LIFT:

A minimum rated capacity of 60,000 pounds designed to accommodate 18' to 22' long 40 cubic yard capacity containers. The unit must be designed and equipped as follows:

1. Required operational cycle times:
 - a. Extended dump in under 60 seconds.
 - b. Retract dump in under 45 seconds.
 - c. Extend or retract jib in under 5 seconds.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

2. Positive lock mechanism for dump cycles and a raised dump angle must be able to achieve 50 degrees and has compatibility with existing equipment and conditions.
3. Pickup hook must be replaceable and manufactured from no less than T-1 steel, minimum yield 110,000#.
4. All cylinder ends shall be equipped with hardened steel bushings.
5. All cylinder shafts shall be chrome plated.
6. All rollers and moving parts shall have grease fittings
7. All pivot points shall be equipped with hardened steel bushings and grease fittings.
8. The jib boom shall have polymer replaceable wear pads or an equal approved by the County at the pre-construction conference.
9. The vehicle shall be supplied with an appropriately rated and sized Groeneveld auto lube system that services all recommended body grease points by dispensing the recommended rates and amounts of grease at all recommended locations.

3.22 HYDRAULIC PUMP:

NO SUBSTITUTION

1. The pump shall be a Parker P-50.
2. The front pump shall be directly connected to the engines crank shaft without use of a clutch.
3. The pump drive shaft u-joints shall have grease fittings on the end caps and must be in alignment.
4. The pump shall be controlled by engine electronics via dash mounted controls.
5. The pump shall be set to provide maximum safe operating pressure at the lowest possible engine RPM.
6. The pump must be designed to disengage at speeds over 5 MPH in forward or reverse gear. The pump is not to re-engage automatically when the vehicle's speed falls below 5 MPH. The system will need to be manually reset at the dashboard.

3.23 CONTROLS:

1. Lever type (two spool for Hoist Lift, three spool for Hook Arm) must be manually operated outside the cab and air operated inside the cab.
2. The control bank must be mounted on the left side of the chassis near the rear of the cab.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

3. The levers shall be of the self-centering type which causes the cycle to cease if they are released.
4. The levers shall also be capable of reversing the cycle at the opposite throw.
5. The levers must be clearly and permanently identified as to the operation they control.
6. A throttle control mounted outside adjacent to the hydraulic control bank is required.
7. A micro-switch controlled audible/visible alarm that actuates (to alert the operator) when the rail assembly or hook arm is not in a completely down position is required. Switch # 1BAFI-2RN18-LH manufactured by Micro-Switch is to be used NO SUBSTITUTION, with the mounting location to be established at the pre-construction conference. The transmission must be limited to 1" and reverse gears when the body is in the up position.

3.24 HYDRAULIC RESERVOIR:

1. Standard configuration shall be .125" thick all steel or .134" thick all aluminum tank with no less than a 50 gallon capacity chassis mounted on the left (driver) side. If available for the return side, include a removable magnetic strainer to remove ferrous material from the returning oil. Include a ball type valve on the suction side of the tank that can be closed to prevent the draining of the entire tank when changing the suction hose to the pump.
2. The filler port shall be a 2 inch opening with a water tight cap.
3. The reservoir must include a sight glass showing both the full and low oil mark levels.
4. All exposed hydraulic pressure hoses must be secured and shielded to prevent spraying around in case of a hose rupture.
5. The hydraulic tank must have an air breather equipped with a spin-on-filter. This shall be mounted at the top of the tank. The venting capacity must be equal to the displacement capacity of the hydraulic system.

3.25 FILTRATION:

A Pall system with a 7 micron full flow through a single cartridge with 50 GPM capability mounted in a manner that provides for convenient servicing.

3.26 RELIEF VALVE:

A Pilot type valve set to its manufacturer's recommended setting shall be provide in the system to prevent damage or rupture to the hydraulic system by any manual attempt to exceed the maximum safe pressure.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

3.27 ENGINE OVERSPEED:

The engine overspeed must be performed by engine electronics. This unit is to be pre-set by the hoist or hook manufacturer to work in conjunction with the hydraulic pump and required flows. NO SUBSTITUTION

3.28 NET COVER:

Donovan Quick flip hydraulic powered unit or equal hydraulically operated cover mechanism must be included that is:

1. Capable of being operated from in or outside the cab.
2. Elevator type accommodating 20 to 40-yard capacity containers.
3. Is manufactured from 16-ounce nylon coated Neoprene net.

3.29 BACK-UP ALARM:

1. Alarm must be Velvac, Preco or other equal self-adjusting volume type, meeting current SAE loudness standards.
2. The alarm shall activate when the vehicle transmission selector is placed in the reverse position.
3. The alarm shall be connected to the back-up light circuitry and produce a clear intermittent sound conforming to applicable OSHA and SAE standards.

3.30 PAINT AND RUSTPROOFING:

The entire unit(s) inclusive of whatever body may be requested shall be prepared and painted Two-Tone White and Black as designated in A, B or C below. NO SUBSTITUTION.

All structural elements shall be thoroughly cleaned to remove all grease, oil and foreign matter. Weld splatter, slag, flux and rust or corrosion shall be completely removed by chipping, wire-brushing, shot blasting or sand-blasting prior to priming and painting.

PRIMER - Only the highest quality rust inhibiting primer specified for use with the designated finish coat shall be used.

FINISH COAT - Shall be smooth, hard and free from imperfections. The unit(s) shall be finished in White with the wheels in black powder coat, running boards, bumpers, hoist and frame assembly, finished in black. No outside metal surface void of paint shall be accepted.

- A. P.P.G. Durethane 750/1000 Basecoat Clear coat process shall be accepted for use on this vehicle.
- B. The Imron 6000 Basecoat Clear coat process or Imron Elite paint process shall be accepted for use on this vehicle.

SECTION 3
TECHNICAL SPECIFICATIONS

TITLE: Tilt Frame Roll Off Trucks

- C. Other primer and finish coat applications of equally high quality that may be approved by the County. Requests for approval shall be tendered pursuant to Section 2.20.2.
- D. The unit(s) shall be guaranteed against peeling cracking or oxidation for a period of three (3) years from date of acceptance.
- E. The units shall have an application of rust and corrosion protection. The warranty shall protect all underside surfaces excluding fiberglass and driveline. All closed in areas such as roof ribs, body posts, support pillars, rocker panels and all other areas subject to rusting from the inside out, that have not been treated at the time of manufacture, shall be drilled, treated and plugged as required. The awarded Bidder shall provide any periodic services required to maintain warranty coverage.

SECTION 4
BID SUBMITTAL FORM

Submit Bid To:
CLERK OF THE BOARD
Stephen P. Clark Center
111 NW 1st Street
17th Floor, Suite 202
Miami, Florida 33128-1983

OPENING: 2:00 P.M.
Wednesday
January 9, 2013



**PLEASE QUOTE PRICES F.O.B. DESTINATION, FREIGHT ALLOWED, LESS TAXES,
DELIVERED IN MIAMI-DADE COUNTY, FLORIDA.**

NOTE: Miami-Dade County is exempt from all taxes (Federal, State, Local). Bid price should be less all taxes. Tax Exemption Certificate furnished upon request.

Issued by: ISD/PM
Lourdes
Betancourt

Date Issued:
12/18/2012

This Bid Submittal Consists of
Pages **19** through **24**

Sealed bids subject to the Terms and Conditions of this Invitation to Bid and the accompanying Bid Submittal. Such other contract provisions, specifications, drawings or other data as are attached or incorporated by reference in the Bid Submittal, will be received at the office of the Clerk of the Board at the address shown above until the above stated time and date, and at that time, publicly opened for furnishing the supplies or services described in the accompanying Bid Submittal Requirement.

Title:
Tilt Frame Roll Off Trucks

A Bid Deposit in the amount of **N/A** the total amount of the bid shall accompany all bids.

A Performance Bond in the amount of **N/A** the total amount of the bid will be required upon execution of the contract by the successful bidder and Miami-Dade County.

DO NOT WRITE IN THIS SPACE	
ACCEPTED _____	HIGHER THAN LOW _____
NON-RESPONSIVE _____	NON-RESPONSIBLE _____
DATE B.C.C. _____	NO BID _____
ITEM NOS. ACCEPTED _____	
COMMODITY CODE: 070-51	
Procurement Contracting Officer:	Lourdes Betancourt

FIRM NAME _____

RETURN ONE ORIGINAL AND TWO COPIES OF BID SUBMITTAL PAGES AND AFFIDAVITS.

FAILURE TO SIGN THE BID SUBMITTAL FORM IN SECTION 4 WILL RENDER YOUR BID NON-RESPONSIVE.

**SECTION 4
BID SUBMITTAL FOR:**

FIRM NAME: _____

TRUCK A:

Description	Estimated Quantity	Price Per Truck
TRUCK A. CABLE HOIST Purchase of Model Year 2013 Tilt Frame Roll Off Truck	3 Trucks	\$ _____
Delivery: _____ days after receipt of order (not to exceed 270 days)		

	CHECKLIST	Check as Completed
1.	Attach truck manufacturer, fabricator, or approved dealer documentation per Section 2.6.1.	()
2.	Local Service Facility in Miami-Dade or Broward County per Section 2.6.2. Name of Facility: _____ Address: _____ City: _____	()
3.	Attach license in accordance with Chapter 320 of the Florida Statutes, SS320.27 per Section 2.6.3.	()
4.	Attach Dimensional Drawing Chart showing the dimensions of the projected build as well as weight charts showing the weight distribution of the vehicle both loaded and unloaded and wall to wall and curb to curb turning circle charts for the truck proposed using a standard manufacturer's front bumper.	()
5.	Is skid plate available directly from truck's manufacturer?	Circle one: Yes or No
6.	If skid plate is not available directly from the truck's manufacturer, the Bidder shall provide details and drawings of the proposed local installation (see Section 3.7).	()
7.	When an equal product is bid, the Bidder shall furnish the factory information sheets (specifications, brochures, etc.) that show the product meets or exceeds the required specifications. Manufacturer's standard information sheets, catalogues, brochures and all supporting documentation submitted must show the product meets or exceeds the required specifications. Bids that are submitted with standard product literature which offer technical data or product descriptions indicating the item or product bid does not meet the required specifications must be accompanied by a letter, on the Bidder's company stationary, identifying those differences and describing how compliance with the required specifications is to be accomplished.	()

**SECTION 4
BID SUBMITTAL FOR:**

FIRM NAME: _____

TRUCK B:

Description	Estimated Quantity	Price Per Truck
TRUCK B. HOOK ARM LIFT Purchase of Model Year 2013 Tilt Frame Roll Off Truck	9 Trucks	\$ _____
Delivery: _____ days after receipt of order (not to exceed 270 days)		

	CHECKLIST	Check as Completed
1.	Attach truck manufacturer, fabricator, or approved dealer documentation per Section 2.6.1.	()
2.	Local Service Facility in Miami-Dade or Broward County per Section 2.6.2. Name of Facility: _____ Address: _____ City: _____	()
3.	Attach license in accordance with Chapter 320 of the Florida Statutes, SS320.27 per Section 2.6.3.	()
4.	Attach Dimensional Drawing Chart showing the dimensions of the projected build as well as weight charts showing the weight distribution of the vehicle both loaded and unloaded and wall to wall and curb to curb turning circle charts for the truck proposed using a standard manufacturer's front bumper.	()
5.	Is skid plate available directly from truck's manufacturer?	Circle one: Yes or No
6.	If skid plate is not available directly from the truck's manufacturer, the Bidder shall provide details and drawings of the proposed local installation (see Section 3.7).	()
7.	When an equal product is bid, the Bidder shall furnish the factory information sheets (specifications, brochures, etc.) that show the product meets or exceeds the required specifications. Manufacturer's standard information sheets, catalogues, brochures and all supporting documentation submitted must show the product meets or exceeds the required specifications. Bids that are submitted with standard product literature which offer technical data or product descriptions indicating the item or product bid does not meet the required specifications must be accompanied by a letter, on the Bidder's company stationary, identifying those differences and describing how compliance with the required specifications is to be accomplished.	()

SECTION 4
BID SUBMITTAL FOR:
Tilt Frame Roll Off Trucks

ACKNOWLEDGEMENT OF ADDENDA

INSTRUCTIONS: COMPLETE PART I OR PART II, WHICHEVER APPLIES

PART I:

LIST BELOW THE DATES OF ISSUE FOR EACH ADDENDUM RECEIVED IN CONNECTION WITH THIS BID

Addendum #1, Dated _____

Addendum #2, Dated _____

Addendum #3, Dated _____

Addendum #4, Dated _____

Addendum #5, Dated _____

Addendum #6, Dated _____

Addendum #7, Dated _____

Addendum #8, Dated _____

PART II:

NO ADDENDUM WAS RECEIVED IN CONNECTION WITH THIS BID

FIRM NAME: _____

AUTHORIZED SIGNATURE: _____

DATE: _____

TITLE OF OFFICER: _____



Bid Title: Tilt Frame Roll Off Trucks

By signing this Bid Submittal Form the Bidder certifies that it satisfies all legal requirements (as an entity) to do business with the County, including all Conflict of Interest and Code of Ethics provisions in Section 2-11 of the Miami-Dade County Code. Any County employee or member of his or her immediate family seeking to contract with the County shall seek a conflict of interest opinion from the Miami-Dade County Ethics Commission prior to submittal of a Bid response or application of any type to contract with the County by the employee or his or her immediate family and file a copy of that request for opinion and any opinion or waiver from the Board of County Commissioners with the Clerk of the Board. The affected employee shall file with the Clerk of the Board a statement in a form satisfactory to the Clerk disclosing the employee's interest or the interest of his or her immediate family in the proposed contract and the nature of the intended contract at the same time as or before submitting a Bid, response, or application of any type to contract with the County. Also a copy of the request for a conflict of interest opinion from the Ethics Commission and any corresponding opinion, or any waiver issued by the Board of County Commissioners, must be submitted with the response to the solicitation.

In accordance with Sec. 2-11.1(s) of the County Code as amended, prior to conducting any lobbying **regarding this solicitation, the Bidder must file the appropriate form with the Clerk of the Board stating that a particular lobbyist is authorized to represent the Bidder.** Failure to file the appropriate form in relation to each solicitation may be considered as evidence that the Bidder is not a responsible contractor.

The Bidder confirms that this Bid is made without prior understanding, agreement, or connection with any corporation, firm, or person submitting a Bid for the same goods and/or services and in all respects is without collusion, and that the Bidder will accept any resultant award. Further, the undersigned acknowledges that award of a contract is contingent upon vendor registration. Failure to register as a vendor within the specified time may result in your firm not being considered for award.

Pursuant to Miami-Dade County Ordinance 94-34, any individual, corporation, partnership, joint venture or other legal entity having an officer, director, or executive who has been convicted of a felony during the past ten (10) years shall disclose this information at the time of bid or proposal submission.

Place a check mark here only if bidder has such conviction to disclose.

By executing this proposal through a duly authorized representative, the proposer certifies that the proposer is not on the Scrutinized Companies with Activities in Sudan List or the Scrutinized Companies with Activities in the Iran Petroleum Energy Sector List, as those terms are used and defined in sections 287.135 and 215.473 of the Florida Statutes. In the event that the proposer is unable to provide such certification but still seeks to be considered for award of this solicitation, the proposer shall execute the proposal through a duly authorized representative and shall also initial this space: _____. In such event, the proposer shall furnish together with its proposal a duly executed written explanation of the facts supporting any exception to the requirement for certification that it claims under Section 287.135 of the Florida Statutes. The proposer agrees to cooperate fully with the County in any investigation undertaken by the County to determine whether the claimed exception would be applicable. The County shall have the right to terminate any contract resulting from this solicitation for default if the proposer is found to have submitted a false certification or to have been placed on the Scrutinized Companies for Activities in Sudan List or the Scrutinized Companies with Activities in the Iran Petroleum Energy Sector List.

LOCAL PREFERENCE CERTIFICATION: For the purpose of this certification, a "local business" is a business located within the limits of Miami-Dade County (or Broward County in accordance with the Interlocal Agreement between the two counties) that conforms with the provisions of Section 1.10 of the General Terms and Conditions of this solicitation and contributes to the economic development of the community in a verifiable and measurable way. This may include, but not be limited to, the retention and expansion of employment opportunities and the support and increase to the County's tax base.

Place a check mark here only if affirming bidder meets requirements for Local Preference. Failure to complete this certification at this time (by checking the box above) may render the vendor ineligible for Local Preference.

LOCALLY-HEADQUARTERED BUSINESS CERTIFICATION: For the purpose of this certification, a "locally-headquartered business" is a Local Business whose "principal place of business" is in Miami-Dade County, as defined in Section 1.10 of the General Terms and Conditions of this solicitation.

Place a check mark here only if affirming bidder meets requirements for the Locally-Headquartered Preference (LHP). Failure to complete this certification at this time (by checking the box above) may render the vendor ineligible for the LHP. The address of the locally-headquartered office is _____.



LOCAL CERTIFIED SERVICE-DISABLED VETERAN BUSINESS ENTERPRISE CERTIFICATION: A Local Certified Service-Disabled Veteran Business Enterprise is a firm that is (a) a local business pursuant to Section 2-8.5 of the Code of Miami-Dade County and (b) prior to bid submission is certified by the State of Florida Department of Management Services as a service-disabled veteran business enterprise pursuant to Section 295.187 of the Florida Statutes.

Place a check mark here only if affirming bidder is a Local Certified Service-Disabled Veteran Business Enterprise. A copy of the certification must be submitted with this proposal.

COUNTY USER ACCESS PROGRAM (UAP): Joint purchase and entity revenue sharing program

For the County's information, the bidder is requested to indicate, at 'A' and 'B' below, its general interest in participating in the Joint Purchase Program of the County User Access Program (UAP) described in Section 2.21 of this contract solicitation, if that section is present in this solicitation document. Bidder participation in the Joint Purchase portion of the UAP is voluntary, and the bidder's expression of general interest at 'A' and 'B' below is for the County's information only and shall not be binding on the bidder.

A. If awarded this County contract, would you be interest in participating in the Joint Purchase portion of the UAP with respect to other governmental, quasi-governmental or not-for-profit entities located within the geographical boundaries of Miami-Dade County?

Yes _____ No _____

B. If awarded this County contract, would you be interested in participating in the Joint Purchase portion of the UAP with respect to other governmental, quasi-governmental or not-for-profit entities located outside the geographical boundaries of Miami-Dade County?

Yes _____ No _____

Firm Name: _____

Street Address: _____

Mailing Address (if different): _____

Telephone No.: _____ Fax No.: _____

Email Address: _____ FEIN No. _/_- _/_/_/_/_/_/_

Prompt Payment Terms: ____% ____ days net ____ days (Please see paragraph 1.2 H of General Terms and Conditions)

Signature: _____ (Signature of authorized agent)

*"By signing this document the bidder agrees to all Terms and Conditions of this Solicitation and the resulting Contract."

Print Name: _____ Title: _____

THE EXECUTION OF THIS FORM CONSTITUTES THE UNEQUIVOCAL OFFER OF PROPOSER TO BE BOUND BY THE TERMS OF ITS PROPOSAL. FAILURE TO SIGN THIS SOLICITATION WHERE INDICATED ABOVE BY AN AUTHORIZED REPRESENTATIVE SHALL RENDER THE PROPOSAL NON-RESPONSIVE. THE COUNTY MAY, HOWEVER, IN ITS SOLE DISCRETION, ACCEPT ANY PROPOSAL THAT INCLUDES AN EXECUTED DOCUMENT WHICH UNEQUIVOCALLY BINDS THE PROPOSER TO THE TERMS OF ITS OFFER.



APPENDIX

AFFIDAVITS FORMAL BIDS



Miami-Dade County
Internal Services Department
Procurement Management Division
Affirmation of Vendor Affidavits

In accordance with Ordinance 07-143 amending Section 2-8.1 of the Code of Miami-Dade County, effective June 1, 2008, vendors are required to complete a new Vendor Registration Package, including a Uniform Affidavit Packet (Vendor Affidavits Form), before being awarded a new contract. The undersigned affirms that the Vendor Affidavits Form submitted with the Vendor Registration Package is current, complete and accurate for each affidavit listed below.

Contract No. : _____ Federal Employer Identification Number (FEIN): _____

Contract Title: _____

Affidavits and Legislation/ Governing Body

1.	Miami-Dade County Ownership Disclosure <i>Sec. 2-8.1 of the County Code</i>	6.	Miami-Dade County Vendor Obligation to County <i>Section 2-8.1 of the County Code</i>
2.	Miami-Dade County Employment Disclosure <i>County Ordinance No. 90-133, amending Section 2-8-1(d)(2) of the County Code</i>	7.	Miami-Dade County Code of Business Ethics <i>Article 1, Section 2-8.1(f) and 2-11(b)(1) of the County Code through (d) and (9) of the County Code and County Ordinance No 00-1 amending Section 2-11.1(c) of the County Code</i>
3.	Miami-Dade County Employment Drug-free Workplace Certification <i>Section 2-8.1.2(b) of the County Code</i>	8.	Miami-Dade County Family Leave <i>Article V of Chapter 11 of the County Code</i>
4.	Miami-Dade County Disability Non-Discrimination <i>Article 1, Section 2-8.1.5 Resolution R182-00 amending R-385-95</i>	9.	Miami-Dade County Living Wage <i>Section 2-8.9 of the County Code</i>
5.	Miami-Dade County Debarment Disclosure <i>Section 10.38 of the County Code</i>	10.	Miami-Dade County Domestic Leave and Reporting <i>Article 8, Section 11A-60 11A-67 of the County Code</i>

Printed Name of Affiant

Printed Title of Affiant

Signature of Affiant

Name of Firm

Date

Address of Firm

State

Zip Code

Notary Public Information

Notary Public – State of _____ County of _____

Subscribed and sworn to (or affirmed) before me this _____ day of, _____ 20 _____

by _____ He or she is personally known to me or has produced identification

Type of identification produced _____

Signature of Notary Public

Serial Number

Print or Stamp of Notary Public

Expiration Date

Notary Public Seal

SUBCONTRACTOR/SUPPLIER LISTING
 (Miami-Dade County Code Sections 2-8.1, 2-8.8 and 10-34)

Firm Name of Prime Contractor/Respondent _____ FEIN # _____
 Project/Contract Number _____

In accordance with Sections 2-8.1, 2-8.8 and 10-34 of the Miami-Dade County Code, this form must be submitted as a condition of award by all bidders/respondents on County contracts for purchase of supplies, materials or services, including professional services which involve expenditures of \$100,000 or more, and all bid/responses on County or Public Health Trust construction contracts which involve expenditures of \$100,000 or more. The bidder/respondent who is awarded this bid/contract shall not change or substitute bid for subcontractor or direct supplier or the portions of the contract work to be performed or materials to be supplied from those identified, except upon written approval of the County. The bidder/respondent should enter the word "NONE" under the appropriate heading of this form if no subcontractors or suppliers will be used on the contract.

In accordance with Ordinance No. 11-02, an entity contracting with the County shall report the race, gender and ethnic origin of the owners and employees of all bid for subcontractors/suppliers. In the event that the successful bidder demonstrates to the County prior to award that the race, gender, and ethnic information is not reasonably available at that time, the successful bidder shall be obligated to make diligent efforts to obtain that information and provide the same to the County not later than ten (10) days after it becomes available and, in any event, prior to final payment under the contract.
 (Please duplicate this form if additional space is needed.)

Business Name and Address of First Tier Subcontractor/ Subcontractor	Principal Owner	Scope of Work to be Performed by Subcontractor/ Subcontractor	Principal Owner (Enter the number of male and female owners by race/ethnicity)							Employee(s) (Enter the number of male and female employees and the number of employees by race/ethnicity)							
			Gender		Race/Ethnicity					Gender		Race/Ethnicity					
			M	F	White	Black	Hispanic	Asian/Pacific Islander	Native American/Alaskan	Other	M	F	White	Black	Hispanic	Asian/Pacific Islander	Native American/Alaskan

Mark here if race, gender and ethnicity information is not available and will be provided at a later date. This data may be submitted to Community/Local development or on-line to the Small Business Development Division of the Regulatory and Economic Resources Department at <http://new.miamidade.gov/business/business-development.asp>.

I certify that the representations contained in this Subcontractor/Supplier listing are to the best of my knowledge true and accurate.

Signature of Bidder/Respondent _____ Print Name _____ Print Title _____ Date _____