



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

## NOTICE OF ACCEPTANCE (NOA)

**Instant Asphalt, Inc. dba. Metacrylics**  
**365 Obata Court**  
**Gilroy, CA 95020**

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: **Metacrylics Extreme Weather White**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No. 16-0125.03 and consists of pages 1 through 3.

The submitted documentation was reviewed by **Freddy Semino** 



NOA No.: 19-0204.02  
Expiration Date: 04/07/21  
Approval Date: 04/04/19  
Page 1 of 3

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Coatings  
**Material:** Elastomeric  
**Maximum Design Pressure:** N/A  
**Fire Classification:** See Limitation #1

### SCOPE:

This approves “Metacrylics Extreme Weather White” as a roof maintenance coating manufactured by Instant Asphalt, Inc. dba Metacrylics, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone.

### EVIDENCE SUBMITTED:

| <u>Test Agency</u>                      | <u>Test Identifier</u> | <u>Test Name/Report</u> | <u>Date</u> |
|---|------------------------|-------------------------|-------------|
| PRI Construction Materials Technologies | MIA-004-02-01          | ASTM D 6083             | 12/28/10    |
|   | MIA-011-02-01          | ASTM D 6083             | 01/11/2019  |

### MANUFACTURING LOCATION:

- Gilroy, CA.

## PHYSICAL PROPERTIES OF COMPONENTS

**Trade names:** Metacrylics Extreme Weather White  
**Thickness:** See Table Below  
**Specifications:** ASTM D 6083  
**Description:** A white water-based acrylic elastomeric maintenance coating membrane applied at an application rate as listed in the table below;  
**Container Size:** 5 gallon pails; 55 gallons steel drums; 275 gallons IBC totes.  
**Note all precautions on container.**  
**Systems Approvals:** Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

| Approved Substrates            | Primer             |                                 | Top Coat              |                                 |
|--------------------------------|--------------------|---------------------------------|-----------------------|---------------------------------|
|                                | Product            | Rate (gal/100 ft <sup>2</sup> ) | Product               | Rate (gal/100 ft <sup>2</sup> ) |
| Galvanized Metal               | Black Primer       | 1                               | Extreme Weather White | 2.40                            |
| SBS Modified Bitumen - Granule | Roof & Tile Primer | 1                               | Extreme Weather White | 2.40                            |
| Polyurethane Foam              | Roof & Tile Primer | 1                               | Extreme Weather White | 2.40                            |



| Approved Substrates<br>(continued from page 2) | Primer              |                                    | Top Coat              |                                 |
|--|---------------------|------------------------------------|-----------------------|---------------------------------|
|  | Product             | Rate<br>(gal/100 ft <sup>2</sup> ) | Product               | Rate (gal/100 ft <sup>2</sup> ) |
| Plywood  | Direct to Substrate |                                    | Extreme Weather White | 3                               |
| Concrete                                       | Direct to Substrate |                                    | Extreme Weather White | 3                               |
| Aged PVC Single Ply                            | Roof & Tile Primer  | 0.3<br>(gal/100 ft <sup>2</sup> )  | Extreme Weather White | 3                               |

**LIMITATIONS:**

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
2. Metacrylics Extreme Weather White shall not be applied in inclement weather conditions.
3. Metacrylics Extreme Weather White shall not be applied over asphaltic shingles, metal shingles, fiber-cement shingles, quarry slate, cement or clay roofing tile, or wood shingles or shakes.
4. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
5. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



6. Metacrylics Extreme Weather White shall only be applied by a factory trained and certified applicators.
7. Metacrylics Extreme Weather White shall be applied in accordance with manufacturer’s published application instructions.
8. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
9. The use of a reinforcing fabric in a maintenance coating is only to enhance the coatings ability to deliver efficient and long term performance through the protection of the underlying roof system and in this particular use does not become a roof system itself.
10. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance

**END OF THIS ACCEPTANCE**

