



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599

[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

## NOTICE OF ACCEPTANCE (NOA)

**Tremco CPG, Inc.**  
**3735 Green Road**  
**Beachwood, OH 44122**

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami-Dade County and other areas, where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: Tremco CPG Roofing Membranes and Accessories

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA# 21-0420.20 and consists of pages 1 through 3.  
The submitted documentation was reviewed by Alex Tigera.



NOA-No.: 22-0228.13  
Expiration Date: 07/15/26  
Approval Date: 09/22/22  
Page 1 of 3

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Roofing Membranes and Accessories  
**Material:** Asphalt and Modified Bitumen Roofing Membranes and accessories

<b><u>Product</u></b>	<b><u>Dimensions</u></b>	<b><u>Test Specifications</u></b>	<b><u>Product Description</u></b>
POWERply Standard FR <i>Manufacturing location: #1</i>	36" x 38' Roll	D6163, Type I, Grade G	Fire Rated Granule Surfaced Modified Bitumen Membrane
POWERply Heavy Duty Base Sheet <i>Manufacturing location: #1</i>	36" x 36' Roll	D6163, Type III, Grade S	Smooth Surfaced, Fiberglass Bilaminate Reinforced Modified Bitumen Membrane
THERMglass Type IV <i>Manufacturing location: #2</i>	36" x 180' Roll	D2178, Type VI	High Performance Fiberglass Type IV Ply Sheet
THERMglass Premium VI <i>Manufacturing location: #2</i>	36" x 180' Roll	D2178, Type VI	High Performance Fiberglass Type VI Ply Sheet
POWERply Endure 100 FR <i>Manufacturing location: #1</i>	36" x 38' Roll	ASTM D6163	Fire Rated, Granule Surfaced, High Tensile Fiberglass Reinforced SBS Modified Bitumen Membrane
POWERply Endure 100 Smooth <i>Manufacturing location: #1</i>	36" x 56'8" Roll	ASTM D6163	Smooth Surfaced, High Tensile, Fiberglass Reinforced SBS Modified Bitumen Membrane
POWERply Endure 200 FR <i>Manufacturing location: #1</i>	39-3/8" x 34'5"	ASTM D6164	Fire Rated, Granule Surfaced, Polyester Reinforced SBS Modified Bitumen Membrane
POWERply Endure 200 Smooth <i>Manufacturing location: #1</i>	39-3/8" x 51'6"	ASTM D6164	Smooth Surface Polyester Reinforced SBS Modified Bitumen Membrane
POWERply Endure 300 FR <i>Manufacturing location: #1</i>	39-3/8" x 34'5"	ASTM D6162	Fire Rated, Granule Surfaced, Reinforced SBS Modified Bitumen Membrane
POWERply Endure 320 FR <i>Manufacturing location: #1</i>	39-3/8" x 34'5"	ASTM D6162	Fire Rated, Granule Surfaced, Reinforced SBS Modified Bitumen Membrane
POWERply Endure 320 Smooth <i>Manufacturing location: #1</i>	39-3/8" x 51'6"	ASTM D6162	Smooth Surfaced, Reinforced SBS Modified Bitumen Membrane
POWERply Endure 300 Smooth <i>Manufacturing location: #1</i>	39-3/8" x 51'6"	ASTM D6162	Smooth Surfaced, Reinforced SBS Modified Bitumen Membrane

## MANUFACTURING LOCATIONS:

1. Cleveland, OH
2. Oklahoma City, OK



## EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
NEMO ETC LLC	ASTM D6163	TRM-SC16860.04.18	4/27/2018
	ASTM D2178	4-TRM-18-002.04.18-2	4/27/2018
	ASTM D6162	4q-TRM-19-SSMBB-01.A	2/7/2020
	ASTM D6162	4q-TRM-19-SSMBB-01.B	10/24/2019
	ASTM D6162	4q-TRM-19-SSMBB-01.C	10/24/2019
	ASTM D6162	4q-TRM-19-SSMBB-01.D	10/24/2019
	ASTM D6163	4q-TRM-19-SSMBB-01.E	10/24/2019
	ASTM D6163	4q-TRM-19-SSMBB-01.F	10/24/2019
	ASTM D6164	4q-TRM-19-SSMBB-01.G	10/24/2019
	ASTM D6164	4q-TRM-19-SSMBB-01.H	10/24/2019
	ASTM D6163	4q-TRM-19-SSMBB-03.C	04/22/20

## LABELING:

All membranes and accessories or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



## LIMITATIONS:

1. Fire classification is not part of this acceptance. Refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Tremco CPG Roofing Membranes are designed for use as specified within approved roofing system NOA assemblies.
3. This acceptance establishes the required physical properties testing and traceability of roofing membrane and accessory components listed in approved roofing applications. Minimum deck requirements shall be in compliance with applicable building code. Tremco CPG Roofing Membranes shall be installed in strict compliance with applicable Building Codes, Product Approvals and Manufacturers' specifications and guidelines.
4. Change in materials or manufacturing process or location of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
5. Tremco CPG Roofing Membranes may be used with any approved Roof Assembly Notice of Acceptance listing Tremco CPG Roofing Membranes as a component part of an assembly in the Notice of Acceptance. If Tremco CPG Roofing Membranes is not listed, a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval, provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
6. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

## END OF THIS ACCEPTANCE

