



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786)315-2590 F (786) 31525-99

www.miamidade.gov/economy

Simon Roofing & Sheet Metal Corp. dba SR Products
70 Karago Ave.
Youngstown, OH 44512

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: SR Products BUR and Modified Bitumen Roofing Membranes and Accessories

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 5

The submitted documentation was reviewed by Jorge L. Acebo.

10/02/25



NOA No.: 25-0611.05
Expiration Date: 08/04/27
Approval Date: 10/02/25
Page 1 of 5

ROOFING COMPONENT APPROVAL

<u>Category:</u>	Roofing
<u>Sub-Category:</u>	Roofing Membranes and Accessories
<u>Material:</u>	BUR and Modified Bitumen Roofing

SCOPE:

This approves **SR Products BUR and Modified Bitumen Roofing Membranes and Accessories** as roofing components, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone. Please refer to "Limitations" herein for limits of use.

PRODUCT DESCRIPTION:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
Pika Ply Base (TG) <i>Manufacturing location #1, 2</i>	39" x 49' (1.5 sq.)	ASTM D6163, Type I, Smooth	Fiberglass reinforced modified bitumen membrane covered on both sides with a plastic burn-off film. Applied by heat welding.
Pika Ply MS-4G (TG) <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6163, Type I, Granule	Fiberglass reinforced modified bitumen membrane with fire retardants, a plastic burn-off film on the bottom and mineral granules on the top. Applied by heat welding.
Premium Cap Sheet <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6163, Type I, Granule	Fiberglass reinforced modified bitumen membrane with fire retardants, sanded on the bottom and mineral granules on the top. Applied in hot asphalt, cold adhesive or ribbon stripping.
Pika Ply 2.2 (FS) <i>Manufacturing location #1</i>	39" x 49' (1.5sq.)	ASTM D6163, Type I, Smooth	Glass reinforced modified bitumen membrane with a plastic burn-off film for heat weld bonding to the top side. Applied in hot asphalt, cold adhesive or ribbon stripping.
Pika Ply SS-3G <i>Manufacturing location #1, 3</i>	39" x 33' (1sq.)	ASTM D6163, Type I, Smooth	Fiberglass reinforced modified bitumen membrane sanded on both sides. Applied in hot asphalt, cold adhesive or ribbon stripped.
Pika Ply 180 (SF) <i>Manufacturing location #1</i>	39" x 49' (1.5 sq.)	ASTM D6163, Type I, Smooth	Glass reinforced modified bitumen membrane with a plastic burn-off film on the bottom and sanded on the top. Applied by heat welding or ribbon stripping (after removal of plastic burn-off film).
Performance Ply MS FR <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type I, Granule	Non-woven polyester reinforced modified bitumen membrane with fire retardants, a sanded bottom and a mineral granules top. Applied in hot asphalt, cold applied adhesive or ribbon stripping (after removal of plastic burn-off film).
Pika Ply SS-3P <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.) 39" x 26' (¾ sq.)	ASTM D6164, Type I, Smooth	Non-woven polyester reinforced modified bitumen membrane sanded on both sides. Applied in hot asphalt, cold adhesive or ribbon stripping.



PRODUCT DESCRIPTION:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
Pika Ply 180 (S) <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type I, Smooth	Non-woven polyester reinforced modified bitumen membrane sanded on both sides. Applied in hot asphalt or cold adhesive.
Pika Ply 180 (SF) 3.5 <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type I, Smooth	Non-woven polyester reinforced modified bitumen membrane with a plastic burn-off film on the bottom and sanded on the top. Applied by heat welding or ribbon stripping (after removal of plastic burn-off film).
Pika Ply MS-4 <i>Manufacturing location #1</i>	39" x 33' (1 sq.)	ASTM D6164, Type II, Granule	Non-woven polyester reinforced modified bitumen membrane with fire retardants, a sanded bottom and a mineral granules top. Applied in hot asphalt, cold applied adhesive or ribbon stripping (after removal of plastic burn-off film).
Pika Ply SS-3P (TG) <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type I, Smooth	Non-woven polyester reinforced SBS modified bitumen membrane, both sides covered with a plastic burn-off film. Applied by heat welding or ribbon stripping (after removal of plastic burn-off film).
Pika Ply MS-4 (TG) <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type I, Granule	Non-woven polyester reinforced modified bitumen membrane with fire retardants, a plastic burn-off film on the bottom and mineral granules on the top. Applied by heat welding or ribbon stripping (after removal of plastic burn-off film).
Pika Ply 250 S (TG) <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type II, Smooth	Non-woven polyester reinforced SBS modified bitumen membrane, both sides covered with a plastic burn-off film. Applied by heat welding or ribbon stripping (after removal of plastic burn-off film).
Pika Ply 250 GR FR (TG) <i>Manufacturing location #1</i>	39" x 33' (1 sq.)	ASTM D6164, Type II, Granule	Non-woven polyester reinforced modified bitumen membrane with fire retardants, a plastic burn-off film on the bottom and mineral granules on the top. Applied by heat welding or ribbon stripping (after removal of plastic burn-off film).
Pika Ply SA Sanded <i>Manufacturing location #1, 2</i>	39" x 33' (1 sq.)	ASTM D6164, Type I, Smooth	Self-adhered, polyester reinforced membrane with a release film on the bottom and a sanded top.

MANUFACTURING LOCATIONS:

1. Wadsworth, OH
2. Gulfport, MS
3. Kansas, MO



EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
NEMO ETC, LLC.	S39970.07.12-2	ASTM D6164	07/12/12
	S43400.08.14-7-R1	ASTM D6164	08/08/14
	S43400.08.14-4-R1	ASTM D6163	08/26/14
	S43400.08.14-6	ASTM D6164	08/26/14
	S44110.08.14-5	ASTM D6164	08/29/14
	S43400.09.14-9	ASTM D6164	09/02/14
	S44110.09.14-7C	ASTM D6164	09/02/14
	S44110.01.15-4A-R3	ASTM D6164	01/12/15
	S43400.08.14-5-R1	ASTM D6163	05/03/17
	4q-SOP-19-SSMBB-01.C	ASTM D4601	03/11/19
	4q-SOP-20-SSMBB-01.A	ASTM D6163	11/05/20
	4q-SOP-20-SSMBB-01.B	ASTM D6164	11/05/20
	4q-SOP-20-SSMBB-02.A	ASTM D6164	05/04/21
	4q-SOP-21-SSMBB-01.A	ASTM D6163	05/04/21
	4q-SOP-21-SSMBB-02.A	ASTM D6162	11/11/21
	4q-SOP-20-SSMBB-01.D	ASTM D6164	12/01/21
	4q-SOP-20-SSMBB-03.A	ASTM D6164	12/01/21
	4q-SOP-SSMBB-03.B	ASTM D6163	12/01/21
	4q-SOP-20-SSMBB-03.C	ASTM D4601	12/01/21
	4q-SOP-21-SSMBB-04.A	ASTM D6163	02/08/22
	4q-SOP-21-SSMBB-04.B	ASTM D6164	04/08/22
	4q-SOP-21-SSMBB-04.C	ASTM D6164	07/01/22
	4q-SOP-22-SSMBB-02.A	ASTM D4601	12/02/22
	4q-SOP-22-SSMBB-03.C	ASTM D6164	12/09/22
	4q-SOP-22-SSMBB-03.D	ASTM D6163	12/09/22
	4q-SOP-21-SSMBB-05.A	ASTM D6162	01/01/23
	4q-SOP-22-SSMBB-04.A	ASTM D2178	01/10/23
	4q-SOP-22-SSMBB-04.B	ASTM D4897	01/16/23
	4q-SOP-22-SSMBB-03.G	ASTM D6164	02/15/23
	4q-SOP-22-SSMBB-03.E	ASTM D6164	07/31/23
	4q-SOP-22-SSMBB-03.F	ASTM D6163	07/31/23
	4q-SOP-22-SSMBB-02.B	ASTM D6163	11/01/23
	4q-SOP-22-SSMBB-02.C	ASTM D6164	11/01/23
	4q-SOP-22-SSMBB-03.A	ASTM D4601	11/01/23
	4q-SOP-22-SSMBB-03.B.R1	ASTM D6163	11/01/23
	4q-SOP-21-SSMBB-03.A.R1	ASTM D6163	12/14/23
	4q-SOP-22-SSMBB-03.H	ASTM D6298	02/29/24
	4q-SOP-22-SSMBB-03.I.R1	ASTM D6164	04/23/24
	R11436	UL 790	05/30/24
UL LLC			



LABELING:

All membranes and accessories or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. SR Products BUR, Modified Bitumen Roofing Membranes and Accessories are designed for use as specified within approved roofing system NOA assemblies.
3. This acceptance establishes the required physical properties testing and traceability of roofing membrane and accessory components listed in approved roofing applications. Minimum deck requirements shall be in compliance with applicable building code. SR Products BUR, Modified Bitumen Roofing Membranes and Accessories shall be installed in strict compliance with applicable Building Codes, Product Approvals and Manufacturers' specifications and guidelines.
4. Change in materials or manufacturing process or location of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
5. SR Products BUR, Modified Bitumen Roofing Membranes and Accessories may be used with any approved Roof Assembly Notice of Acceptance listing SR Products BUR, Modified Bitumen Roofing Membranes and Accessories as a component part of an assembly in the Notice of Acceptance. If SR Products BUR, Modified Bitumen Roofing Membranes and Accessories are not listed; a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
6. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

END OF THIS ACCEPTANCE

