



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

## NOTICE OF ACCEPTANCE (NOA)

**GAF**  
**1 Campus Drive**  
**Parsippany, NJ 07054**

**MIAMI-DADE COUNTY**  
**PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786)315-2590 F (786) 31525-99

[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: GAF Conventional Built-Up-Roof Membranes and Accessories.

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 5.

The submitted documentation was reviewed by Jorge L. Acebo.

11/06/25



NOA-No.: 25-0709.01  
Expiration Date: 11/06/30  
Approval Date: 11/06/25  
Page 1 of 5

## ROOFING COMPONENT APPROVAL

<b>Category:</b>	Roofing
<b>Sub-Category:</b>	Roofing Membranes and Accessories
<b>Material:</b>	BUR and Modified Roofing

### SCOPE:

This approves **GAF Conventional Built-Up-Roof Membranes and Accessories** as roofing components, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone. Please refer to "Limitations" herein for limits of use.

### PRODUCT DESCRIPTION:

<b><u>Product</u></b>	<b><u>Dimensions</u></b>	<b><u>Test Specifications</u></b>	<b><u>Product Description</u></b>
GAFGlas® Ply 4 <i>Manufacturing location: #1, 3</i>	39.37" (1 meter) Wide	ASTM D2178	A smooth surfaced asphaltic ply sheet reinforced with fiberglass mat.
Tri-Ply® Ply 4 <i>Manufacturing location: #1, 3</i>	39.37" (1 meter) Wide	ASTM D2178	A smooth surfaced asphaltic ply sheet reinforced with fiberglass mat.
GAFGlas® Ply 4 M <i>Manufacturing location: #4</i>	39.37" (1 meter) Wide	ASTM D2178	A smooth surfaced asphaltic ply sheet reinforced with fiberglass mat.
GAFGlas® FlexPly™ 6 <i>Manufacturing location: #1</i>	39.37" (1 meter) Wide	ASTM D2178	A smooth surfaced asphaltic ply sheet reinforced with fiberglass mat.
GAFGlas® FlexPly™ 6 5L <i>Manufacturing location: #1</i>	39.37" (1 meter) Wide	ASTM D2178	A smooth surfaced asphaltic ply sheet reinforced with fiberglass mat.
GAFGlas® FlexPly™ 6 M <i>Manufacturing location: #4</i>	39.37" (1 meter) Wide	ASTM D2178	A smooth surfaced asphaltic ply sheet reinforced with fiberglass mat.
GAFGlas® #75 Base Sheet <i>Manufacturing location: #1, 3, 4</i>	39.37" (1 meter) Wide	ASTM D4601	A smooth asphaltic base or base/ply sheet reinforced with fiberglass mat.
Tri-Ply® #75 Base Sheet <i>Manufacturing location: #1, 4</i>	39.37" (1 meter) Wide	ASTM D4601	A smooth asphaltic base or base/ply sheet reinforced with fiberglass mat.
GAFGlas® #80 Ultima™ Base Sheet <i>Manufacturing location: #1, 4</i>	39.37" (1 meter) Wide	ASTM D4601	A smooth asphaltic base or base/ply sheet reinforced with fiberglass mat.
GAFGlas® Stratavent® Eliminator™ Perforated Venting Base Sheet <i>Manufacturing location: #1, 4</i>	39.37" (1 meter) Wide	ASTM D4897	A smooth surfaced asphaltic perforated venting base sheet reinforced with fiberglass mat.
GAFGlas® Stratavent® Eliminator™ Nailable Venting Base Sheet <i>Manufacturing location: #1, 4</i>	39.37" (1 meter) Wide	ASTM D4897	A smooth surfaced asphaltic nailable venting base sheet reinforced with fiberglass mat. Bottom side surfaced with granules.



## PRODUCT DESCRIPTION: (CONTINUED)

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
GAFGlas® Mineral Surfaced Cap Sheet <i>Manufacturing location: #1, 3, 4</i>	39.37" (1 meter) Wide	ASTM D3909	A granule surfaced asphaltic cap sheet reinforced with fiberglass mat.
Tri-Ply® BUR Granule Cap Sheet <i>Manufacturing location: #1</i>	39.37" (1 meter) Wide	ASTM D3909	A granule surfaced asphaltic cap sheet reinforced with a fiberglass mat.
GAFGlas® EnergyCap™ Mineral Surface Cap Sheet <i>Manufacturing location: #2</i>	39.37" (1 meter) Wide	ASTM D3909	Smooth surfaced torch applied APP base or ply sheet reinforced with a polyester mat. The top surface is covered with an enhanced white granule surfacing.
Ruberoid® UltraClad SBS Membrane <i>Manufacturing location: #5</i>	39.37" (1 meter) Wide	ASTM D6298	Fire retardant aluminum foil-faced SBS flashing membrane.
Matrix™ 102 SBS Membrane Adhesive <i>Manufacturing location: #6</i>	3, 5 or 55 Gallons	ASTM D3019	Fiber reinforced rubberized cold-applied adhesive for modified bitumen roof systems.
Matrix™ 201 Premium SBS Flashing Cement <i>Manufacturing location: #6</i>	11 oz. Tubes Or 5 gallons	ASTM D4586	Cold applied flashing cement in SBS-modified bitumen asphalt roof systems.
Matrix™ 307 Premium Asphalt Primer <i>Manufacturing location: #6</i>	3, 5 or 55 Gallons	ASTM D41	Asphalt concrete primer used to promote adhesion of all types of asphalt-based roofing materials.
VersaShield® Fire-Resistant Roof Deck Protection <i>Manufacturing location: #7</i>	12" x 100' rolls	ASTM D226	Non-asphaltic fiberglass-based underlayment and/or fire barrier.
VersaShield® Solo™ Fire-Resistant Slip Sheet <i>Manufacturing location: #7</i>	42" roll wide, 100 ft.	ASTM D226	Non-asphaltic, fire resistant fiberglass underlayment.

## MANUFACTURING LOCATIONS:

1. Savannah, GA
2. Stockton, CA
3. Fontana, CA
4. Tuscaloosa, AL
5. Arkadelphia, AR
6. Hallandale, FL
7. Conover, NC



**EVIDENCE SUBMITTED:**

<b><u>Test Agency</u></b>	<b><u>Test Identifier</u></b>	<b><u>Test Name/Report</u></b>	<b><u>Date</u></b>
PRI Construction Materials Technologies LLC	MSA-039-02-02	ASTM D2178	09/27/17
	376T0140	ASTM D6164	08/18/21
	376T0143	ASTM D6222	08/23/21
	376T0144	ASTM D6222	08/26/21
	376T0227	ASTM D4897	12/20/21
	376T0228	ASTM D4897	12/20/21
	376T0229	ASTM D4601	12/20/21
	376T0240	ASTM D4601	12/21/21
	376T0221	ASTM D6164	01/17/22
	376T0222	ASTM D6222	01/18/22
	376T0141	ASTM D6163	01/26/22
	376T0272	ASTM D3909	02/03/22
	376T0276	ASTM D4601	02/03/22
	376T0220	ASTM D6164	03/08/22
	376T0230	ASTM D6222	03/24/22
	376T0274	ASTM D6222	05/04/22
	376T0273	ASTM D6222	05/04/22
	824T0051	ASTM D6164	06/09/22
	824T0046	ASTM D6163	06/30/22
	824T0047	ASTM D6163	06/30/22
	824T0098	ASTM D6298	03/21/23
	376T0480	ASTM D6163	02/29/24
	376T0481	ASTM D6164	02/29/24
	376T0482	ASTM D6164	02/29/24
	376T0486	ASTM D6164	04/12/24
	824T0155	ASTM D6163	04/18/24
	376T0483	ASTM D6164	07/12/24
NEMO ETC, LLC	4S-GAF-18-001.11.18	ASTM D6163	11/06/18
	4S-GAF-18-001.01.19-1	ASTM D2178	01/02/19
	4S-GAF-18-001.03.19.A-R1	ASTM D6222	03/13/19
	4Q-GAF-19-SSMBB-02.A	ASTM D6163	04/08/19
	4Q-GAF-20-SSMBB-01.A	ASTM D3909	03/04/21
	4q-GAF-21-SSMBB-01.A	ASTM D4601	09/07/21
	4q-GAF-21-SSMBB-01.B	ASTM D4897	09/07/21
	4Q-GAF-21-SSMBB-02.A	ASTM D3909	12/02/21
	4q-GAF-22-SSMBB-01.A	ASTM D6164	04/22/23
	4q-GAF-SSMBB-003.A	ASTM D6222	01/06/24
	4q-GAF-SSMBB-002.A	ASTM D6164	12/05/24
	4q-GAF-SSMBB-001.A	ASTM D6164	12/05/24
	4q-GAF-SSMBB-005.A	ASTM D3909	12/13/24
	4q-GAF-SSMBB-004.A	ASTM D6164	02/05/25
Trinity   ERD	G46160.02.15-2D-1	ASTM D6163	02/09/16
	SC10680.05.16	ASTM D6163	05/10/16
	SC13105.03.17-R1	ASTM D6164	03/23/17

## **LABELING:**

All membranes and accessories or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



## **LIMITATIONS:**

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. The GAF Conventional Built-Up-Roof Membranes and Accessories listed herein are designed for use as specified within approved roofing system NOA assemblies.
3. This acceptance establishes the required physical properties testing and traceability of roofing membrane and accessory components listed in approved roofing applications. Minimum deck requirements shall be in compliance with applicable building code. The GAF Conventional Built-Up-Roof Membranes and Accessories listed herein shall be installed in strict compliance with applicable Building Codes, Product Approvals and Manufacturers' specifications and guidelines.
4. Change in materials or manufacturing process or location of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
5. The GAF Conventional Built-Up-Roof Membranes and Accessories listed herein may be used with any approved Roof Assembly Notice of Acceptance listing the GAF Conventional Built-Up-Roof Membranes and Accessories listed herein as a component part of an assembly in the Notice of Acceptance. If the GAF Conventional Built-Up-Roof Membranes and Accessories listed herein are not listed; a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
6. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

**END OF THIS ACCEPTANCE**



NOA-No.: 25-0709.01  
Expiration Date: 11/06/30  
Approval Date: 11/06/25  
Page 5 of 5