



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

GAF
1 Campus Drive
Parsippany, NJ 07054

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786)315-2590 F (786) 31525-99

www.miamidade.gov/economy

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: GAF Modified Bitumen Roof Membranes and Accessories.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 6.

The submitted documentation was reviewed by Jorge L. Acebo.

11/06/25



NOA-No.: 25-0717.05
Expiration Date: 11/06/30
Approval Date: 11/06/25
Page 1 of 6

ROOFING COMPONENT APPROVAL

| | |
|-----------------------------|-----------------------------------|
| <u>Category:</u> | Roofing |
| <u>Sub-Category:</u> | Roofing Membranes and Accessories |
| <u>Material:</u> | BUR and Modified Roofing |

SCOPE:

This approves **GAF Modified Bitumen Roof Membranes and Accessories** as roofing components, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone. Please refer to "Limitations" herein for limits of use.

PRODUCT DESCRIPTION:

| <u>Product</u> | <u>Dimensions</u> | <u>Test Specifications</u> | <u>Product Description</u> |
|--|--------------------------|-----------------------------------|---|
| Ruberoid® HW 20 Smooth <i>Manufacturing location: #4</i> | 39.37" (1 meter) Wide | ASTM D6163 | Smooth surfaced torch applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® HW 25 Smooth <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6163 | Smooth surfaced torch applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® HW 30 Smooth <i>Manufacturing location: #4</i> | 39.37" (1 meter) Wide | ASTM D6163 | Smooth surfaced torch applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® HW 30 Granule FR <i>Manufacturing location: #4</i> | 39.37" (1 meter) Wide | ASTM D6163 | Fire retardant granule surfaced heat-welded SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® HW Smooth <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Smooth surfaced torch applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® HW Granule <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Granule surfaced torch applied SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® HW Granule FR <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Fire retardant granule surfaced heat-welded SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® HW Plus Granule <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Granule surfaced torch applied SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® HW Plus Granule FR <i>Manufacturing location: #4</i> | 39.37" (1 meter) Wide | ASTM D6164 | Fire retardant granule surfaced heat-welded SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® EnergyCap™ HW 30 Granule FR <i>Manufacturing location: #4</i> | 39.37" (1 meter) Wide | ASTM D6163 | Fire retardant granule surfaced heat-welded SBS cap sheet reinforced with a polyester mat. The top surface is covered with an enhanced white granule surfacing. |



PRODUCT DESCRIPTION: (CONTINUED)

| <u>Product</u> | <u>Dimensions</u> | <u>Test Specifications</u> | <u>Product Description</u> |
|---|--------------------------|----------------------------|---|
| Ruberoid® EnergyCap™ HW Plus Granule FR <i>Manufacturing location: #2, 4</i> | 39.37" (1 meter) Wide | ASTM D6164 | Fire retardant granule surfaced heat-welded SBS cap sheet reinforced with a polyester mat. The top surface is covered with an enhanced white granule surfacing. |
| Ruberoid® Torch Smooth <i>Manufacturing location: #1, 2, 3</i> | 39.37" (1 meter) Wide | ASTM D6222 | Smooth surfaced torch applied APP base or ply sheet reinforced with a polyester mat. |
| Tri-Ply® APP Smooth <i>Manufacturing location: #1, 2, 3</i> | 39.37" (1 meter) Wide | ASTM D6222 | Smooth surfaced torch applied APP base or ply sheet reinforced with a polyester mat. |
| Tri-Ply® APP Smooth NB <i>Manufacturing location: #7</i> | 39.37" (1 meter) Wide | ASTM D6222 | Smooth surfaced torch applied APP base or ply sheet reinforced with a polyester mat. |
| Ruberoid® Torch Granule <i>Manufacturing location: #1, 2, 3</i> | 39.37" (1 meter) Wide | ASTM D6222 | Granule surfaced torch applied APP cap sheet reinforced with a polyester mat. |
| Tri-Ply® APP Granule <i>Manufacturing location: #1, 2, 3</i> | 39.37" (1 meter) Wide | ASTM D6222 | Granule surfaced torch applied APP cap sheet reinforced with a polyester mat. |
| Ruberoid® Torch Plus Granule FR <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6222 | Fire retardant granule surfaced torch applied APP cap sheet reinforced with a polyester mat. |
| Ruberoid® EnergyCap™ Torch Granule FR <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6222 | Fire retardant granule surfaced torch applied APP cap sheet reinforced with a polyester mat. The top surface is covered with an enhanced white granule surfacing. |
| Ruberoid® 20 Smooth <i>Manufacturing location: #1, 4</i> | 39.37" (1 meter) Wide | ASTM D6163 | SBS polymer-modified asphalt base or ply sheet reinforced with a fiberglass mat. |
| Ruberoid® 30 Granule <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6163 | Granule surfaced mop applied SBS cap sheet reinforced with a fiberglass mat. |
| Ruberoid® 30 Granule FR <i>Manufacturing location: #2, 4</i> | 39.37" (1 meter) Wide | ASTM D6163 | Fire retardant granule surfaced mop applied SBS cap sheet reinforced with fiberglass mat. |
| Ruberoid® Mop Granule <i>Manufacturing location: #1, 2</i> | 39.37" (1 meter) Wide | ASTM D6164 | Granule surfaced mop applied SBS cap sheet reinforced with a polyester mat. |
| Tri-Ply® SBS Granule <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Granule surfaced mop applied SBS cap sheet reinforced with a polyester mat. |
| Intec Flex PRF <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Granule surfaced mop applied SBS cap sheet reinforced with a polyester mat. |

PRODUCT DESCRIPTION: (CONTINUED)

| <u>Product</u> | <u>Dimensions</u> | <u>Test Specifications</u> | <u>Product Description</u> |
|---|------------------------------|----------------------------|--|
| Ruberoid® Mop Smooth <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Smooth surfaced mop applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® Mop Smooth 1.5 <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Smooth surfaced mop applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® Mop Plus Smooth <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Smooth surfaced mop applied SBS base or ply sheet reinforced with a polyester mat. |
| Ruberoid® Mop Plus Granule FR <i>Manufacturing location: #1, 4</i> | 39.37" (1 meter) Wide | ASTM D6164 | Fire retardant granule surfaced mop applied SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® EnergyCap™ Mop Plus Granule FR <i>Manufacturing location: #2, 4</i> | 39.37" (1 meter) Wide | ASTM D6164 | Fire retardant granule surfaced mop applied SBS cap sheet reinforced with a polyester mat. The top surface is covered with an enhanced white granule surfacing. |
| Ruberoid® Mop Granule FR <i>Manufacturing location: #1</i> | 39.37" (1 meter) Wide | ASTM D6164 | Fire retardant granule surfaced mop applied SBS cap sheet reinforced with a polyester mat. |
| Ruberoid® EnergyCap™ 30 Granule FR <i>Manufacturing location: #1, 4</i> | 39.37" (1 meter) Wide | ASTM D6163 | Fire retardant granule surfaced mop applied SBS cap sheet reinforced with a fiberglass mat. The top surface is covered with an enhanced white granule surfacing. |
| Ruberoid® UltraClad SBS Membrane <i>Manufacturing location: #4</i> | 39.37" (1 meter) Wide | ASTM D6298 | Fire retardant aluminum foil-faced SBS flashing membrane. |
| Matrix™ 102 SBS Membrane Adhesive <i>Manufacturing location: #5</i> | 3, 5 or 55 Gallons | ASTM D3019 | Fiber reinforced rubberized cold-applied adhesive for modified bitumen roof systems. |
| Matrix™ 201 Premium SBS Flashing Cement <i>Manufacturing location: #5</i> | 11 oz. Tubes Or 5 gallons | ASTM D4586 | Cold applied flashing cement in SBS-modified bitumen asphalt roof systems. |
| Matrix™ 307 Premium Asphalt Primer <i>Manufacturing location: #5</i> | 3, 5 or 55 Gallons | ASTM D41 | Asphalt concrete primer used to promote adhesion of all types of asphalt-based roofing materials. |
| VersaShield® Fire-Resistant Roof Deck Protection <i>Manufacturing location: #6</i> | 12" x 100' rolls | ASTM D226 | Non-asphaltic fiberglass-based underlayment and/or fire barrier |
| VersaShield® Solo™ Fire-Resistant Slip Sheet <i>Manufacturing location: #6</i> | 42" roll wide, 100 ft. | ASTM D226 | Non-asphaltic, fire resistant fiberglass underlayment |

MANUFACTURING LOCATIONS:

1. Savannah, GA
2. Stockton, CA
3. Mt. Vernon, IN
4. Arkadelphia, AR
5. Hallandale, FL
6. Conover, NC
7. Verona, Italy

EVIDENCE SUBMITTED:

| <u>Test Agency</u> | <u>Test Identifier</u> | <u>Test Name/Report</u> | <u>Date</u> |
|--|--------------------------|-------------------------|-------------|
| PRI Construction Materials Technologies LLC | PRI 376T0140 | ASTM D6164 | 08/18/21 |
| | PRI 376T0143 | ASTM D6222 | 08/23/21 |
| | PRI 376T0144 | ASTM D6222 | 08/26/21 |
| | PRI 376T0221 | ASTM D6164 | 01/17/22 |
| | PRI 376T0222 | ASTM D6222 | 01/18/22 |
| | PRI 376T0141 | ASTM D6163 | 01/26/22 |
| | PRI 376T0220 | ASTM D6164 | 03/08/22 |
| | PRI 376T0230 | ASTM D6222 | 03/24/22 |
| | PRI 376T0274 | ASTM D6222 | 05/04/22 |
| | PRI 376T0273 | ASTM D6222 | 05/04/22 |
| | PRI 824T0051 | ASTM D6164 | 06/09/22 |
| | PRI 824T0046 | ASTM D6163 | 06/30/22 |
| | PRI 824T0047 | ASTM D6163 | 06/30/22 |
| | PRI 824T0098 | ASTM D6298 | 03/21/23 |
| | PRI 376T0480 | ASTM D6163 | 02/29/24 |
| | PRI 376T0481 | ASTM D6164 | 02/29/24 |
| | PRI 376T0482 | ASTM D6164 | 02/29/24 |
| | PRI 376T0483 | ASTM D6164 | 04/12/24 |
| | PRI 376T0486 | ASTM D6164 | 04/12/24 |
| | PRI 824T0155 | ASTM D6163 | 04/18/24 |
| | PRI 376T0483 | ASTM D6164 | 07/12/24 |
| NEMO ETC, LLC | 4S-GAF-18-001.11.18 | ASTM D6163 | 11/06/18 |
| | 4S-GAF-18-001.03.19.A-R1 | ASTM D6222 | 03/13/19 |
| | 4Q-GAF-19-SSMBB-02.A | ASTM D6163 | 04/08/19 |
| | 4q-GAF-22-SSMBB-01.A | ASTM D6164 | 04/22/23 |
| | 4q-GAF-SSMBB-003.A | ASTM D6222 | 01/06/24 |
| | 4q-GAF-SSMBB-002.A | ASTM D6164 | 12/05/24 |
| | 4q-GAF-SSMBB-001.A | ASTM D6164 | 12/05/24 |
| Trinity ERD | 4q-GAF-SSMBB-004.A | ASTM D6164 | 02/05/25 |
| | G46160.02.15-2D-1 | ASTM D6163 | 02/09/16 |
| | SC10680.05.16 | ASTM D6163 | 05/10/16 |
| | SC13105.03.17-R1 | ASTM D6164 | 03/23/17 |

LABELING:

All membranes and accessories or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. The GAF Modified Bitumen Roof Membranes and Accessories listed herein are designed for use as specified within approved roofing system NOA assemblies.
3. This acceptance establishes the required physical properties testing and traceability of roofing membrane and accessory components listed in approved roofing applications. Minimum deck requirements shall be in compliance with applicable building code. The GAF Modified Bitumen Roof Membranes and Accessories listed herein shall be installed in strict compliance with applicable Building Codes, Product Approvals and Manufacturers' specifications and guidelines.
4. Change in materials or manufacturing process or location of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
5. The GAF Modified Bitumen Roof Membranes and Accessories listed herein may be used with any approved Roof Assembly Notice of Acceptance listing the GAF Modified Bitumen Roof Membranes and Accessories listed herein as a component part of an assembly in the Notice of Acceptance. If the GAF Modified Bitumen Roof Membranes and Accessories listed herein are not listed; a request may be made to the Authority Having Jurisdiction (AHJ) or the Miami-Dade County Product Control Department for approval provided that appropriate documentation is provided to detail compatibility of the products, wind uplift resistance, and fire testing results.
6. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

END OF THIS ACCEPTANCE



NOA-No.: 25-0717.05
Expiration Date: 11/06/30
Approval Date: 11/06/25
Page 6 of 6