



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786)315-2590 F (786) 31525-99
www.miamidade.gov/economy

PolyCon LLC
1755 Transcentral Ct., Ste. 400
Houston, TX 77032

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: PolyCon PCA 1000 Color Series, PolyCon PCA 1000 Quickset Color Series, PolyCon PCA 1500HT Color Series and PolyCon PCR 5000 Color Series Acrylic Roof Coatings.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 4.

The submitted documentation was reviewed by Jorge L. Acebo.

05/07/26



NOA No.: 26-0225.04
Expiration Date: 05/07/31
Approval Date: 05/07/26
Page 1 of 4

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cement-Adhesive-Coatings
Material: Acrylic Elastomeric

SCOPE:

This approves “PolyCon PCA 1000 Color Series, PolyCon PCA 1000 Quickset Color Series, PolyCon PCA 1500HT Color Series and PolyCon PCR 5000 Color Series Acrylic Roof Coatings” as a roof maintenance coating, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone.

TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
PCA 1000 Color Series	5 gal. pail 55 gal. drum 275 gal. tote	ASTM D6083	A high solids, fire retardant, thixotropic, acrylic elastomeric coating.
PCA 1000 Quickset Color Series	5 gal. pail 55 gal. drum 275 gal. tote	ASTM D6083	A high solids, fire retardant, thixotropic, acrylic elastomeric coating.
PCA 1500HT Color Series	5 gal. pail 55 gal. drum 275 gal. tote	ASTM D6083	A high solids, fire retardant, thixotropic, acrylic elastomeric coating.
PCR 5000 Color Series	5 gal. pail 55 gal. drum 275 gal. tote	ASTM D6083	A 100%-acrylic polymer formulated elastomeric coating.

MANUFACTURING LOCATIONS:

1. Houston, TX

EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Construction Materials	2763T0001	ASTM D6083	04/24/25
Technologies LLC	2763T0002	ASTM D6083	04/24/25
	2763T0003	ASTM D6083	04/24/25

PHYSICAL PROPERTIES OF COMPONENTS

Trade names: PCA 1000 Color Series
Thickness: See Description and System Approvals Below
Specifications: ASTM D6083
Description: A high solids, fire retardant, thixotropic, acrylic elastomeric coating applied at an application rate listed below;

Surface

Application Rate

- Spray Polyurethane Foam Roofs Apply two coats of PCA 1000 Color Series at a minimum rate of 1.5 to 3 gal./100 ft² to a minimum allowable dry mil thickness of 24 mils.

Container Size: 5, 55 and 275 gallon containers. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

NOA No.: 26-0225.04
Expiration Date: 05/07/31
Approval Date: 05/07/26
Page 2 of 4

PHYSICAL PROPERTIES OF COMPONENTS (CONTINUED)

Trade names: **PCA 1000 Quickset Color Series**
Thickness: See Description and System Approvals Below
Specifications: ASTM D6083
Description: A high solids, fire retardant, thixotropic, acrylic elastomeric coating applied at an application rate listed below;

Surface

Application Rate

- Spray Polyurethane Foam Roofs Apply two coats of PCA 1000 Quickset Color Series at a minimum rate of 1.5 to 3 gal./100 ft² to a minimum allowable dry mil thickness of 24 mils.

Container Size: 5, 55 and 275 gallon containers. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

Trade names: **PCA 1500HT Color Series**

Thickness: See Description and System Approvals Below

Specifications: ASTM D6083

Description: A high solids, fire retardant, thixotropic, acrylic elastomeric coating applied at an application rate listed below;

Surface

Application Rate

- Spray Polyurethane Foam Roofs Apply two coats of PCA 1500HT Color Series at a minimum rate of 1.5 to 3 gal./100 ft² to a minimum allowable dry mil thickness of 24 mils.

Container Size: 5, 55 and 275 gallon containers. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

Trade names: **PCR 5000 Color Series**

Thickness: See Description and System Approvals Below

Specifications: ASTM D6083

Description: A high solids, fire retardant, thixotropic, acrylic elastomeric coating applied at an application rate listed below;

Surface

Application Rate

- Aged PVC Single Ply Roofing Apply two coats of PCR 5000 Color Series at a minimum rate of 1.5 to 3 gal./100 ft² to a minimum allowable dry mil thickness of 24 mils.
- Aged Granular SBS Mod. Bit. Roofing Membrane Apply two coats of PCR 5000 Color Series at a minimum rate of 1.5 to 3 gal./100 ft² to a minimum allowable dry mil thickness of 24 mils.
- Galvanized Metal Roofing Apply two coats of PCR 5000 Color Series at a minimum rate of 1.5 to 3 gal./100 ft² to a minimum allowable dry mil thickness of 24 mils.

Container Size: 5, 55 and 275 gallon containers. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

LIMITATIONS:

1. **PolyCon PCA 1000 Color Series, PolyCon PCA 1000 Quickset Color Series, PolyCon PCA 1500HT Color Series and PolyCon PCR 5000 Color Series Acrylic Roof Coatings as listed within the scope of this document are not approved as and shall not be used as a Roof System or Waterproofing System as required by the Florida Building Code Chapter 15 HVHZ.**
2. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
3. PolyCon PCA 1000 Color Series, PolyCon PCA 1000 Quickset Color Series, PolyCon PCA 1500HT Color Series and PolyCon PCR 5000 Color Series Acrylic Roof Coatings shall not be applied in inclement weather conditions.
4. PolyCon PCA 1000 Color Series, PolyCon PCA 1000 Quickset Color Series, PolyCon PCA 1500HT Color Series and PolyCon PCR 5000 Color Series Acrylic Roof Coatings shall not be applied over asphaltic shingles, fiber-cement shingles, quarry slate, cement or clay roofing tile, or wood shingles or shakes.
5. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assembly's Notice of Acceptance. For applications over existing single ply, granulated modified systems, refer to applicable building code for requirements.
6. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.

A black oval seal with a white border. Inside, the text "MIAMI-DADE COUNTY" is written in white, bold, uppercase letters. Below it, the word "APPROVED" is written in white, bold, uppercase letters, separated from the county name by a thin white vertical line.
7. PolyCon PCA 1000 Color Series, PolyCon PCA 1000 Quickset Color Series, PolyCon PCA 1500HT Color Series and PolyCon PCR 5000 Color Series Acrylic Roof Coatings shall only be applied by a factory trained and certified applicators and in accordance with manufacturer's published application instructions.
8. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade Product Control upon request.
9. Change in materials use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
10. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.

END OF THIS ACCEPTANCE

