



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

**MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

The Sherwin Williams Company
1 Sherwin Way
Cleveland, OH 44113

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Uniflex & Kool Seal Roof Coatings

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews and revises NOA# 25-0917.02 and consists of pages 1 through 12.
The submitted documentation was reviewed by Rafael Macedo.

07/23/26



NOA-No.: 26-0504.03
Expiration Date: 07/01/31
Approval Date: 07/23/26
Page 1 of 12

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cement-Adhesive-Coatings
Materials: Elastomeric

SCOPE:

This approves “**Uniflex and Kool Seal Roof Coatings**” as maintenance roof coatings as manufactured by The Sherwin Williams Company, and as described in this Notice of Acceptance. This product has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:

TABLE 1

<u>Product</u>	<u>Container Size</u>	<u>Test Specification</u>	<u>Product Description</u>
Uniflex Premium Elastomeric Finish Coat White 41-300 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Uniflex Premium Elastomeric Finish Coat Adobe Light Tan 41-30T <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Uniflex Premium Elastomeric Finish Coat Sedona Tan 41-300T <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Uniflex Premium Elastomeric Finish Coat Black 41-325 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Kool Seal Elastomeric Finish Coat White 63-900 <i>Manufacturing Location #1</i>	1, 5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Uniflex Premium Elastomeric Base Coat Gray 41-320 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Kool Seal Premium ELASTOMERIC BASE COAT GRAY 34-100 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Acrylic elastomeric coating
Uniflex SPE Acrylic Primer Gray 41-321 <i>Manufacturing Location #2</i>	5, 55, 275 gallons	Proprietary	Acrylic elastomeric primer coat
Kool Seal SPE Acrylic Primer Gray 34-500 <i>Manufacturing Location #2</i>	5, 55, 275 gallons	Proprietary	Acrylic elastomeric primer coat



NOA-No.: 26-0504.03
Expiration Date: 07/01/31
Approval Date: 07/23/26
Page 2 of 12

<u>Product</u>	<u>Container Size</u>	<u>Test Specification</u>	<u>Product Description</u>
Uniflex Elastomeric MB Primer White 41-510 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	Proprietary	Acrylic elastomeric primer coat
Kool Seal Elastomeric MB Primer White 34-300 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	Proprietary	Acrylic elastomeric primer coat
Uniflex Elastomeric MB Primer Gray 41-512 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	Proprietary	Acrylic elastomeric primer coat
Uniflex Commercial Grade Acrylic Elastomeric Finish Coat White 41-500 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Modified acrylic elastomeric coating
Uniflex Commercial Grade Acrylic Elastomeric Finish Coat Sedona Tan 41-500T <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Modified acrylic elastomeric coating
Uniflex Commercial Grade Acrylic Elastomeric Base Coat Gray 41-520 <i>Manufacturing Location #1</i>	5, 55, 275 gallons	ASTM D6083	Modified acrylic elastomeric coating
Uniflex Rubberized Silicone Roof Coating 44-300 White <i>Manufacturing Location #3</i>	5, 55, 275 gallons	ASTM D6694	A single component, elastomeric silicone coating.
Kool-Seal Tundra Rubberized Silicone Roof Coating KS0064900 White <i>Manufacturing Location #3</i>	5, 55, 275 gallons	ASTM D6694	A single component, elastomeric silicone coating.
Uniflex Silicone 22 Rubberized Silicone Roof Coating 44-500 <i>Manufacturing Location #3</i>	5, 55 gallons	ASTM D6694	A single component, elastomeric silicone coating.
Kool Seal Tundra Low Solid Silicone 64-700 <i>Manufacturing Location #3</i>	5, 55 gallons	ASTM D6694	A single component, elastomeric silicone coating.
Uniflex Rubberized Silicone Roof Coating 44-600 White <i>Manufacturing Location #4</i>	5, 55 gallons	ASTM D6694	A single component, elastomeric silicone coating.
Kool Seal Tundra Rubberized Silicone Roof Coating KS0064800 White <i>Manufacturing Location #4</i>	5, 55 gallons	ASTM D6694	A single component, elastomeric silicone coating.
Uniflex Bleed Blocker 41-530 <i>Manufacturing Location #3</i>	5, 55 gallons	Proprietary	High-performance waterborne epoxy primer.



<u>Product</u>	<u>Container Size</u>	<u>Test Specification</u>	<u>Product Description</u>
Kool Seal Bleed Blocker 34-400 <i>Manufacturing Location #3</i>	5, 55 gallons	Proprietary	High-performance waterborne epoxy primer.
Uniflex One Flash GRAY 51-920 <i>Manufacturing Location #5</i>	20 ounces; 2, 5 gallons	Proprietary	Premium flashing grade, UV stable, weather resistant sealant
Kool Seal Freedom Flash GRAY 66-920 <i>Manufacturing Location #5</i>	20 ounces; 2, 5 gallons	Proprietary	Premium flashing grade, UV stable, weather resistant sealant
Uniflex One Flash WHITE 51-921 <i>Manufacturing Location #5</i>	20 ounces; 2, 5 gallons	Proprietary	Premium flashing grade, UV stable, weather resistant sealant
Kool Seal Freedom Flash WHITE 66-921 <i>Manufacturing Location #5</i>	20 ounces; 2, 5 gallons	Proprietary	Premium flashing grade, UV stable, weather resistant sealant
Uniflex Urethane88 WHITE 46-600 <i>Manufacturing Location #6</i>	5 gallons	ASTM D6083	Single component Aliphatic moisture curing polyurethane
Uniflex Urethane88 GRAY 46-620 <i>Manufacturing Location #6</i>	5 gallons	ASTM D6083	Single component Aliphatic moisture curing polyurethane

MANUFACTURING LOCATIONS:

1. Orlando, FL
2. Victorville, CA
3. Tampa, FL
4. Elizabethtown, KY
5. Waconia, MN
6. Federalsburg, MD

BUILDING PERMIT REQUIREMENTS:

Application for building permit shall be accompanied by copies of the following:

1. This Notice of Acceptance
2. Any other documents required by the building official or the Applicable Building Code in order to properly evaluate the installation of this system.



EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
UL LLC	R12209	UL 790	11/01/22
Trinity ERD	KST-SC10595.06.16-R1	ASTM D6083	07/27/16
	KST-SC13915.11.17-2	ASTM D6083	11/30/17
	KST-SC13915.11.17-1-R1	ASTM D6083	12/27/17
PRI Construction Materials Technologies, LLC	SWC-016-02-01	ASTM D6083/D903	12/13/17
	1272T0012	ASTM D6694/D903	10/08/20
	2403T0001	ASTM D6083	02/03/22
	1272T0062	Physical Properties	12/11/24
	1272T0060	Physical Properties	01/30/25
	1272T0061	Physical Properties	01/30/25
NEMO ETC, LLC	4p-KST-19-SSLAP-02.A.R1	ASTM D6694	10/01/20
	4g-KST-19-LSVRS-01.A	ASTM D6904	08/26/19
	4p-KST-22-SSLAP-02.A	ASTM D6694	06/04/24
	4p-KST-SSLAP-001.A	Physical Properties	06/24/26
	4p-KST-SSLAP-002.B	ASTM D6694	05/29/26



PHYSICAL PROPERTIES OF COMPONENTS & APPLICATION:

Top Coat: Uniflex Premium Elastomeric Finish Coat White 41-300;
Uniflex Premium Elastomeric Finish Coat Adobe Light Tan 41-30T;
Uniflex Premium Elastomeric Finish Coat Sedona Tan 41-300T;
Uniflex Premium Elastomeric Finish Coat Black 41-325;
Kool Seal Elastomeric Finish Coat White 63-900

Base Coat: Uniflex Premium Elastomeric Base Coat Gray 41-320;
Kool Seal Premium ELASTOMERIC BASE COAT GRAY 34-100;

Primer: Uniflex SPE Acrylic Primer Gray 41-321;
Kool Seal SPE Acrylic Primer Gray 34-500;
Uniflex Elastomeric MB Primer White 41-510;
Kool Seal Elastomeric MB Primer White 34-300;
Uniflex Elastomeric MB Primer Gray 41-512;

Description: A liquid applied coating membrane applied at an application rate listed below:

- Galvanized Metal Roofs; Apply Top Coat at 1.5 gal/100 ft² over one coat of Uniflex Premium Elastomeric Base Coat Gray 41-320 or Kool Seal Premium ELASTOMERIC BASE COAT GRAY 34-100 at an application of 1.5 gal/100 ft².
- Granule Surfaced SBS Modified Bitumen Membranes; Apply Uniflex Elastomeric MB Primer White 41-510 or Kool Seal Elastomeric MB Primer White 34-300 or Uniflex Elastomeric MB Primer Gray 41-512 at 1.5 gal/100 ft².
- Smooth Surfaced Asphalt Build-up Roof (BUR); Apply Uniflex Elastomeric MB Primer White 41-510 or Kool Seal Elastomeric MB Primer White 34-300 or Uniflex Elastomeric MB Primer Gray 41-512 at 1.5 gal/100 ft².
- New PVC Single Ply Membranes; Apply Uniflex SPE Acrylic Primer Gray 41-321 or Kool Seal SPE Acrylic Primer Gray 34-500 at 1.5 gal/100 ft².
- New TPO Single Ply Membranes; Apply Uniflex SPE Acrylic Primer Gray 41-321 or Kool Seal SPE Acrylic Primer Gray 34-500 at 1.5 gal/100 ft². Concrete*; Apply Top Coat directly (Do Not Use a Base Coat.) to concrete at 1.5 gal/100 ft².
- New EPDM Single Ply Membranes; Apply Uniflex SPE Acrylic Primer Gray 41-321 or Kool Seal SPE Acrylic Primer Gray 34-500 at 1.5 gal/100 ft².
- New Hypalon Single Ply Membranes; Apply Uniflex SPE Acrylic Primer Gray 41-321 or Kool Seal SPE Acrylic Primer Gray 34-500 at 1.5 gal/100 ft².
- Concrete*; Apply Top Coat directly (Do Not Use a Base Coat or Primer.) to concrete at 1.5 gal/100 ft².

***Note: See Limitation #1**

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA. Note: All cautions on container label.



Top Coat:	Uniflex Commercial Grade Elastomeric Finish Coat White 41-500; Uniflex Commercial Grade Elastomeric Finish Coat Sedona Tan 41-500T; Uniflex Commercial Grade Elastomeric Base Coat Gray 41-520;
Primer:	Uniflex SPE Acrylic Primer Gray 41-321; Kool Seal SPE Acrylic Primer Gray 34-500; Uniflex Elastomeric MB Primer White 41-510; Kool Seal Elastomeric MB Primer White 34-300; Uniflex Elastomeric MB Primer Gray 41-512;
Description:	A liquid applied coating membrane applied at an application rate listed below: • Granule Surfaced SBS Modified Bitumen Membranes; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex Elastomeric MB Primer White 41-510 or Kool Seal Elastomeric MB Primer White 34-300 or Uniflex Elastomeric MB Primer Gray 41-512 at an application of 1.5 gal/100 ft². • New or existing PVC Single Ply Membranes; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex SPE Acrylic Primer Gray 41-321 or Kool Seal SPE Acrylic Primer Gray 34-500 at an application of 1.5 gal/100 ft². Optional priming of membrane with Uniflex BOND-IT Wash Primer (38-620) at 1 gallon per 400 – 500 square feet; set time to rinse: 10 – 15 minutes. A new application shall be required if primer allowed to dry. • Existing TPO Single Ply Membranes; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex SPE Acrylic Primer Gray 41-321 or Kool Seal SPE Acrylic Primer Gray 34-500 at an application of 1.5 gal/100 ft². Optional priming of membrane with Uniflex BOND-IT Wash Primer (38-620) at 1 gallon per 400 – 500 square feet; set time to rinse: 10 – 15 minutes. A new application shall be required if primer allowed to dry.
Systems Approvals:	Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA. Note all cautions on container label.

Top Coat: **Uniflex Rubberized Silicone Roof Coating 44-300 White**
Kool-Seal Tundra Rubberized Silicone Roof Coating KS0064900 White

Description: A liquid applied coating membrane applied at an application rate listed below:

- Galvanized Metal Roofs; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Granule Surfaced SBS Modified Bitumen Membranes; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Concrete*; Apply Top Coat directly to concrete at 1.5 gal/100 ft².
- Spray Polyurethane Foam; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- New Smooth Surfaced APP Modified Bitumen; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Existing Granule Surfaced APP Modified Bitumen; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- New Smooth or Granule Surfaced SBS Modified Bitumen; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- New EPDM Single Ply Black; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with APOC 296 Single Ply Primer at 1 gallon per 400 – 600 ft².
- Existing EPDM Single Ply Black; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex BOND-IT Wash Primer (38-620) at 1 gallon per 400 – 500 ft².
- New TPO Single Ply; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with APOC 296 Single Ply Primer at 1 gallon per 400 – 600 ft².

***Note: See Limitation #1.**

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA. Note all cautions on container label.



Top Coat: **Uniflex Silicone 22 Rubberized Silicone Roof Coating 44-500**
Kool Seal Tundra Low Solids Silicone 64-700

Description: A liquid applied coating membrane applied at an application rate listed below:

- New and Aged Galvanized Metal Roofs; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- New and Aged Aluminum; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Granule SBS Modified Bitumen Membrane Roof Systems; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Granule APP Modified Bitumen Membrane Roof Systems; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Aged EPDM Membrane Roof Systems; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex BOND-IT Wash Primer (38-620) at 1 gallon per 400 – 500 ft².
- PVC Membrane Roof Systems; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Aged PVC Membrane Roof Systems; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Aged Granule SBS Modified Bitumen Membrane Roof Systems; Apply Top Coat at 1.5 gal/100 ft² over one coat of Uniflex Elastomeric MB Base Coat Gray (41-512) @ 1.0gal/100ft²
- Spray Polyurethane Foam; Apply Top Coat direct to substrate at 1.5 gal/100 ft².

***Note: See Limitation #1.**

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA. Note all cautions on container label.



Top Coat: **Uniflex Rubberized Silicone Roof Coating 44-600 White**
 Kool Seal Tundra Rubberized Silicone Roof Coating KS0064800 White

Description: A liquid applied coating membrane applied at an application rate listed below:

- Aluminum; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Aged PVC Membrane Roof Systems; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Aged EPDM Membrane Roof System; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex BOND-IT Wash Primer (38-620) at 1 gallon per 400-500 ft².
- Aged EPDM Membrane Roof System; Apply Top Coat at 1.5 gal/100 ft² to substrate primed with Uniflex BOND-IT Wash Primer (38-620) at 1 gallon per 400-500 ft² followed by Uniflex Silicone 22 (44-500) at 1.0gal/100ft²
- Concrete*; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Concrete*; Apply Top Coat at 1.5 gal/100 ft² over one coat of Uniflex Silicone 22 (44-500) at 1.0 gal/100 ft²
- Spray Polyurethane Foam; Apply Top Coat direct to substrate at 1.5 gal/100 ft².
- Spray Polyurethane Foam; Apply Top Coat at 1.5 gal/100 ft² over one coat of Uniflex Silicone 22 (44-500) at 1.0 gal/100ft²
- Aged Granule APP Modified Bitumen Roofing Systems; Apply Top Coat direct to the substrate at 1.5 gal/100 ft².
- Aged Granule SBS Modified Bitumen Roofing Systems; Apply Top Coat direct to the substrate at 1.5 gal/100 ft².
- Granule SBS Modified Bitumen Roofing Systems; Apply Top Coat direct to the substrate at 1.5 gal/100 ft².
- Galvanized steel; Apply Top Coat direct to substrate at 1.5 gal/100 ft².

***Note: See Limitation #1.**

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA. Note all cautions on container label.



Top Coat: Uniflex Urethane88 WHITE 46-600

Base Coat: Uniflex Urethane88 GRAY 46-620

Description: A liquid applied coating membrane applied at an application rate listed below:

- Smooth-Surfaced SBS Modified Bitumen; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- Granule-Surfaced SBS Modified Bitumen; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- Smooth-Surfaced APP Modified Bitumen; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- Granule-Surfaced APP Modified Bitumen; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- Concrete*; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- PVC Single-Ply; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- EDPM Single-Ply; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- TPO Single-Ply; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.
- Galvanized Metal; Apply one coat of Uniflex Urethane88 WHITE 46-600 at 70 sq. ft. per gallon over one coat of Uniflex Urethane88 GRAY 46-620 at 70 sq. ft. per gallon.

***Note: See Limitation #1.**

Systems Approvals: Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA. Note all cautions on container label.



LIMITATIONS:

1. **Uniflex and Kool Seal Roof Coatings is not approved as and shall not be used as a Roof or Waterproofing System as required by the Florida Building Code Chapter 15 HVHZ.**
2. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
3. Uniflex & Kool Seal Roof Coatings shall not be applied in inclement weather conditions.
4. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list the products listed herein as part of their roof assemblies Notice of Acceptance.
5. Uniflex & Kool Seal Roof Coatings shall not be applied over asphaltic shingles, fiber-cement shingles, quarry slate, cement or clay roofing tile, or wood shingles or shakes.
6. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade Product Control upon request.
7. Change in materials, use, or manufacture of any products listed herein shall be cause for termination of this Notice of Acceptance.
8. Uniflex & Kool Seal Roof Coatings shall be applied in accordance with manufacturer's published application instructions. Uniflex & Kool Seal Roof Coatings are not to be used as a waterproofing system only as maintenance coating.
9. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
10. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE

