

AAA-01-17-2020-A

RFI STATUS: Submitted to county

DATE: 1/16/2020

### Corner Guards Replacement

**RFI Line Items**

ECPU: ESTIMATED COST P/UNIT

PMP: POTENTIAL MINIMUM PURCHASE

PAP: POTENTIAL ANNUAL PURCHASE

PF: PURCHASE FREQUENCY

ETD: ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
Corner Guards Replacement				1			1	15	SEE ATTACHED SCOPE OF WORK FOR SPECIFIC ANGLES AND QUANTITIES
Totals									

AAA -01-17-2020-A

## **Corner Guards Replacement**

### **APPROXIMATE PROJECT COST:**

### **SCOPE OF WORK:**

- Furnish and install all labor (including field measurements), materials, equipment, and tools necessary to complete the following:
  - Removal and disposal of existing corner guards.
  - Supply and install new custom-made corner guards.
    - Stainless Steel Fingerprint Resistant Black Onyx finish

### **CORNERGUARD ANGLES, QUANTITIES AND DIMENSIONS:**

- 90 DEGREE APERTURE
  - QTY: 15
  - APPROXIMATE DIMENSION: 3.5 INCHES X 3.5 INCHES X 48 INCHES
  - THICKNESS: 20 GAUGE
- 110 DEGREE APERTURE
  - QTY: 1
  - APPROXIMATE DIMENSION: 3.5 INCHES X 3.5 INCHES X 48 INCHES
  - THICKNESS: 20 GAUGE
- 115 DEGREE APERTURE
  - QTY: 2
  - APPROXIMATE DIMENSION: 3.5 INCHES X 3.5 INCHES X 48 INCHES
  - THICKNESS: 20 GAUGE
- 90 DEGREE APERTURE
  - QTY: 4
  - APPROXIMATE DIMENSION: 2.5 INCHES X 2.5 INCHES X 48 INCHES
  - THICKNESS: 20 GAUGE
- 90 DEGREE APERTURE
  - QTY: 1
  - APPROXIMATE DIMENSION: 6 - 7/16 INCH X 2.5 INCHES X 48 INCHES
  - THICKNESS: 20 GAUGE

### **TIMELINE:**

- Procurement of materials and installation of must be completed within three (3) weeks of vendor approval.
- Vendor must coordinate field measurements and installation schedule with event schedule to avoid delay of work.
- Vendor must submit a schedule of anticipated work days to Director of Operations for approval and must account for events as follows:
  - Event Days – crews allowed onsite from 7am – 3pm when the event occurs in the evening;
    - Crews will not be allowed onsite when an event occurs in the morning and/or afternoon (e.g., matinees and school shows); and
  - Non-Event Days – crews allowed onsite for extended hours as needed.

**Corner Guards Replacement**

- Work shall be 100% complete in any given area when events intervene.

**WARRANTY:**

- Ten (10) years from the date of manufacture that the product will not suffer material edge separation or obstruction of vision.

**RESTRICTIONS:**

- The proposed Vendor must have the following experience and certifications:
  - Vendor shall provide a list of a minimum of three (3) facilities (facility, contact name, title, address and current phone number) where the Vendor has provided corner guard replacement and installation projects of equivalent size and scope within the last five (5) years.
- Proof of completed projects must be submitted at time of proposal.

**INSURANCE:**

- Vendor shall purchase and maintain during the entire project and for two years after project completion insurance with the minimum limits and coverage shown below from insurance companies acceptable to [redacted] has the right to reject unacceptable insurance carriers.

STANDARD INSURANCE REQUIREMENTS	
Coverage Type	Limits
General Liability	Per Occurrence; General Aggregate; Completed Operations Aggregate
Auto Liability (All Hired Non-Owned)	for all jobs
Worker's Compensation	Statutory Limits; Employers Liability

- Vendor shall carry standard ISO General Liability coverage, written on an occurrence basis including Completed Operations. Coverages on an occurrence basis shall be maintained without interruption from date of commencement of the Vendor's Work until date of final payment or date coverage is required to be maintained after final payment to the Vendor, whichever is later. The coverage must be endorsed to name [redacted], City of Miami, and Miami-Dade County as additional insureds on a primary and non-contributory basis.