

Control Room - BirdDog Eyes Camera

RFI Line Items									
EPCU:ESTIMATED COST P/UNIT	PMP:POTENTIAL MINIMUM PURCHASE	PAP:POTENTIAL ANNUAL PURCHASE	PF:PURCHASE FREQUENCY	ETD:ESTIMATED DELIVERY TIME					
Product name	MFR	MFR product #	EPCU	Min qty	PMP	PAP	PF	ETD	Details
BirdDog Eyes P100 1080p Full NDI PTZ Camera	BirdDog	BDP100B		1			1	5	Up to 1080p60 resolution; 10x optical zoom ideal for small to mid-size environments; Simultaneous 3G-SDI and NDI outputs; Includes breakout cable with an Ethernet port (NDI), composite output, 3.5mm audio jacks, and RS-232/422/485 control ports; 128 presets; Up to 150°/s preset adjustment speed; 350° continuous pan; Auto, manual, and push focus; 0.5 lux minimum illumination; Includes BirdDog Comms Lite NDI audio intercom platform (Windows) Image Sensor; 1-Chip 1/2.86" CMOS Sensor; Sensor Resolution 2.2 MP; Minimum Illumination 0.5 Lux; Camera Shutter Speed 1/1 to 1/30,000 sec Max Digital Zoom 12x Lens; Optical Zoom Ratio 10x; Focal Length 4.7 to 47mm Field of View Horizontal: 6.43 to 60.9°; Maximum Aperture f/1.6 to 3; Focus Control: Autofocus/Manual Focus; Video Output Formats: SDI, RJ45: 1920 x 1080p at 25, 29.97, 50, 59.94, 60 fps; 1920 x 1080i at 50, 59.94, 60 fps; 1280 x 720p at 25, 29.97, 50, 59.94, 60 fps; Control Presets 128; Move Speed 150°/sec Movement Range Pan: 350°; Tilt: -15 to 90°; Tally Light No; Supported Control Protocols: Pelco-D/ VISCA Interfaces; Video Output Connectors 1 x BNC (3G-SDI / HD-SDI / SD-SDI) Male; 1 x RJ45 (NDI); 1 x RCA (Composite) General Dimensions:6.06 x 5.71 x 5.71" / 15.4 x 14.5 x 14.5 cm Weight: 2.2 lb / 1 kg
Totals									