

Control Room Altronix Rack Mount Power Supply

RFI Line Items

ECPU:ESTIMATED COST P/UNIT PMP:POTENTIAL MINIMUM PURCHASE PAP:POTENTIAL ANNUAL PURCHASE PF:PURCHASE FREQUENCY ETD:ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
CCTV Rack Mount Power Supply	Altronix	Altrvertiline166c		1			1	2	Input Voltage 115VAC, 60Hz, 4A. Output Sixteen (16) individually selectable power outputs with OFF position. Voltage 24VAC or 28VAC. Current 14A max. total supply current. Fusing Individual outputs' fuses rated @ 3A. Main fuse rated @ 15A. Other Short circuit and thermal overload protection. Filtered and regulated. Indicators (LED) Master Illuminated master power disconnect circuit breaker with manual reset. Output Sixteen (16) individual LEDs. Agency Listings UL UL2044 (Commercial CCTV Equipment).cUL CSA Standard C22.2 No.1-04, Audio, Video and Similar Equipment. CE European Conformity.Dimensions (H x W x D) 1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm). Product Weight 15.4 lbs. (6.99 kg). Shipping Weight 16.75 lbs. (7.57 kg). Temperature Operating 0°C to 49°C (32°F to 120°F). Storage -20°C to 70°C (-4°F to 158°F). Relative Humidity 85% +/-5%. BTU/Hr. (approx.): 24VAC: 172 BTU/Hr. 28VAC: 201 BTU/Hr.
Rack Mount DC Power Supply	Altronix	ALTRVERTILINE33TD		1			1	2	Input Voltage 115VAC, 60Hz, 3A. Output Voltage 12VDC. Current 16A max. total supply current. Fusing Individual outputs' PTCs rated @ 2.5A. Other Short circuit and thermal overload protection. Filtered and regulated. Indicators (LED) Master Illuminated master power disconnect circuit breaker with manual reset. Output Sixteen (16) individual LEDs. Agency Listings CE European Conformity. Dimensions (H x W x D) 1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm). Product Weight 7.95 lbs. (3.61 kg). Shipping Weight 9.05 lbs. (4.11 kg). Temperature Operating 0°C to 49°C (32°F to 120°F). Storage -20°C to 70°C (-4°F to 158°F).Relative Humidity 85% +/-5%. BTU/Hr. (approx.): 98 BTU/Hr.
Totals									