

Control Room PAGLINK Time Battery

RFI Line Items

ECPU:ESTIMATED COST P/UNIT PMP:POTENTIAL MINIMUM PURCHASE PAP:POTENTIAL ANNUAL PURCHASE PF:PURCHASE FREQUENCY ETD:ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
PAGlink HC-PL94T Time Battery Gold Mount (14.8V, 94Wh)	PAGlink	9306		4			1	2	Key Features: High Current 14.8V, 94Wh, 6.4Ah Li-Ion Linkable with Other Units for More Power; 10A Draw; 12A When Two Units Combined; Numeric Run-Time and Capacity Display; Display Accuracy Maintenance Feature; No Memory Effect Fail-Safe Electronic System; Communicates Data to Supporting Cameras; High-Impact, Molded Polycarbonate Case; Unrestricted Hand-Luggage Carry-On. Mount Type: Gold Mount; Chemistry: Lithium-Ion; Capacity (Wh) 94 Wh; Amp-Hours 6400 mAh; Output Voltage 14.8 VDC; Maximum Load 150 W, 10 A; Charging Voltage 16.8 VDC Storage Temperature 14 to 104°F / -10 to 40°C; Charging Temperature 32 to 104°F / 0 to 40°C; Discharging Temperature -4 to 122°F / -20 to 50°C; Dimensions (W x H x D) 5 x 3.4 x 2.3" / 127 x 94 x 58 mm Weight 1.6 lb / 0.7 kg
Totals									