

AAA-03-19-2018

RFI STATUS: Submitted to county

PREPARED BY: [REDACTED]

DATE: 3/19/2018

Food Service Equipment Parts

RFI Line Items

EQU: ESTIMATED COST P/UNIT	PMP: POTENTIAL MINIMUM PURCHASE	PAP: POTENTIAL ANNUAL PURCHASE	PF: PURCHASE FREQUENCY	ETD: ESTIMATED DELIVERY TIME
EASIMOUNT STRIP CURTAIN, SINGLE STRIP	Kason 401SA6060084	[REDACTED] 40	[REDACTED] 1	5 REPLACEMENT STRIP, 6" x 84"
CAP END FOR KASON CURTAINS	Generic	[REDACTED] 10	[REDACTED] 1	3 COLOR: BLACK; MATERIAL: PLASTIC; WEIGHT: .001 lb; LENGTH: 1 3/16" 30 mm; WIDTH: 1 1/16" 17 mm; DEPTH: 9/16" 14 mm
KPU DUAL PRESSURE CONTROL	DANFOSS 060-5253	[REDACTED] 5	[REDACTED] 1	3 KPU-16B, RANGE 6" TO 108" PSIG, DIF 10-60, RESET AUTO/MANUAL CONVERTIBLE, RANGE 100 TO 600 PSIG, DIF 60 FIXED, RESET AUTO/MANUAL CONVERTIBLE, CAP 36", 1/4" FLARE NUT SWITCH SPDT WITH LP/HP SENSING UNIV
FAN MOTOR KIT		[REDACTED] 10	[REDACTED] 1	3 W/ 4" & 5-1/2" BLADES, 120V; 3/16" SHAFT X 1-3/8" LONG, 3000RPM; REPLACES C-FRAME OR ROUND FAN MOTORS, HARDWARE INCLUDED
HARTLAND CONTACTOR	HARTLAND	[REDACTED] 5	[REDACTED] 1	3 3 POLE; 110/120 VOLT; 50 AMP INDUCTIVE; 65 AMP RESISTIVE
HEX REDUCER BUSING	DORMONT 70-4132	[REDACTED] 5	[REDACTED] 1	3 BLACK PIPE; 3/4" MPT X 1/2" FPT REDUCER
LAMP-SILICONE	Generic	[REDACTED] 2	[REDACTED] 1	3 LAMP, 5-3/8" X 1-1/4"; [130V] [40W] MEDIUM BASE, [TUBULAR TYPE] SILICONE; COATING, FOR REFRIGERATION OR OTHER NON-OVEN USE.
THERMOSTAT W/ DIAL	Generic	[REDACTED] 2	[REDACTED] 1	3 [TYPE - K]; [TEMP 100-550]; [BULB 1/4" X 5-3/4"]; [CAP 36"] [INCLUDES DIAL # 22-1002 OFF-10-1; W/ 4 WAY MOUNT]
op CONTROL, TEMPERATURE	DELFIELD 3516047	[REDACTED] 5	[REDACTED] 1	3 TEMP RANGE -25 TO 20 F, CAP 50", SHAFT STEM, DIAL PLATE & KNOB
BIN TEMPERATURE CONTROL KIT	DELFIELD 3516010	[REDACTED] 5	[REDACTED] 1	3 W/ MOUNTING PLATE, DIAL AND HARDWARE; TEMP 32 TO 61 F, CAP 84"; VICTORY REFRIGERATION ALARM CONTROL

[illegible]