

Clear-Com headset - Control Room

RFI Line Items

ECPU:ESTIMATED COST P/UNIT

PMP:POTENTIAL MINIMUM PURCHASE

PAP:POTENTIAL ANNUAL PURCHASE

PF:PURCHASE FREQUENCY

ETD:ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
Clear-Com CC-110-X4 Lightweight single-Ear Headset	Clear-Com	CC-110-X4		3			1	1	Type: Closed-back; Driver: 36mm diameter, neodymium magnet, copper-clad aluminum wire voice coil Frequency Response: 20Hz v- 20kHz. Element: Dynamic Driver: 15mm, neodymium magnet Polar Pattern: Cardio Type: Closed-back Driver: 36mm diameter, neodymium magnet, copper-clad aluminum wire voice coil Frequency Response: 20Hz v- 20kHz Element: Dynamic Driver: 15mm, neodymium magnet Polar Pattern: Cardioid Frequency Response: 250Hz – 20kHz Open Circuit Sensitivity: -64 dB ±3.5 dB; at 1kHz, typical 99 dB ±3 dB (SPL); at 1kHz typical Maximum: 500mW 400 ohms ±30%; at 1kHz typical Cable: 5ft (1.55m) long with 8-pin connector at headset end; 4-pin Female XLR
Totals									