AMA-06-09-2016-D

F&B ORDER 4 - FOOD SERVICE EQUIPMENT & INSTALLATION

RFI Line Items

ECPU: ESTIMATED COST P/UNIT   PMP: POTENTIAL MINIMUM PURCHASE   PAP: POTENTIAL ANNUAL PURCHASE   PF: PURCHASE FREQUENCY   ETD: ESTIMATED DELIVERY TIME

ITEM	MFR	MFR PART # /SKU	ECPU	MIN QTY	PMP	PAP	PF	ETD	DETAILS
HAND SINK - Hand Sink, wall model, 14" wide x 10" front-to-back x 5" deep bowl, 20 gauge 304 series stainless steel, 7-3/4" high side splashes, with splash mounted faucet, wall bracket, NSF, cCSAus	Advance Tabco	7-PS-66-2X	▮	3	▮	▮	1	28	
COMBI OVEN - Combitherm® CT PROformance™ Combi Oven/Steamer, gas, boilerfree, floor model with roll-in cart, (20) non-tilt support rails, (20) 18" x 26" full size sheet or (40) 12" x 20" full size hotel pan (1/1 GN) capacity, PROtouch control with steam	Alto-Shaam	CTP20-20G	▮	1	▮	▮	1	28	programmable cool-down, SafeVent™ steam venting, single point removable probe, CombiClean PLUS™ with (5) cleaning levels, CoolTouch3™ glass window, door hinged right, high efficiency LED lighting, stainless steel construction, seismic legs, 266,000 BTU, EcoSmart®, cULus, UL-EPH, ANSI/NSF 4, CE, IP X5, Gastec, 120v/60/1-ph, 13.6 amps, 1.7kW, 14 AWG, NQ cord or plug, standard
SAFETY SYSTEM MOVEABLE GAS CONNECTOR - Dormont Blue Hose™ Moveable Gas Connector Kit, 1" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC	Dormont Manufacturing	16100KIT2S48	▮	10	▮	▮	1	28	1 SnapFast® QD, 2 Swivel MAX®, 1 full port valve, coiled restraining cable with hardware, 295,000 BTU/hr minimum flow capacity, limited lifetime warranty
HI PSI WATER CONNECTORS & FITTINGS - Dormont Hi-PSI® Water Connector Hose, 3/4" dia., 60" long, covered with stainless steel braid, brass two-way Quick Disconnect coupling, limited lifetime warranty	Dormont Manufacturing	W75B2Q60	▮	2	▮	▮	1	28	
WATER FILTRATION SYSTEM - FX Water Filter System, single 20" sump, (1) CTOS-20 cartridge with IsoNet®, 30,000 gallon capacity, 3 gpm, 0.5 micron sediment and chlorine, taste, odor reduction, scale inhibition	OptiPure	FX-12	▮	1	▮	▮	1	28	for use with ice makers (up to 1,500 lb. cuber/2,000lb. flaker), coffee makers, steamers and combi ovens, NSF (160-50/110)
FLOOR TROUGH - Floor Trough, 24" x 72", subway-style stainless steel grating, 6"Deep 14/304 stainless steel all-welded drain pan with anti-splash design	Eagle Group	ASFT-2472-SG	▮	1	▮	▮	1	28	accommodates up to a 4"Diameter pipe, includes stainless steel removable perforated basket
TILTING SKILLET, GAS - Braising Pan, Gas, 40-gallon capacity, 46" wide open base, manual tilt, 9" deep stainless steel pan with gallon markings, pouring lip & removable strainer	Vulcan	VG40	▮	2	▮	▮	1	28	spring assist cover with drip edge, pan holder, thermostatic control, includes L faucet bracket, electric ignition, 12" stainless steel legs with adjustable flanged feet, 120,000 BTU

Description	Manufacturer	Model	Qty				Notes
WSHDWN DOUBLE FOR TILTING SKILLET - Pantry Deck Mount. Faucet, with backflow preventer, 16" add on faucet, washdown hose, wall hook, NSF and Lead Reduction Compliant	Vulcan	DBPTYTS	2		1	28	Item for Tilting Skillet, Vulcan, Model #VG40
VALVE FOR TILTING SKILLET - 2" draw-off valve, left front straight with strainer (pan support not available on 30-gallon)	Vulcan	BPDOV-1	2		1	28	Item for Tilting Skillet, Vulcan, Model #VG40
CONVECTION OVEN - Marathoner Gold Convection Oven, gas, double deck, bakery depth, electronic ignition, solid state controls, interior lights	Southbend	GB/25SC	2		1	28	includes (5) racks per deck, stainless steel front, sides, top, rear jacket & 6" legs, 180,000 BTU, CSA, NSF, (2) 120v/60/1-ph, 7.9 amps, NEMA 5-15P, standard
CASTERS FOR CONVECTION OVEN - 6" Casters in lieu of legs	Southbend		2		1	28	Item for Southbend, Model #GB/25SC
FRYER - Fryer, gas, 21" W, free-standing, 85-90 lb. capacity, millivolt thermostat controls, twin baskets	Vulcan	1GR85M	3		1	28	stainless steel cabinet and fry tank, adjustable casters (2 swivel locking & 2 non-locking), 150,000 BTU, CSA, NSF
HD RANGE, 36", 6 OPEN BURNERS - V Series Heavy Duty Range, gas, 36", (6) 33,000 BTU open burners, cast iron grates, convection oven, stainless steel front	Vulcan	V6B36C	1		1	28	front top ledge, sides, base, burner box & stub back, 6" adjustable legs, 230,000 BTU, CSA, NSF
PRESSURE REGULATOR FOR HD RANGE - 1-1/4" NPT pressure regulator (Natural gas)	Vulcan	PRESREG-NA11/4	1		1	28	Item for HD Range, Vulcan, Model #V6B36C
HEIGHT RISER FOR HD RANGE - Single deck height riser, no shelf, non overlapping, 36"	Vulcan	V36ST22	1		1	28	Item for HD Range, Vulcan, Model #V6B36C
CASTERS FOR HD RANGE - Casters (set of 4)	Vulcan	RR4	1		1	28	Item for HD Range, Vulcan, Model #V6B36C
SAFETY SYSTEM MOVEABLE GAS CONNECTOR - Dormont Blue Hose™ Moveable Gas Connector Kit, 1-1/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC.	Dormont Manufacturing	16125KIT2S48	1		1	28	1 SnapFast® QD, 2 Swivel MAX®, 1 full port valve, coiled restraining cable with hardware, 449,000 BTU/hr minimum, limited lifetime warranty
COUNTERTOP GRIDDLE - Heavy Duty Griddle, countertop, gas, 48" W x 24" D cooking surface, 1" thick polished steel griddle plate, embedded mechanical snap action thermostat every 12"	Vulcan	MSA48	1		1	28	millivolt pilot safety, manual ignition, low profile, stainless steel front, sides, front grease trough, 4" back & tapered side splashes, 4" adjustable legs, 108,000 BTU, CSA, NSF
EQUIP STAND FOR COUNTERTOP GRIDDLE - Equipment Stand, universal, 48" W x 24" H, 1/2" marine edge, undershelf, stainless steel, 5" casters	Vulcan	STAND/C-48	1		1	28	Item for Countertop Griddle, Vulcan, Model #MSA48
CHARBROILER - Achiever Charbroiler, countertop, 36", (6) 17,000 BTU cast iron burners, infinite heat control valves, fully welded chassis, (1) drip tray	Vulcan	VACB36	1		1	28	stainless steel front, sides & top trim, backsplash & grease trough, 4" adjustable legs, 102,000 BTU, CSA, NSF
EQUIP STAND FOR CHARBROILER - Equipment Stand, universal, 37" W x 24" H, 1/2" marine edge, undershelf, stainless steel, 5" casters	Vulcan	STAND/C-36	1		1	28	Item for Charbroiler, Vulcan, Model #VACB36
FRENCH FRY WARMER - Crisp 'N Hold® Crispy Food Station, countertop, 17 - 9/16"W, 1050 cu.in. interior capacity, 190°F maximum temperature, on/off toggle switch with rubber boot, mechanical thermostat, removable filter & stainless steel food grate	Carter-Hoffmann	CNH-18	1		1	28	integrated collection pan, includes (2) stainless steel food bay dividers, forced-air heating system, polycarbonate rail on front, stainless steel construction, 1" rubber feet, cULus, NSF, 120v/60/1-ph, 1820 watts, 15.1 amps, NEMA 5-20P standard

Description	Manufacturer	Model	Qty	Ref	Notes
REACH-IN UNDERCOUNTER FREEZER - Low Profile Undercounter Freezer, -10° F., (2) shelves, stainless steel top & sides, clear coated aluminum interior with stainless steel floor, (1) stainless steel door	True Food Service Equipment	TUC-27F-LP-HC	1	28	1-1/2" diameter dual wheel castors, 31-7/8"H counter height, front breathing, R290 Hydrocarbon refrigerant, 1/3 HP, 115v/60/1, 5.0 amps, NEMA 5-15P, 7' cord,
FINISH FOR REACH-IN UNDERCOUNTER FREEZER - 16 ga. Stainless steel top	True Food Service Equipment		1	28	Finish for Reach-In Undercounter Freezer, True Food Service Equipment, Model #TUC-27F-LP-HC
WALK IN COOLER/FREEZER - Cooler Interior Dimensions: 9-0 1/2" x 21'-0" x 8'-2 1/4"; Freezer Interior Dimensions: 9-0 1/2" x 6'-2" x 7'-10 5/8"	Kolpak		1	28	Full Specs provided at bid
WIRE SHELVING - Centaur® Shelving, wire, 48"W x 24"D, green epoxy, NSF	Centaur	C2448K	56	28	
WIRE SHELVING - Centaur® Shelving, wire, 54"W x 24"D, green epoxy, NSF	Centaur	C2454K	4	28	
WIRE SHELVING -Centaur® Shelving, wire, 60"W x 24"D, green epoxy, NSF	Centaur	C2460K	4	28	
WIRE SHELVING - Centaur® Shelving, wire, 36"W x 24"D, green epoxy, NSF	Centaur	C2436K	16	28	
POSTS FOR WIRE SHELVING - Centaur® Stationary Post, 74-5/8"H, with leveling bolt & cap, green epoxy	Centaur	C74K	96	28	
SHELF FOR WIRE SHELVING - open wire construction with 2" x 2" mesh panels, (2) doors with hasps for padlock	Eagle Group	CSC2448E	1	28	EAGLEgard® hybrid epoxy finish with MICROGARD® antimicrobial protection, (2) swivel & (2) swivel/brake 5" stem casters with poly tread, KD, NSF
SECURITY UNIT - Security Unit, mobile, 51-1/4"W x 27-1/4"D x 69"H,	Eagle Group	2448C-X	1	28	Item for Security Unit, Eagle Group, Model #2448C-X
DUNNAGE RACK - S-Series Dunnage Rack, slotted top, 3000 lb. load capacity, 21"D x 48"W x 12"H	Cambro	DRS480480	1	28	polypropylene, one-piece, seamless double wall construction, 4" square legs, speckled gray, NSF
SHELF FOR SECURITY UNIT - Shelf, wire, 48"W x 24"D, patented QuadTruss® design, includes (4) pairs of split sleeves per shelf, 800 lbs. capacity, chromeplated finish, NSF (FLYER)			1	28	
ROLL-IN BLAST CHILLER - Quickchiller™ Blast Chiller, roll-in, self-contained with dual refrigeration systems, touch control with (20) preset menu options, (3) product temp probes	Alto-Shaam	QC2-100	1	28	quick freeze soft-chill hard-chill and holding modes, automatic defrost cycle, with rack (40) full-size pan capacity, stainless steel interior and exterior, (4) adjustable legs, cULus, NSF
ELECTRICAL FOR ROLL IN BLAST CHILLER - 115/208-230/60/3-ph, 16.0 amps, 3.68 kW, 5 wire direct connection, no cord or plug	Alto-Shaam		1	28	Item for Roll-In Blast Chiller, Alto-Shaam, Model # QC2-100
WIRE SHELVING - Centaur® Shelving, wire, 54"W x 24"D, chrome, NSF	Centaur	C2454C	15	28	
WIRE SHELVING - Centaur® Shelving, wire, 30"W x 24"D, chrome, NSF	Centaur	C2430C	5	28	
WIRE SHELVING - Centaur® Shelving, wire, 36"W x 24"D, chrome, NSF	Centaur	C2436C	10	28	
WORK TABLE - Work Table, per drawing	Advance Tabco	TKSS-3012	1	28	

Item Description	Manufacturer	Model	Qty		28	Notes
WALL / SPLASH MOUNT FAUCET - Sink Mixing Faucet, 12" swing nozzle, wall mounted, 8" centers on sink faucet with 1/2" IPS eccentric flanged female inlets, lever handles	T&S Brass	B-0231	1	1	28	Item for Faucet, T&S Brass, Model # B-0231
INSTALLATION KIT FOR WALL/SPLASH MOUNT FAUCET - (2) 1/2" NPT nipples, lock nuts and washers, (2) short "Ell" 1/2" NPT female x male	T&S Brass	B-0230-K	1	1	28	Item for Faucet, T&S Brass, Model # B-0231
WASTE VALVE FOR WALL/SPLASH MOUNT FAUCET - twist handle, 3-1/2" sink opening, 2" drain outlet	T&S Brass	B-3952	2	1	28	
WORK TABLE - Work Table, 60"W x 30"D, 14 gauge 304 series stainless steel top without splash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with adjustable stainless steel bullet feet, NSF	Advance Tabco	SS-305	6	1	28	(6) TA-22 Square edge table
WORK TABLE - Work Table, 72"W x 30"D, 14 gauge 304 series stainless steel top with 5"H backsplash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with stainless steel bullet feet, NSF	Advance Tabco	SS-306	2	1	28	(6) TA-22 Square edge table
WORK TABLE - Work Table, 96"W x 30"D, 14 gauge 304 series stainless steel top with steel top with	Advance Tabco	KSS-308	1	1	28	
CASTERS FOR WORK TABLES - Casters, 5" diameter, set of 4 (2 with brakes) with stainless steel legs for standard working height of 35-1/2"	Advance Tabco	TA-25S-4	11	1	28	
WORK TABLE - Work Table, 5"H backsplash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with stainless steel bullet feet, NSF	Advance Tabco		1	1	28	
MEAT SLICER - Heavy Duty Meat Slicer, automatic, 13" CleanCut™ removable knife with removal tool, (3) stroke lengths, & burnished finish, (3) stroke speeds, removable meat grip assembly	Hobart	HS7-1	1	1	28	removable meat grip assembly, removable ring guard cover, single action top mounted sharpener with Borazon™ stones, manual lift lever, 1/2 hp motor, 5.6amps, 120v/60hz/1-ph, NSF cETLus
PLANETARY MIXER - 200-240/50/60/3 Mixer, with bowl, beater, whip, & spiral dough arm; US/EXP configuration	Hobart	HL400-1STD	1	1	28	Legacy Planetary Mixer, 1.5 hp, 40-qt. capacity, (3) fixed speeds, geardriven transmission, 20 minute timer, #12 taper attachment hub, manual bowl lift, bowl guard, stainless steel bowl, "B" beater, "D" whip, "ED" dough hook
REACH-IN UNDER COUNTER REFRIGERATOR - Low Profile Undercounter Refrigerator, 33-38° F, (2) shelves, stainless steel top & sides, clear coated aluminum interior with stainless steel floor	True Food Service Equipment	TUC-27-LP-HC	1	1	28	(1) stainless steel door, 1-1/2" diameter dual wheel castors, 31-7/8" counter height, front breathing, R290 Hydrocarbon refrigerant, 1/6 HP, 115v/60/1, 2.0 amps, 7' cord, NEMA 5-15P, cULus, NSF, CE, 1-1/2" diameter dual wheel casters, standard
WORK TABLE - Work Table, per drawing	Advance Tabco	TKSS-3011	1	1	28	
WORK TABLE - Work Table, 36"W x 24"D, 14 gauge 304 series stainless steel top without splash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with adjustable stainless steel bullet feet, NSF	Advance Tabco	SS-243	1	1	28	

Item / Description	Manufacturer	Model	Qty	Ref	Notes
WORK TABLE - Work Table, 48"W x 24"D, 14 gauge 304 series stainless steel top without splash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with adjustable stainless steel bullet feet, NSF	Advance Tabco	SS-244	1	28	
PAN RACK, BUN - Bun Pan Rack, standard, 70-1/4"H, 3" spacing, capacity (20) 18" x 26" bun pans, front loading, welded, heavy duty aluminum construction, 5" swivel plate caster, NSF	Channel Manufacturing	401A	4	28	
PAN CART, ROLL-IN - Roll-In Plate Cart, 84 plates capacity, 3-11/16" vertical spacing, fits 20-20E, 20-20G, 20-20MW and QC2-100, stainless steel construction, (4) casters (2 locking)	Alto-Shaam	5016480	4	28	
PAN RACK, BUN - Roll-In Pan Cart, 20 shelf pan trolley, 2-9/16" vertical spacing, fits 20-20E, 20-20G, 20-20MW and QC2-100, stainless steel construction, (4) casters (2 locking)	Alto-Shaam	5017976	2	28	
DISH CART - Poker Chip Dish Dolly, 26-5/8"W x 26-5/8"D x 31-15/16"H, adjustable, dish size 4-1/4" to 11-3/4", removable dividers & towers, two-handed access	Metro	PCD11A	1	28	recessed handles, 5" dia. swivel casters with neoprene wheels (two with brakes), chip-resistant polymer shell with Microban antimicrobial protection, aesthetic blue, vinyl dust/water splash cover, NSF
HEATED CABINET, MOBILE - Cabinet, Mobile Heated, with humidity, insulated, bottom-mount heater assembly, recessed push/pull handles, (11) sets of chrome plated wire universal angle slides on 4-1/2" centers adjustable 1-1/2" centers	Cres Cor	H-135-WUA-11-R	5	28	(4) 5" swivel casters (2) braked, anti-microbial latches, analog thermometer, aluminum construction, red dutch doors, 1920watt, CSA
HEATED BANQUET CART - Cabinet, Mobile Banquet, insulated, two doors, with thermostatically controlled heat unit	Cres Cor	CCB-120A	1	28	capacity (120) 11" covered plates or (90) 11-3/4" covered plates or (60) 13" covered plates, stainless steel riveted, welded & finished, perimeter bumper
BACK BAR COOLER - Refrigerated Back Bar Cabinet, two section, 60"W, self-contained refrigeration, (16) cu.ft. internal volume, front vented, stainless steel top & sides,	Perlick Corporation	BBS60	1	28	(2) hinged doors with locks, stainless steel interior, galvanized steel back, (2) vinyl-coated shelves per door, digital thermostat, automatic defrost, LED interior lighting, automatic evaporator condensate, includes floor drain, R134a, 1/4 HP, NSF, cULus
FINISH FOR BACK BAR COOLER - Condensing unit cover finish: Stainless steel	Perlick Corporation		1	28	Finish for Back Bar Cooler, Perlick Corp, Model # BBS60
DOOR FOR BACK BAR COOLER - Door type, first: glass with stainless steel door frame	Perlick Corporation		1	28	Door for Back Bar Cooler, Perlick Corp, Model # BBS60
DOOR FOR BACK BAR COOLER - Door type, second: glass with stainless steel door frame	Perlick Corporation		1	28	Door for Back Bar Cooler, Perlick Corp, Model # BBS60
CASTERS FOR BACK BAR COOLER - Set of rollers (1-5/8"), for 2', 3', 4' & 5' models	Perlick Corporation	63771A	1	28	Casters for Back Bar Cooler, Perlick Corp, Model # BBS60
BACK BAR COOLER - Refrigerated Back Bar Cabinet, four section, 108"W, self-contained refrigeration, (33.5) cu.ft. internal volume, front vented, stainless steel top & sides, (4) hinged doors with locks, stainless steel interior	Perlick Corporation	BBS108	1	28	galvanized steel back, (2) vinyl-coated shelves per door, digital thermostat, automatic defrost, LED interior lighting, automatic evaporator condensate, includes floor drain, R134a, 1/3 HP, NSF, cULus, 120v/60/1-ph, 6.3 amps, NEMA 5-15P
FINISH FOR BACK BAR COOLER - Condensing unit cover finish: Stainless steel	Perlick Corporation		1	28	Finish for Back Bar Cooler, Perlick Corp, Model # BBS108

Description	Manufacturer	Model	Qty	Qty	Qty	Qty	Notes
DOOR FOR BACK BAR COOLER - Door type, first: glass with stainless steel door frame	Perlick Corporation		1	1	1	28	Door for Back Bar Cooler, Perlick Corp. Model # BBS108
DOOR FOR BACK BAR COOLER - Door type, second: glass with stainless steel door frame	Perlick Corporation		1	1	1	28	Door for Back Bar Cooler, Perlick Corp. Model # BBS108
DOOR FOR BACK BAR COOLER - Door type, third: glass with stainless steel door frame	Perlick Corporation		1	1	1	28	Door for Back Bar Cooler, Perlick Corp. Model # BBS108
DOOR FOR BACK BAR COOLER - Door type, fourth: glass with stainless steel door frame	Perlick Corporation		1	1	1	28	Door for Back Bar Cooler, Perlick Corp. Model # BBS108
CASTERS FOR BACK BAR COOLER - Set of rollers (1-5/8"), for 6 & 8 models	Perlick Corporation	63771A-2	1	1	1	28	Casters for Back Bar Cooler, Perlick Corp. Model # BBS108
PASS-THRU ICE BIN - Service Station Ice Chest, with cold plate, 30"W, concealed 10-circuit cold plate, 144 lb. ice capacity, ABS top ledge, stainless steel front & sides, stainless steel legs with thermoplastic feet	Perlick Corporation	SS30IC10	1	1	1	28	Item for Ice Bin, Perlick Corp. Model # SS30IC10
UNDERBAR BOTTLE WELL FOR ICE BIN - with Ice Chest Cover Assembly, 6- bottle capacity, 4-piece stainless steel sliding cover assembly, (3) black polypropylene bottle wells on each side	Perlick Corporation	BW-SS6-30	1	1	1	28	Item for Ice Bin, Perlick Corp. Model # SS30IC10
SPEED RAIL FOR ICE BIN - Single Speed Rail, 30"W, locking, factory installed	Perlick Corporation	SR-SL30	1	1	1	28	Item for Ice Bin, Perlick Corp. Model # SS30IC10
SODA GUN FOR ICE BIN - TSS Series Soda Gun Filler Section, 6" wide depth to match series, designed for use with Wunder-Bar® and Schroeder America™ 8-14 product soda gun / manifold	Perlick Corporation	TSS6DSGA	1	1	1	28	6" Backsplash standard
DRAINBOARD - TS Series Underbar Drainboard, 24"W x 18-9/16"D, embossed top, 6"H backsplash, stainless steel legs with adjustable thermoplastic feet, stainless steel construction, NSF	Perlick Corporation	TS24	2	1	1	28	Item for Drainboard, Perlick Corp. Model # TS24
SPEED RAIL FOR DRAINBOARD - Single Speed Rail, 24"W, locking, factory installed	Perlick Corporation	SR-SL24	1	1	1	28	Item for Drainboard, Perlick Corp. Model # TS24
CHEMICAL STORAGE CABINET - Chemical Storage Cabinet, 12" W, with sink less faucet, cabinet base with removable dump box, water tight pan, quick disconnect spray hose, stainless steel exterior & 6" backsplash	Perlick Corporation	7057-3	1	1	1	28	Item for Chemical Storage Cabinet, Perlick Corp. Model # 7057-3
FAUCET FOR CHEMICAL STORAGE CABINET - Lead Free Faucet with gooseneck spout, wall mounted	Perlick Corporation	924GN-LF	1	1	1	28	Item for Chemical Storage Cabinet, Perlick Corp. Model # 7057-3
DRAIN SCREEN FOR CHEMICAL STORAGE CABINET - Drain Screen, for 1-1/2" drain socket	Perlick Corporation	54965-1	1	1	1	1	Item for Chemical Storage Cabinet, Perlick Corp. Model # 7057-3
GLASS WASHER - Underbar Glass Washer, batch rotary type, 24"W, low temperature chemical sanitizing, (720) 2-1/4" dia. glasses per hour, 10" maximum glass height, top mounted instrument panel, upper & lower wash arms	Perlick Corporation	PKBR24	1	1	1	28	peristaltic metering pumps, removable vinyl-coated glass racks, metal divider with safety switch, 650W wash tank heater included, stainless steel construction, 6" adjustable legs, 120v/60/1-ph, 5.4 amps, NEMA 5-15P, cULus, UL-EPH

Description	Manufacturer	Model #	Qty	Qty	Specification
HAND SINK - TS Series Underbar Hand Sink Unit, free standing, 12"W x 22-1/4"D, 6" backsplash, 10" wide x 14" front-to-back x 9-1/4" deep sink, 4" O.C. splash mount faucet holes, 16 oz. pump soap dispenser	Perlick Corporation	TS12HSN	1	28	C-fold paper towel dispenser on front apron, sound deadened underside, (1) 8-1/2" standpipe, 1-1/2" NPS male drain, stainless steel construction, stainless steel legs with adjustable thermoplastic feet, NSF
FAUCET FOR HAND SINK - Lead Free Faucet with gooseneck spout, wall mounted	Perlick Corporation	924GN-LF	1	28	Item for Hand Sink, Perlick Corp, Model # TS12HSN
DRIP TROUGH - Drip Tray Trough, drop-in, 30"W x 18"D, for service station, (2) removable glass racks,	Perlick Corporation	RDP18X30	2	28	stainless steel construction (28-13/16" x 16-13/16" cutout required)
CUSTOM INSTALLATION - REFRIGERATION			1	5	
CUSTOM INSTALLATION - EQUIPMENT			1	5	Receive, uncrate, assemble and set in place for final connections
Totals					