Control Room CANARE Camera Cable Assembly

RFI Line Items

ECPU:ESTIMATED COST P/UNIT PMP:POTENTIAL MINIMUM PURCHASE PAP:POTENTIAL ANNUAL PURCHASE PF:PURCHASE FREQUENCY ETD:ESTIMATED DELIVERY TIME

| Product name | MFR | MFR product # | ECPU | Min qty | PMP | PAP | PF | ETD | Details |
|--|--------|---------------|------|---------|-----|-----|----|-----|--|
| 25m HFO Camera Cable Assembly | CANARE | FCC25N-CCA | | 3 | | | 1 | 1 | Canare FCC25N is a 25-meter hybrid fiber-optic camera cable.SMPTE 304M, 311M, and ARIB BTA S-105B compliant Connector body material is stainless steel Color rings (included 2 pcs each of black, red, yellow, green, blue, gray, and white are convenient to identify the type of signal Compliant with the ARIB BTA S-1005B and SMPTE 304M and 311M With AdPC polish (RL>45dB) and insertion loss of 0.5dB or less |
| Canare SMPTE 311 Fiber Camera Cable 50 Meter /164 feet | CANARE | FCC50N-CCA | | 1 | | | 1 | 1 | Canare FCC50N is a 50-meter hybrid fiber-optic camera cable. Canare FCC50N Features: SMPTE 304M, 311M, and ARIB BTA S- 105B compliant Connector body material is stainless steel Color rings (included 2 pcs each of black, red, yellow, green, blue, gray, and white are convenient to identify the type of signal Compliant with the ARIB BTA S-1005B and SMPTE 304M and 311M With AdPC polish (RL>45dB) and insertion loss of 0.5dB or less |
| Canare Hybrid Fiber Optic Camera-Cable Assembly w/ FCMA & FCFA Connectors (328') | CANARE | FCC100N-CCA | | 1 | | | 1 | 1 | Canare VIC cords are useful for both inter-rack harness wiring and longer video cable runs. This super flexible 8281F type pre-made 75 ohm BNC BNC assembly is available in a variety of colors. Our low loss cord offers outstanding video bandwidth performance because all components used are impedance matched for cleaner and sharper video resolution. |
| 75 OHM BNC CRIMP PLUG | CANARE | BCP-B5F | | 300 | | | 1 | 1 | Canare BCP-B5F BCP-B Series BNC Connector for L-5CFB and LS-5CFB Part of the Canare BCP Series of high quality 75 Ohm BNC crimp plug connectors, the Canare BCP-B5F is rated for all SMPTE 424M & 292M applications to confidently transmit 3G-SDI bit-rates in 1080p video production. Canare BCP BNC connectors feature an elongated body for better finger grip and a unique position mark on the body allows the connector bayonet fit to be checked easily. The BCP-B5F BNC connector is designed for Belden L-5CFB coaxial to deliver a combination of superior cable pull strength you won't find with other connectors. Its gold plated center pins 'snaps' into place to ensure perfect alignment with connected video gear and patch panels. |
| CRIMP TOOL | CANARE | TC-1 | | 1 | | | 1 | 1 | Canare TC-1 Hand Crimp Tool is made with Hardened Swedish Steel and features a Ratchet Release. Features Interchangeable die sets Scissor ratchet action Emergency release lever Adjustable crimp force via drag washer Hardened Swedish Steel construction Rated at 50,000 dura-cycle lifespan Applications: Canare Crimp Plugs, BNC, F, RCA and More! Serial Digital Video HDTV Upgrades NTSC Analog Test Equipment Satellite Headends TELCOM |

Control Room CANARE Camera Cable Assembly

| Crimp tool for TC-1 | CANARE | TCD-5CF | 1 | | 1 | 1 | Features 2 piece precision fit design 2 Hex Bolts for quick hand tool loading Tight dimensional tolerances 1 and 2 Hex Sleeve versions Engraved Model I.D. Applications Canare Crimp Plugs, BNC, F, RCA and More! Serial Digital Video HDTV Upgrades NTSC Analog Test Equipment Satellite Headends TELCOM |
|---|--------|---------|---|--|---|---|--|
| Canare L-5CFB 75 Ohm HD-SDI Coax Cable RG-6 Type by the Ft Black | CANARE | L-5CFB | 1 | | 1 | 1 | Canare 75 ohm precision digital video cables, offers the professional Broadcaster a high performance, 100 Sweep Tested, low cost, low loss coax that meets the demands of today's facility migration trends toward Serial Digital Video and HDTV standards.Features Solid Copper Center Conductor Foam PE Dielectric Tinned Copper Braid + 100% Foil Shield Dielectric strips away clean from Conductor Precision Coax 100% Sweep Tested Cable Type Video / audio cable (optical) Technology Shielded American Wire Gauge (AWG) 20/25 Jacket Material PVC Compliant Standards SMPTE Length 328 ft Recommended Use Camera Features Abrasion-resistant Color Black Connectivity CONNECTOR FCFA Connector (Second End) FCMA |
| Totals | | | | | | | |