

### Press Conference Room Sound Purchases

**RFI Line Items**

ECPU:ESTIMATED COST P/UNIT

PMP:POTENTIAL MINIMUM PURCHASE

PAP:POTENTIAL ANNUAL PURCHASE

PF:PURCHASE FREQUENCY

ETD:ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
4-Channel Output Dante Wall Plate	PRO CO SOUND	AODDP-4XM		1			1	1	Channels: 4 Outputs Analog Signal: Line Level Analog I/O: 4 x Neutrik XLR 3-Pin Male Outputs Dante Connection: 4 x Neutrik etherCON Female (Locking) Digital Audio: AES67 Compliant Power Requirement: PoE Construction Material: Aluminum Installation: 4 x Front-Panel Screw Holes Fits in 2-Gang Deep Well J-Box
4-Channel Input Dante Wall Plate	PRO CO SOUND	AODDP-4XF		1			1	1	Channels: 4 Inputs Analog Signal: Line Level Analog I/O: 4 x Neutrik XLR 3-Pin Female Inputs (Locking) Dante Connection: 4 x Neutrik etherCON Female (Locking) Digital Audio: AES67 Compliant Power Requirement: PoE Construction Material: Aluminum Installation: 4 x Front-Panel Screw Holes Fits in 2-Gang Deep Well J-Box
1-VOLUME/ 4-Switch Control Panel for the MTX Series	YAMAHA	DCP1V4S		1			1	1	1 volume & 4 switches equipped wall mount control panel 1 DCP can be connected to 1 MA2030 Simple connection via Cat5. Operating temperature range: 0 to +40 °C Storage temperature range: 20 to +60 °C Connectors: Cat5 or higher Dimensions (H x W): 7.2" (120 mm) x 2.76" (70 mm)
Totals									